

# Spring Boot Actuator Web API Documentation

Andy Wilkinson

# Table of Contents

1. Overview .....	2
1.1. URLs.....	2
1.2. Timestamps .....	2
2. Audit Events ( <a href="#">auditevents</a> ).....	3
2.1. Retrieving Audit Events .....	3
2.1.1. Query Parameters.....	3
2.1.2. Response Structure .....	3
3. Beans ( <a href="#">beans</a> ) .....	5
3.1. Retrieving the Beans .....	5
3.1.1. Response Structure .....	6
4. Conditions Evaluation Report ( <a href="#">conditions</a> ) .....	8
4.1. Retrieving the Report .....	8
4.1.1. Response Structure .....	9
5. Configuration Properties ( <a href="#">configprops</a> ) .....	11
5.1. Retrieving the <a href="#">@ConfigurationProperties</a> Bean.....	11
5.1.1. Response Structure .....	13
6. Environment ( <a href="#">env</a> ) .....	14
6.1. Retrieving the Entire Environment.....	14
6.1.1. Response Structure .....	15
6.2. Retrieving a Single Property .....	16
6.2.1. Response Structure .....	16
7. Flyway ( <a href="#">flyway</a> ).....	18
7.1. Retrieving the Migrations .....	18
7.1.1. Response Structure .....	18
8. Health ( <a href="#">health</a> ) .....	20
8.1. Retrieving the Health .....	20
8.1.1. Response Structure .....	20
9. Heap Dump ( <a href="#">heapdump</a> ) .....	22
9.1. Retrieving the Heap Dump .....	22
10. HTTP Trace ( <a href="#">httptrace</a> ) .....	23
10.1. Retrieving the Traces .....	23
10.1.1. Response Structure .....	23
11. Info ( <a href="#">info</a> ) .....	25
11.1. Retrieving the Info.....	25
11.1.1. Response Structure .....	25
<a href="#">build</a> Response Structure .....	25
<a href="#">git</a> Response Structure .....	26
12. Liquibase ( <a href="#">liquibase</a> ) .....	27

12.1. Retrieving the Changes .....	27
12.1.1. Response Structure .....	27
13. Log File ( <a href="#">logfile</a> ) .....	29
13.1. Retrieving the Log File .....	29
13.2. Retrieving Part of the Log File .....	31
14. Loggers ( <a href="#">loggers</a> ) .....	32
14.1. Retrieving All Loggers .....	32
14.1.1. Response Structure .....	32
14.2. Retrieving a Single Logger .....	33
14.2.1. Response Structure .....	33
14.3. Setting a Log Level .....	33
14.3.1. Request Structure .....	33
14.4. Clearing a Log Level .....	34
15. Mappings ( <a href="#">mappings</a> ) .....	35
15.1. Retrieving the Mappings .....	35
15.1.1. Response Structure .....	38
15.1.2. Dispatcher Servlets Response Structure .....	39
15.1.3. Servlets Response Structure .....	40
15.1.4. Servlet Filters Response Structure .....	40
15.1.5. Dispatcher Handlers Response Structure .....	41
16. Metrics ( <a href="#">metrics</a> ) .....	43
16.1. Retrieving Metric Names .....	43
16.1.1. Response Structure .....	43
16.2. Retrieving a Metric .....	43
16.2.1. Query Parameters .....	44
16.2.2. Response structure .....	44
16.3. Drilling Down .....	45
17. Prometheus ( <a href="#">prometheus</a> ) .....	46
17.1. Retrieving the Metrics .....	46
18. Scheduled Tasks ( <a href="#">scheduledtasks</a> ) .....	48
18.1. Retrieving the Scheduled Tasks .....	48
18.1.1. Response Structure .....	48
19. Sessions ( <a href="#">sessions</a> ) .....	50
19.1. Retrieving Sessions .....	50
19.1.1. Query Parameters .....	51
19.1.2. Response Structure .....	51
19.2. Retrieving a Single Session .....	51
19.2.1. Response Structure .....	52
19.3. Deleting a Session .....	52
20. Shutdown ( <a href="#">shutdown</a> ) .....	53
20.1. Shutting Down the Application .....	53

20.1.1. Response Structure .....	53
21. Thread Dump ( <b>threaddump</b> ) .....	54
21.1. Retrieving the Thread Dump.....	54
21.1.1. Response Structure .....	57

This API documentation describes Spring Boot Actuators web endpoints.

# Chapter 1. Overview

Before you proceed, you should read the following topics:

- [URLs](#)
- [Timestamps](#)

## 1.1. URLs

By default, all web endpoints are available beneath the path `/actuator` with URLs of the form `/actuator/{id}`. The `/actuator` base path can be configured by using the `management.endpoints.web.base-path` property, as shown in the following example:

```
management.endpoints.web.base-path=/manage
```

The preceding `application.properties` example changes the form of the endpoint URLs from `/actuator/{id}` to `/manage/{id}`. For example, the URL `info` endpoint would become `/manage/info`.

## 1.2. Timestamps

All timestamps that are consumed by the endpoints, either as query parameters or in the request body, must be formatted as an offset date and time as specified in [ISO 8601](#).

# Chapter 2. Audit Events (auditevents)

The `auditevents` endpoint provides information about the application's audit events.

## 2.1. Retrieving Audit Events

To retrieve the audit events, make a `GET` request to `/actuator/auditevents`, as shown in the following curl-based example:

```
$ curl 'http://localhost:8080/actuator/auditevents?principal=alice&after=2018-07-30T14%3A13%3A18.671Z&type=logout' -i -X GET
```

The preceding example retrieves `logout` events for the principal, `alice`, that occurred after 09:37 on 7 November 2017 in the UTC timezone. The resulting response is similar to the following:

```
HTTP/1.1 200 OK
Content-Type: application/vnd.spring-boot.actuator.v2+json; charset=UTF-8
Content-Length: 121

{
  "events" : [ {
    "timestamp" : "2018-07-30T14:13:18.673Z",
    "principal" : "alice",
    "type" : "logout"
  } ]
}
```

### 2.1.1. Query Parameters

The endpoint uses query parameters to limit the events that it returns. The following table shows the supported query parameters:

Parameter	Description
<code>after</code>	Restricts the events to those that occurred after the given time. Optional.
<code>principal</code>	Restricts the events to those with the given principal. Optional.
<code>type</code>	Restricts the events to those with the given type. Optional.

### 2.1.2. Response Structure

The response contains details of all of the audit events that matched the query. The following table describes the structure of the response:

<b>Path</b>	<b>Type</b>	<b>Description</b>
events	Array	An array of audit events.
events.[].timestamp	String	The timestamp of when the event occurred.
events.[].principal	String	The principal that triggered the event.
events.[].type	String	The type of the event.

# Chapter 3. Beans (beans)

The `beans` endpoint provides information about the application's beans.

## 3.1. Retrieving the Beans

To retrieve the beans, make a `GET` request to `/actuator/beans`, as shown in the following curl-based example:

```
$ curl 'http://localhost:8080/actuator/beans' -i -X GET
```

The resulting response is similar to the following:

HTTP/1.1 200 OK

Content-Type: application/vnd.spring-boot.actuator.v2+json; charset=UTF-8

Content-Length: 1150

```
{  
    "contexts" : {  
        "application" : {  
            "beans" : {  
                "defaultServletHandlerMapping" : {  
                    "aliases" : [ ],  
                    "scope" : "singleton",  
                    "type" :  
"org.springframework.web.servlet.config.annotation.WebMvcConfigurationSupport$EmptyHan  
dlerMapping",  
                    "resource" :  
"org.springframework.boot.autoconfigure.web.servlet.WebMvcAutoConfiguration$EnableWebM  
vcConfiguration",  
                    "dependencies" : [ ]  
                },  
  
"org.springframework.boot.autoconfigure.web.servlet.DispatcherServletAutoConfiguration  
" : {  
                "aliases" : [ ],  
                "scope" : "singleton",  
                "type" :  
"org.springframework.boot.autoconfigure.web.servlet.DispatcherServletAutoConfiguration  
$$EnhancerBySpringCGLIB$$e16fc8b8",  
                "dependencies" : [ ]  
            },  
  
"org.springframework.boot.autoconfigure.context.PropertyPlaceholderAutoConfiguration"  
: {  
                "aliases" : [ ],  
                "scope" : "singleton",  
                "type" :  
"org.springframework.boot.autoconfigure.context.PropertyPlaceholderAutoConfiguration$$  
EnhancerBySpringCGLIB$$f3c3e634",  
                "dependencies" : [ ]  
            },  
        }  
    }  
}
```

### 3.1.1. Response Structure

The response contains details of the application's beans. The following table describes the structure of the response:

<b>Path</b>	<b>Type</b>	<b>Description</b>
<code>contexts</code>	<code>Object</code>	Application contexts keyed by id.
<code>contexts.*.parentId</code>	<code>String</code>	Id of the parent application context, if any.
<code>contexts.*.beans</code>	<code>Object</code>	Beans in the application context keyed by name.
<code>contexts.*.beans.*.aliases</code>	<code>Array</code>	Names of any aliases.
<code>contexts.*.beans.*.scope</code>	<code>String</code>	Scope of the bean.
<code>contexts.*.beans.*.type</code>	<code>String</code>	Fully qualified type of the bean.
<code>contexts.*.beans.*.resource</code>	<code>String</code>	Resource in which the bean was defined, if any.
<code>contexts.*.beans.*.dependencies</code>	<code>Array</code>	Names of any dependencies.

# Chapter 4. Conditions Evaluation Report (conditions)

The `conditions` endpoint provides information about the evaluation of conditions on configuration and auto-configuration classes.

## 4.1. Retrieving the Report

To retrieve the report, make a `GET` request to `/actuator/conditions`, as shown in the following curl-based example:

```
$ curl 'http://localhost:8080/actuator/conditions' -i -X GET
```

The resulting response is similar to the following:

```
HTTP/1.1 200 OK
Content-Type: application/vnd.spring-boot.actuator.v2+json; charset=UTF-8
Content-Length: 3230

{
  "contexts" : {
    "application" : {
      "positiveMatches" : [
        "EndpointAutoConfiguration#endpointOperationParameterMapper" : [ {
          "condition" : "OnBeanCondition",
          "message" : "@ConditionalOnMissingBean (types: org.springframework.boot.actuate.endpoint.invoke.ParameterValueMapper; SearchStrategy: all) did not find any beans"
        } ],
        "EndpointAutoConfiguration#endpointCachingOperationInvokerAdvisor" : [ {
          "condition" : "OnBeanCondition",
          "message" : "@ConditionalOnMissingBean (types: org.springframework.boot.actuate.endpoint.invoker.cache.CachingOperationInvokerAdvisor; SearchStrategy: all) did not find any beans"
        } ],
        "WebEndpointAutoConfiguration" : [ {
          "condition" : "OnWebApplicationCondition",
          "message" : "@ConditionalOnWebApplication (required) found 'session' scope"
        } ]
      },
      "negativeMatches" : {
        "WebFluxEndpointManagementContextConfiguration" : {
          "notMatched" : [ {
            "condition" : "OnWebApplicationCondition",
            "message" : "not a reactive web application"
          } ],
          "matched" : [ {
            "condition" : "OnWebApplicationCondition",
            "message" : "not a reactive web application"
          } ]
        }
      }
    }
  }
}
```

```

        "condition" : "OnClassCondition",
        "message" : "@ConditionalOnClass found required classes
'org.springframework.web.reactive.DispatcherHandler',
'org.springframework.http.server.reactive.HttpHandler'; @ConditionalOnMissingClass did
not find unwanted class"
    } ]
},
"GsonHttpMessageConvertersConfiguration.GsonHttpMessageConverterConfiguration"
: {
    "notMatched" : [ {
        "condition" :
"GsonHttpMessageConvertersConfiguration.PreferGsonOrJacksonAndJsonbUnavailableCondition",
        "message" : "AnyNestedCondition 0 matched 2 did not; NestedCondition on
GsonHttpMessageConvertersConfiguration.PreferGsonOrJacksonAndJsonbUnavailableCondition
.JacksonJsonbUnavailable NoneNestedConditions 1 matched 1 did not; NestedCondition on
GsonHttpMessageConvertersConfiguration.JacksonAndJsonbUnavailableCondition.JsonbPrefer
red @ConditionalOnProperty (spring.http.converters.preferred-json-mapper=jsonb) did
not find property 'spring.http.converters.preferred-json-mapper'; NestedCondition on
GsonHttpMessageConvertersConfiguration.JacksonAndJsonbUnavailableCondition.JacksonAvai
lable @ConditionalOnBean (types:
org.springframework.http.converter.json.MappingJackson2HttpMessageConverter;
SearchStrategy: all) found bean 'mappingJackson2HttpMessageConverter'; NestedCondition
on
GsonHttpMessageConvertersConfiguration.PreferGsonOrJacksonAndJsonbUnavailableCondition
.JsonPreferred @ConditionalOnProperty (spring.http.converters.preferred-json-
mapper=gson) did not find property 'spring.http.converters.preferred-json-mapper'"
    } ],
    "matched" : [ ]
},
"GsonbHttpMessageConvertersConfiguration" : {
    "notMatched" : [ {
        "condition" : "OnClassCondition",
        "message" : "@ConditionalOnClass did not find required class
'javax.json.bind.Jsonb'"
    } ],
    "matched" : [ ]
}
},
"unconditionalClasses" : [
"org.springframework.boot.autoconfigure.context.PropertyPlaceholderAutoConfiguration"
]
}
}
}

```

#### 4.1.1. Response Structure

The response contains details of the application's condition evaluation. The following table describes the structure of the response:

<b>Path</b>	<b>Type</b>	<b>Description</b>
contexts	Object	Application contexts keyed by id.
contexts.*.positiveMatches	Object	Classes and methods with conditions that were matched.
contexts.*.positiveMatches.*.[].condition	String	Name of the condition.
contexts.*.positiveMatches.*.[].message	String	Details of why the condition was matched.
contexts.*.negativeMatches	Object	Classes and methods with conditions that were not matched.
contexts.*.negativeMatches.*.notMatched	Array	Conditions that were matched.
contexts.*.negativeMatches.*.notMatched.[].condition	String	Name of the condition.
contexts.*.negativeMatches.*.notMatched.[].message	String	Details of why the condition was not matched.
contexts.*.negativeMatches.*.matched	Array	Conditions that were matched.
contexts.*.negativeMatches.*.matched.[].condition	String	Name of the condition.
contexts.*.negativeMatches.*.matched.[].message	String	Details of why the condition was matched.
contexts.*.unconditionalClasses	Array	Names of unconditional auto-configuration classes if any.
contexts.*.parentId	String	Id of the parent application context, if any.

# Chapter 5. Configuration Properties (configprops)

The `configprops` endpoint provides information about the application's `@ConfigurationProperties` beans.

## 5.1. Retrieving the `@ConfigurationProperties` Bean

To retrieve the `@ConfigurationProperties` beans, make a `GET` request to `/actuator/configprops`, as shown in the following curl-based example:

```
$ curl 'http://localhost:8080/actuator/configprops' -i -X GET
```

The resulting response is similar to the following:

HTTP/1.1 200 OK  
Content-Type: application/vnd.spring-boot.actuator.v2+json; charset=UTF-8  
Content-Length: 1266

```
{  
    "contexts" : {  
        "application" : {  
            "beans" : {  
                "management.endpoints.web.cors-  
org.springframework.boot.actuate.autoconfigure.endpoint.web.CorsEndpointProperties" :  
{  
            "prefix" : "management.endpoints.web.cors",  
            "properties" : {  
                "allowedHeaders" : [ ],  
                "allowedMethods" : [ ],  
                "allowedOrigins" : [ ],  
                "maxAge" : {  
                    "units" : [ "SECONDS", "NANOS" ]  
                },  
                "exposedHeaders" : [ ]  
            }  
        },  
        "spring.http.encoding-  
org.springframework.boot.autoconfigure.http.HttpEncodingProperties" : {  
            "prefix" : "spring.http.encoding",  
            "properties" : {  
                "charset" : "UTF-8",  
                "force" : false,  
                "forceRequest" : false,  
                "forceResponse" : false  
            }  
        },  
        "management.endpoints.web-  
org.springframework.boot.actuate.autoconfigure.endpoint.web.WebEndpointProperties" : {  
            "prefix" : "management.endpoints.web",  
            "properties" : {  
                "pathMapping" : { },  
                "exposure" : {  
                    "include" : [ "*" ],  
                    "exclude" : [ ]  
                },  
                "basePath" : "/actuator"  
            }  
        }  
    }  
}
```

### 5.1.1. Response Structure

The response contains details of the application's `@ConfigurationProperties` beans. The following table describes the structure of the response:

Path	Type	Description
<code>contexts</code>	<code>Object</code>	Application contexts keyed by id.
<code>contexts.*.beans.*</code>	<code>Object</code>	<code>@ConfigurationProperties</code> beans keyed by bean name.
<code>contexts.*.beans.*.prefix</code>	<code>String</code>	Prefix applied to the names of the bean's properties.
<code>contexts.*.beans.*.properties</code>	<code>Object</code>	Properties of the bean as name-value pairs.
<code>contexts.*.parentId</code>	<code>String</code>	Id of the parent application context, if any.

# Chapter 6. Environment (env)

The `env` endpoint provides information about the application's `Environment`.

## 6.1. Retrieving the Entire Environment

To retrieve the entire environment, make a `GET` request to `/actuator/env`, as shown in the following curl-based example:

```
$ curl 'http://localhost:8080/actuator/env' -i -X GET
```

The resulting response is similar to the following:

```
HTTP/1.1 200 OK
Content-Type: application/vnd.spring-boot.actuator.v2+json; charset=UTF-8
Content-Length: 799
```

```
{
  "activeProfiles" : [ ],
  "propertySources" : [ {
    "name" : "systemProperties",
    "properties" : {
      "java.runtime.name" : {
        "value" : "OpenJDK Runtime Environment"
      },
      "java.vm.version" : {
        "value" : "25.141-b15"
      },
      "java.vm.vendor" : {
        "value" : "Oracle Corporation"
      }
    }
  }, {
    "name" : "systemEnvironment",
    "properties" : {
      "JAVA_HOME" : {
        "value" : "/docker-java-home",
        "origin" : "System Environment Property \\"JAVA_HOME\\""
      }
    }
  }, {
    "name" : "applicationConfig: [classpath:/application.properties]",
    "properties" : {
      "com.example.cache.max-size" : {
        "value" : "1000",
        "origin" : "class path resource [application.properties]:1:29"
      }
    }
  } ]
}
```

### 6.1.1. Response Structure

The response contains details of the application's [Environment](#). The following table describes the structure of the response:

Path	Type	Description
activeProfiles	Array	Names of the active profiles, if any.
propertySources	Array	Property sources in order of precedence.
propertySources.[].name	String	Name of the property source.

Path	Type	Description
<code>propertySources.[].properties</code>	<code>Object</code>	Properties in the property source keyed by property name.
<code>propertySources.[].properties.*.value</code>	<code>String</code>	Value of the property.
<code>propertySources.[].properties.*.origin</code>	<code>String</code>	Origin of the property, if any.

## 6.2. Retrieving a Single Property

To retrieve a single property, make a `GET` request to `/actuator/env/{property.name}`, as shown in the following curl-based example:

```
$ curl 'http://localhost:8080/actuator/env/com.example.cache.max-size' -i -X GET
```

The preceding example retrieves information about the property named `com.example.cache.max-size`. The resulting response is similar to the following:

```
HTTP/1.1 200 OK
Content-Disposition: inline;filename=f.txt
Content-Type: application/vnd.spring-boot.actuator.v2+json;charset=UTF-8
Content-Length: 445

{
  "property" : {
    "source" : "applicationConfig: [classpath:/application.properties]",
    "value" : "1000"
  },
  "activeProfiles" : [ ],
  "propertySources" : [ {
    "name" : "systemProperties"
  }, {
    "name" : "systemEnvironment"
  }, {
    "name" : "applicationConfig: [classpath:/application.properties]",
    "property" : {
      "value" : "1000",
      "origin" : "class path resource [application.properties]:1:29"
    }
  } ]
}
```

### 6.2.1. Response Structure

The response contains details of the requested property. The following table describes the structure of the response:

<b>Path</b>	<b>Type</b>	<b>Description</b>
<code>property</code>	<code>Object</code>	Property from the environment, if found.
<code>property.source</code>	<code>String</code>	Name of the source of the property.
<code>property.value</code>	<code>String</code>	Value of the property.
<code>activeProfiles</code>	<code>Array</code>	Names of the active profiles, if any.
<code>propertySources</code>	<code>Array</code>	Property sources in order of precedence.
<code>propertySources.[].name</code>	<code>String</code>	Name of the property source.
<code>propertySources.[].property</code>	<code>Object</code>	Property in the property source, if any.
<code>propertySources.[].property.value</code>	<code>String</code>	Value of the property.
<code>propertySources.[].property.origin</code>	<code>String</code>	Origin of the property, if any.

# Chapter 7. Flyway ([flyway](#))

The [flyway](#) endpoint provides information about database migrations performed by Flyway.

## 7.1. Retrieving the Migrations

To retrieve the migrations, make a [GET](#) request to [/actuator/flyway](#), as shown in the following curl-based example:

```
$ curl 'http://localhost:8080/actuator/flyway' -i -X GET
```

The resulting response is similar to the following:

```
HTTP/1.1 200 OK
Content-Type: application/vnd.spring-boot.actuator.v2+json; charset=UTF-8
Content-Length: 506

{
  "contexts" : {
    "application" : {
      "flywayBeans" : {
        "flyway" : {
          "migrations" : [ {
            "type" : "SQL",
            "checksum" : 0,
            "version" : "1",
            "description" : "init",
            "script" : "V1_init.sql",
            "state" : "SUCCESS",
            "installedBy" : "SA",
            "installedOn" : "2018-07-30T14:13:24.012Z",
            "installedRank" : 1,
            "executionTime" : 0
          } ]
        }
      }
    }
  }
}
```

### 7.1.1. Response Structure

The response contains details of the application's Flyway migrations. The following table describes the structure of the response:

<b>Path</b>	<b>Type</b>	<b>Description</b>
contexts	Object	Application contexts keyed by id
contexts.*.flywayBeans.*.migrations	Array	Migrations performed by the Flyway instance, keyed by Flyway bean name.
contexts.*.flywayBeans.*.migrations.[].checksum	Number	Checksum of the migration, if any.
contexts.*.flywayBeans.*.migrations.[].description	String	Description of the migration, if any.
contexts.*.flywayBeans.*.migrations.[].executionTime	Number	Execution time in milliseconds of an applied migration.
contexts.*.flywayBeans.*.migrations.[].installedBy	String	User that installed the applied migration, if any.
contexts.*.flywayBeans.*.migrations.[].installedOn	String	Timestamp of when the applied migration was installed, if any.
contexts.*.flywayBeans.*.migrations.[].installedRank	Number	Rank of the applied migration, if any. Later migrations have higher ranks.
contexts.*.flywayBeans.*.migrations.[].script	String	Name of the script used to execute the migration, if any.
contexts.*.flywayBeans.*.migrations.[].state	String	State of the migration. (PENDING, ABOVE_TARGET, BELOW_BASELINE, BASELINE, IGNORED, MISSING_SUCCESS, MISSING_FAILED, SUCCESS, UNDONE, AVAILABLE, FAILED, OUT_OF_ORDER, FUTURE_SUCCESS, FUTURE_FAILED, OUTDATED, SUPERSEDED)
contexts.*.flywayBeans.*.migrations.[].type	String	Type of the migration. (SCHEMA, BASELINE, SQL, UNDO_SQL, JDBC, UNDO_JDBC, SPRING_JDBC, UNDO_SPRING_JDBC, CUSTOM, UNDO_CUSTOM)
contexts.*.flywayBeans.*.migrations.[].version	String	Version of the database after applying the migration, if any.
contexts.*.parentId	String	Id of the parent application context, if any.

# Chapter 8. Health (health)

The `health` endpoint provides detailed information about the health of the application.

## 8.1. Retrieving the Health

To retrieve the health of the application, make a `GET` request to `/actuator/health`, as shown in the following curl-based example:

```
$ curl 'http://localhost:8080/actuator/health' -i -X GET
```

The resulting response is similar to the following:

```
HTTP/1.1 200 OK
Content-Type: application/vnd.spring-boot.actuator.v2+json; charset=UTF-8
Content-Length: 386

{
  "status" : "UP",
  "details" : {
    "diskSpaceHealthIndicator" : {
      "status" : "UP",
      "details" : {
        "total" : 136535855104,
        "free" : 58060185600,
        "threshold" : 10485760
      }
    },
    "dataSourceHealthIndicator" : {
      "status" : "UP",
      "details" : {
        "database" : "HSQL Database Engine",
        "hello" : 1
      }
    }
  }
}
```

### 8.1.1. Response Structure

The response contains details of the health of the application. The following table describes the structure of the response:

Path	Type	Description
<code>status</code>	<code>String</code>	Overall status of the application.

<b>Path</b>	<b>Type</b>	<b>Description</b>
<code>details</code>	<code>Object</code>	Details of the health of the application. Presence is controlled by <code>management.endpoint.health.show-details</code> .
<code>details.*.status</code>	<code>String</code>	Status of a specific part of the application.
<code>details.*.details</code>	<code>Object</code>	Details of the health of a specific part of the application.

# Chapter 9. Heap Dump (`heapdump`)

The `heapdump` endpoint provides a heap dump from the application's JVM.

## 9.1. Retrieving the Heap Dump

To retrieve the heap dump, make a `GET` request to `/actuator/heapdump`. The response is binary data in `HPROF` format and can be large. Typically, you should save the response to disk for subsequent analysis. When using curl, this can be achieved by using the `-O` option, as shown in the following example:

```
$ curl 'http://localhost:8080/actuator/heapdump' -O
```

The preceding example results in a file named `heapdump` being written to the current working directory.

# Chapter 10. HTTP Trace ([httptrace](#))

The [httptrace](#) endpoint provides information about HTTP request-response exchanges.

## 10.1. Retrieving the Traces

To retrieve the traces, make a `GET` request to [/actuator/httptrace](#), as shown in the following curl-based example:

```
$ curl 'http://localhost:8080/actuator/httptrace' -i -X GET
```

The resulting response is similar to the following:

```
HTTP/1.1 200 OK
Content-Type: application/vnd.spring-boot.actuator.v2+json; charset=UTF-8
Content-Length: 503

{
  "traces" : [ {
    "timestamp" : "2018-07-30T14:13:27.460Z",
    "principal" : {
      "name" : "alice"
    },
    "session" : {
      "id" : "d3a55e98-b3da-41c0-bc6c-b96700018fb2"
    },
    "request" : {
      "method" : "GET",
      "uri" : "https://api.example.com",
      "headers" : {
        "Accept" : [ "application/json" ]
      }
    },
    "response" : {
      "status" : 200,
      "headers" : {
        "Content-Type" : [ "application/json" ]
      }
    },
    "timeTaken" : 5
  } ]
}
```

### 10.1.1. Response Structure

The response contains details of the traced HTTP request-response exchanges. The following table describes the structure of the response:

<b>Path</b>	<b>Type</b>	<b>Description</b>
<code>traces</code>	<code>Array</code>	An array of traced HTTP request-response exchanges.
<code>traces.[].timestamp</code>	<code>String</code>	Timestamp of when the traced exchange occurred.
<code>traces.[].principal</code>	<code>Object</code>	Principal of the exchange, if any.
<code>traces.[].principal.name</code>	<code>String</code>	Name of the principal.
<code>traces.[].request.method</code>	<code>String</code>	HTTP method of the request.
<code>traces.[].request.remoteAddress</code>	<code>String</code>	Remote address from which the request was received, if known.
<code>traces.[].request.uri</code>	<code>String</code>	URI of the request.
<code>traces.[].request.headers</code>	<code>Object</code>	Headers of the request, keyed by header name.
<code>traces.[].request.headers.*.[ ]</code>	<code>Array</code>	Values of the header
<code>traces.[].response.status</code>	<code>Number</code>	Status of the response
<code>traces.[].response.headers</code>	<code>Object</code>	Headers of the response, keyed by header name.
<code>traces.[].response.headers.*.[ ]</code>	<code>Array</code>	Values of the header
<code>traces.[].session</code>	<code>Object</code>	Session associated with the exchange, if any.
<code>traces.[].session.id</code>	<code>String</code>	ID of the session.
<code>traces.[].timeTaken</code>	<code>Number</code>	Time, in milliseconds, taken to handle the exchange.

# Chapter 11. Info ([info](#))

The [info](#) endpoint provides general information about the application.

## 11.1. Retrieving the Info

To retrieve the information about the application, make a [GET](#) request to [/actuator/info](#), as shown in the following curl-based example:

```
$ curl 'http://localhost:8080/actuator/info' -i -X GET
```

The resulting response is similar to the following:

```
HTTP/1.1 200 OK
Content-Type: application/vnd.spring-boot.actuator.v2+json; charset=UTF-8
Content-Length: 235

{
  "git" : {
    "commit" : {
      "time" : "+50547-07-27T16:32:30Z",
      "id" : "df027cf"
    },
    "branch" : "master"
  },
  "build" : {
    "version" : "1.0.3",
    "artifact" : "application",
    "group" : "com.example"
  }
}
```

### 11.1.1. Response Structure

The response contains general information about the application. Each section of the response is contributed by an [InfoContributor](#). Spring Boot provides [build](#) and [git](#) contributions.

#### [build](#) Response Structure

The following table describe the structure of the [build](#) section of the response:

Path	Type	Description
<a href="#">artifact</a>	<a href="#">String</a>	Artifact ID of the application, if any.
<a href="#">group</a>	<a href="#">String</a>	Group ID of the application, if any.
<a href="#">name</a>	<a href="#">String</a>	Name of the application, if any.

<b>Path</b>	<b>Type</b>	<b>Description</b>
<code>version</code>	<code>String</code>	Version of the application, if any.
<code>time</code>	<code>Varies</code>	Timestamp of when the application was built, if any.

## git Response Structure

The following table describes the structure of the `git` section of the response:

<b>Path</b>	<b>Type</b>	<b>Description</b>
<code>branch</code>	<code>String</code>	Name of the Git branch, if any.
<code>commit</code>	<code>Object</code>	Details of the Git commit, if any.
<code>commit.time</code>	<code>Varies</code>	Timestamp of the commit, if any.
<code>commit.id</code>	<code>String</code>	ID of the commit, if any.

# Chapter 12. Liquibase (liquibase)

The `liquibase` endpoint provides information about database change sets applied by Liquibase.

## 12.1. Retrieving the Changes

To retrieve the changes, make a `GET` request to `/actuator/liquibase`, as shown in the following curl-based example:

```
$ curl 'http://localhost:8080/actuator/liquibase' -i -X GET
```

The resulting response is similar to the following:

```
HTTP/1.1 200 OK
Content-Type: application/vnd.spring-boot.actuator.v2+json; charset=UTF-8
Content-Length: 688

{
  "contexts" : {
    "application" : {
      "liquibaseBeans" : {
        "liquibase" : {
          "changeSets" : [ {
            "author" : "marceloverdijk",
            "changeLog" : "classpath:/db/changelog/db.changelog-master.yaml",
            "comments" : "",
            "contexts" : [ ],
            "dateExecuted" : "2018-07-30T14:12:24.860Z",
            "deploymentId" : "2959944846",
            "description" : "createTable tableName=customer",
            "execType" : "EXECUTED",
            "id" : "1",
            "labels" : [ ],
            "checksum" : "7:0cfbff0a94f5ba816ab56eaca6b8affc",
            "orderExecuted" : 1
          } ]
        }
      }
    }
  }
}
```

### 12.1.1. Response Structure

The response contains details of the application's Liquibase change sets. The following table describes the structure of the response:

<b>Path</b>	<b>Type</b>	<b>Description</b>
contexts	Object	Application contexts keyed by id
contexts.*.liquibaseBeans.*.changeSets	Array	Change sets made by the Liquibase beans, keyed by bean name.
contexts.*.liquibaseBeans.*.changeSets[].author	String	Author of the change set.
contexts.*.liquibaseBeans.*.changeSets[].changeLog	String	Change log that contains the change set.
contexts.*.liquibaseBeans.*.changeSets[].comments	String	Comments on the change set.
contexts.*.liquibaseBeans.*.changeSets[].contexts	Array	Contexts of the change set.
contexts.*.liquibaseBeans.*.changeSets[].dateExecuted	String	Timestamp of when the change set was executed.
contexts.*.liquibaseBeans.*.changeSets[].deploymentId	String	ID of the deployment that ran the change set.
contexts.*.liquibaseBeans.*.changeSets[].description	String	Description of the change set.
contexts.*.liquibaseBeans.*.changeSets[].execType	String	Execution type of the change set ( <a href="#">EXECUTED</a> , <a href="#">FAILED</a> , <a href="#">SKIPPED</a> , <a href="#">RERAN</a> , <a href="#">MARK_RAN</a> ).
contexts.*.liquibaseBeans.*.changeSets[].id	String	ID of the change set.
contexts.*.liquibaseBeans.*.changeSets[].labels	Array	Labels associated with the change set.
contexts.*.liquibaseBeans.*.changeSets[].checksum	String	Checksum of the change set.
contexts.*.liquibaseBeans.*.changeSets[].orderExecuted	Number	Order of the execution of the change set.
contexts.*.liquibaseBeans.*.changeSets[].tag	String	Tag associated with the change set, if any.
contexts.*.parentId	String	Id of the parent application context, if any.

# Chapter 13. Log File (`logfile`)

The `logfile` endpoint provides access to the contents of the application's log file.

## 13.1. Retrieving the Log File

To retrieve the log file, make a `GET` request to `/actuator/logfile`, as shown in the following curl-based example:

```
$ curl 'http://localhost:8080/actuator/logfile' -i -X GET
```

The resulting response is similar to the following:

```
HTTP/1.1 200 OK
Accept-Ranges: bytes
Content-Type: text/plain
Content-Length: 4723

. . . . .
\ \ / _ _ _ ' _ _ _ ( _ ) _ _ _ \ \ \ \ \
( ( ) \ _ _ | ' _ | ' _ | ' _ \ \ _ ' | \ \ \ \
\ \ / _ _ ) | ( _ ) | | | | | | ( _ | ) ) ) )
' | _ _ | . _ | | | | | \ _ , | / / / /
=====|_|=====|_|/_=/_/_/_/
:: Spring Boot ::

2017-08-08 17:12:30.910 INFO 19866 --- [           main]
s.f.SampleWebFreeMarkerApplication      : Starting SampleWebFreeMarkerApplication on
host.local with PID 19866
2017-08-08 17:12:30.913 INFO 19866 --- [           main]
s.f.SampleWebFreeMarkerApplication      : No active profile set, falling back to
default profiles: default
2017-08-08 17:12:30.952 INFO 19866 --- [           main]
ConfigServletWebServerApplicationContext : Refreshing
org.springframework.boot.web.servlet.context.AnnotationConfigServletWebServerApplication
onContext@76b10754: startup date [Tue Aug 08 17:12:30 BST 2017]; root of context
hierarchy
2017-08-08 17:12:31.878 INFO 19866 --- [           main]
o.s.b.w.embedded.tomcat.TomcatWebServer : Tomcat initialized with port(s): 8080
(http)
2017-08-08 17:12:31.889 INFO 19866 --- [           main]
o.apache.catalina.core.StandardService   : Starting service [Tomcat]
2017-08-08 17:12:31.890 INFO 19866 --- [           main]
org.apache.catalina.core.StandardEngine  : Starting Servlet Engine: Apache
Tomcat/8.5.16
2017-08-08 17:12:31.978 INFO 19866 --- [ost-startStop-1]
o.a.c.c.C.[Tomcat].[localhost].[/]       : Initializing Spring embedded
WebApplicationContext
```

```
2017-08-08 17:12:31.978 INFO 19866 --- [ost-startStop-1]
o.s.web.context.ContextLoader : Root WebApplicationContext: initialization
completed in 1028 ms
2017-08-08 17:12:32.080 INFO 19866 --- [ost-startStop-1]
o.s.b.w.servlet.ServletRegistrationBean : Mapping servlet: 'dispatcherServlet' to [/]
2017-08-08 17:12:32.084 INFO 19866 --- [ost-startStop-1]
o.s.b.w.servlet.FilterRegistrationBean : Mapping filter: 'characterEncodingFilter'
to: [//*]
2017-08-08 17:12:32.084 INFO 19866 --- [ost-startStop-1]
o.s.b.w.servlet.FilterRegistrationBean : Mapping filter: 'hiddenHttpMethodFilter'
to: [//*]
2017-08-08 17:12:32.084 INFO 19866 --- [ost-startStop-1]
o.s.b.w.servlet.FilterRegistrationBean : Mapping filter: 'httpPutFormContentFilter'
to: [//*]
2017-08-08 17:12:32.084 INFO 19866 --- [ost-startStop-1]
o.s.b.w.servlet.FilterRegistrationBean : Mapping filter: 'requestContextFilter' to:
[//*]
2017-08-08 17:12:32.349 INFO 19866 --- [           main]
s.w.s.m.m.a.RequestMappingHandlerAdapter : Looking for @ControllerAdvice:
org.springframework.boot.web.servlet.context.AnnotationConfigServletWebServerApplication@76b10754: startup date [Tue Aug 08 17:12:30 BST 2017]; root of context
hierarchy
2017-08-08 17:12:32.420 INFO 19866 --- [           main]
s.w.s.m.m.a.RequestMappingHandlerMapping : Mapped "{[/error]}" onto public
org.springframework.http.ResponseEntity<java.util.Map<java.lang.String,
java.lang.Object>>
org.springframework.boot.autoconfigure.web.servlet.error.BasicErrorController.error(ja
vax.servlet.http.HttpServletRequest)
2017-08-08 17:12:32.421 INFO 19866 --- [           main]
s.w.s.m.m.a.RequestMappingHandlerMapping : Mapped "{[/error],produces=[text/html]}"
onto public org.springframework.web.servlet.ModelAndView
org.springframework.boot.autoconfigure.web.servlet.error.BasicErrorController.errorHtm
l(javax.servlet.http.HttpServletRequest,javax.servlet.http.HttpServletResponse)
2017-08-08 17:12:32.444 INFO 19866 --- [           main]
o.s.w.s.handler.SimpleUrlHandlerMapping : Mapped URL path [/webjars/**] onto handler
of type [class org.springframework.web.servlet.resource.ResourceHttpRequestHandler]
2017-08-08 17:12:32.444 INFO 19866 --- [           main]
o.s.w.s.handler.SimpleUrlHandlerMapping : Mapped URL path [/**] onto handler of type
[class org.springframework.web.servlet.resource.ResourceHttpRequestHandler]
2017-08-08 17:12:32.471 INFO 19866 --- [           main]
o.s.w.s.handler.SimpleUrlHandlerMapping : Mapped URL path [/**/favicon.ico] onto
handler of type [class
org.springframework.web.servlet.resource.ResourceHttpRequestHandler]
2017-08-08 17:12:32.600 INFO 19866 --- [           main]
o.s.w.s.v.f.FreeMarkerConfigurer : ClassTemplateLoader for Spring macros added
to FreeMarker configuration
2017-08-08 17:12:32.681 INFO 19866 --- [           main]
o.s.j.e.a.AnnotationMBeanExporter : Registering beans for JMX exposure on
startup
2017-08-08 17:12:32.744 INFO 19866 --- [           main]
o.s.b.w.embedded.tomcat.TomcatWebServer : Tomcat started on port(s): 8080 (http)
```

```
2017-08-08 17:12:32.750 INFO 19866 --- [           main]
s.f.SampleWebFreeMarkerApplication      : Started SampleWebFreeMarkerApplication in
2.172 seconds (JVM running for 2.479)
```

## 13.2. Retrieving Part of the Log File



Retrieving part of the log file is not supported when using Jersey.

To retrieve part of the log file, make a `GET` request to `/actuator/logfile` by using the `Range` header, as shown in the following curl-based example:

```
$ curl 'http://localhost:8080/actuator/logfile' -i -X GET \
-H 'Range: bytes=0-1023'
```

The preceding example retrieves the first 1024 bytes of the log file. The resulting response is similar to the following:

```
HTTP/1.1 206 Partial Content
Accept-Ranges: bytes
Content-Type: text/plain
Content-Range: bytes 0-1023/4723
Content-Length: 1024
```

```
.-----'
/\ / ____'_ _ _ _(_)_ _ _ _ _ \ \ \ \ \
(( ))\___| '_| '_| | '_` | \ \ \ \ \
\ \ \_ )|_|_|_|_|_| || (_|_| ) ) ) )
' |_____| .__|_|_|_|_|_|_|_\_,_| / / / /
=====|_|=====|_|=/_/_/_/
:: Spring Boot ::
```

```
2017-08-08 17:12:30.910 INFO 19866 --- [           main]
s.f.SampleWebFreeMarkerApplication      : Starting SampleWebFreeMarkerApplication on
host.local with PID 19866
2017-08-08 17:12:30.913 INFO 19866 --- [           main]
s.f.SampleWebFreeMarkerApplication      : No active profile set, falling back to
default profiles: default
2017-08-08 17:12:30.952 INFO 19866 --- [           main]
ConfigServletWebServerApplicationContext : Refreshing
org.springframework.boot.web.servlet.context.AnnotationConfigServletWebServerApplication
onContext@76b10754: startup date [Tue Aug 08 17:12:30 BST 2017]; root of context
hierarchy
2017-08-08 17:12:31.878 INFO 19866 --- [           main]
o.s.b.w.embedded.tomcat.TomcatWebServer : Tomcat initialized with port(
```

# Chapter 14. Loggers (loggers)

The `loggers` endpoint provides access to the application's loggers and the configuration of their levels.

## 14.1. Retrieving All Loggers

To retrieve the application's loggers, make a `GET` request to `/actuator/loggers`, as shown in the following curl-based example:

```
$ curl 'http://localhost:8080/actuator/loggers' -i -X GET
```

The resulting response is similar to the following:

```
HTTP/1.1 200 OK
Content-Type: application/vnd.spring-boot.actuator.v2+json; charset=UTF-8
Content-Length: 283

{
  "levels" : [ "OFF", "FATAL", "ERROR", "WARN", "INFO", "DEBUG", "TRACE" ],
  "loggers" : {
    "ROOT" : {
      "configuredLevel" : "INFO",
      "effectiveLevel" : "INFO"
    },
    "com.example" : {
      "configuredLevel" : "DEBUG",
      "effectiveLevel" : "DEBUG"
    }
  }
}
```

### 14.1.1. Response Structure

The response contains details of the application's loggers. The following table describes the structure of the response:

Path	Type	Description
<code>levels</code>	Array	Levels support by the logging system.
<code>loggers</code>	Object	Loggers keyed by name.
<code>loggers.*.configuredLevel</code>	String	Configured level of the logger, if any.
<code>loggers.*.effectiveLevel</code>	String	Effective level of the logger.

## 14.2. Retrieving a Single Logger

To retrieve a single logger, make a **GET** request to `/actuator/loggers/{logger.name}`, as shown in the following curl-based example:

```
$ curl 'http://localhost:8080/actuator/loggers/com.example' -i -X GET
```

The preceding example retrieves information about the logger named `com.example`. The resulting response is similar to the following:

```
HTTP/1.1 200 OK
Content-Disposition: inline;filename=f.txt
Content-Type: application/vnd.spring-boot.actuator.v2+json;charset=UTF-8
Content-Length: 61

{
  "configuredLevel" : "INFO",
  "effectiveLevel" : "INFO"
}
```

### 14.2.1. Response Structure

The response contains details of the requested logger. The following table describes the structure of the response:

Path	Type	Description
<code>configuredLevel</code>	<code>String</code>	Configured level of the logger, if any.
<code>effectiveLevel</code>	<code>String</code>	Effective level of the logger.

## 14.3. Setting a Log Level

To set the level of a logger, make a **POST** request to `/actuator/loggers/{logger.name}` with a JSON body that specifies the configured level for the logger, as shown in the following curl-based example:

```
$ curl 'http://localhost:8080/actuator/loggers/com.example' -i -X POST \
-H 'Content-Type: application/json' \
-d '{"configuredLevel":"debug"}'
```

The preceding example sets the `configuredLevel` of the `com.example` logger to `DEBUG`.

### 14.3.1. Request Structure

The request specifies the desired level of the logger. The following table describes the structure of

the request:

Path	Type	Description
configuredLevel	String	Level for the logger. May be omitted to clear the level.

## 14.4. Clearing a Log Level

To clear the level of a logger, make a `POST` request to `/actuator/loggers/{logger.name}` with a JSON body containing an empty object, as shown in the following curl-based example:

```
$ curl 'http://localhost:8080/actuator/loggers/com.example' -i -X POST \
-H 'Content-Type: application/json' \
-d '{}'
```

The preceding example clears the configured level of the `com.example` logger.

# Chapter 15. Mappings ([mappings](#))

The [mappings](#) endpoint provides information about the application's request mappings.

## 15.1. Retrieving the Mappings

To retrieve the mappings, make a [GET](#) request to [/actuator/mappings](#), as shown in the following curl-based example:

```
$ curl 'http://localhost:34532/actuator/mappings' -i -X GET
```

The resulting response is similar to the following:

```
HTTP/1.1 200 OK
Content-Type: application/vnd.spring-boot.actuator.v2+json; charset=UTF-8
Transfer-Encoding: chunked
Date: Mon, 30 Jul 2018 14:13:34 GMT
Content-Length: 6505

{
  "contexts" : {
    "application" : {
      "mappings" : {
        "dispatcherServlets" : {
          "dispatcherServlet" : [ {
            "handler" : "ResourceHttpRequestHandler [locations=[class path resource [META-INF/resources/], class path resource [resources/], class path resource [static/], class path resource [public/], ServletContext resource [/], class path resource []], resolvers=[org.springframework.web.servlet.resource.PathResourceResolver@1f7bdd51]], predicate" : "/**/favicon.ico"
          }, {
            "handler" : "public java.lang.Object
org.springframework.boot.actuate.endpoint.web.servlet.AbstractWebMvcEndpointHandlerMapping$OperationHandler.handle(javax.servlet.http.HttpServletRequest,java.util.Map<java.lang.String, java.lang.String>)",
              "predicate" :
              "[{/actuator/mappings},methods=[GET],produces=[application/vnd.spring-boot.actuator.v2+json || application/json]]",
              "details" : {
                "handlerMethod" : {
                  "className" :
"org.springframework.boot.actuate.endpoint.web.servlet.AbstractWebMvcEndpointHandlerMapping$OperationHandler",
                  "name" : "handle",
                  "descriptor" :
"(Ljavax/servlet/http/HttpServletRequest;Ljava/util/Map;)Ljava/lang/Object;"
              },
            }
          }
        }
      }
    }
  }
}
```

```

    "requestMappingConditions" : {
        "consumes" : [ ],
        "headers" : [ ],
        "methods" : [ "GET" ],
        "params" : [ ],
        "patterns" : [ "/actuator/mappings" ],
        "produces" : [ {
            "mediaType" : "application/vnd.spring-boot.actuator.v2+json",
            "negated" : false
        }, {
            "mediaType" : "application/json",
            "negated" : false
        } ]
    }
},
{
    "handler" : "protected java.util.Map<java.lang.String,
java.util.Map<java.lang.String, org.springframework.boot.actuate.endpoint.web.Link>>
org.springframework.boot.actuate.endpoint.web.servlet.WebMvcEndpointHandlerMapping.links(javax.servlet.http.HttpServletRequest,javax.servlet.http.HttpServletResponse)",
    "predicate" :
"{{[actuator],methods=[GET],produces=[application/vnd.spring-boot.actuator.v2+json || application/json]}",
    "details" : {
        "handlerMethod" : {
            "className" :
"org.springframework.boot.actuate.endpoint.web.servlet.WebMvcEndpointHandlerMapping",
            "name" : "links",
            "descriptor" :
"(Ljavax/servlet/http/HttpServletRequest;Ljavax/servlet/http/HttpServletResponse;)Ljava/
util/Map;"
        },
        "requestMappingConditions" : {
            "consumes" : [ ],
            "headers" : [ ],
            "methods" : [ "GET" ],
            "params" : [ ],
            "patterns" : [ "/actuator" ],
            "produces" : [ {
                "mediaType" : "application/vnd.spring-boot.actuator.v2+json",
                "negated" : false
            }, {
                "mediaType" : "application/json",
                "negated" : false
            } ]
        }
    }
},
{
    "handler" : "public java.lang.String
org.springframework.boot.actuate.autoconfigure.endpoint.web.documentation.MappingsEndp
ointServletDocumentationTests$ExampleController.example()",

```

```

"predicate" : "[/,methods=[POST],params=[a!=alpha],headers=[X-Custom=Foo],consumes=[application/json || !application/xml],produces=[text/plain]]",
"details" : {
    "handlerMethod" : {
        "className" :
"org.springframework.boot.actuate.autoconfigure.endpoint.web.documentation.MappingsEndpointServletDocumentationTests.ExampleController",
        "name" : "example",
        "descriptor" : "()Ljava/lang/String;"
    },
    "requestMappingConditions" : {
        "consumes" : [ {
            "mediaType" : "application/json",
            "negated" : false
        }, {
            "mediaType" : "application/xml",
            "negated" : true
        } ],
        "headers" : [ {
            "name" : "X-Custom",
            "value" : "Foo",
            "negated" : false
        } ],
        "methods" : [ "POST" ],
        "params" : [ {
            "name" : "a",
            "value" : "alpha",
            "negated" : true
        } ],
        "patterns" : [ "/" ],
        "produces" : [ {
            "mediaType" : "text/plain",
            "negated" : false
        } ]
    }
},
{
    "handler" : "ResourceHttpRequestHandler [locations=[class path resource [META-INF/resources/webjars/]],resolvers=[org.springframework.web.servlet.resource.PathResourceResolver@3a88ff44]]",
    "predicate" : "/webjars/**"
},
{
    "handler" : "ResourceHttpRequestHandler [locations=[class path resource [META-INF/resources/], class path resource [resources/], class path resource [static/], class path resource [public/], ServletContext resource [/]],resolvers=[org.springframework.web.servlet.resource.PathResourceResolver@5eb97b5b]]",
    "predicate" : "/**"
}
},
{
    "servletFilters" : [ {
        "servletNameMappings" : [ ],

```

```

        "urlPatternMappings" : [ "/" ],
        "name" : "requestContextFilter",
        "className" :
"org.springframework.boot.web.servlet.filter.OrderedRequestContextFilter"
    }, {
        "servletNameMappings" : [ ],
        "urlPatternMappings" : [ "/" ],
        "name" : "httpPutFormContentFilter",
        "className" :
"org.springframework.boot.web.servlet.filter.OrderedHttpPutFormContentFilter"
    }, {
        "servletNameMappings" : [ ],
        "urlPatternMappings" : [ "/" ],
        "name" : "hiddenHttpMethodFilter",
        "className" :
"org.springframework.boot.web.servlet.filter.OrderedHiddenHttpMethodFilter"
    } ],
    "servlets" : [ {
        "mappings" : [ ],
        "name" : "default",
        "className" : "org.apache.catalina.servlets.DefaultServlet"
    }, {
        "mappings" : [ "/" ],
        "name" : "dispatcherServlet",
        "className" : "org.springframework.web.servlet.DispatcherServlet"
    } ]
}
}
}
}

```

### 15.1.1. Response Structure

The response contains details of the application's mappings. The items found in the response depend on the type of web application (reactive or Servlet-based). The following table describes the structure of the common elements of the response:

Path	Type	Description
contexts	Object	Application contexts keyed by id.
contexts.*.mappings	Object	Mappings in the context, keyed by mapping type.
contexts.*.mappings.dispatcherServlets	Object	Dispatcher servlet mappings, if any.
contexts.*.mappings.servletFilters	Array	Servlet filter mappings, if any.
contexts.*.mappings.servlets	Array	Servlet mappings, if any.
contexts.*.mappings.dispatcherHandlers	Object	Dispatcher handler mappings, if any.

Path	Type	Description
contexts.*.parentId	String	Id of the parent application context, if any.

The entries that may be found in `contexts.*.mappings` are described in the following sections.

## 15.1.2. Dispatcher Servlets Response Structure

When using Spring MVC, the response contains details of any `DispatcherServlet` request mappings beneath `contexts.*.mappings.dispatcherServlets`. The following table describes the structure of this section of the response:

Path	Type	Description
*	Array	Dispatcher servlet mappings, if any, keyed by dispatcher servlet bean name.
*.[].details	Object	Additional implementation-specific details about the mapping. Optional.
*.[].handler	String	Handler for the mapping.
*.[].predicate	String	Predicate for the mapping.
*.[].details.handlerMethod	Object	Details of the method, if any, that will handle requests to this mapping.
*.[].details.handlerMethod.className	String	Fully qualified name of the class of the method.
*.[].details.handlerMethod.name	String	Name of the method.
*.[].details.handlerMethod.descriptor	String	Descriptor of the method as specified in the Java Language Specification.
*.[].details.requestMappingConditions	Object	Details of the request mapping conditions.
*.[].details.requestMappingConditions.consumes	Array	Details of the consumes condition
*.[].details.requestMappingConditions.consumes[].mediaType	String	Consumed media type.
*.[].details.requestMappingConditions.consumes[].negated	Boolean	Whether the media type is negated.
*.[].details.requestMappingConditions.headers	Array	Details of the headers condition.
*.[].details.requestMappingConditions.headers[].name	String	Name of the header.

Path	Type	Description
<code>*.[].details.requestMappingConditions.headers.[].value</code>	<code>String</code>	Required value of the header, if any.
<code>*.[].details.requestMappingConditions.headers.[].negated</code>	<code>Boolean</code>	Whether the value is negated.
<code>*.[].details.requestMappingConditions.methods</code>	<code>Array</code>	HTTP methods that are handled.
<code>*.[].details.requestMappingConditions.params</code>	<code>Array</code>	Details of the params condition.
<code>*.[].details.requestMappingConditions.params.[].name</code>	<code>String</code>	Name of the parameter.
<code>*.[].details.requestMappingConditions.params.[].value</code>	<code>String</code>	Required value of the parameter, if any.
<code>*.[].details.requestMappingConditions.params.[].negated</code>	<code>Boolean</code>	Whether the value is negated.
<code>*.[].details.requestMappingConditions.patterns</code>	<code>Array</code>	Patterns identifying the paths handled by the mapping.
<code>*.[].details.requestMappingConditions.produces</code>	<code>Array</code>	Details of the produces condition.
<code>*.[].details.requestMappingConditions.produces.[].mediaType</code>	<code>String</code>	Produced media type.
<code>*.[].details.requestMappingConditions.produces.[].negated</code>	<code>Boolean</code>	Whether the media type is negated.

### 15.1.3. Servlets Response Structure

When using the Servlet stack, the response contains details of any `Servlet` mappings beneath `contexts.*.mappings.servlets`. The following table describes the structure of this section of the response:

Path	Type	Description
<code>[].mappings</code>	<code>Array</code>	Mappings of the servlet.
<code>[].name</code>	<code>String</code>	Name of the servlet.
<code>[].className</code>	<code>String</code>	Class name of the servlet

### 15.1.4. Servlet Filters Response Structure

When using the Servlet stack, the response contains details of any `Filter` mappings beneath `contexts.*.mappings.servletFilters`. The following table describes the structure of this section of the response:

Path	Type	Description
[].servletNameMappings	Array	Names of the servlets to which the filter is mapped.
[].urlPatternMappings	Array	URL pattern to which the filter is mapped.
[].name	String	Name of the filter.
[].className	String	Class name of the filter

### 15.1.5. Dispatcher Handlers Response Structure

When using Spring WebFlux, the response contains details of any `DispatcherHandler` request mappings beneath `contexts.*.mappings.dispatcherHandlers`. The following table describes the structure of this section of the response:

Path	Type	Description
*	Array	Dispatcher handler mappings, if any, keyed by dispatcher handler bean name.
*.[].details	Object	Additional implementation-specific details about the mapping. Optional.
*.[].handler	String	Handler for the mapping.
*.[].predicate	String	Predicate for the mapping.
*.[].details.requestMappingConditions	Object	Details of the request mapping conditions.
*.[].details.requestMappingConditions.consumes	Array	Details of the consumes condition
*.[].details.requestMappingConditions.consumes.[].mediaType	String	Consumed media type.
*.[].details.requestMappingConditions.consumes.[].negated	Boolean	Whether the media type is negated.
*.[].details.requestMappingConditions.headers	Array	Details of the headers condition.
*.[].details.requestMappingConditions.headers.[].name	String	Name of the header.
*.[].details.requestMappingConditions.headers.[].value	String	Required value of the header, if any.
*.[].details.requestMappingConditions.headers.[].negated	Boolean	Whether the value is negated.
*.[].details.requestMappingConditions.methods	Array	HTTP methods that are handled.

<b>Path</b>	<b>Type</b>	<b>Description</b>
<code>*.[].details.requestMappingConditions.params</code>	<code>Array</code>	Details of the params condition.
<code>*.[].details.requestMappingConditions.params.[].name</code>	<code>String</code>	Name of the parameter.
<code>*.[].details.requestMappingConditions.params.[].value</code>	<code>String</code>	Required value of the parameter, if any.
<code>*.[].details.requestMappingConditions.params.[].negated</code>	<code>Boolean</code>	Whether the value is negated.
<code>*.[].details.requestMappingConditions.patterns</code>	<code>Array</code>	Patterns identifying the paths handled by the mapping.
<code>*.[].details.requestMappingConditions.produces</code>	<code>Array</code>	Details of the produces condition.
<code>*.[].details.requestMappingConditions.produces.[].mediaType</code>	<code>String</code>	Produced media type.
<code>*.[].details.requestMappingConditions.produces.[].negated</code>	<code>Boolean</code>	Whether the media type is negated.
<code>*.[].details.handlerMethod</code>	<code>Object</code>	Details of the method, if any, that will handle requests to this mapping.
<code>*.[].details.handlerMethod.className</code>	<code>String</code>	Fully qualified name of the class of the method.
<code>*.[].details.handlerMethod.name</code>	<code>String</code>	Name of the method.
<code>*.[].details.handlerMethod.descriptor</code>	<code>String</code>	Descriptor of the method as specified in the Java Language Specification.
<code>*.[].details.handlerFunction</code>	<code>Object</code>	Details of the function, if any, that will handle requests to this mapping.
<code>*.[].details.handlerFunction.className</code>	<code>String</code>	Fully qualified name of the class of the function.

# Chapter 16. Metrics (`metrics`)

The `metrics` endpoint provides access to application metrics.

## 16.1. Retrieving Metric Names

To retrieve the names of the available metrics, make a `GET` request to `/actuator/metrics`, as shown in the following curl-based example:

```
$ curl 'http://localhost:8080/actuator/metrics' -i -X GET
```

The resulting response is similar to the following:

```
HTTP/1.1 200 OK
Content-Type: application/vnd.spring-boot.actuator.v2+json; charset=UTF-8
Content-Length: 154

{
  "names" : [ "jvm.memory.max", "jvm.memory.used", "jvm.memory.committed",
  "jvm.buffer.memory.used", "jvm.buffer.count", "jvm.buffer.total.capacity" ]
}
```

### 16.1.1. Response Structure

The response contains details of the metric names. The following table describes the structure of the response:

Path	Type	Description
<code>names</code>	Array	Names of the known metrics.

## 16.2. Retrieving a Metric

To retrieve a metric, make a `GET` request to `/actuator/metrics/{metric.name}`, as shown in the following curl-based example:

```
$ curl 'http://localhost:8080/actuator/metrics/jvm.memory.max' -i -X GET
```

The preceding example retrieves information about the metric named `jvm.memory.max`. The resulting response is similar to the following:

```
HTTP/1.1 200 OK
Content-Disposition: inline;filename=f.txt
Content-Type: application/vnd.spring-boot.actuator.v2+json;charset=UTF-8
Content-Length: 474
```

```
{
  "name" : "jvm.memory.max",
  "description" : "The maximum amount of memory in bytes that can be used for memory management",
  "baseUnit" : "bytes",
  "measurements" : [ {
    "statistic" : "VALUE",
    "value" : 2.382888959E9
  }],
  "availableTags" : [ {
    "tag" : "area",
    "values" : [ "heap", "nonheap" ]
  }, {
    "tag" : "id",
    "values" : [ "Compressed Class Space", "PS Survivor Space", "PS Old Gen",
    "Metaspace", "PS Eden Space", "Code Cache" ]
  }
}
```

### 16.2.1. Query Parameters

The endpoint uses query parameters to [drill down](#) into a metric by using its tags. The following table shows the single supported query parameter:

Parameter	Description
tag	A tag to use for drill-down in the form <code>name:value</code> .

### 16.2.2. Response structure

The response contains details of the metric. The following table describes the structure of the response:

Path	Type	Description
<code>name</code>	<code>String</code>	Name of the metric
<code>description</code>	<code>String</code>	Description of the metric
<code>baseUnit</code>	<code>String</code>	Base unit of the metric
<code>measurements</code>	<code>Array</code>	Measurements of the metric

Path	Type	Description
measurements[].statistic	String	Statistic of the measurement. (TOTAL, TOTAL_TIME, COUNT, MAX, VALUE, UNKNOWN, ACTIVE_TASKS, DURATION).
measurements[].value	Number	Value of the measurement.
availableTags	Array	Tags that are available for drill-down.
availableTags[].tag	String	Name of the tag.
availableTags[].values	Array	Possible values of the tag.

## 16.3. Drilling Down

To drill down into a metric, make a `GET` request to `/actuator/metrics/{metric.name}` using the `tag` query parameter, as shown in the following curl-based example:

```
$ curl
'http://localhost:8080/actuator/metrics/jvm.memory.max?tag=area%3Aonheap&tag=id%3ACom
pressed+Class+Space' -i -X GET
```

The preceding example retrieves the `jvm.memory.max` metric, where the `area` tag has a value of `nonheap` and the `id` attribute has a value of `Compressed Class Space`. The resulting response is similar to the following:

```
HTTP/1.1 200 OK
Content-Disposition: inline;filename=f.txt
Content-Type: application/vnd.spring-boot.actuator.v2+json;charset=UTF-8
Content-Length: 263

{
  "name" : "jvm.memory.max",
  "description" : "The maximum amount of memory in bytes that can be used for memory management",
  "baseUnit" : "bytes",
  "measurements" : [ {
    "statistic" : "VALUE",
    "value" : 1.073741824E9
  }],
  "availableTags" : [ ]
}
```

# Chapter 17. Prometheus (`prometheus`)

The `prometheus` endpoint provides Spring Boot application's metrics in the format required for scraping by a Prometheus server.

## 17.1. Retrieving the Metrics

To retrieve the metrics, make a `GET` request to `/actuator/prometheus`, as shown in the following curl-based example:

```
$ curl 'http://localhost:8080/actuator/prometheus' -i -X GET
```

The resulting response is similar to the following:

HTTP/1.1 200 OK

Content-Type: text/plain;version=0.0.4;charset=utf-8

Content-Length: 2337

```
# HELP jvm_buffer_count An estimate of the number of buffers in the pool
# TYPE jvm_buffer_count gauge
jvm_buffer_count{id="direct",} 3.0
jvm_buffer_count{id="mapped",} 0.0
# HELP jvm_memory_used_bytes The amount of used memory
# TYPE jvm_memory_used_bytes gauge
jvm_memory_used_bytes{area="nonheap",id="Code Cache",} 5.1867776E7
jvm_memory_used_bytes{area="nonheap",id="Metaspace",} 1.32233056E8
jvm_memory_used_bytes{area="nonheap",id="Compressed Class Space",} 1.7790472E7
jvm_memory_used_bytes{area="heap",id="PS Eden Space",} 1.33577776E8
jvm_memory_used_bytes{area="heap",id="PS Survivor Space",} 9241512.0
jvm_memory_used_bytes{area="heap",id="PS Old Gen",} 1.51023928E8
# HELP jvm_buffer_total_capacity_bytes An estimate of the total capacity of the
buffers in this pool
# TYPE jvm_buffer_total_capacity_bytes gauge
jvm_buffer_total_capacity_bytes{id="direct",} 28051.0
jvm_buffer_total_capacity_bytes{id="mapped",} 0.0
# HELP jvm_buffer_memory_used_bytes An estimate of the memory that the Java virtual
machine is using for this buffer pool
# TYPE jvm_buffer_memory_used_bytes gauge
jvm_buffer_memory_used_bytes{id="direct",} 28052.0
jvm_buffer_memory_used_bytes{id="mapped",} 0.0
# HELP jvm_memory_committed_bytes The amount of memory in bytes that is committed for
the Java virtual machine to use
# TYPE jvm_memory_committed_bytes gauge
jvm_memory_committed_bytes{area="nonheap",id="Code Cache",} 5.2625408E7
jvm_memory_committed_bytes{area="nonheap",id="Metaspace",} 1.40115968E8
jvm_memory_committed_bytes{area="nonheap",id="Compressed Class Space",} 1.9529728E7
jvm_memory_committed_bytes{area="heap",id="PS Eden Space",} 3.2505856E8
jvm_memory_committed_bytes{area="heap",id="PS Survivor Space",} 1.6252928E7
jvm_memory_committed_bytes{area="heap",id="PS Old Gen",} 4.11041792E8
# HELP jvm_memory_max_bytes The maximum amount of memory in bytes that can be used for
memory management
# TYPE jvm_memory_max_bytes gauge
jvm_memory_max_bytes{area="nonheap",id="Code Cache",} 2.5165824E8
jvm_memory_max_bytes{area="nonheap",id="Metaspace",} -1.0
jvm_memory_max_bytes{area="nonheap",id="Compressed Class Space",} 1.073741824E9
jvm_memory_max_bytes{area="heap",id="PS Eden Space",} 3.2505856E8
jvm_memory_max_bytes{area="heap",id="PS Survivor Space",} 1.6252928E7
jvm_memory_max_bytes{area="heap",id="PS Old Gen",} 7.16177408E8
```

# Chapter 18. Scheduled Tasks (scheduledtasks)

The `scheduledtasks` endpoint provides information about the application's scheduled tasks.

## 18.1. Retrieving the Scheduled Tasks

To retrieve the scheduled tasks, make a `GET` request to `/actuator/scheduledtasks`, as shown in the following curl-based example:

```
$ curl 'http://localhost:8080/actuator/scheduledtasks' -i -X GET
```

The resulting response is similar to the following:

```
HTTP/1.1 200 OK
Content-Type: application/vnd.spring-boot.actuator.v2+json; charset=UTF-8
Content-Length: 451

{
  "cron" : [ {
    "runnable" : {
      "target" : "com.example.Processor.processOrders"
    },
    "expression" : "0 0 0/3 1/1 * ?"
  }],
  "fixedDelay" : [ {
    "runnable" : {
      "target" : "com.example.Processor.purge"
    },
    "initialDelay" : 5000,
    "interval" : 5000
  }],
  "fixedRate" : [ {
    "runnable" : {
      "target" : "com.example.Processor.retrieveIssues"
    },
    "initialDelay" : 10000,
    "interval" : 3000
  }]
}
```

### 18.1.1. Response Structure

The response contains details of the application's scheduled tasks. The following table describes the structure of the response:

<b>Path</b>	<b>Type</b>	<b>Description</b>
<code>cron</code>	<code>Array</code>	Cron tasks, if any.
<code>cron.[] runnable.target</code>	<code>String</code>	Target that will be executed.
<code>cron.[] .expression</code>	<code>String</code>	Cron expression.
<code>fixedDelay</code>	<code>Array</code>	Fixed delay tasks, if any.
<code>fixedDelay.[] runnable.target</code>	<code>String</code>	Target that will be executed.
<code>fixedDelay.[] .initialDelay</code>	<code>Number</code>	Delay, in milliseconds, before first execution.
<code>fixedDelay.[] .interval</code>	<code>Number</code>	Interval, in milliseconds, between the end of the last execution and the start of the next.
<code>fixedRate</code>	<code>Array</code>	Fixed rate tasks, if any.
<code>fixedRate.[] runnable.target</code>	<code>String</code>	Target that will be executed.
<code>fixedRate.[] .interval</code>	<code>Number</code>	Interval, in milliseconds, between the start of each execution.
<code>fixedRate.[] .initialDelay</code>	<code>Number</code>	Delay, in milliseconds, before first execution.

# Chapter 19. Sessions (`sessions`)

The `sessions` endpoint provides information about the application's HTTP sessions that are managed by Spring Session.

## 19.1. Retrieving Sessions

To retrieve the sessions, make a `GET` request to `/actuator/sessions`, as shown in the following curl-based example:

```
$ curl 'http://localhost:8080/actuator/sessions?username=alice' -i -X GET
```

The preceding examples retrieves all of the sessions for the user whose username is `alice`.

The resulting response is similar to the following:

```
HTTP/1.1 200 OK
Content-Type: application/vnd.spring-boot.actuator.v2+json; charset=UTF-8
Content-Length: 753

{
  "sessions" : [ {
    "id" : "4686b833-b9d6-46b8-8c34-70a783c1e127",
    "attributeNames" : [ ],
    "creationTime" : "2018-07-30T12:13:37.152Z",
    "lastAccessedTime" : "2018-07-30T14:13:25.152Z",
    "maxInactiveInterval" : 1800,
    "expired" : false
  }, {
    "id" : "4db5efcc-99cb-4d05-a52c-b49acfbb7ea9",
    "attributeNames" : [ ],
    "creationTime" : "2018-07-30T09:13:37.152Z",
    "lastAccessedTime" : "2018-07-30T14:13:00.152Z",
    "maxInactiveInterval" : 1800,
    "expired" : false
  }, {
    "id" : "77be7674-d71f-435e-b327-550a96f5af17",
    "attributeNames" : [ ],
    "creationTime" : "2018-07-30T02:13:37.151Z",
    "lastAccessedTime" : "2018-07-30T14:12:52.152Z",
    "maxInactiveInterval" : 1800,
    "expired" : false
  } ]
}
```

### 19.1.1. Query Parameters

The endpoint uses query parameters to limit the sessions that it returns. The following table shows the single required query parameter:

Parameter	Description
username	Name of the user.

### 19.1.2. Response Structure

The response contains details of the matching sessions. The following table describes the structure of the response:

Path	Type	Description
sessions	Array	Sessions for the given username.
sessions.[].id	String	ID of the session.
sessions.[].attributeNames	Array	Names of the attributes stored in the session.
sessions.[].creationTime	String	Timestamp of when the session was created.
sessions.[].lastAccessedTime	String	Timestamp of when the session was last accessed.
sessions.[].maxInactiveInterval	Number	Maximum permitted period of inactivity, in seconds, before the session will expire.
sessions.[].expired	Boolean	Whether the session has expired.

## 19.2. Retrieving a Single Session

To retrieve a single session, make a `GET` request to `/actuator/sessions/{id}`, as shown in the following curl-based example:

```
$ curl 'http://localhost:8080/actuator/sessions/4db5efcc-99cb-4d05-a52c-b49acfbb7ea9'  
-i -X GET
```

The preceding example retrieves the session with the `id` of `4db5efcc-99cb-4d05-a52c-b49acfbb7ea9`. The resulting response is similar to the following:

```
HTTP/1.1 200 OK
Content-Type: application/vnd.spring-boot.actuator.v2+json; charset=UTF-8
Content-Length: 228
```

```
{
  "id" : "4db5efcc-99cb-4d05-a52c-b49acfbb7ea9",
  "attributeNames" : [ ],
  "creationTime" : "2018-07-30T09:13:37.152Z",
  "lastAccessedTime" : "2018-07-30T14:13:00.152Z",
  "maxInactiveInterval" : 1800,
  "expired" : false
}
```

## 19.2.1. Response Structure

The response contains details of the requested session. The following table describes the structure of the response:

Path	Type	Description
<code>id</code>	<code>String</code>	ID of the session.
<code>attributeNames</code>	<code>Array</code>	Names of the attributes stored in the session.
<code>creationTime</code>	<code>String</code>	Timestamp of when the session was created.
<code>lastAccessedTime</code>	<code>String</code>	Timestamp of when the session was last accessed.
<code>maxInactiveInterval</code>	<code>Number</code>	Maximum permitted period of inactivity, in seconds, before the session will expire.
<code>expired</code>	<code>Boolean</code>	Whether the session has expired.

## 19.3. Deleting a Session

To delete a session, make a `DELETE` request to `/actuator/sessions/{id}`, as shown in the following curl-based example:

```
$ curl 'http://localhost:8080/actuator/sessions/4db5efcc-99cb-4d05-a52c-b49acfbb7ea9'
-i -X DELETE
```

The preceding example deletes the session with the `id` of `4db5efcc-99cb-4d05-a52c-b49acfbb7ea9`.

# Chapter 20. Shutdown (`shutdown`)

The `shutdown` endpoint is used to shut down the application.

## 20.1. Shutting Down the Application

To shut down the application, make a `POST` request to `/actuator/shutdown`, as shown in the following curl-based example:

```
$ curl 'http://localhost:8080/actuator/shutdown' -i -X POST
```

A response similar to the following is produced:

```
HTTP/1.1 200 OK
Content-Type: application/vnd.spring-boot.actuator.v2+json; charset=UTF-8
Content-Length: 41

{
  "message" : "Shutting down, bye..."
}
```

### 20.1.1. Response Structure

The response contains details of the result of the shutdown request. The following table describes the structure of the response:

Path	Type	Description
<code>message</code>	<code>String</code>	Message describing the result of the request.

# Chapter 21. Thread Dump (`threaddump`)

The `threaddump` endpoint provides a thread dump from the application's JVM.

## 21.1. Retrieving the Thread Dump

To retrieve the thread dump, make a `GET` request to `/actuator/threaddump`, as shown in the following curl-based example:

```
$ curl 'http://localhost:8080/actuator/threaddump' -i -X GET
```

The resulting response is similar to the following:

```
HTTP/1.1 200 OK
Content-Type: application/vnd.spring-boot.actuator.v2+json; charset=UTF-8
Content-Length: 4521

{
  "threads" : [ {
    "threadName" : "Thread-600",
    "threadId" : 1000,
    "blockedTime" : -1,
    "blockedCount" : 0,
    "waitedTime" : -1,
    "waitedCount" : 1,
    "lockOwnerId" : -1,
    "inNative" : false,
    "suspended" : false,
    "threadState" : "TIMED_WAITING",
    "stackTrace" : [ {
      "methodName" : "sleep",
      "fileName" : "Thread.java",
      "lineNumber" : -2,
      "className" : "java.lang.Thread",
      "nativeMethod" : true
    }, {
      "methodName" : "performShutdown",
      "fileName" : "ShutdownEndpoint.java",
      "lineNumber" : 67,
      "className" : "org.springframework.boot.actuate.context.ShutdownEndpoint",
      "nativeMethod" : false
    }, {
      "methodName" : "run",
      "lineNumber" : -1,
      "className" :
"org.springframework.boot.actuate.context.ShutdownEndpoint$$Lambda$1138/1758052088",
      "nativeMethod" : false
    }, {
  }
```

```

        "methodName" : "run",
        "fileName" : "Thread.java",
        "lineNumber" : 748,
        "className" : "java.lang.Thread",
        "nativeMethod" : false
    } ],
    "lockedMonitors" : [ ],
    "lockedSynchronizers" : [ ]
}, {
    "threadName" : "pool-8-thread-1",
    "threadId" : 995,
    "blockedTime" : -1,
    "blockedCount" : 0,
    "waitedTime" : -1,
    "waitedCount" : 1,
    "lockName" :
"java.util.concurrent.locks.AbstractQueuedSynchronizer$ConditionObject@271b7fb1",
    "lockOwnerId" : -1,
    "inNative" : false,
    "suspended" : false,
    "threadState" : "TIMED_WAITING",
    "stackTrace" : [ {
        "methodName" : "park",
        "fileName" : "Unsafe.java",
        "lineNumber" : -2,
        "className" : "sun.misc.Unsafe",
        "nativeMethod" : true
    }, {
        "methodName" : "parkNanos",
        "fileName" : "LockSupport.java",
        "lineNumber" : 215,
        "className" : "java.util.concurrent.locks.LockSupport",
        "nativeMethod" : false
    }, {
        "methodName" : "awaitNanos",
        "fileName" : "AbstractQueuedSynchronizer.java",
        "lineNumber" : 2078,
        "className" :
"java.util.concurrent.locks.AbstractQueuedSynchronizer$ConditionObject",
        "nativeMethod" : false
    }, {
        "methodName" : "take",
        "fileName" : "ScheduledThreadPoolExecutor.java",
        "lineNumber" : 1093,
        "className" :
"java.util.concurrent.ScheduledThreadPoolExecutor$DelayedWorkQueue",
        "nativeMethod" : false
    }, {
        "methodName" : "take",
        "fileName" : "ScheduledThreadPoolExecutor.java",
        "lineNumber" : 809,

```

```
    "className" :  
"java.util.concurrent.ScheduledThreadPoolExecutor$DelayedWorkQueue",  
    "nativeMethod" : false  
, {  
    "methodName" : "getTask",  
    "fileName" : "ThreadPoolExecutor.java",  
    "lineNumber" : 1074,  
    "className" : "java.util.concurrent.ThreadPoolExecutor",  
    "nativeMethod" : false  
, {  
    "methodName" : "runWorker",  
    "fileName" : "ThreadPoolExecutor.java",  
    "lineNumber" : 1134,  
    "className" : "java.util.concurrent.ThreadPoolExecutor",  
    "nativeMethod" : false  
, {  
    "methodName" : "run",  
    "fileName" : "ThreadPoolExecutor.java",  
    "lineNumber" : 624,  
    "className" : "java.util.concurrent.ThreadPoolExecutor$Worker",  
    "nativeMethod" : false  
, {  
    "methodName" : "run",  
    "fileName" : "Thread.java",  
    "lineNumber" : 748,  
    "className" : "java.lang.Thread",  
    "nativeMethod" : false  
} ],  
"lockedMonitors" : [ ],  
"lockedSynchronizers" : [ ],  
"lockInfo" : {  
    "className" :  
"java.util.concurrent.locks.AbstractQueuedSynchronizer$ConditionObject",  
    "identityHashCode" : 656113585  
}  
, {  
    "threadName" : "http-nio-auto-9-34532-AsyncTimeout",  
    "threadId" : 991,  
    "blockedTime" : -1,  
    "blockedCount" : 0,  
    "waitedTime" : -1,  
    "waitedCount" : 6,  
    "lockOwnerId" : -1,  
    "inNative" : false,  
    "suspended" : false,  
    "threadState" : "TIMED_WAITING",  
    "stackTrace" : [ {  
        "methodName" : "sleep",  
        "fileName" : "Thread.java",  
        "lineNumber" : -2,  
        "className" : "java.lang.Thread",
```

```

    "nativeMethod" : true
  }, {
    "methodName" : "run",
    "fileName" : "AbstractProtocol.java",
    "lineNumber" : 1143,
    "className" : "org.apache.coyote.AbstractProtocol$AsyncTimeout",
    "nativeMethod" : false
  }, {
    "methodName" : "run",
    "fileName" : "Thread.java",
    "lineNumber" : 748,
    "className" : "java.lang.Thread",
    "nativeMethod" : false
  } ],
  "lockedMonitors" : [ ],
  "lockedSynchronizers" : [ ]
} ]
}

```

### 21.1.1. Response Structure

The response contains details of the JVM's threads. The following table describes the structure of the response:

Path	Type	Description
<code>threads</code>	Array	JVM's threads.
<code>threads.[].blockedCount</code>	Number	Total number of times that the thread has been blocked.
<code>threads.[].blockedTime</code>	Number	Time in milliseconds that the thread has spent blocked. -1 if thread contention monitoring is disabled.
<code>threads.[].daemon</code>	Boolean	Whether the thread is a daemon thread. Only available on Java 9 or later.
<code>threads.[].inNative</code>	Boolean	Whether the thread is executing native code.
<code>threads.[].lockName</code>	String	Description of the object on which the thread is blocked, if any.
<code>threads.[].lockInfo</code>	Object	Object for which the thread is blocked waiting.
<code>threads.[].lockInfo.className</code>	String	Fully qualified class name of the lock object.

<b>Path</b>	<b>Type</b>	<b>Description</b>
<code>threads.[].lockInfo.identityHashCode</code>	<code>Number</code>	Identity hash code of the lock object.
<code>threads.[].lockedMonitors</code>	<code>Array</code>	Monitors locked by this thread, if any
<code>threads.[].lockedMonitors.[].className</code>	<code>String</code>	Class name of the lock object.
<code>threads.[].lockedMonitors.[].identityHashCode</code>	<code>Number</code>	Identity hash code of the lock object.
<code>threads.[].lockedMonitors.[].lockedStackDepth</code>	<code>Number</code>	Stack depth where the monitor was locked.
<code>threads.[].lockedMonitors.[].lockedStackFrame</code>	<code>Object</code>	Stack frame that locked the monitor.
<code>threads.[].lockedSynchronizers</code>	<code>Array</code>	Synchronizers locked by this thread.
<code>threads.[].lockedSynchronizers.[].className</code>	<code>String</code>	Class name of the locked synchronizer.
<code>threads.[].lockedSynchronizers.[].identifyHashCode</code>	<code>Number</code>	Identity hash code of the locked synchronizer.
<code>threads.[].lockOwnerId</code>	<code>Number</code>	ID of the thread that owns the object on which the thread is blocked. <code>-1</code> if the thread is not blocked.
<code>threads.[].lockOwnerName</code>	<code>String</code>	Name of the thread that owns the object on which the thread is blocked, if any.
<code>threads.[].priority</code>	<code>Number</code>	Priority of the thread. Only available on Java 9 or later.
<code>threads.[].stackTrace</code>	<code>Array</code>	Stack trace of the thread.
<code>threads.[].stackTrace.[].classLoaderName</code>	<code>String</code>	Name of the class loader of the class that contains the execution point identified by this entry, if any. Only available on Java 9 or later.
<code>threads.[].stackTrace.[].className</code>	<code>String</code>	Name of the class that contains the execution point identified by this entry.
<code>threads.[].stackTrace.[].fileName</code>	<code>String</code>	Name of the source file that contains the execution point identified by this entry, if any.

<b>Path</b>	<b>Type</b>	<b>Description</b>
<code>threads.[].stackTrace.[].lineNumber</code>	<code>Number</code>	Line number of the execution point identified by this entry. Negative if unknown.
<code>threads.[].stackTrace.[].methodName</code>	<code>String</code>	Name of the method.
<code>threads.[].stackTrace.[].moduleName</code>	<code>String</code>	Name of the module that contains the execution point identified by this entry, if any. Only available on Java 9 or later.
<code>threads.[].stackTrace.[].moduleVersion</code>	<code>String</code>	Version of the module that contains the execution point identified by this entry, if any. Only available on Java 9 or later.
<code>threads.[].stackTrace.[].nativeMethod</code>	<code>Boolean</code>	Whether the execution point is a native method.
<code>threads.[].suspended</code>	<code>Boolean</code>	Whether the thread is suspended.
<code>threads.[].threadId</code>	<code>Number</code>	ID of the thread.
<code>threads.[].threadName</code>	<code>String</code>	Name of the thread.
<code>threads.[].threadState</code>	<code>String</code>	State of the thread ( <code>NEW</code> , <code>RUNNABLE</code> , <code>BLOCKED</code> , <code>WAITING</code> , <code>TIMED_WAITING</code> , <code>TERMINATED</code> ).
<code>threads.[].waitedCount</code>	<code>Number</code>	Total number of times that the thread has waited for notification.
<code>threads.[].waitedTime</code>	<code>Number</code>	Time in milliseconds that the thread has spent waiting. -1 if thread contention monitoring is disabled