

Spring Boot Actuator Web API Documentation

Andy Wilkinson

Table of Contents

1. Overview	2
1.1. URLs	2
1.2. Timestamps	2
2. Audit Events (auditevents)	3
2.1. Retrieving Audit Events	3
2.1.1. Query Parameters	3
2.1.2. Response Structure	3
3. Beans (beans)	5
3.1. Retrieving the Beans	5
3.1.1. Response Structure	6
4. Caches (caches)	8
4.1. Retrieving All Caches	8
4.1.1. Response Structure	8
4.2. Retrieving Caches by Name	9
4.2.1. Query Parameters	9
4.2.2. Response Structure	9
4.3. Evict All Caches	10
4.4. Evict a Cache by Name	10
4.4.1. Request Structure	10
5. Conditions Evaluation Report (conditions)	11
5.1. Retrieving the Report	11
5.1.1. Response Structure	12
6. Configuration Properties (configprops)	14
6.1. Retrieving the @ConfigurationProperties Bean	14
6.1.1. Response Structure	16
7. Environment (env)	17
7.1. Retrieving the Entire Environment	17
7.1.1. Response Structure	18
7.2. Retrieving a Single Property	19
7.2.1. Response Structure	19
8. Flyway (flyway)	21
8.1. Retrieving the Migrations	21
8.1.1. Response Structure	21
9. Health (health)	23
9.1. Retrieving the Health of the application	23
9.1.1. Response Structure	24
9.2. Retrieving the Health of a component	25
9.2.1. Response Structure	25

9.3. Retrieving the Health of a nested component	26
9.3.1. Response Structure	26
10. Heap Dump (heapdump)	27
10.1. Retrieving the Heap Dump	27
11. HTTP Trace (httptrace)	28
11.1. Retrieving the Traces	28
11.1.1. Response Structure	28
12. Info (info)	30
12.1. Retrieving the Info	30
12.1.1. Response Structure	30
Build Response Structure	30
Git Response Structure	31
13. Spring Integration graph (integrationgraph)	32
13.1. Retrieving the Spring Integration graph	32
13.1.1. Response Structure	33
13.2. Rebuilding the Spring Integration graph	34
14. Liquibase (liquibase)	35
14.1. Retrieving the Changes	35
14.1.1. Response Structure	35
15. Log File (logfile)	37
15.1. Retrieving the Log File	37
15.2. Retrieving Part of the Log File	39
16. Loggers (loggers)	40
16.1. Retrieving All Loggers	40
16.1.1. Response Structure	41
16.2. Retrieving a Single Logger	41
16.2.1. Response Structure	41
16.3. Retrieving a Single Group	42
16.3.1. Response Structure	42
16.4. Setting a Log Level	42
16.4.1. Request Structure	43
16.5. Setting a Log Level for a Group	43
16.5.1. Request Structure	43
16.6. Clearing a Log Level	43
17. Mappings (mappings)	44
17.1. Retrieving the Mappings	44
17.1.1. Response Structure	47
17.1.2. Dispatcher Servlets Response Structure	47
17.1.3. Servlets Response Structure	49
17.1.4. Servlet Filters Response Structure	49
17.1.5. Dispatcher Handlers Response Structure	49

18. Metrics (metrics)	52
18.1. Retrieving Metric Names	52
18.1.1. Response Structure	52
18.2. Retrieving a Metric	52
18.2.1. Query Parameters	53
18.2.2. Response structure	53
18.3. Drilling Down	54
19. Prometheus (prometheus)	55
19.1. Retrieving the Metrics	55
20. Scheduled Tasks (scheduledtasks)	57
20.1. Retrieving the Scheduled Tasks	57
20.1.1. Response Structure	58
21. Sessions (sessions)	59
21.1. Retrieving Sessions	59
21.1.1. Query Parameters	60
21.1.2. Response Structure	60
21.2. Retrieving a Single Session	60
21.2.1. Response Structure	61
21.3. Deleting a Session	61
22. Shutdown (shutdown)	62
22.1. Shutting Down the Application	62
22.1.1. Response Structure	62
23. Thread Dump (threaddump)	63
23.1. Retrieving the Thread Dump as JSON	63
23.1.1. Response Structure	68
23.2. Retrieving the Thread Dump as Text	70

This API documentation describes Spring Boot Actuators web endpoints.

Chapter 1. Overview

Before you proceed, you should read the following topics:

- [URLs](#)
- [Timestamps](#)



In order to get the correct JSON responses documented below, Jackson must be available.

1.1. URLs

By default, all web endpoints are available beneath the path `/actuator` with URLs of the form `/actuator/{id}`. The `/actuator` base path can be configured by using the `management.endpoints.web.base-path` property, as shown in the following example:

```
management.endpoints.web.base-path=/manage
```

The preceding `application.properties` example changes the form of the endpoint URLs from `/actuator/{id}` to `/manage/{id}`. For example, the URL `info` endpoint would become `/manage/info`.

1.2. Timestamps

All timestamps that are consumed by the endpoints, either as query parameters or in the request body, must be formatted as an offset date and time as specified in [ISO 8601](#).

Chapter 2. Audit Events (auditevents)

The `auditevents` endpoint provides information about the application's audit events.

2.1. Retrieving Audit Events

To retrieve the audit events, make a `GET` request to `/actuator/auditevents`, as shown in the following curl-based example:

```
$ curl 'http://localhost:8080/actuator/auditevents?principal=alice&after=2020-11-12T08%3A35%3A05.436Z&type=logout' -i -X GET
```

The preceding example retrieves `logout` events for the principal, `alice`, that occurred after 09:37 on 7 November 2017 in the UTC timezone. The resulting response is similar to the following:

```
HTTP/1.1 200 OK
Content-Type: application/vnd.spring-boot.actuator.v3+json
Content-Length: 121

{
  "events" : [ {
    "timestamp" : "2020-11-12T08:35:05.436Z",
    "principal" : "alice",
    "type" : "logout"
  } ]
}
```

2.1.1. Query Parameters

The endpoint uses query parameters to limit the events that it returns. The following table shows the supported query parameters:

Parameter	Description
<code>after</code>	Restricts the events to those that occurred after the given time. Optional.
<code>principal</code>	Restricts the events to those with the given principal. Optional.
<code>type</code>	Restricts the events to those with the given type. Optional.

2.1.2. Response Structure

The response contains details of all of the audit events that matched the query. The following table describes the structure of the response:

Path	Type	Description
events	Array	An array of audit events.
events[].timestamp	String	The timestamp of when the event occurred.
events[].principal	String	The principal that triggered the event.
events[].type	String	The type of the event.

Chapter 3. Beans (beans)

The **beans** endpoint provides information about the application's beans.

3.1. Retrieving the Beans

To retrieve the beans, make a **GET** request to **/actuator/beans**, as shown in the following curl-based example:

```
$ curl 'http://localhost:8080/actuator/beans' -i -X GET
```

The resulting response is similar to the following:

```

HTTP/1.1 200 OK
Content-Type: application/vnd.spring-boot.actuator.v3+json
Content-Length: 1062

{
  "contexts" : {
    "application" : {
      "beans" : {
        "defaultServletHandlerMapping" : {
          "aliases" : [ ],
          "scope" : "singleton",
          "type" : "org.springframework.web.servlet.HandlerMapping",
          "resource" : "class path resource
[org/springframework/boot/autoconfigure/web/servlet/WebMvcAutoConfiguration$EnableWebM
vcConfiguration.class]",
          "dependencies" : [ ]
        },

"org.springframework.boot.autoconfigure.context.PropertyPlaceholderAutoConfiguration"
: {
          "aliases" : [ ],
          "scope" : "singleton",
          "type" :
"org.springframework.boot.autoconfigure.context.PropertyPlaceholderAutoConfiguration",
          "dependencies" : [ ]
        },

"org.springframework.boot.autoconfigure.web.servlet.DispatcherServletAutoConfiguration
" : {
          "aliases" : [ ],
          "scope" : "singleton",
          "type" :
"org.springframework.boot.autoconfigure.web.servlet.DispatcherServletAutoConfiguration
",
          "dependencies" : [ ]
        }
      }
    }
  }
}

```

3.1.1. Response Structure

The response contains details of the application's beans. The following table describes the structure of the response:

Path	Type	Description
<code>contexts</code>	<code>Object</code>	Application contexts keyed by id.

Path	Type	Description
contexts.*.parentId	String	Id of the parent application context, if any.
contexts.*.beans	Object	Beans in the application context keyed by name.
contexts.*.beans.*.aliases	Array	Names of any aliases.
contexts.*.beans.*.scope	String	Scope of the bean.
contexts.*.beans.*.type	String	Fully qualified type of the bean.
contexts.*.beans.*.resource	String	Resource in which the bean was defined, if any.
contexts.*.beans.*.dependencies	Array	Names of any dependencies.

Chapter 4. Caches (caches)

The **caches** endpoint provides access to the application's caches.

4.1. Retrieving All Caches

To retrieve the application's caches, make a **GET** request to **/actuator/caches**, as shown in the following curl-based example:

```
$ curl 'http://localhost:8080/actuator/caches' -i -X GET
```

The resulting response is similar to the following:

```
HTTP/1.1 200 OK
Content-Type: application/vnd.spring-boot.actuator.v3+json
Content-Length: 435

{
  "cacheManagers" : {
    "anotherCacheManager" : {
      "caches" : {
        "countries" : {
          "target" : "java.util.concurrent.ConcurrentHashMap"
        }
      }
    },
    "cacheManager" : {
      "caches" : {
        "cities" : {
          "target" : "java.util.concurrent.ConcurrentHashMap"
        },
        "countries" : {
          "target" : "java.util.concurrent.ConcurrentHashMap"
        }
      }
    }
  }
}
```

4.1.1. Response Structure

The response contains details of the application's caches. The following table describes the structure of the response:

Path	Type	Description
cacheManagers	Object	Cache managers keyed by id.

Path	Type	Description
<code>cacheManagers.*.caches</code>	<code>Object</code>	Caches in the application context keyed by name.
<code>cacheManagers.*.caches.*.target</code>	<code>String</code>	Fully qualified name of the native cache.

4.2. Retrieving Caches by Name

To retrieve a cache by name, make a `GET` request to `/actuator/caches/{name}`, as shown in the following curl-based example:

```
$ curl 'http://localhost:8080/actuator/caches/cities' -i -X GET
```

The preceding example retrieves information about the cache named `cities`. The resulting response is similar to the following:

```
HTTP/1.1 200 OK
Content-Type: application/vnd.spring-boot.actuator.v3+json
Content-Length: 113

{
  "target" : "java.util.concurrent.ConcurrentHashMap",
  "name" : "cities",
  "cacheManager" : "cacheManager"
}
```

4.2.1. Query Parameters

If the requested name is specific enough to identify a single cache, no extra parameter is required. Otherwise, the `cacheManager` must be specified. The following table shows the supported query parameters:

Parameter	Description
<code>cacheManager</code>	Name of the cacheManager to qualify the cache. May be omitted if the cache name is unique.

4.2.2. Response Structure

The response contains details of the requested cache. The following table describes the structure of the response:

Path	Type	Description
<code>name</code>	<code>String</code>	Cache name.
<code>cacheManager</code>	<code>String</code>	Cache manager name.

Path	Type	Description
<code>target</code>	<code>String</code>	Fully qualified name of the native cache.

4.3. Evict All Caches

To clear all available caches, make a `DELETE` request to `/actuator/caches` as shown in the following curl-based example:

```
$ curl 'http://localhost:8080/actuator/caches' -i -X DELETE
```

4.4. Evict a Cache by Name

To evict a particular cache, make a `DELETE` request to `/actuator/caches/{name}` as shown in the following curl-based example:

```
$ curl
'http://localhost:8080/actuator/caches/countries?cacheManager=anotherCacheManager' -i
-X DELETE
```



As there are two caches named `countries`, the `cacheManager` has to be provided to specify which `Cache` should be cleared.

4.4.1. Request Structure

If the requested name is specific enough to identify a single cache, no extra parameter is required. Otherwise, the `cacheManager` must be specified. The following table shows the supported query parameters:

Parameter	Description
<code>cacheManager</code>	Name of the cacheManager to qualify the cache. May be omitted if the cache name is unique.

Chapter 5. Conditions Evaluation Report

(conditions)

The `conditions` endpoint provides information about the evaluation of conditions on configuration and auto-configuration classes.

5.1. Retrieving the Report

To retrieve the report, make a `GET` request to `/actuator/conditions`, as shown in the following curl-based example:

```
$ curl 'http://localhost:8080/actuator/conditions' -i -X GET
```

The resulting response is similar to the following:

```
HTTP/1.1 200 OK
Content-Type: application/vnd.spring-boot.actuator.v3+json
Content-Length: 3255

{
  "contexts" : {
    "application" : {
      "positiveMatches" : {
        "EndpointAutoConfiguration#endpointOperationParameterMapper" : [ {
          "condition" : "OnBeanCondition",
          "message" : "@ConditionalOnMissingBean (types:
org.springframework.boot.actuate.endpoint.invoke.ParameterValueMapper; SearchStrategy:
all) did not find any beans"
        } ],
        "EndpointAutoConfiguration#endpointCachingOperationInvokerAdvisor" : [ {
          "condition" : "OnBeanCondition",
          "message" : "@ConditionalOnMissingBean (types:
org.springframework.boot.actuate.endpoint.invoke.cache.CachingOperationInvokerAdvisor
; SearchStrategy: all) did not find any beans"
        } ],
        "WebEndpointAutoConfiguration" : [ {
          "condition" : "OnWebApplicationCondition",
          "message" : "@ConditionalOnWebApplication (required) found 'session' scope"
        } ]
      },
      "negativeMatches" : {
        "WebFluxEndpointManagementContextConfiguration" : {
          "notMatched" : [ {
            "condition" : "OnWebApplicationCondition",
            "message" : "not a reactive web application"
          } ],
          "matched" : [ {
```

```

        "condition" : "OnClassCondition",
        "message" : "@ConditionalOnClass found required classes
'org.springframework.web.reactive.DispatcherHandler',
'org.springframework.http.server.reactive.HttpHandler'"
    } ]
},
"GsonHttpMessageConvertersConfiguration.GsonHttpMessageConverterConfiguration"
: {
    "notMatched" : [ {
        "condition" :
"GsonHttpMessageConvertersConfiguration.PreferGsonOrJacksonAndJsonbUnavailableCondition",
        "message" : "AnyNestedCondition 0 matched 2 did not; NestedCondition on
GsonHttpMessageConvertersConfiguration.PreferGsonOrJacksonAndJsonbUnavailableCondition
.JacksonJsonbUnavailable NoneNestedConditions 1 matched 1 did not; NestedCondition on
GsonHttpMessageConvertersConfiguration.JacksonAndJsonbUnavailableCondition.JsonbPreferred
@ConditionalOnProperty (spring.mvc.converters.preferred-json-mapper=jsonb) did not
find property 'spring.mvc.converters.preferred-json-mapper'; NestedCondition on
GsonHttpMessageConvertersConfiguration.JacksonAndJsonbUnavailableCondition.JacksonAvai
lable @ConditionalOnBean (types:
org.springframework.http.converter.json.MappingJackson2HttpMessageConverter;
SearchStrategy: all) found bean 'mappingJackson2HttpMessageConverter'; NestedCondition
on
GsonHttpMessageConvertersConfiguration.PreferGsonOrJacksonAndJsonbUnavailableCondition
.GsonPreferred @ConditionalOnProperty (spring.mvc.converters.preferred-json-
mapper=gson) did not find property 'spring.mvc.converters.preferred-json-mapper'"
    } ],
    "matched" : [ ]
},
"JsonbHttpMessageConvertersConfiguration" : {
    "notMatched" : [ {
        "condition" : "OnClassCondition",
        "message" : "@ConditionalOnClass did not find required class
'javax.json.bind.Jsonb'"
    } ],
    "matched" : [ ]
}
},
"unconditionalClasses" : [
"org.springframework.boot.autoconfigure.context.PropertyPlaceholderAutoConfiguration",
"org.springframework.boot.actuate.autoconfigure.endpoint.EndpointAutoConfiguration" ]
}
}
}

```

5.1.1. Response Structure

The response contains details of the application's condition evaluation. The following table describes the structure of the response:

Path	Type	Description
contexts	Object	Application contexts keyed by id.
contexts.*.positiveMatches	Object	Classes and methods with conditions that were matched.
contexts.*.positiveMatches.*.[]condition	String	Name of the condition.
contexts.*.positiveMatches.*.[]message	String	Details of why the condition was matched.
contexts.*.negativeMatches	Object	Classes and methods with conditions that were not matched.
contexts.*.negativeMatches.*.notMatched	Array	Conditions that were matched.
contexts.*.negativeMatches.*.notMatched.[]condition	String	Name of the condition.
contexts.*.negativeMatches.*.notMatched.[]message	String	Details of why the condition was not matched.
contexts.*.negativeMatches.*.matched	Array	Conditions that were matched.
contexts.*.negativeMatches.*.matched.[]condition	String	Name of the condition.
contexts.*.negativeMatches.*.matched.[]message	String	Details of why the condition was matched.
contexts.*.unconditionalClasses	Array	Names of unconditional auto-configuration classes if any.
contexts.*.parentId	String	Id of the parent application context, if any.

Chapter 6. Configuration Properties

(configprops)

The `configprops` endpoint provides information about the application's `@ConfigurationProperties` beans.

6.1. Retrieving the `@ConfigurationProperties` Bean

To retrieve the `@ConfigurationProperties` beans, make a `GET` request to `/actuator/configprops`, as shown in the following curl-based example:

```
$ curl 'http://localhost:8080/actuator/configprops' -i -X GET
```

The resulting response is similar to the following:

```
HTTP/1.1 200 OK
Content-Type: application/vnd.spring-boot.actuator.v3+json
Content-Length: 2958

{
  "contexts" : {
    "application" : {
      "beans" : {
        "management.endpoints.web.cors-
org.springframework.boot.actuate.autoconfigure.endpoint.web.CorsEndpointProperties" :
{
      "prefix" : "management.endpoints.web.cors",
      "properties" : {
        "allowedHeaders" : [ ],
        "allowedMethods" : [ ],
        "allowedOrigins" : [ ],
        "maxAge" : "PT30M",
        "exposedHeaders" : [ ]
      },
      "inputs" : {
        "allowedHeaders" : [ ],
        "allowedMethods" : [ ],
        "allowedOrigins" : [ ],
        "maxAge" : { },
        "exposedHeaders" : [ ]
      }
    },
    "management.endpoints.web-
org.springframework.boot.actuate.autoconfigure.endpoint.web.WebEndpointProperties" : {
      "prefix" : "management.endpoints.web",
      "properties" : {
        "pathMapping" : { },
```

```

        "exposure" : {
            "include" : [ "*" ],
            "exclude" : [ ]
        },
        "basePath" : "/actuator"
    },
    "inputs" : {
        "pathMapping" : { },
        "exposure" : {
            "include" : [ {
                "origin" : "\"management.endpoints.web.exposure.include\" from
property source \"Inlined Test Properties\"",
                "value" : "*"
            } ],
            "exclude" : [ ]
        },
        "basePath" : { }
    }
},
"spring.resources-
org.springframework.boot.autoconfigure.web.ResourceProperties" : {
    "prefix" : "spring.resources",
    "properties" : {
        "addMappings" : true,
        "chain" : {
            "cache" : true,
            "htmlApplicationCache" : false,
            "compressed" : false,
            "strategy" : {
                "fixed" : {
                    "enabled" : false,
                    "paths" : [ "/*" ]
                },
                "content" : {
                    "enabled" : false,
                    "paths" : [ "/*" ]
                }
            }
        },
        "cache" : {
            "cachecontrol" : { }
        },
        "staticLocations" : [ "classpath:/META-INF/resources/",
"classpath:/resources/", "classpath:/static/", "classpath:/public/" ]
    },
    "inputs" : {
        "addMappings" : { },
        "chain" : {
            "cache" : { },
            "htmlApplicationCache" : { },
            "compressed" : { },

```

```

    "strategy" : {
      "fixed" : {
        "enabled" : { },
        "paths" : [ { } ]
      },
      "content" : {
        "enabled" : { },
        "paths" : [ { } ]
      }
    },
    "cache" : {
      "cachecontrol" : { }
    },
    "staticLocations" : [ { }, { }, { }, { } ]
  }
}
}
}
}
}

```

6.1.1. Response Structure

The response contains details of the application's `@ConfigurationProperties` beans. The following table describes the structure of the response:

Path	Type	Description
<code>contexts</code>	Object	Application contexts keyed by id.
<code>contexts.*.beans.*</code>	Object	<code>@ConfigurationProperties</code> beans keyed by bean name.
<code>contexts.*.beans.*.prefix</code>	String	Prefix applied to the names of the bean's properties.
<code>contexts.*.beans.*.properties</code>	Object	Properties of the bean as name-value pairs.
<code>contexts.*.beans.*.inputs</code>	Object	Origin and value of the configuration property used when binding to this bean.
<code>contexts.*.parentId</code>	String	Id of the parent application context, if any.

Chapter 7. Environment (env)

The `env` endpoint provides information about the application's `Environment`.

7.1. Retrieving the Entire Environment

To retrieve the entire environment, make a `GET` request to `/actuator/env`, as shown in the following curl-based example:

```
$ curl 'http://localhost:8080/actuator/env' -i -X GET
```

The resulting response is similar to the following:

```
HTTP/1.1 200 OK
Content-Type: application/vnd.spring-boot.actuator.v3+json
Content-Length: 788
```

```
{
  "activeProfiles" : [ ],
  "propertySources" : [ {
    "name" : "systemProperties",
    "properties" : {
      "java.runtime.name" : {
        "value" : "OpenJDK Runtime Environment"
      },
      "java.vm.version" : {
        "value" : "25.272-b10"
      },
      "java.vm.vendor" : {
        "value" : "AdoptOpenJDK"
      }
    }
  }, {
    "name" : "systemEnvironment",
    "properties" : {
      "JAVA_HOME" : {
        "value" : "/opt/openjdk",
        "origin" : "System Environment Property \"JAVA_HOME\""
      }
    }
  }, {
    "name" : "applicationConfig: [classpath:/application.properties]",
    "properties" : {
      "com.example.cache.max-size" : {
        "value" : "1000",
        "origin" : "class path resource [application.properties]:1:29"
      }
    }
  }
]
}
```

7.1.1. Response Structure

The response contains details of the application's **Environment**. The following table describes the structure of the response:

Path	Type	Description
<code>activeProfiles</code>	Array	Names of the active profiles, if any.
<code>propertySources</code>	Array	Property sources in order of precedence.
<code>propertySources[].name</code>	String	Name of the property source.

Path	Type	Description
<code>propertySources[].properties</code>	Object	Properties in the property source keyed by property name.
<code>propertySources[].properties.*.value</code>	String	Value of the property.
<code>propertySources[].properties.*.origin</code>	String	Origin of the property, if any.

7.2. Retrieving a Single Property

To retrieve a single property, make a **GET** request to `/actuator/env/{property.name}`, as shown in the following curl-based example:

```
$ curl 'http://localhost:8080/actuator/env/com.example.cache.max-size' -i -X GET
```

The preceding example retrieves information about the property named `com.example.cache.max-size`. The resulting response is similar to the following:

```
HTTP/1.1 200 OK
Content-Disposition: inline;filename=f.txt
Content-Type: application/vnd.spring-boot.actuator.v3+json
Content-Length: 445

{
  "property" : {
    "source" : "applicationConfig: [classpath:/application.properties]",
    "value" : "1000"
  },
  "activeProfiles" : [ ],
  "propertySources" : [ {
    "name" : "systemProperties"
  }, {
    "name" : "systemEnvironment"
  }, {
    "name" : "applicationConfig: [classpath:/application.properties]",
    "property" : {
      "value" : "1000",
      "origin" : "class path resource [application.properties]:1:29"
    }
  } ]
}
```

7.2.1. Response Structure

The response contains details of the requested property. The following table describes the structure of the response:

Path	Type	Description
property	Object	Property from the environment, if found.
property.source	String	Name of the source of the property.
property.value	String	Value of the property.
activeProfiles	Array	Names of the active profiles, if any.
propertySources	Array	Property sources in order of precedence.
propertySources[].name	String	Name of the property source.
propertySources[].property	Object	Property in the property source, if any.
propertySources[].property.value	Varies	Value of the property.
propertySources[].property.origin	String	Origin of the property, if any.

Chapter 8. Flyway (flyway)

The **flyway** endpoint provides information about database migrations performed by Flyway.

8.1. Retrieving the Migrations

To retrieve the migrations, make a **GET** request to **/actuator/flyway**, as shown in the following curl-based example:

```
$ curl 'http://localhost:8080/actuator/flyway' -i -X GET
```

The resulting response is similar to the following:

```
HTTP/1.1 200 OK
Content-Type: application/vnd.spring-boot.actuator.v3+json
Content-Length: 515

{
  "contexts" : {
    "application" : {
      "flywayBeans" : {
        "flyway" : {
          "migrations" : [ {
            "type" : "SQL",
            "checksum" : -156244537,
            "version" : "1",
            "description" : "init",
            "script" : "V1__init.sql",
            "state" : "SUCCESS",
            "installedBy" : "SA",
            "installedOn" : "2020-11-12T08:35:12.070Z",
            "installedRank" : 1,
            "executionTime" : 2
          } ]
        }
      }
    }
  }
}
```

8.1.1. Response Structure

The response contains details of the application's Flyway migrations. The following table describes the structure of the response:

Path	Type	Description
<code>contexts</code>	Object	Application contexts keyed by id
<code>contexts.*.flywayBeans.*.migrations</code>	Array	Migrations performed by the Flyway instance, keyed by Flyway bean name.
<code>contexts.*.flywayBeans.*.migrations[].checksum</code>	Number	Checksum of the migration, if any.
<code>contexts.*.flywayBeans.*.migrations[].description</code>	String	Description of the migration, if any.
<code>contexts.*.flywayBeans.*.migrations[].executionTime</code>	Number	Execution time in milliseconds of an applied migration.
<code>contexts.*.flywayBeans.*.migrations[].installedBy</code>	String	User that installed the applied migration, if any.
<code>contexts.*.flywayBeans.*.migrations[].installedOn</code>	String	Timestamp of when the applied migration was installed, if any.
<code>contexts.*.flywayBeans.*.migrations[].installedRank</code>	Number	Rank of the applied migration, if any. Later migrations have higher ranks.
<code>contexts.*.flywayBeans.*.migrations[].script</code>	String	Name of the script used to execute the migration, if any.
<code>contexts.*.flywayBeans.*.migrations[].state</code>	String	State of the migration. (<code>PENDING</code> , <code>ABOVE_TARGET</code> , <code>BELOW_BASELINE</code> , <code>BASELINE</code> , <code>IGNORED</code> , <code>MISSING_SUCCESS</code> , <code>MISSING_FAILED</code> , <code>SUCCESS</code> , <code>UNDONE</code> , <code>AVAILABLE</code> , <code>FAILED</code> , <code>OUT_OF_ORDER</code> , <code>FUTURE_SUCCESS</code> , <code>FUTURE_FAILED</code> , <code>OUTDATED</code> , <code>SUPERSEDED</code>)
<code>contexts.*.flywayBeans.*.migrations[].type</code>	String	Type of the migration. (<code>SCHEMA</code> , <code>BASELINE</code> , <code>SQL</code> , <code>UNDO_SQL</code> , <code>JDBC</code> , <code>UNDO_JDBC</code> , <code>SPRING_JDBC</code> , <code>UNDO_SPRING_JDBC</code> , <code>CUSTOM</code> , <code>UNDO_CUSTOM</code>)
<code>contexts.*.flywayBeans.*.migrations[].version</code>	String	Version of the database after applying the migration, if any.
<code>contexts.*.parentId</code>	String	Id of the parent application context, if any.

Chapter 9. Health (health)

The **health** endpoint provides detailed information about the health of the application.

9.1. Retrieving the Health of the application

To retrieve the health of the application, make a **GET** request to **/actuator/health**, as shown in the following curl-based example:

```
$ curl 'http://localhost:8080/actuator/health' -i -X GET \  
-H 'Accept: application/json'
```

The resulting response is similar to the following:

```

HTTP/1.1 200 OK
Content-Type: application/json
Content-Length: 703

{
  "status" : "UP",
  "components" : {
    "broker" : {
      "status" : "UP",
      "components" : {
        "us1" : {
          "status" : "UP",
          "details" : {
            "version" : "1.0.2"
          }
        },
        "us2" : {
          "status" : "UP",
          "details" : {
            "version" : "1.0.4"
          }
        }
      }
    },
    "db" : {
      "status" : "UP",
      "details" : {
        "database" : "H2",
        "validationQuery" : "isValid()"
      }
    },
    "diskSpace" : {
      "status" : "UP",
      "details" : {
        "total" : 194687758336,
        "free" : 59156598784,
        "threshold" : 10485760,
        "exists" : true
      }
    }
  }
}

```

9.1.1. Response Structure

The response contains details of the health of the application. The following table describes the structure of the response:

Path	Type	Description
<code>status</code>	<code>String</code>	Overall status of the application.
<code>components</code>	<code>Object</code>	The components that make up the health.
<code>components.*.status</code>	<code>String</code>	Status of a specific part of the application.
<code>components.*.components</code>	<code>Object</code>	The nested components that make up the health.
<code>components.*.details</code>	<code>Object</code>	Details of the health of a specific part of the application. Presence is controlled by <code>management.endpoint.health.show-details</code> .



The response fields above are for the V3 API. If you need to return V2 JSON you should use an accept header or `application/vnd.spring-boot.actuator.v2+json`

9.2. Retrieving the Health of a component

To retrieve the health of a particular component of the application's health, make a `GET` request to `/actuator/health/{component}`, as shown in the following curl-based example:

```
$ curl 'http://localhost:8080/actuator/health/db' -i -X GET \
-H 'Accept: application/json'
```

The resulting response is similar to the following:

```
HTTP/1.1 200 OK
Content-Type: application/json
Content-Length: 101

{
  "status" : "UP",
  "details" : {
    "database" : "H2",
    "validationQuery" : "isValid()"
  }
}
```

9.2.1. Response Structure

The response contains details of the health of a particular component of the application's health. The following table describes the structure of the response:

Path	Type	Description
<code>status</code>	<code>String</code>	Status of a specific part of the application
<code>details</code>	<code>Object</code>	Details of the health of a specific part of the application.

9.3. Retrieving the Health of a nested component

If a particular component contains other nested components (as the **broker** indicator in the example above), the health of such a nested component can be retrieved by issuing a **GET** request to `/actuator/health/{component}/{subcomponent}`, as shown in the following curl-based example:

```
$ curl 'http://localhost:8080/actuator/health/broker/us1' -i -X GET \
-H 'Accept: application/json'
```

The resulting response is similar to the following:

```
HTTP/1.1 200 OK
Content-Type: application/json
Content-Length: 66

{
  "status" : "UP",
  "details" : {
    "version" : "1.0.2"
  }
}
```

Components of an application's health may be nested arbitrarily deep depending on the application's health indicators and how they have been grouped. The health endpoint supports any number of `/health/{component}` identifiers in the URL to allow the health of a component at any depth to be retrieved.

9.3.1. Response Structure

The response contains details of the health of an instance of a particular component of the application. The following table describes the structure of the response:

Path	Type	Description
<code>status</code>	<code>String</code>	Status of a specific part of the application
<code>details</code>	<code>Object</code>	Details of the health of a specific part of the application.

Chapter 10. Heap Dump (heapdump)

The `heapdump` endpoint provides a heap dump from the application's JVM.

10.1. Retrieving the Heap Dump

To retrieve the heap dump, make a `GET` request to `/actuator/heapdump`. The response is binary data in `HPROF` format and can be large. Typically, you should save the response to disk for subsequent analysis. When using `curl`, this can be achieved by using the `-O` option, as shown in the following example:

```
$ curl 'http://localhost:8080/actuator/heapdump' -O
```

The preceding example results in a file named `heapdump` being written to the current working directory.

Chapter 11. HTTP Trace (**httptrace**)

The **httptrace** endpoint provides information about HTTP request-response exchanges.

11.1. Retrieving the Traces

To retrieve the traces, make a **GET** request to **/actuator/httptrace**, as shown in the following curl-based example:

```
$ curl 'http://localhost:8080/actuator/httptrace' -i -X GET
```

The resulting response is similar to the following:

```
HTTP/1.1 200 OK
Content-Type: application/vnd.spring-boot.actuator.v3+json
Content-Length: 503

{
  "traces" : [ {
    "timestamp" : "2020-11-12T08:35:11.358Z",
    "principal" : {
      "name" : "alice"
    },
    "session" : {
      "id" : "40c19c1b-226f-435c-8f99-217b8a43c861"
    },
    "request" : {
      "method" : "GET",
      "uri" : "https://api.example.com",
      "headers" : {
        "Accept" : [ "application/json" ]
      }
    },
    "response" : {
      "status" : 200,
      "headers" : {
        "Content-Type" : [ "application/json" ]
      }
    },
    "timeTaken" : 1
  } ]
}
```

11.1.1. Response Structure

The response contains details of the traced HTTP request-response exchanges. The following table describes the structure of the response:

Path	Type	Description
traces	Array	An array of traced HTTP request-response exchanges.
traces[].timestamp	String	Timestamp of when the traced exchange occurred.
traces[].principal	Object	Principal of the exchange, if any.
traces[].principal.name	String	Name of the principal.
traces[].request.method	String	HTTP method of the request.
traces[].request.remoteAddress	String	Remote address from which the request was received, if known.
traces[].request.uri	String	URI of the request.
traces[].request.headers	Object	Headers of the request, keyed by header name.
traces[].request.headers.*.[]	Array	Values of the header
traces[].response.status	Number	Status of the response
traces[].response.headers	Object	Headers of the response, keyed by header name.
traces[].response.headers.*.[]	Array	Values of the header
traces[].session	Object	Session associated with the exchange, if any.
traces[].session.id	String	ID of the session.
traces[].timeTaken	Number	Time, in milliseconds, taken to handle the exchange.

Chapter 12. Info (info)

The **info** endpoint provides general information about the application.

12.1. Retrieving the Info

To retrieve the information about the application, make a **GET** request to **/actuator/info**, as shown in the following curl-based example:

```
$ curl 'http://localhost:8080/actuator/info' -i -X GET
```

The resulting response is similar to the following:

```
HTTP/1.1 200 OK
Content-Type: application/vnd.spring-boot.actuator.v3+json
Content-Length: 235

{
  "git" : {
    "commit" : {
      "time" : "+52835-10-25T18:12:37Z",
      "id" : "df027cf"
    },
    "branch" : "master"
  },
  "build" : {
    "version" : "1.0.3",
    "artifact" : "application",
    "group" : "com.example"
  }
}
```

12.1.1. Response Structure

The response contains general information about the application. Each section of the response is contributed by an **InfoContributor**. Spring Boot provides **build** and **git** contributions.

Build Response Structure

The following table describe the structure of the **build** section of the response:

Path	Type	Description
artifact	String	Artifact ID of the application, if any.
group	String	Group ID of the application, if any.
name	String	Name of the application, if any.

Path	Type	Description
version	String	Version of the application, if any.
time	Varies	Timestamp of when the application was built, if any.

Git Response Structure

The following table describes the structure of the `git` section of the response:

Path	Type	Description
branch	String	Name of the Git branch, if any.
commit	Object	Details of the Git commit, if any.
commit.time	Varies	Timestamp of the commit, if any.
commit.id	String	ID of the commit, if any.

Chapter 13. Spring Integration graph (*integrationgraph*)

The *integrationgraph* endpoint exposes a graph containing all Spring Integration components.

13.1. Retrieving the Spring Integration graph

To retrieve the information about the application, make a *GET* request to */actuator/integrationgraph*, as shown in the following curl-based example:

```
$ curl 'http://localhost:8080/actuator/integrationgraph' -i -X GET
```

The resulting response is similar to the following:

```
HTTP/1.1 200 OK
Content-Type: application/vnd.spring-boot.actuator.v3+json
Content-Length: 969
```

```
{
  "contentDescriptor" : {
    "providerVersion" : "5.3.4.RELEASE",
    "providerFormatVersion" : 1.2,
    "provider" : "spring-integration"
  },
  "nodes" : [ {
    "nodeId" : 1,
    "componentType" : "null-channel",
    "integrationPatternType" : "null_channel",
    "integrationPatternCategory" : "messaging_channel",
    "properties" : { },
    "name" : "nullChannel"
  }, {
    "nodeId" : 2,
    "componentType" : "publish-subscribe-channel",
    "integrationPatternType" : "publish_subscribe_channel",
    "integrationPatternCategory" : "messaging_channel",
    "properties" : { },
    "name" : "errorChannel"
  }, {
    "nodeId" : 3,
    "componentType" : "logging-channel-adapter",
    "integrationPatternType" : "outbound_channel_adapter",
    "integrationPatternCategory" : "messaging_endpoint",
    "properties" : { },
    "input" : "errorChannel",
    "name" : "errorLogger"
  } ],
  "links" : [ {
    "from" : 2,
    "to" : 3,
    "type" : "input"
  } ]
}
```

13.1.1. Response Structure

The response contains all Spring Integration components used within the application, as well as the links between them. More information about the structure can be found in the [reference documentation](#).

13.2. Rebuilding the Spring Integration graph

To rebuild the exposed graph, make a **POST** request to `/actuator/integrationgraph`, as shown in the following curl-based example:

```
$ curl 'http://localhost:8080/actuator/integrationgraph' -i -X POST
```

This will result in a **204 - No Content** response:

```
HTTP/1.1 204 No Content
```

Chapter 14. Liquibase (liquibase)

The **liquibase** endpoint provides information about database change sets applied by Liquibase.

14.1. Retrieving the Changes

To retrieve the changes, make a **GET** request to `/actuator/liquibase`, as shown in the following curl-based example:

```
$ curl 'http://localhost:8080/actuator/liquibase' -i -X GET
```

The resulting response is similar to the following:

```
HTTP/1.1 200 OK
Content-Type: application/vnd.spring-boot.actuator.v3+json
Content-Length: 688

{
  "contexts" : {
    "application" : {
      "liquibaseBeans" : {
        "liquibase" : {
          "changeSets" : [ {
            "author" : "marceloverdijk",
            "changeLog" : "classpath:/db/changelog/db.changelog-master.yaml",
            "comments" : "",
            "contexts" : [ ],
            "dateExecuted" : "2020-11-12T08:35:10.038Z",
            "deploymentId" : "5170110018",
            "description" : "createTable tableName=customer",
            "execType" : "EXECUTED",
            "id" : "1",
            "labels" : [ ],
            "checksum" : "8:46debf252cce6d7b25e28ddeb9fc4bf6",
            "orderExecuted" : 1
          } ]
        }
      }
    }
  }
}
```

14.1.1. Response Structure

The response contains details of the application's Liquibase change sets. The following table describes the structure of the response:

Path	Type	Description
contexts	Object	Application contexts keyed by id
contexts.*.liquibaseBeans.*.changeSets	Array	Change sets made by the Liquibase beans, keyed by bean name.
contexts.*.liquibaseBeans.*.changeSets[].author	String	Author of the change set.
contexts.*.liquibaseBeans.*.changeSets[].changelog	String	Change log that contains the change set.
contexts.*.liquibaseBeans.*.changeSets[].comments	String	Comments on the change set.
contexts.*.liquibaseBeans.*.changeSets[].contexts	Array	Contexts of the change set.
contexts.*.liquibaseBeans.*.changeSets[].dateExecuted	String	Timestamp of when the change set was executed.
contexts.*.liquibaseBeans.*.changeSets[].deploymentId	String	ID of the deployment that ran the change set.
contexts.*.liquibaseBeans.*.changeSets[].description	String	Description of the change set.
contexts.*.liquibaseBeans.*.changeSets[].execType	String	Execution type of the change set (EXECUTED , FAILED , SKIPPED , RERAN , MARK_RAN).
contexts.*.liquibaseBeans.*.changeSets[].id	String	ID of the change set.
contexts.*.liquibaseBeans.*.changeSets[].labels	Array	Labels associated with the change set.
contexts.*.liquibaseBeans.*.changeSets[].checksum	String	Checksum of the change set.
contexts.*.liquibaseBeans.*.changeSets[].orderExecuted	Number	Order of the execution of the change set.
contexts.*.liquibaseBeans.*.changeSets[].tag	String	Tag associated with the change set, if any.
contexts.*.parentId	String	Id of the parent application context, if any.

Chapter 15. Log File (logfile)

The **logfile** endpoint provides access to the contents of the application's log file.

15.1. Retrieving the Log File

To retrieve the log file, make a **GET** request to `/actuator/logfile`, as shown in the following curl-based example:

```
$ curl 'http://localhost:8080/actuator/logfile' -i -X GET
```

The resulting response is similar to the following:

```
HTTP/1.1 200 OK
Accept-Ranges: bytes
Content-Type: text/plain;charset=UTF-8
Content-Length: 4723
```

```

      .  _ _ _ _ _
    /\ /  _ _ _ _ _ ( ) _ _ _ _ _ \ \ \ \ \
  ( ( ) \ _ _ _ _ _ | ' _ | ' _ | ' _ \ / ' _ | \ \ \ \ \
    \ \ /  _ _ _ _ _ | | _ | | | | | | ( _ | ) ) ) )
      ' _ | _ _ _ _ _ | . _ _ | _ | _ | _ \ _ _ , | / / / /
=====|_|=====|_| _ _ / = / _ / _ /
:: Spring Boot ::

```

```

2017-08-08 17:12:30.910 INFO 19866 --- [          main]
s.f.SampleWebFreeMarkerApplication      : Starting SampleWebFreeMarkerApplication on
host.local with PID 19866
2017-08-08 17:12:30.913 INFO 19866 --- [          main]
s.f.SampleWebFreeMarkerApplication      : No active profile set, falling back to
default profiles: default
2017-08-08 17:12:30.952 INFO 19866 --- [          main]
ConfigServletWebServerApplicationContext : Refreshing
org.springframework.boot.web.servlet.context.AnnotationConfigServletWebServerApplicati
onContext@76b10754: startup date [Tue Aug 08 17:12:30 BST 2017]; root of context
hierarchy
2017-08-08 17:12:31.878 INFO 19866 --- [          main]
o.s.b.w.embedded.tomcat.TomcatWebServer : Tomcat initialized with port(s): 8080
(http)
2017-08-08 17:12:31.889 INFO 19866 --- [          main]
o.apache.catalina.core.StandardService  : Starting service [Tomcat]
2017-08-08 17:12:31.890 INFO 19866 --- [          main]
org.apache.catalina.core.StandardEngine  : Starting Servlet Engine: Apache
Tomcat/8.5.16
2017-08-08 17:12:31.978 INFO 19866 --- [ost-startStop-1]
o.a.c.c.C.[Tomcat].[localhost].[/]      : Initializing Spring embedded
WebApplicationContext

```

```

2017-08-08 17:12:31.978 INFO 19866 --- [ost-startStop-1]
o.s.web.context.ContextLoader      : Root WebApplicationContext: initialization
completed in 1028 ms
2017-08-08 17:12:32.080 INFO 19866 --- [ost-startStop-1]
o.s.b.w.servlet.ServletRegistrationBean : Mapping servlet: 'dispatcherServlet' to [/]
2017-08-08 17:12:32.084 INFO 19866 --- [ost-startStop-1]
o.s.b.w.servlet.FilterRegistrationBean : Mapping filter: 'characterEncodingFilter'
to: [/*]
2017-08-08 17:12:32.084 INFO 19866 --- [ost-startStop-1]
o.s.b.w.servlet.FilterRegistrationBean : Mapping filter: 'hiddenHttpMethodFilter'
to: [/*]
2017-08-08 17:12:32.084 INFO 19866 --- [ost-startStop-1]
o.s.b.w.servlet.FilterRegistrationBean : Mapping filter: 'httpPutFormContentFilter'
to: [/*]
2017-08-08 17:12:32.084 INFO 19866 --- [ost-startStop-1]
o.s.b.w.servlet.FilterRegistrationBean : Mapping filter: 'requestContextFilter' to:
[/*]
2017-08-08 17:12:32.349 INFO 19866 --- [          main]
s.w.s.m.m.a.RequestMappingHandlerAdapter : Looking for @ControllerAdvice:
org.springframework.boot.web.servlet.context.AnnotationConfigServletWebServerApplicati
onContext@76b10754: startup date [Tue Aug 08 17:12:30 BST 2017]; root of context
hierarchy
2017-08-08 17:12:32.420 INFO 19866 --- [          main]
s.w.s.m.m.a.RequestMappingHandlerMapping : Mapped "{[/error]}" onto public
org.springframework.http.ResponseEntity<java.util.Map<java.lang.String,
java.lang.Object>>
org.springframework.boot.autoconfigure.web.servlet.error.BasicErrorController.error(ja
vax.servlet.http.HttpServletRequest)
2017-08-08 17:12:32.421 INFO 19866 --- [          main]
s.w.s.m.m.a.RequestMappingHandlerMapping : Mapped "{[/error],produces=[text/html]}"
onto public org.springframework.web.servlet.ModelAndView
org.springframework.boot.autoconfigure.web.servlet.error.BasicErrorController.errorHtm
l(javax.servlet.http.HttpServletRequest,javax.servlet.http.HttpServletResponse)
2017-08-08 17:12:32.444 INFO 19866 --- [          main]
o.s.w.s.handler.SimpleUrlHandlerMapping : Mapped URL path [/webjars/**] onto handler
of type [class org.springframework.web.servlet.resource.ResourceHttpRequestHandler]
2017-08-08 17:12:32.444 INFO 19866 --- [          main]
o.s.w.s.handler.SimpleUrlHandlerMapping : Mapped URL path [/**] onto handler of type
[class org.springframework.web.servlet.resource.ResourceHttpRequestHandler]
2017-08-08 17:12:32.471 INFO 19866 --- [          main]
o.s.w.s.handler.SimpleUrlHandlerMapping : Mapped URL path [/**/favicon.ico] onto
handler of type [class
org.springframework.web.servlet.resource.ResourceHttpRequestHandler]
2017-08-08 17:12:32.600 INFO 19866 --- [          main]
o.s.w.s.v.f.FreeMarkerConfigurer    : ClassTemplateLoader for Spring macros added
to FreeMarker configuration
2017-08-08 17:12:32.681 INFO 19866 --- [          main]
o.s.j.e.a.AnnotationMBeanExporter    : Registering beans for JMX exposure on
startup
2017-08-08 17:12:32.744 INFO 19866 --- [          main]
o.s.b.w.embedded.tomcat.TomcatWebServer : Tomcat started on port(s): 8080 (http)

```

```
2017-08-08 17:12:32.750 INFO 19866 --- [          main]
s.f.SampleWebFreeMarkerApplication : Started SampleWebFreeMarkerApplication in
2.172 seconds (JVM running for 2.479)
```

15.2. Retrieving Part of the Log File



Retrieving part of the log file is not supported when using Jersey.

To retrieve part of the log file, make a **GET** request to **/actuator/logfile** by using the **Range** header, as shown in the following curl-based example:

```
$ curl 'http://localhost:8080/actuator/logfile' -i -X GET \
-H 'Range: bytes=0-1023'
```

The preceding example retrieves the first 1024 bytes of the log file. The resulting response is similar to the following:

```
HTTP/1.1 206 Partial Content
Accept-Ranges: bytes
Content-Type: text/plain;charset=UTF-8
Content-Range: bytes 0-1023/4723
Content-Length: 1024
```

```
  .
 /\ / _ _ _ _ _ ( _ ) _ _ _ _ _ \ \ \ \
( ( ) \ _ _ | ' _ | ' _ | ' _ \ _ | \ \ \ \
 \ \ _ _ ) | | ) | | | | | | ( _ | ) ) ) )
  ' | _ _ | . _ _ | | _ | | \ _ , | / / / /
=====|_|=====|___/=//_/_/_/
:: Spring Boot ::
```

```
2017-08-08 17:12:30.910 INFO 19866 --- [          main]
s.f.SampleWebFreeMarkerApplication : Starting SampleWebFreeMarkerApplication on
host.local with PID 19866
2017-08-08 17:12:30.913 INFO 19866 --- [          main]
s.f.SampleWebFreeMarkerApplication : No active profile set, falling back to
default profiles: default
2017-08-08 17:12:30.952 INFO 19866 --- [          main]
ConfigServletWebServerApplicationContext : Refreshing
org.springframework.boot.web.servlet.context.AnnotationConfigServletWebServerApplicati
onContext@76b10754: startup date [Tue Aug 08 17:12:30 BST 2017]; root of context
hierarchy
2017-08-08 17:12:31.878 INFO 19866 --- [          main]
o.s.b.w.embedded.tomcat.TomcatWebServer : Tomcat initialized with port(
```

Chapter 16. Loggers (loggers)

The **loggers** endpoint provides access to the application's loggers and the configuration of their levels.

16.1. Retrieving All Loggers

To retrieve the application's loggers, make a **GET** request to **/actuator/loggers**, as shown in the following curl-based example:

```
$ curl 'http://localhost:8080/actuator/loggers' -i -X GET
```

The resulting response is similar to the following:

```
HTTP/1.1 200 OK
Content-Type: application/vnd.spring-boot.actuator.v3+json
Content-Length: 791

{
  "levels" : [ "OFF", "FATAL", "ERROR", "WARN", "INFO", "DEBUG", "TRACE" ],
  "loggers" : {
    "ROOT" : {
      "configuredLevel" : "INFO",
      "effectiveLevel" : "INFO"
    },
    "com.example" : {
      "configuredLevel" : "DEBUG",
      "effectiveLevel" : "DEBUG"
    }
  },
  "groups" : {
    "test" : {
      "configuredLevel" : "INFO",
      "members" : [ "test.member1", "test.member2" ]
    },
    "web" : {
      "members" : [ "org.springframework.core.codec", "org.springframework.http",
"org.springframework.web", "org.springframework.boot.actuate.endpoint.web",
"org.springframework.boot.web.servlet.ServletContextInitializerBeans" ]
    },
    "sql" : {
      "members" : [ "org.springframework.jdbc.core", "org.hibernate.SQL",
"org.jooq.tools.LoggerListener" ]
    }
  }
}
```

16.1.1. Response Structure

The response contains details of the application's loggers. The following table describes the structure of the response:

Path	Type	Description
levels	Array	Levels support by the logging system.
loggers	Object	Loggers keyed by name.
groups	Object	Logger groups keyed by name
loggers.*.configuredLevel	String	Configured level of the logger, if any.
loggers.*.effectiveLevel	String	Effective level of the logger.
groups.*.configuredLevel	String	Configured level of the logger group, if any.
groups.*.members	Array	Loggers that are part of this group

16.2. Retrieving a Single Logger

To retrieve a single logger, make a **GET** request to `/actuator/loggers/{logger.name}`, as shown in the following curl-based example:

```
$ curl 'http://localhost:8080/actuator/loggers/com.example' -i -X GET
```

The preceding example retrieves information about the logger named `com.example`. The resulting response is similar to the following:

```
HTTP/1.1 200 OK
Content-Disposition: inline;filename=f.txt
Content-Type: application/vnd.spring-boot.actuator.v3+json
Content-Length: 61

{
  "configuredLevel" : "INFO",
  "effectiveLevel" : "INFO"
}
```

16.2.1. Response Structure

The response contains details of the requested logger. The following table describes the structure of the response:

Path	Type	Description
configuredLevel	String	Configured level of the logger, if any.

Path	Type	Description
<code>effectiveLevel</code>	<code>String</code>	Effective level of the logger.

16.3. Retrieving a Single Group

To retrieve a single group, make a `GET` request to `/actuator/loggers/{group.name}`, as shown in the following curl-based example:

```
$ curl 'http://localhost:8080/actuator/loggers/test' -i -X GET
```

The preceding example retrieves information about the logger group named `test`. The resulting response is similar to the following:

```
HTTP/1.1 200 OK
Content-Type: application/vnd.spring-boot.actuator.v3+json
Content-Length: 82

{
  "configuredLevel" : "INFO",
  "members" : [ "test.member1", "test.member2" ]
}
```

16.3.1. Response Structure

The response contains details of the requested group. The following table describes the structure of the response:

Path	Type	Description
<code>configuredLevel</code>	<code>String</code>	Configured level of the logger group, if any.
<code>members</code>	<code>Array</code>	Loggers that are part of this group

16.4. Setting a Log Level

To set the level of a logger, make a `POST` request to `/actuator/loggers/{logger.name}` with a JSON body that specifies the configured level for the logger, as shown in the following curl-based example:

```
$ curl 'http://localhost:8080/actuator/loggers/com.example' -i -X POST \
  -H 'Content-Type: application/json' \
  -d '{"configuredLevel":"debug"}'
```

The preceding example sets the `configuredLevel` of the `com.example` logger to `DEBUG`.

16.4.1. Request Structure

The request specifies the desired level of the logger. The following table describes the structure of the request:

Path	Type	Description
<code>configuredLevel</code>	<code>String</code>	Level for the logger. May be omitted to clear the level.

16.5. Setting a Log Level for a Group

To set the level of a logger, make a `POST` request to `/actuator/loggers/{group.name}` with a JSON body that specifies the configured level for the logger group, as shown in the following curl-based example:

```
$ curl 'http://localhost:8080/actuator/loggers/test' -i -X POST \  
  -H 'Content-Type: application/json' \  
  -d '{"configuredLevel":"debug"}'
```

The preceding example sets the `configuredLevel` of the `test` logger group to `DEBUG`.

16.5.1. Request Structure

The request specifies the desired level of the logger group. The following table describes the structure of the request:

Path	Type	Description
<code>configuredLevel</code>	<code>String</code>	Level for the logger. May be omitted to clear the level.

16.6. Clearing a Log Level

To clear the level of a logger, make a `POST` request to `/actuator/loggers/{logger.name}` with a JSON body containing an empty object, as shown in the following curl-based example:

```
$ curl 'http://localhost:8080/actuator/loggers/com.example' -i -X POST \  
  -H 'Content-Type: application/json' \  
  -d '{}'
```

The preceding example clears the configured level of the `com.example` logger.

Chapter 17. Mappings (mappings)

The `mappings` endpoint provides information about the application's request mappings.

17.1. Retrieving the Mappings

To retrieve the mappings, make a `GET` request to `/actuator/mappings`, as shown in the following curl-based example:

```
$ curl 'http://localhost:45033/actuator/mappings' -i -X GET
```

The resulting response is similar to the following:

```
HTTP/1.1 200 OK
Content-Type: application/vnd.spring-boot.actuator.v3+json
Transfer-Encoding: chunked
Date: Thu, 12 Nov 2020 08:35:10 GMT
Content-Length: 5476

{
  "contexts" : {
    "application" : {
      "mappings" : {
        "dispatcherServlets" : {
          "dispatcherServlet" : [ {
            "handler" : "Actuator web endpoint 'mappings'",
            "predicate" : "{GET /actuator/mappings, produces [application/vnd.spring-boot.actuator.v3+json || application/vnd.spring-boot.actuator.v2+json || application/json]}",
            "details" : {
              "handlerMethod" : {
                "className" :
"org.springframework.boot.actuate.endpoint.web.servlet.AbstractWebMvcEndpointHandlerMa
pping.OperationHandler",
                "name" : "handle",
                "descriptor" :
"(Ljavax/servlet/http/HttpServletRequest;Ljava/util/Map;)Ljava/lang/Object;"
              },
              "requestMappingConditions" : {
                "consumes" : [ ],
                "headers" : [ ],
                "methods" : [ "GET" ],
                "params" : [ ],
                "patterns" : [ "/actuator/mappings" ],
                "produces" : [ {
                  "mediaType" : "application/vnd.spring-boot.actuator.v3+json",
                  "negated" : false
                } ], {
```



```

        "mediaType" : "application/vnd.spring-boot.actuator.v2+json",
        "negated" : false
    }, {
        "mediaType" : "application/json",
        "negated" : false
    } ]
    }
}
}, {
    "handler" : "Actuator root web endpoint",
    "predicate" : "{GET /actuator, produces [application/vnd.spring-
boot.actuator.v3+json || application/vnd.spring-boot.actuator.v2+json ||
application/json]}",
    "details" : {
        "handlerMethod" : {
            "className" :
"org.springframework.boot.actuate.endpoint.web.servlet.WebMvcEndpointHandlerMapping.Web
MvcLinksHandler",
            "name" : "links",
            "descriptor" :
"(Ljavax/servlet/http/HttpServletRequest;Ljavax/servlet/http/HttpServletResponse;)Ljav
a/lang/Object;"
        },
        "requestMappingConditions" : {
            "consumes" : [ ],
            "headers" : [ ],
            "methods" : [ "GET" ],
            "params" : [ ],
            "patterns" : [ "/actuator" ],
            "produces" : [ {
                "mediaType" : "application/vnd.spring-boot.actuator.v3+json",
                "negated" : false
            }, {
                "mediaType" : "application/vnd.spring-boot.actuator.v2+json",
                "negated" : false
            }, {
                "mediaType" : "application/json",
                "negated" : false
            } ]
        }
    }
}, {
    "handler" :
"org.springframework.boot.actuate.autoconfigure.endpoint.web.documentation.MappingsEnd
pointServletDocumentationTests$ExampleController#example()",
    "predicate" : "{POST /, params [a!=alpha], headers [X-Custom=Foo],
consumes [application/json || !application/xml], produces [text/plain]}",
    "details" : {
        "handlerMethod" : {
            "className" :
"org.springframework.boot.actuate.autoconfigure.endpoint.web.documentation.MappingsEnd

```

```

pointServletDocumentationTests.ExampleController",
    "name" : "example",
    "descriptor" : "()Ljava/lang/String;"
},
"requestMappingConditions" : {
    "consumes" : [ {
        "mediaType" : "application/json",
        "negated" : false
    }, {
        "mediaType" : "application/xml",
        "negated" : true
    } ],
    "headers" : [ {
        "name" : "X-Custom",
        "value" : "Foo",
        "negated" : false
    } ],
    "methods" : [ "POST" ],
    "params" : [ {
        "name" : "a",
        "value" : "alpha",
        "negated" : true
    } ],
    "patterns" : [ "/" ],
    "produces" : [ {
        "mediaType" : "text/plain",
        "negated" : false
    } ]
}
}, {
    "handler" : "ResourceHttpRequestHandler [\"classpath:/META-INF/resources/webjars/\"]",
    "predicate" : "/webjars/**"
}, {
    "handler" : "ResourceHttpRequestHandler [\"classpath:/META-INF/resources/\", \"classpath:/resources/\", \"classpath:/static/\", \"classpath:/public/\", \"/\"]",
    "predicate" : "/*"
} ]
},
"servletFilters" : [ {
    "servletNameMappings" : [ ],
    "urlPatternMappings" : [ "/*" ],
    "name" : "requestContextFilter",
    "className" :
"org.springframework.boot.web.servlet.filter.OrderedRequestContextFilter"
}, {
    "servletNameMappings" : [ ],
    "urlPatternMappings" : [ "/*" ],
    "name" : "formContentFilter",

```

```

        "className" :
"org.springframework.boot.web.servlet.filter.OrderedFormContentFilter"
    } ],
    "servlets" : [ {
        "mappings" : [ ],
        "name" : "default",
        "className" : "org.apache.catalina.servlets.DefaultServlet"
    }, {
        "mappings" : [ "/" ],
        "name" : "dispatcherServlet",
        "className" : "org.springframework.web.servlet.DispatcherServlet"
    } ]
    }
}
}
}

```

17.1.1. Response Structure

The response contains details of the application's mappings. The items found in the response depend on the type of web application (reactive or Servlet-based). The following table describes the structure of the common elements of the response:

Path	Type	Description
<code>contexts</code>	Object	Application contexts keyed by id.
<code>contexts.*.mappings</code>	Object	Mappings in the context, keyed by mapping type.
<code>contexts.*.mappings.dispatcherServlets</code>	Object	Dispatcher servlet mappings, if any.
<code>contexts.*.mappings.servletFilters</code>	Array	Servlet filter mappings, if any.
<code>contexts.*.mappings.servlets</code>	Array	Servlet mappings, if any.
<code>contexts.*.mappings.dispatcherHandlers</code>	Object	Dispatcher handler mappings, if any.
<code>contexts.*.parentId</code>	String	Id of the parent application context, if any.

The entries that may be found in `contexts.*.mappings` are described in the following sections.

17.1.2. Dispatcher Servlets Response Structure

When using Spring MVC, the response contains details of any `DispatcherServlet` request mappings beneath `contexts.*.mappings.dispatcherServlets`. The following table describes the structure of this section of the response:

Path	Type	Description
*	Array	Dispatcher servlet mappings, if any, keyed by dispatcher servlet bean name.
*.[].details	Object	Additional implementation-specific details about the mapping. Optional.
*.[].handler	String	Handler for the mapping.
*.[].predicate	String	Predicate for the mapping.
*.[].details.handlerMethod	Object	Details of the method, if any, that will handle requests to this mapping.
*.[].details.handlerMethod.className	Varies	Fully qualified name of the class of the method.
*.[].details.handlerMethod.name	Varies	Name of the method.
*.[].details.handlerMethod.descriptor	Varies	Descriptor of the method as specified in the Java Language Specification.
*.[].details.requestMappingConditions	Object	Details of the request mapping conditions.
*.[].details.requestMappingConditions.consumes	Varies	Details of the consumes condition
*.[].details.requestMappingConditions.consumes[].mediaType	Varies	Consumed media type.
*.[].details.requestMappingConditions.consumes[].negated	Varies	Whether the media type is negated.
*.[].details.requestMappingConditions.headers	Varies	Details of the headers condition.
*.[].details.requestMappingConditions.headers[].name	Varies	Name of the header.
*.[].details.requestMappingConditions.headers[].value	Varies	Required value of the header, if any.
*.[].details.requestMappingConditions.headers[].negated	Varies	Whether the value is negated.
*.[].details.requestMappingConditions.methods	Varies	HTTP methods that are handled.
*.[].details.requestMappingConditions.params	Varies	Details of the params condition.
*.[].details.requestMappingConditions.params[].name	Varies	Name of the parameter.

Path	Type	Description
*.[] details.requestMappingConditions.params.[] value	Varies	Required value of the parameter, if any.
*.[] details.requestMappingConditions.params.[] negated	Varies	Whether the value is negated.
*.[] details.requestMappingConditions.patterns	Varies	Patterns identifying the paths handled by the mapping.
*.[] details.requestMappingConditions.produces	Varies	Details of the produces condition.
*.[] details.requestMappingConditions.produces.[] mediaType	Varies	Produced media type.
*.[] details.requestMappingConditions.produces.[] negated	Varies	Whether the media type is negated.

17.1.3. Servlets Response Structure

When using the Servlet stack, the response contains details of any **Servlet** mappings beneath `contexts.*.mappings.servlets`. The following table describes the structure of this section of the response:

Path	Type	Description
[] mappings	Array	Mappings of the servlet.
[] name	String	Name of the servlet.
[] className	String	Class name of the servlet

17.1.4. Servlet Filters Response Structure

When using the Servlet stack, the response contains details of any **Filter** mappings beneath `contexts.*.mappings.servletFilters`. The following table describes the structure of this section of the response:

Path	Type	Description
[] servletNameMappings	Array	Names of the servlets to which the filter is mapped.
[] urlPatternMappings	Array	URL pattern to which the filter is mapped.
[] name	String	Name of the filter.
[] className	String	Class name of the filter

17.1.5. Dispatcher Handlers Response Structure

When using Spring WebFlux, the response contains details of any **DispatcherHandler** request mappings beneath `contexts.*.mappings.dispatcherHandlers`. The following table describes the

structure of this section of the response:

Path	Type	Description
*	Array	Dispatcher handler mappings, if any, keyed by dispatcher handler bean name.
*. []. details	Object	Additional implementation-specific details about the mapping. Optional.
*. []. handler	String	Handler for the mapping.
*. []. predicate	String	Predicate for the mapping.
*. []. details. requestMappingConditions	Object	Details of the request mapping conditions.
*. []. details. requestMappingConditions. consumes	Array	Details of the consumes condition
*. []. details. requestMappingConditions. consumes. []. mediaType	String	Consumed media type.
*. []. details. requestMappingConditions. consumes. []. negated	Boolean	Whether the media type is negated.
*. []. details. requestMappingConditions. headers	Array	Details of the headers condition.
*. []. details. requestMappingConditions. headers. []. name	String	Name of the header.
*. []. details. requestMappingConditions. headers. []. value	String	Required value of the header, if any.
*. []. details. requestMappingConditions. headers. []. negated	Boolean	Whether the value is negated.
*. []. details. requestMappingConditions. methods	Array	HTTP methods that are handled.
*. []. details. requestMappingConditions. params	Array	Details of the params condition.
*. []. details. requestMappingConditions. params. []. name	String	Name of the parameter.
*. []. details. requestMappingConditions. params. []. value	String	Required value of the parameter, if any.
*. []. details. requestMappingConditions. params. []. negated	Boolean	Whether the value is negated.
*. []. details. requestMappingConditions. patterns	Array	Patterns identifying the paths handled by the mapping.

Path	Type	Description
*. [].details.requestMappingConditions.produces	Array	Details of the produces condition.
*. [].details.requestMappingConditions.produces. [].mediaType	String	Produced media type.
*. [].details.requestMappingConditions.produces. [].negated	Boolean	Whether the media type is negated.
*. [].details.handlerMethod	Object	Details of the method, if any, that will handle requests to this mapping.
*. [].details.handlerMethod.className	String	Fully qualified name of the class of the method.
*. [].details.handlerMethod.name	String	Name of the method.
*. [].details.handlerMethod.descriptor	String	Descriptor of the method as specified in the Java Language Specification.
*. [].details.handlerFunction	Object	Details of the function, if any, that will handle requests to this mapping.
*. [].details.handlerFunction.className	String	Fully qualified name of the class of the function.

Chapter 18. Metrics (metrics)

The `metrics` endpoint provides access to application metrics.

18.1. Retrieving Metric Names

To retrieve the names of the available metrics, make a `GET` request to `/actuator/metrics`, as shown in the following curl-based example:

```
$ curl 'http://localhost:8080/actuator/metrics' -i -X GET
```

The resulting response is similar to the following:

```
HTTP/1.1 200 OK
Content-Type: application/vnd.spring-boot.actuator.v3+json
Content-Length: 154

{
  "names" : [ "jvm.buffer.count", "jvm.buffer.memory.used",
    "jvm.buffer.total.capacity", "jvm.memory.committed", "jvm.memory.max",
    "jvm.memory.used" ]
}
```

18.1.1. Response Structure

The response contains details of the metric names. The following table describes the structure of the response:

Path	Type	Description
<code>names</code>	<code>Array</code>	Names of the known metrics.

18.2. Retrieving a Metric

To retrieve a metric, make a `GET` request to `/actuator/metrics/{metric.name}`, as shown in the following curl-based example:

```
$ curl 'http://localhost:8080/actuator/metrics/jvm.memory.max' -i -X GET
```

The preceding example retrieves information about the metric named `jvm.memory.max`. The resulting response is similar to the following:


```
HTTP/1.1 200 OK
Content-Disposition: inline;filename=f.txt
Content-Type: application/vnd.spring-boot.actuator.v3+json
Content-Length: 474

{
  "name" : "jvm.memory.max",
  "description" : "The maximum amount of memory in bytes that can be used for memory
management",
  "baseUnit" : "bytes",
  "measurements" : [ {
    "statistic" : "VALUE",
    "value" : 2.361393151E9
  } ],
  "availableTags" : [ {
    "tag" : "area",
    "values" : [ "heap", "nonheap" ]
  }, {
    "tag" : "id",
    "values" : [ "Compressed Class Space", "PS Old Gen", "PS Survivor Space",
"Metaspace", "PS Eden Space", "Code Cache" ]
  } ]
}
```

18.2.1. Query Parameters

The endpoint uses query parameters to [drill down](#) into a metric by using its tags. The following table shows the single supported query parameter:

Parameter	Description
<code>tag</code>	A tag to use for drill-down in the form <code>name:value</code> .

18.2.2. Response structure

The response contains details of the metric. The following table describes the structure of the response:

Path	Type	Description
<code>name</code>	<code>String</code>	Name of the metric
<code>description</code>	<code>String</code>	Description of the metric
<code>baseUnit</code>	<code>String</code>	Base unit of the metric
<code>measurements</code>	<code>Array</code>	Measurements of the metric

Path	Type	Description
<code>measurements[].statistic</code>	String	Statistic of the measurement. (TOTAL, TOTAL_TIME, COUNT, MAX, VALUE, UNKNOWN, ACTIVE_TASKS, DURATION).
<code>measurements[].value</code>	Number	Value of the measurement.
<code>availableTags</code>	Array	Tags that are available for drill-down.
<code>availableTags[].tag</code>	String	Name of the tag.
<code>availableTags[].values</code>	Array	Possible values of the tag.

18.3. Drilling Down

To drill down into a metric, make a **GET** request to `/actuator/metrics/{metric.name}` using the **tag** query parameter, as shown in the following curl-based example:

```
$ curl
'http://localhost:8080/actuator/metrics/jvm.memory.max?tag=area%3Aanonheap&tag=id%3ACompressed+Class+Space' -i -X GET
```

The preceding example retrieves the `jvm.memory.max` metric, where the `area` tag has a value of `nonheap` and the `id` attribute has a value of `Compressed Class Space`. The resulting response is similar to the following:

```
HTTP/1.1 200 OK
Content-Disposition: inline;filename=f.txt
Content-Type: application/vnd.spring-boot.actuator.v3+json
Content-Length: 263

{
  "name" : "jvm.memory.max",
  "description" : "The maximum amount of memory in bytes that can be used for memory management",
  "baseUnit" : "bytes",
  "measurements" : [ {
    "statistic" : "VALUE",
    "value" : 1.073741824E9
  } ],
  "availableTags" : [ ]
}
```

Chapter 19. Prometheus (prometheus)

The `prometheus` endpoint provides Spring Boot application's metrics in the format required for scraping by a Prometheus server.

19.1. Retrieving the Metrics

To retrieve the metrics, make a `GET` request to `/actuator/prometheus`, as shown in the following curl-based example:

```
$ curl 'http://localhost:8080/actuator/prometheus' -i -X GET
```

The resulting response is similar to the following:

HTTP/1.1 200 OK

Content-Type: text/plain;version=0.0.4;charset=utf-8

Content-Length: 2372

HELP jvm_buffer_memory_used_bytes An estimate of the memory that the Java virtual machine is using for this buffer pool

TYPE jvm_buffer_memory_used_bytes gauge

jvm_buffer_memory_used_bytes{id="direct"}, 466950.0

jvm_buffer_memory_used_bytes{id="mapped"}, 0.0

HELP jvm_memory_used_bytes The amount of used memory

TYPE jvm_memory_used_bytes gauge

jvm_memory_used_bytes{area="heap",id="PS Survivor Space"}, 9919440.0

jvm_memory_used_bytes{area="heap",id="PS Old Gen"}, 2.50636104E8

jvm_memory_used_bytes{area="heap",id="PS Eden Space"}, 2.87720448E8

jvm_memory_used_bytes{area="nonheap",id="Metaspace"}, 2.53096832E8

jvm_memory_used_bytes{area="nonheap",id="Code Cache"}, 7.2729728E7

jvm_memory_used_bytes{area="nonheap",id="Compressed Class Space"}, 3.629536E7

HELP jvm_memory_committed_bytes The amount of memory in bytes that is committed for the Java virtual machine to use

TYPE jvm_memory_committed_bytes gauge

jvm_memory_committed_bytes{area="heap",id="PS Survivor Space"}, 2.6738688E7

jvm_memory_committed_bytes{area="heap",id="PS Old Gen"}, 4.30440448E8

jvm_memory_committed_bytes{area="heap",id="PS Eden Space"}, 3.00417024E8

jvm_memory_committed_bytes{area="nonheap",id="Metaspace"}, 2.72105472E8

jvm_memory_committed_bytes{area="nonheap",id="Code Cache"}, 7.471104E7

jvm_memory_committed_bytes{area="nonheap",id="Compressed Class Space"}, 3.9845888E7

HELP jvm_memory_max_bytes The maximum amount of memory in bytes that can be used for memory management

TYPE jvm_memory_max_bytes gauge

jvm_memory_max_bytes{area="heap",id="PS Survivor Space"}, 2.6738688E7

jvm_memory_max_bytes{area="heap",id="PS Old Gen"}, 7.16177408E8

jvm_memory_max_bytes{area="heap",id="PS Eden Space"}, 3.05659904E8

jvm_memory_max_bytes{area="nonheap",id="Metaspace"}, -1.0

jvm_memory_max_bytes{area="nonheap",id="Code Cache"}, 2.5165824E8

jvm_memory_max_bytes{area="nonheap",id="Compressed Class Space"}, 1.073741824E9

HELP jvm_buffer_count_buffers An estimate of the number of buffers in the pool

TYPE jvm_buffer_count_buffers gauge

jvm_buffer_count_buffers{id="direct"}, 20.0

jvm_buffer_count_buffers{id="mapped"}, 0.0

HELP jvm_buffer_total_capacity_bytes An estimate of the total capacity of the buffers in this pool

TYPE jvm_buffer_total_capacity_bytes gauge

jvm_buffer_total_capacity_bytes{id="direct"}, 466948.0

jvm_buffer_total_capacity_bytes{id="mapped"}, 0.0

Chapter 20. Scheduled Tasks (scheduledtasks)

The `scheduledtasks` endpoint provides information about the application's scheduled tasks.

20.1. Retrieving the Scheduled Tasks

To retrieve the scheduled tasks, make a `GET` request to `/actuator/scheduledtasks`, as shown in the following curl-based example:

```
$ curl 'http://localhost:8080/actuator/scheduledtasks' -i -X GET
```

The resulting response is similar to the following:

```
HTTP/1.1 200 OK
Content-Type: application/vnd.spring-boot.actuator.v3+json
Content-Length: 629

{
  "cron" : [ {
    "runnable" : {
      "target" : "com.example.Processor.processOrders"
    },
    "expression" : "0 0 0/3 1/1 * ?"
  } ],
  "fixedDelay" : [ {
    "runnable" : {
      "target" : "com.example.Processor.purge"
    },
    "initialDelay" : 5000,
    "interval" : 5000
  } ],
  "fixedRate" : [ {
    "runnable" : {
      "target" : "com.example.Processor.retrieveIssues"
    },
    "initialDelay" : 10000,
    "interval" : 3000
  } ],
  "custom" : [ {
    "runnable" : {
      "target" : "com.example.Processor$CustomTriggeredRunnable"
    },
    "trigger" : "com.example.Processor$CustomTrigger@706b63ea"
  } ]
}
```

20.1.1. Response Structure

The response contains details of the application's scheduled tasks. The following table describes the structure of the response:

Path	Type	Description
<code>cron</code>	Array	Cron tasks, if any.
<code>cron[].runnable.target</code>	String	Target that will be executed.
<code>cron[].expression</code>	String	Cron expression.
<code>fixedDelay</code>	Array	Fixed delay tasks, if any.
<code>fixedDelay[].runnable.target</code>	String	Target that will be executed.
<code>fixedDelay[].initialDelay</code>	Number	Delay, in milliseconds, before first execution.
<code>fixedDelay[].interval</code>	Number	Interval, in milliseconds, between the end of the last execution and the start of the next.
<code>fixedRate</code>	Array	Fixed rate tasks, if any.
<code>fixedRate[].runnable.target</code>	String	Target that will be executed.
<code>fixedRate[].interval</code>	Number	Interval, in milliseconds, between the start of each execution.
<code>fixedRate[].initialDelay</code>	Number	Delay, in milliseconds, before first execution.
<code>custom</code>	Array	Tasks with custom triggers, if any.
<code>custom[].runnable.target</code>	String	Target that will be executed.
<code>custom[].trigger</code>	String	Trigger for the task.

Chapter 21. Sessions (sessions)

The `sessions` endpoint provides information about the application's HTTP sessions that are managed by Spring Session.

21.1. Retrieving Sessions

To retrieve the sessions, make a `GET` request to `/actuator/sessions`, as shown in the following curl-based example:

```
$ curl 'http://localhost:8080/actuator/sessions?username=alice' -i -X GET
```

The preceding examples retrieves all of the sessions for the user whose username is `alice`. The resulting response is similar to the following:

```
HTTP/1.1 200 OK
Content-Type: application/vnd.spring-boot.actuator.v3+json
Content-Length: 753

{
  "sessions" : [ {
    "id" : "c69c2c50-1383-4f7c-b3e5-a3dfdf59abca",
    "attributeNames" : [ ],
    "creationTime" : "2020-11-11T20:35:04.658Z",
    "lastAccessedTime" : "2020-11-12T08:34:19.658Z",
    "maxInactiveInterval" : 1800,
    "expired" : false
  }, {
    "id" : "4db5efcc-99cb-4d05-a52c-b49acfb7ea9",
    "attributeNames" : [ ],
    "creationTime" : "2020-11-12T03:35:04.659Z",
    "lastAccessedTime" : "2020-11-12T08:34:27.659Z",
    "maxInactiveInterval" : 1800,
    "expired" : false
  }, {
    "id" : "c9ef45a4-e763-4d4c-b032-1f2558ebf9d1",
    "attributeNames" : [ ],
    "creationTime" : "2020-11-12T06:35:04.659Z",
    "lastAccessedTime" : "2020-11-12T08:34:52.659Z",
    "maxInactiveInterval" : 1800,
    "expired" : false
  } ]
}
```

21.1.1. Query Parameters

The endpoint uses query parameters to limit the sessions that it returns. The following table shows the single required query parameter:

Parameter	Description
<code>username</code>	Name of the user.

21.1.2. Response Structure

The response contains details of the matching sessions. The following table describes the structure of the response:

Path	Type	Description
<code>sessions</code>	Array	Sessions for the given username.
<code>sessions[].id</code>	String	ID of the session.
<code>sessions[].attributeNames</code>	Array	Names of the attributes stored in the session.
<code>sessions[].creationTime</code>	String	Timestamp of when the session was created.
<code>sessions[].lastAccessedTime</code>	String	Timestamp of when the session was last accessed.
<code>sessions[].maxInactiveInterval</code>	Number	Maximum permitted period of inactivity, in seconds, before the session will expire.
<code>sessions[].expired</code>	Boolean	Whether the session has expired.

21.2. Retrieving a Single Session

To retrieve a single session, make a `GET` request to `/actuator/sessions/{id}`, as shown in the following curl-based example:

```
$ curl 'http://localhost:8080/actuator/sessions/4db5efcc-99cb-4d05-a52c-b49acfb7ea9'
-i -X GET
```

The preceding example retrieves the session with the `id` of `4db5efcc-99cb-4d05-a52c-b49acfb7ea9`. The resulting response is similar to the following:


```
HTTP/1.1 200 OK
Content-Type: application/vnd.spring-boot.actuator.v3+json
Content-Length: 228

{
  "id" : "4db5efcc-99cb-4d05-a52c-b49acfb7ea9",
  "attributeNames" : [ ],
  "creationTime" : "2020-11-12T03:35:04.659Z",
  "lastAccessedTime" : "2020-11-12T08:34:27.659Z",
  "maxInactiveInterval" : 1800,
  "expired" : false
}
```

21.2.1. Response Structure

The response contains details of the requested session. The following table describes the structure of the response:

Path	Type	Description
<code>id</code>	<code>String</code>	ID of the session.
<code>attributeNames</code>	<code>Array</code>	Names of the attributes stored in the session.
<code>creationTime</code>	<code>String</code>	Timestamp of when the session was created.
<code>lastAccessedTime</code>	<code>String</code>	Timestamp of when the session was last accessed.
<code>maxInactiveInterval</code>	<code>Number</code>	Maximum permitted period of inactivity, in seconds, before the session will expire.
<code>expired</code>	<code>Boolean</code>	Whether the session has expired.

21.3. Deleting a Session

To delete a session, make a **DELETE** request to `/actuator/sessions/{id}`, as shown in the following curl-based example:

```
$ curl 'http://localhost:8080/actuator/sessions/4db5efcc-99cb-4d05-a52c-b49acfb7ea9'
-i -X DELETE
```

The preceding example deletes the session with the `id` of `4db5efcc-99cb-4d05-a52c-b49acfb7ea9`.

Chapter 22. Shutdown (shutdown)

The **shutdown** endpoint is used to shut down the application.

22.1. Shutting Down the Application

To shut down the application, make a **POST** request to **/actuator/shutdown**, as shown in the following curl-based example:

```
$ curl 'http://localhost:8080/actuator/shutdown' -i -X POST
```

A response similar to the following is produced:

```
HTTP/1.1 200 OK
Content-Type: application/vnd.spring-boot.actuator.v3+json
Content-Length: 41

{
  "message" : "Shutting down, bye..."
}
```

22.1.1. Response Structure

The response contains details of the result of the shutdown request. The following table describes the structure of the response:

Path	Type	Description
message	String	Message describing the result of the request.

Chapter 23. Thread Dump (threaddump)

The `threaddump` endpoint provides a thread dump from the application's JVM.

23.1. Retrieving the Thread Dump as JSON

To retrieve the thread dump as JSON, make a `GET` request to `/actuator/threaddump` with an appropriate `Accept` header, as shown in the following curl-based example:

```
$ curl 'http://localhost:8080/actuator/threaddump' -i -X GET \
-H 'Accept: application/json'
```

The resulting response is similar to the following:

```
HTTP/1.1 200 OK
Content-Type: application/json
Content-Length: 7418

{
  "threads" : [ {
    "threadName" : "Thread-201",
    "threadId" : 1465,
    "blockedTime" : -1,
    "blockedCount" : 0,
    "waitedTime" : -1,
    "waitedCount" : 1,
    "lockName" : "java.util.concurrent.CountDownLatch$Sync@375e7668",
    "lockOwnerId" : -1,
    "inNative" : false,
    "suspended" : false,
    "threadState" : "WAITING",
    "stackTrace" : [ {
      "methodName" : "park",
      "fileName" : "Unsafe.java",
      "lineNumber" : -2,
      "className" : "sun.misc.Unsafe",
      "nativeMethod" : true
    }, {
      "methodName" : "park",
      "fileName" : "LockSupport.java",
      "lineNumber" : 175,
      "className" : "java.util.concurrent.locks.LockSupport",
      "nativeMethod" : false
    }, {
      "methodName" : "parkAndCheckInterrupt",
      "fileName" : "AbstractQueuedSynchronizer.java",
      "lineNumber" : 836,
      "className" : "java.util.concurrent.locks.AbstractQueuedSynchronizer",
```

```

    "nativeMethod" : false
  }, {
    "methodName" : "doAcquireSharedInterruptibly",
    "fileName" : "AbstractQueuedSynchronizer.java",
    "lineNumber" : 997,
    "className" : "java.util.concurrent.locks.AbstractQueuedSynchronizer",
    "nativeMethod" : false
  }, {
    "methodName" : "acquireSharedInterruptibly",
    "fileName" : "AbstractQueuedSynchronizer.java",
    "lineNumber" : 1304,
    "className" : "java.util.concurrent.locks.AbstractQueuedSynchronizer",
    "nativeMethod" : false
  }, {
    "methodName" : "await",
    "fileName" : "CountDownLatch.java",
    "lineNumber" : 231,
    "className" : "java.util.concurrent.CountDownLatch",
    "nativeMethod" : false
  }, {
    "methodName" : "lambda$jsonThreadDump$0",
    "fileName" : "ThreadDumpEndpointDocumentationTests.java",
    "lineNumber" : 56,
    "className" :
"org.springframework.boot.actuate.autoconfigure.endpoint.web.documentation.ThreadDumpE
ndpointDocumentationTests",
    "nativeMethod" : false
  }, {
    "methodName" : "run",
    "lineNumber" : -1,
    "className" :
"org.springframework.boot.actuate.autoconfigure.endpoint.web.documentation.ThreadDumpE
ndpointDocumentationTests$$Lambda$5102/1610216352",
    "nativeMethod" : false
  }, {
    "methodName" : "run",
    "fileName" : "Thread.java",
    "lineNumber" : 748,
    "className" : "java.lang.Thread",
    "nativeMethod" : false
  } ],
  "lockedMonitors" : [ ],
  "lockedSynchronizers" : [ {
    "className" : "java.util.concurrent.locks.ReentrantLock$NonfairSync",
    "identityHashCode" : 1853935301
  } ],
  "lockInfo" : {
    "className" : "java.util.concurrent.CountDownLatch$Sync",
    "identityHashCode" : 928937576
  }
}, {

```

```

"threadName" : "HikariPool-14 connection adder",
"threadId" : 1460,
"blockedTime" : -1,
"blockedCount" : 0,
"waitedTime" : -1,
"waitedCount" : 1,
"lockName" :
"java.util.concurrent.locks.AbstractQueuedSynchronizer$ConditionObject@4e4a0be4",
"lockOwnerId" : -1,
"inNative" : false,
"suspended" : false,
"threadState" : "TIMED_WAITING",
"stackTrace" : [ {
  "methodName" : "park",
  "fileName" : "Unsafe.java",
  "lineNumber" : -2,
  "className" : "sun.misc.Unsafe",
  "nativeMethod" : true
}, {
  "methodName" : "parkNanos",
  "fileName" : "LockSupport.java",
  "lineNumber" : 215,
  "className" : "java.util.concurrent.locks.LockSupport",
  "nativeMethod" : false
}, {
  "methodName" : "awaitNanos",
  "fileName" : "AbstractQueuedSynchronizer.java",
  "lineNumber" : 2078,
  "className" :
"java.util.concurrent.locks.AbstractQueuedSynchronizer$ConditionObject",
  "nativeMethod" : false
}, {
  "methodName" : "poll",
  "fileName" : "LinkedBlockingQueue.java",
  "lineNumber" : 467,
  "className" : "java.util.concurrent.LinkedBlockingQueue",
  "nativeMethod" : false
}, {
  "methodName" : "getTask",
  "fileName" : "ThreadPoolExecutor.java",
  "lineNumber" : 1073,
  "className" : "java.util.concurrent.ThreadPoolExecutor",
  "nativeMethod" : false
}, {
  "methodName" : "runWorker",
  "fileName" : "ThreadPoolExecutor.java",
  "lineNumber" : 1134,
  "className" : "java.util.concurrent.ThreadPoolExecutor",
  "nativeMethod" : false
}, {
  "methodName" : "run",

```

```

    "fileName" : "ThreadPoolExecutor.java",
    "lineNumber" : 624,
    "className" : "java.util.concurrent.ThreadPoolExecutor$Worker",
    "nativeMethod" : false
  }, {
    "methodName" : "run",
    "fileName" : "Thread.java",
    "lineNumber" : 748,
    "className" : "java.lang.Thread",
    "nativeMethod" : false
  } ],
  "lockedMonitors" : [ ],
  "lockedSynchronizers" : [ ],
  "lockInfo" : {
    "className" :
"java.util.concurrent.locks.AbstractQueuedSynchronizer$ConditionObject",
    "identityHashCode" : 1313475556
  }
}, {
  "threadName" : "HikariPool-14 housekeeper",
  "threadId" : 1459,
  "blockedTime" : -1,
  "blockedCount" : 0,
  "waitedTime" : -1,
  "waitedCount" : 2,
  "lockName" :
"java.util.concurrent.locks.AbstractQueuedSynchronizer$ConditionObject@49d82fd9",
  "lockOwnerId" : -1,
  "inNative" : false,
  "suspended" : false,
  "threadState" : "TIMED_WAITING",
  "stackTrace" : [ {
    "methodName" : "park",
    "fileName" : "Unsafe.java",
    "lineNumber" : -2,
    "className" : "sun.misc.Unsafe",
    "nativeMethod" : true
  }, {
    "methodName" : "parkNanos",
    "fileName" : "LockSupport.java",
    "lineNumber" : 215,
    "className" : "java.util.concurrent.locks.LockSupport",
    "nativeMethod" : false
  }, {
    "methodName" : "awaitNanos",
    "fileName" : "AbstractQueuedSynchronizer.java",
    "lineNumber" : 2078,
    "className" :
"java.util.concurrent.locks.AbstractQueuedSynchronizer$ConditionObject",
    "nativeMethod" : false
  }, {

```

```

    "methodName" : "take",
    "fileName" : "ScheduledThreadPoolExecutor.java",
    "lineNumber" : 1093,
    "className" :
"java.util.concurrent.ScheduledThreadPoolExecutor$DelayedWorkQueue",
    "nativeMethod" : false
  }, {
    "methodName" : "take",
    "fileName" : "ScheduledThreadPoolExecutor.java",
    "lineNumber" : 809,
    "className" :
"java.util.concurrent.ScheduledThreadPoolExecutor$DelayedWorkQueue",
    "nativeMethod" : false
  }, {
    "methodName" : "getTask",
    "fileName" : "ThreadPoolExecutor.java",
    "lineNumber" : 1074,
    "className" : "java.util.concurrent.ThreadPoolExecutor",
    "nativeMethod" : false
  }, {
    "methodName" : "runWorker",
    "fileName" : "ThreadPoolExecutor.java",
    "lineNumber" : 1134,
    "className" : "java.util.concurrent.ThreadPoolExecutor",
    "nativeMethod" : false
  }, {
    "methodName" : "run",
    "fileName" : "ThreadPoolExecutor.java",
    "lineNumber" : 624,
    "className" : "java.util.concurrent.ThreadPoolExecutor$Worker",
    "nativeMethod" : false
  }, {
    "methodName" : "run",
    "fileName" : "Thread.java",
    "lineNumber" : 748,
    "className" : "java.lang.Thread",
    "nativeMethod" : false
  } ],
  "lockedMonitors" : [ ],
  "lockedSynchronizers" : [ ],
  "lockInfo" : {
    "className" :
"java.util.concurrent.locks.AbstractQueuedSynchronizer$ConditionObject",
    "identityHashCode" : 1238904793
  }
} ]
}

```

23.1.1. Response Structure

The response contains details of the JVM's threads. The following table describes the structure of the response:

Path	Type	Description
<code>threads</code>	Array	JVM's threads.
<code>threads[].blockedCount</code>	Number	Total number of times that the thread has been blocked.
<code>threads[].blockedTime</code>	Number	Time in milliseconds that the thread has spent blocked. -1 if thread contention monitoring is disabled.
<code>threads[].daemon</code>	Boolean	Whether the thread is a daemon thread. Only available on Java 9 or later.
<code>threads[].inNative</code>	Boolean	Whether the thread is executing native code.
<code>threads[].lockName</code>	String	Description of the object on which the thread is blocked, if any.
<code>threads[].lockInfo</code>	Object	Object for which the thread is blocked waiting.
<code>threads[].lockInfo.className</code>	String	Fully qualified class name of the lock object.
<code>threads[].lockInfo.identityHashCode</code>	Number	Identity hash code of the lock object.
<code>threads[].lockedMonitors</code>	Array	Monitors locked by this thread, if any
<code>threads[].lockedMonitors[].className</code>	String	Class name of the lock object.
<code>threads[].lockedMonitors[].identityHashCode</code>	Number	Identity hash code of the lock object.
<code>threads[].lockedMonitors[].lockedStackDepth</code>	Number	Stack depth where the monitor was locked.
<code>threads[].lockedMonitors[].lockedStackFrame</code>	Object	Stack frame that locked the monitor.
<code>threads[].lockedSynchronizers</code>	Array	Synchronizers locked by this thread.
<code>threads[].lockedSynchronizers[].className</code>	String	Class name of the locked synchronizer.

Path	Type	Description
<code>threads[].lockedSynchronizers[].identityHashCode</code>	Number	Identity hash code of the locked synchronizer.
<code>threads[].lockOwnerId</code>	Number	ID of the thread that owns the object on which the thread is blocked. <code>-1</code> if the thread is not blocked.
<code>threads[].lockOwnerName</code>	String	Name of the thread that owns the object on which the thread is blocked, if any.
<code>threads[].priority</code>	Number	Priority of the thread. Only available on Java 9 or later.
<code>threads[].stackTrace</code>	Array	Stack trace of the thread.
<code>threads[].stackTrace[].classLoaderName</code>	String	Name of the class loader of the class that contains the execution point identified by this entry, if any. Only available on Java 9 or later.
<code>threads[].stackTrace[].className</code>	String	Name of the class that contains the execution point identified by this entry.
<code>threads[].stackTrace[].fileName</code>	String	Name of the source file that contains the execution point identified by this entry, if any.
<code>threads[].stackTrace[].lineNumber</code>	Number	Line number of the execution point identified by this entry. Negative if unknown.
<code>threads[].stackTrace[].methodName</code>	String	Name of the method.
<code>threads[].stackTrace[].moduleName</code>	String	Name of the module that contains the execution point identified by this entry, if any. Only available on Java 9 or later.
<code>threads[].stackTrace[].moduleVersion</code>	String	Version of the module that contains the execution point identified by this entry, if any. Only available on Java 9 or later.
<code>threads[].stackTrace[].nativeMethod</code>	Boolean	Whether the execution point is a native method.
<code>threads[].suspended</code>	Boolean	Whether the thread is suspended.

Path	Type	Description
<code>threads[].threadId</code>	Number	ID of the thread.
<code>threads[].threadName</code>	String	Name of the thread.
<code>threads[].threadState</code>	String	State of the thread (NEW, RUNNABLE, BLOCKED, WAITING, TIMED_WAITING, TERMINATED).
<code>threads[].waitedCount</code>	Number	Total number of times that the thread has waited for notification.
<code>threads[].waitedTime</code>	Number	Time in milliseconds that the thread has spent waiting. -1 if thread contention monitoring is disabled

23.2. Retrieving the Thread Dump as Text

To retrieve the thread dump as text, make a `GET` request to `/actuator/threaddump` that accepts `text/plain`, as shown in the following curl-based example:

```
$ curl 'http://localhost:8080/actuator/threaddump' -i -X GET \
-H 'Accept: text/plain'
```

The resulting response is similar to the following:

```
HTTP/1.1 200 OK
Content-Type: text/plain; charset=UTF-8
Content-Length: 81956

2020-11-12 08:35:03
Full thread dump OpenJDK 64-Bit Server VM (25.272-b10 mixed mode):

"HikariPool-14 connection adder" - Thread t@1460
  java.lang.Thread.State: TIMED_WAITING
    at sun.misc.Unsafe.park(Native Method)
      - parking to wait for <4e4a0be4> (a
java.util.concurrent.locks.AbstractQueuedSynchronizer$ConditionObject)
    at java.util.concurrent.locks.LockSupport.parkNanos(LockSupport.java:215)
    at
java.util.concurrent.locks.AbstractQueuedSynchronizer$ConditionObject.awaitNanos(Abstr
actQueuedSynchronizer.java:2078)
    at java.util.concurrent.LinkedBlockingQueue.poll(LinkedBlockingQueue.java:467)
    at java.util.concurrent.ThreadPoolExecutor.getTask(ThreadPoolExecutor.java:1073)
    at java.util.concurrent.ThreadPoolExecutor.runWorker(ThreadPoolExecutor.java:1134)
    at java.util.concurrent.ThreadPoolExecutor$Worker.run(ThreadPoolExecutor.java:624)
    at java.lang.Thread.run(Thread.java:748)
```

Locked ownable synchronizers:

- None

"HikariPool-14 housekeeper" - Thread t@1459

java.lang.Thread.State: TIMED_WAITING

at sun.misc.Unsafe.park(Native Method)

- parking to wait for <49d82fd9> (a

java.util.concurrent.locks.AbstractQueuedSynchronizer\$ConditionObject)

at java.util.concurrent.locks.LockSupport.parkNanos(LockSupport.java:215)

at

java.util.concurrent.locks.AbstractQueuedSynchronizer\$ConditionObject.awaitNanos(AbstractQueuedSynchronizer.java:2078)

at

java.util.concurrent.ScheduledThreadPoolExecutor\$DelayedWorkQueue.take(ScheduledThreadPoolExecutor.java:1093)

at

java.util.concurrent.ScheduledThreadPoolExecutor\$DelayedWorkQueue.take(ScheduledThreadPoolExecutor.java:809)

at java.util.concurrent.ThreadPoolExecutor.getTask(ThreadPoolExecutor.java:1074)

at java.util.concurrent.ThreadPoolExecutor.runWorker(ThreadPoolExecutor.java:1134)

at java.util.concurrent.ThreadPoolExecutor\$Worker.run(ThreadPoolExecutor.java:624)

at java.lang.Thread.run(Thread.java:748)

Locked ownable synchronizers:

- None

"reactor-http-epoll-8" - Thread t@1454

java.lang.Thread.State: RUNNABLE

at io.netty.channel.epoll.Native.epollWait(Native Method)

at io.netty.channel.epoll.Native.epollWait(Native.java:148)

at io.netty.channel.epoll.Native.epollWait(Native.java:141)

at

io.netty.channel.epoll.EpollEventLoop.epollWaitNoTimerChange(EpollEventLoop.java:290)

at io.netty.channel.epoll.EpollEventLoop.run(EpollEventLoop.java:347)

at

io.netty.util.concurrent.SingleThreadEventExecutor\$4.run(SingleThreadEventExecutor.java:989)

at io.netty.util.internal.ThreadExecutorMap\$2.run(ThreadExecutorMap.java:74)

at

io.netty.util.concurrent.FastThreadLocalRunnable.run(FastThreadLocalRunnable.java:30)

at java.lang.Thread.run(Thread.java:748)

Locked ownable synchronizers:

- None

"reactor-http-epoll-7" - Thread t@1453

java.lang.Thread.State: RUNNABLE

at io.netty.channel.epoll.Native.epollWait(Native Method)

at io.netty.channel.epoll.Native.epollWait(Native.java:148)

at io.netty.channel.epoll.Native.epollWait(Native.java:141)

```
at
io.netty.channel.epoll.EpollEventLoop.epollWaitNoTimerChange(EpollEventLoop.java:290)
  at io.netty.channel.epoll.EpollEventLoop.run(EpollEventLoop.java:347)
  at
io.netty.util.concurrent.SingleThreadEventExecutor$4.run(SingleThreadEventExecutor.java:989)
  at io.netty.util.internal.ThreadExecutorMap$2.run(ThreadExecutorMap.java:74)
  at
io.netty.util.concurrent.FastThreadLocalRunnable.run(FastThreadLocalRunnable.java:30)
  at java.lang.Thread.run(Thread.java:748)
```

Locked ownable synchronizers:
- None

"reactor-http-epoll-6" - Thread t@1452

```
java.lang.Thread.State: RUNNABLE
  at io.netty.channel.epoll.Native.epollWait(Native Method)
  at io.netty.channel.epoll.Native.epollWait(Native.java:148)
  at io.netty.channel.epoll.Native.epollWait(Native.java:141)
  at
io.netty.channel.epoll.EpollEventLoop.epollWaitNoTimerChange(EpollEventLoop.java:290)
  at io.netty.channel.epoll.EpollEventLoop.run(EpollEventLoop.java:347)
  at
io.netty.util.concurrent.SingleThreadEventExecutor$4.run(SingleThreadEventExecutor.java:989)
  at io.netty.util.internal.ThreadExecutorMap$2.run(ThreadExecutorMap.java:74)
  at
io.netty.util.concurrent.FastThreadLocalRunnable.run(FastThreadLocalRunnable.java:30)
  at java.lang.Thread.run(Thread.java:748)
```

Locked ownable synchronizers:
- None

"reactor-http-epoll-5" - Thread t@1451

```
java.lang.Thread.State: RUNNABLE
  at io.netty.channel.epoll.Native.epollWait(Native Method)
  at io.netty.channel.epoll.Native.epollWait(Native.java:148)
  at io.netty.channel.epoll.Native.epollWait(Native.java:141)
  at
io.netty.channel.epoll.EpollEventLoop.epollWaitNoTimerChange(EpollEventLoop.java:290)
  at io.netty.channel.epoll.EpollEventLoop.run(EpollEventLoop.java:347)
  at
io.netty.util.concurrent.SingleThreadEventExecutor$4.run(SingleThreadEventExecutor.java:989)
  at io.netty.util.internal.ThreadExecutorMap$2.run(ThreadExecutorMap.java:74)
  at
io.netty.util.concurrent.FastThreadLocalRunnable.run(FastThreadLocalRunnable.java:30)
  at java.lang.Thread.run(Thread.java:748)
```

Locked ownable synchronizers:
- None

```
"reactor-http-epoll-4" - Thread t@1450
  java.lang.Thread.State: RUNNABLE
    at io.netty.channel.epoll.Native.epollWait(Native Method)
    at io.netty.channel.epoll.Native.epollWait(Native.java:148)
    at io.netty.channel.epoll.Native.epollWait(Native.java:141)
    at
io.netty.channel.epoll.EpollEventLoop.epollWaitNoTimerChange(EpollEventLoop.java:290)
    at io.netty.channel.epoll.EpollEventLoop.run(EpollEventLoop.java:347)
    at
io.netty.util.concurrent.SingleThreadEventExecutor$4.run(SingleThreadEventExecutor.java:989)
    at io.netty.util.internal.ThreadExecutorMap$2.run(ThreadExecutorMap.java:74)
    at
io.netty.util.concurrent.FastThreadLocalRunnable.run(FastThreadLocalRunnable.java:30)
    at java.lang.Thread.run(Thread.java:748)
```

Locked ownable synchronizers:
- None

```
"reactor-http-epoll-3" - Thread t@1449
  java.lang.Thread.State: RUNNABLE
    at io.netty.channel.epoll.Native.epollWait(Native Method)
    at io.netty.channel.epoll.Native.epollWait(Native.java:148)
    at io.netty.channel.epoll.Native.epollWait(Native.java:141)
    at
io.netty.channel.epoll.EpollEventLoop.epollWaitNoTimerChange(EpollEventLoop.java:290)
    at io.netty.channel.epoll.EpollEventLoop.run(EpollEventLoop.java:347)
    at
io.netty.util.concurrent.SingleThreadEventExecutor$4.run(SingleThreadEventExecutor.java:989)
    at io.netty.util.internal.ThreadExecutorMap$2.run(ThreadExecutorMap.java:74)
    at
io.netty.util.concurrent.FastThreadLocalRunnable.run(FastThreadLocalRunnable.java:30)
    at java.lang.Thread.run(Thread.java:748)
```

Locked ownable synchronizers:
- None

```
"reactor-http-epoll-2" - Thread t@1448
  java.lang.Thread.State: RUNNABLE
    at io.netty.channel.epoll.Native.epollWait(Native Method)
    at io.netty.channel.epoll.Native.epollWait(Native.java:148)
    at io.netty.channel.epoll.Native.epollWait(Native.java:141)
    at
io.netty.channel.epoll.EpollEventLoop.epollWaitNoTimerChange(EpollEventLoop.java:290)
    at io.netty.channel.epoll.EpollEventLoop.run(EpollEventLoop.java:347)
    at
io.netty.util.concurrent.SingleThreadEventExecutor$4.run(SingleThreadEventExecutor.java:989)
    at io.netty.util.internal.ThreadExecutorMap$2.run(ThreadExecutorMap.java:74)
```

```
at
io.netty.util.concurrent.FastThreadLocalRunnable.run(FastThreadLocalRunnable.java:30)
at java.lang.Thread.run(Thread.java:748)
```

Locked ownable synchronizers:
- None

"server" - Thread t@1447

```
java.lang.Thread.State: WAITING
at sun.misc.Unsafe.park(Native Method)
- parking to wait for <3612a8e7> (a java.util.concurrent.CountDownLatch$Sync)
at java.util.concurrent.locks.LockSupport.park(LockSupport.java:175)
at
java.util.concurrent.locks.AbstractQueuedSynchronizer.parkAndCheckInterrupt(AbstractQueuedSynchronizer.java:836)
at
java.util.concurrent.locks.AbstractQueuedSynchronizer.doAcquireSharedInterruptibly(AbstractQueuedSynchronizer.java:997)
at
java.util.concurrent.locks.AbstractQueuedSynchronizer.acquireSharedInterruptibly(AbstractQueuedSynchronizer.java:1304)
at java.util.concurrent.CountDownLatch.await(CountDownLatch.java:231)
at
reactor.core.publisher.BlockingSingleSubscriber.blockingGet(BlockingSingleSubscriber.java:87)
at reactor.core.publisher.Mono.block(Mono.java:1680)
at
org.springframework.boot.web.embedded.netty.NettyWebServer$1.run(NettyWebServer.java:160)
```

Locked ownable synchronizers:
- None

"reactor-http-epoll-1" - Thread t@1446

```
java.lang.Thread.State: RUNNABLE
at io.netty.channel.epoll.Native.epollWait(Native Method)
at io.netty.channel.epoll.Native.epollWait(Native.java:148)
at io.netty.channel.epoll.Native.epollWait(Native.java:141)
at
io.netty.channel.epoll.EpollEventLoop.epollWaitNoTimerChange(EpollEventLoop.java:290)
at io.netty.channel.epoll.EpollEventLoop.run(EpollEventLoop.java:347)
at
io.netty.util.concurrent.SingleThreadEventExecutor$4.run(SingleThreadEventExecutor.java:989)
at io.netty.util.internal.ThreadExecutorMap$2.run(ThreadExecutorMap.java:74)
at
io.netty.util.concurrent.FastThreadLocalRunnable.run(FastThreadLocalRunnable.java:30)
at java.lang.Thread.run(Thread.java:748)
```

Locked ownable synchronizers:
- None

```
"http-nio-auto-46-Acceptor" - Thread t@1276
java.lang.Thread.State: RUNNABLE
  at sun.nio.ch.ServerSocketChannelImpl.accept0(Native Method)
  at sun.nio.ch.ServerSocketChannelImpl.accept(ServerSocketChannelImpl.java:421)
  at sun.nio.ch.ServerSocketChannelImpl.accept(ServerSocketChannelImpl.java:249)
  - locked <3821cb82> (a java.lang.Object)
  at org.apache.tomcat.util.net.NioEndpoint.serverSocketAccept(NioEndpoint.java:469)
  at org.apache.tomcat.util.net.NioEndpoint.serverSocketAccept(NioEndpoint.java:71)
  at org.apache.tomcat.util.net.Acceptor.run(Acceptor.java:106)
  at java.lang.Thread.run(Thread.java:748)
```

Locked ownable synchronizers:

- None

```
"http-nio-auto-46-ClientPoller" - Thread t@1275
java.lang.Thread.State: RUNNABLE
  at sun.nio.ch.EPollArrayWrapper.epollWait(Native Method)
  at sun.nio.ch.EPollArrayWrapper.poll(EPollArrayWrapper.java:269)
  at sun.nio.ch.EPollSelectorImpl.doSelect(EPollSelectorImpl.java:93)
  at sun.nio.ch.SelectorImpl.lockAndDoSelect(SelectorImpl.java:86)
  - locked <4d698fc0> (a sun.nio.ch.Util$3)
  - locked <73241de8> (a java.util.Collections$UnmodifiableSet)
  - locked <212a5ff8> (a sun.nio.ch.EPollSelectorImpl)
  at sun.nio.ch.SelectorImpl.select(SelectorImpl.java:97)
  at org.apache.tomcat.util.net.NioEndpoint$Poller.run(NioEndpoint.java:709)
  at java.lang.Thread.run(Thread.java:748)
```

Locked ownable synchronizers:

- None

```
"http-nio-auto-46-exec-10" - Thread t@1274
java.lang.Thread.State: WAITING
  at sun.misc.Unsafe.park(Native Method)
  - parking to wait for <17e1fd84> (a
java.util.concurrent.locks.AbstractQueuedSynchronizer$ConditionObject)
  at java.util.concurrent.locks.LockSupport.park(LockSupport.java:175)
  at
java.util.concurrent.locks.AbstractQueuedSynchronizer$ConditionObject.await(AbstractQueuedSynchronizer.java:2039)
  at java.util.concurrent.LinkedBlockingQueue.take(LinkedBlockingQueue.java:442)
  at org.apache.tomcat.util.threads.TaskQueue.take(TaskQueue.java:108)
  at org.apache.tomcat.util.threads.TaskQueue.take(TaskQueue.java:33)
  at java.util.concurrent.ThreadPoolExecutor.getTask(ThreadPoolExecutor.java:1074)
  at java.util.concurrent.ThreadPoolExecutor.runWorker(ThreadPoolExecutor.java:1134)
  at java.util.concurrent.ThreadPoolExecutor$Worker.run(ThreadPoolExecutor.java:624)
  at
org.apache.tomcat.util.threads.TaskThread$WrappingRunnable.run(TaskThread.java:61)
  at java.lang.Thread.run(Thread.java:748)
```

Locked ownable synchronizers:

- None

```
"http-nio-auto-46-exec-9" - Thread t@1273
  java.lang.Thread.State: WAITING
    at sun.misc.Unsafe.park(Native Method)
      - parking to wait for <17e1fd84> (a
java.util.concurrent.locks.AbstractQueuedSynchronizer$ConditionObject)
    at java.util.concurrent.locks.LockSupport.park(LockSupport.java:175)
    at
java.util.concurrent.locks.AbstractQueuedSynchronizer$ConditionObject.await(AbstractQueuedSynchronizer.java:2039)
    at java.util.concurrent.LinkedBlockingQueue.take(LinkedBlockingQueue.java:442)
    at org.apache.tomcat.util.threads.TaskQueue.take(TaskQueue.java:108)
    at org.apache.tomcat.util.threads.TaskQueue.take(TaskQueue.java:33)
    at java.util.concurrent.ThreadPoolExecutor.getTask(ThreadPoolExecutor.java:1074)
    at java.util.concurrent.ThreadPoolExecutor.runWorker(ThreadPoolExecutor.java:1134)
    at java.util.concurrent.ThreadPoolExecutor$Worker.run(ThreadPoolExecutor.java:624)
    at
org.apache.tomcat.util.threads.TaskThread$WrappingRunnable.run(TaskThread.java:61)
    at java.lang.Thread.run(Thread.java:748)
```

Locked ownable synchronizers:

- None

```
"http-nio-auto-46-exec-8" - Thread t@1272
  java.lang.Thread.State: WAITING
    at sun.misc.Unsafe.park(Native Method)
      - parking to wait for <17e1fd84> (a
java.util.concurrent.locks.AbstractQueuedSynchronizer$ConditionObject)
    at java.util.concurrent.locks.LockSupport.park(LockSupport.java:175)
    at
java.util.concurrent.locks.AbstractQueuedSynchronizer$ConditionObject.await(AbstractQueuedSynchronizer.java:2039)
    at java.util.concurrent.LinkedBlockingQueue.take(LinkedBlockingQueue.java:442)
    at org.apache.tomcat.util.threads.TaskQueue.take(TaskQueue.java:108)
    at org.apache.tomcat.util.threads.TaskQueue.take(TaskQueue.java:33)
    at java.util.concurrent.ThreadPoolExecutor.getTask(ThreadPoolExecutor.java:1074)
    at java.util.concurrent.ThreadPoolExecutor.runWorker(ThreadPoolExecutor.java:1134)
    at java.util.concurrent.ThreadPoolExecutor$Worker.run(ThreadPoolExecutor.java:624)
    at
org.apache.tomcat.util.threads.TaskThread$WrappingRunnable.run(TaskThread.java:61)
    at java.lang.Thread.run(Thread.java:748)
```

Locked ownable synchronizers:

- None

```
"http-nio-auto-46-exec-7" - Thread t@1271
  java.lang.Thread.State: WAITING
    at sun.misc.Unsafe.park(Native Method)
      - parking to wait for <17e1fd84> (a
java.util.concurrent.locks.AbstractQueuedSynchronizer$ConditionObject)
```



```
    at java.util.concurrent.locks.LockSupport.park(LockSupport.java:175)
    at
java.util.concurrent.locks.AbstractQueuedSynchronizer$ConditionObject.await(AbstractQueuedSynchronizer.java:2039)
    at java.util.concurrent.LinkedBlockingQueue.take(LinkedBlockingQueue.java:442)
    at org.apache.tomcat.util.threads.TaskQueue.take(TaskQueue.java:108)
    at org.apache.tomcat.util.threads.TaskQueue.take(TaskQueue.java:33)
    at java.util.concurrent.ThreadPoolExecutor.getTask(ThreadPoolExecutor.java:1074)
    at java.util.concurrent.ThreadPoolExecutor.runWorker(ThreadPoolExecutor.java:1134)
    at java.util.concurrent.ThreadPoolExecutor$Worker.run(ThreadPoolExecutor.java:624)
    at
org.apache.tomcat.util.threads.TaskThread$WrappingRunnable.run(TaskThread.java:61)
    at java.lang.Thread.run(Thread.java:748)
```

Locked ownable synchronizers:

- None

"http-nio-auto-46-exec-6" - Thread t@1270

java.lang.Thread.State: WAITING

at sun.misc.Unsafe.park(Native Method)

- parking to wait for <17e1fd84> (a

java.util.concurrent.locks.AbstractQueuedSynchronizer\$ConditionObject)

at java.util.concurrent.locks.LockSupport.park(LockSupport.java:175)

at

java.util.concurrent.locks.AbstractQueuedSynchronizer\$ConditionObject.await(AbstractQueuedSynchronizer.java:2039)

at java.util.concurrent.LinkedBlockingQueue.take(LinkedBlockingQueue.java:442)

at org.apache.tomcat.util.threads.TaskQueue.take(TaskQueue.java:108)

at org.apache.tomcat.util.threads.TaskQueue.take(TaskQueue.java:33)

at java.util.concurrent.ThreadPoolExecutor.getTask(ThreadPoolExecutor.java:1074)

at java.util.concurrent.ThreadPoolExecutor.runWorker(ThreadPoolExecutor.java:1134)

at java.util.concurrent.ThreadPoolExecutor\$Worker.run(ThreadPoolExecutor.java:624)

at

org.apache.tomcat.util.threads.TaskThread\$WrappingRunnable.run(TaskThread.java:61)

at java.lang.Thread.run(Thread.java:748)

Locked ownable synchronizers:

- None

"http-nio-auto-46-exec-5" - Thread t@1269

java.lang.Thread.State: WAITING

at sun.misc.Unsafe.park(Native Method)

- parking to wait for <17e1fd84> (a

java.util.concurrent.locks.AbstractQueuedSynchronizer\$ConditionObject)

at java.util.concurrent.locks.LockSupport.park(LockSupport.java:175)

at

java.util.concurrent.locks.AbstractQueuedSynchronizer\$ConditionObject.await(AbstractQueuedSynchronizer.java:2039)

at java.util.concurrent.LinkedBlockingQueue.take(LinkedBlockingQueue.java:442)

at org.apache.tomcat.util.threads.TaskQueue.take(TaskQueue.java:108)

at org.apache.tomcat.util.threads.TaskQueue.take(TaskQueue.java:33)

```
at java.util.concurrent.ThreadPoolExecutor.getTask(ThreadPoolExecutor.java:1074)
at java.util.concurrent.ThreadPoolExecutor.runWorker(ThreadPoolExecutor.java:1134)
at java.util.concurrent.ThreadPoolExecutor$Worker.run(ThreadPoolExecutor.java:624)
at
org.apache.tomcat.util.threads.TaskThread$WrappingRunnable.run(TaskThread.java:61)
at java.lang.Thread.run(Thread.java:748)
```

Locked ownable synchronizers:

- None

"http-nio-auto-46-exec-4" - Thread t@1268

```
java.lang.Thread.State: WAITING
at sun.misc.Unsafe.park(Native Method)
- parking to wait for <17e1fd84> (a
java.util.concurrent.locks.AbstractQueuedSynchronizer$ConditionObject)
at java.util.concurrent.locks.LockSupport.park(LockSupport.java:175)
at
java.util.concurrent.locks.AbstractQueuedSynchronizer$ConditionObject.await(AbstractQueuedSynchronizer.java:2039)
at java.util.concurrent.LinkedBlockingQueue.take(LinkedBlockingQueue.java:442)
at org.apache.tomcat.util.threads.TaskQueue.take(TaskQueue.java:108)
at org.apache.tomcat.util.threads.TaskQueue.take(TaskQueue.java:33)
at java.util.concurrent.ThreadPoolExecutor.getTask(ThreadPoolExecutor.java:1074)
at java.util.concurrent.ThreadPoolExecutor.runWorker(ThreadPoolExecutor.java:1134)
at java.util.concurrent.ThreadPoolExecutor$Worker.run(ThreadPoolExecutor.java:624)
at
org.apache.tomcat.util.threads.TaskThread$WrappingRunnable.run(TaskThread.java:61)
at java.lang.Thread.run(Thread.java:748)
```

Locked ownable synchronizers:

- None

"http-nio-auto-46-exec-3" - Thread t@1267

```
java.lang.Thread.State: WAITING
at sun.misc.Unsafe.park(Native Method)
- parking to wait for <17e1fd84> (a
java.util.concurrent.locks.AbstractQueuedSynchronizer$ConditionObject)
at java.util.concurrent.locks.LockSupport.park(LockSupport.java:175)
at
java.util.concurrent.locks.AbstractQueuedSynchronizer$ConditionObject.await(AbstractQueuedSynchronizer.java:2039)
at java.util.concurrent.LinkedBlockingQueue.take(LinkedBlockingQueue.java:442)
at org.apache.tomcat.util.threads.TaskQueue.take(TaskQueue.java:108)
at org.apache.tomcat.util.threads.TaskQueue.take(TaskQueue.java:33)
at java.util.concurrent.ThreadPoolExecutor.getTask(ThreadPoolExecutor.java:1074)
at java.util.concurrent.ThreadPoolExecutor.runWorker(ThreadPoolExecutor.java:1134)
at java.util.concurrent.ThreadPoolExecutor$Worker.run(ThreadPoolExecutor.java:624)
at
org.apache.tomcat.util.threads.TaskThread$WrappingRunnable.run(TaskThread.java:61)
at java.lang.Thread.run(Thread.java:748)
```

Locked ownable synchronizers:

- None

"http-nio-auto-46-exec-2" - Thread t@1266

java.lang.Thread.State: WAITING

at sun.misc.Unsafe.park(Native Method)

- parking to wait for <17e1fd84> (a

java.util.concurrent.locks.AbstractQueuedSynchronizer\$ConditionObject)

at java.util.concurrent.locks.LockSupport.park(LockSupport.java:175)

at

java.util.concurrent.locks.AbstractQueuedSynchronizer\$ConditionObject.await(AbstractQueuedSynchronizer.java:2039)

at java.util.concurrent.LinkedBlockingQueue.take(LinkedBlockingQueue.java:442)

at org.apache.tomcat.util.threads.TaskQueue.take(TaskQueue.java:108)

at org.apache.tomcat.util.threads.TaskQueue.take(TaskQueue.java:33)

at java.util.concurrent.ThreadPoolExecutor.getTask(ThreadPoolExecutor.java:1074)

at java.util.concurrent.ThreadPoolExecutor.runWorker(ThreadPoolExecutor.java:1134)

at java.util.concurrent.ThreadPoolExecutor\$Worker.run(ThreadPoolExecutor.java:624)

at

org.apache.tomcat.util.threads.TaskThread\$WrappingRunnable.run(TaskThread.java:61)

at java.lang.Thread.run(Thread.java:748)

Locked ownable synchronizers:

- None

"http-nio-auto-46-exec-1" - Thread t@1265

java.lang.Thread.State: WAITING

at sun.misc.Unsafe.park(Native Method)

- parking to wait for <17e1fd84> (a

java.util.concurrent.locks.AbstractQueuedSynchronizer\$ConditionObject)

at java.util.concurrent.locks.LockSupport.park(LockSupport.java:175)

at

java.util.concurrent.locks.AbstractQueuedSynchronizer\$ConditionObject.await(AbstractQueuedSynchronizer.java:2039)

at java.util.concurrent.LinkedBlockingQueue.take(LinkedBlockingQueue.java:442)

at org.apache.tomcat.util.threads.TaskQueue.take(TaskQueue.java:108)

at org.apache.tomcat.util.threads.TaskQueue.take(TaskQueue.java:33)

at java.util.concurrent.ThreadPoolExecutor.getTask(ThreadPoolExecutor.java:1074)

at java.util.concurrent.ThreadPoolExecutor.runWorker(ThreadPoolExecutor.java:1134)

at java.util.concurrent.ThreadPoolExecutor\$Worker.run(ThreadPoolExecutor.java:624)

at

org.apache.tomcat.util.threads.TaskThread\$WrappingRunnable.run(TaskThread.java:61)

at java.lang.Thread.run(Thread.java:748)

Locked ownable synchronizers:

- None

"http-nio-auto-46-BlockPoller" - Thread t@1264

java.lang.Thread.State: RUNNABLE

at sun.nio.ch.EPollArrayWrapper.epollWait(Native Method)

at sun.nio.ch.EPollArrayWrapper.poll(EPollArrayWrapper.java:269)

```
at sun.nio.ch.EPollSelectorImpl.doSelect(EPollSelectorImpl.java:93)
at sun.nio.ch.SelectorImpl.lockAndDoSelect(SelectorImpl.java:86)
- locked <16777737> (a sun.nio.ch.Util$3)
- locked <456fe34c> (a java.util.Collections$UnmodifiableSet)
- locked <36c9b186> (a sun.nio.ch.EPollSelectorImpl)
at sun.nio.ch.SelectorImpl.select(SelectorImpl.java:97)
at
org.apache.tomcat.util.net.NioBlockingSelector$BlockPoller.run(NioBlockingSelector.java:313)
```

Locked ownable synchronizers:

- None

"Catalina-utility-2" - Thread t@1263

java.lang.Thread.State: TIMED_WAITING

at sun.misc.Unsafe.park(Native Method)

- parking to wait for <2e5c7706> (a

java.util.concurrent.locks.AbstractQueuedSynchronizer\$ConditionObject)

at java.util.concurrent.locks.LockSupport.parkNanos(LockSupport.java:215)

at

java.util.concurrent.locks.AbstractQueuedSynchronizer\$ConditionObject.awaitNanos(AbstractQueuedSynchronizer.java:2078)

at

java.util.concurrent.ScheduledThreadPoolExecutor\$DelayedWorkQueue.take(ScheduledThreadPoolExecutor.java:1093)

at

java.util.concurrent.ScheduledThreadPoolExecutor\$DelayedWorkQueue.take(ScheduledThreadPoolExecutor.java:809)

at java.util.concurrent.ThreadPoolExecutor.getTask(ThreadPoolExecutor.java:1074)

at java.util.concurrent.ThreadPoolExecutor.runWorker(ThreadPoolExecutor.java:1134)

at java.util.concurrent.ThreadPoolExecutor\$Worker.run(ThreadPoolExecutor.java:624)

at

org.apache.tomcat.util.threads.TaskThread\$WrappingRunnable.run(TaskThread.java:61)

at java.lang.Thread.run(Thread.java:748)

Locked ownable synchronizers:

- None

"container-0" - Thread t@1262

java.lang.Thread.State: TIMED_WAITING

at java.lang.Thread.sleep(Native Method)

at org.apache.catalina.core.StandardServer.await(StandardServer.java:570)

at

org.springframework.boot.web.embedded.tomcat.TomcatWebServer\$1.run(TomcatWebServer.java:197)

Locked ownable synchronizers:

- None

"Catalina-utility-1" - Thread t@1261

java.lang.Thread.State: WAITING

```

    at sun.misc.Unsafe.park(Native Method)
    - parking to wait for <2e5c7706> (a
java.util.concurrent.locks.AbstractQueuedSynchronizer$ConditionObject)
    at java.util.concurrent.locks.LockSupport.park(LockSupport.java:175)
    at
java.util.concurrent.locks.AbstractQueuedSynchronizer$ConditionObject.await(AbstractQueuedSynchronizer.java:2039)
    at
java.util.concurrent.ScheduledThreadPoolExecutor$DelayedWorkQueue.take(ScheduledThreadPoolExecutor.java:1088)
    at
java.util.concurrent.ScheduledThreadPoolExecutor$DelayedWorkQueue.take(ScheduledThreadPoolExecutor.java:809)
    at java.util.concurrent.ThreadPoolExecutor.getTask(ThreadPoolExecutor.java:1074)
    at java.util.concurrent.ThreadPoolExecutor.runWorker(ThreadPoolExecutor.java:1134)
    at java.util.concurrent.ThreadPoolExecutor$Worker.run(ThreadPoolExecutor.java:624)
    at
org.apache.tomcat.util.threads.TaskThread$WrappingRunnable.run(TaskThread.java:61)
    at java.lang.Thread.run(Thread.java:748)

```

Locked ownable synchronizers:

- None

"secondOne housekeeper" - Thread t@1226

```

java.lang.Thread.State: TIMED_WAITING
    at sun.misc.Unsafe.park(Native Method)
    - parking to wait for <33f7335> (a
java.util.concurrent.locks.AbstractQueuedSynchronizer$ConditionObject)
    at java.util.concurrent.locks.LockSupport.parkNanos(LockSupport.java:215)
    at
java.util.concurrent.locks.AbstractQueuedSynchronizer$ConditionObject.awaitNanos(AbstractQueuedSynchronizer.java:2078)
    at
java.util.concurrent.ScheduledThreadPoolExecutor$DelayedWorkQueue.take(ScheduledThreadPoolExecutor.java:1093)
    at
java.util.concurrent.ScheduledThreadPoolExecutor$DelayedWorkQueue.take(ScheduledThreadPoolExecutor.java:809)
    at java.util.concurrent.ThreadPoolExecutor.getTask(ThreadPoolExecutor.java:1074)
    at java.util.concurrent.ThreadPoolExecutor.runWorker(ThreadPoolExecutor.java:1134)
    at java.util.concurrent.ThreadPoolExecutor$Worker.run(ThreadPoolExecutor.java:624)
    at java.lang.Thread.run(Thread.java:748)

```

Locked ownable synchronizers:

- None

"parallel-8" - Thread t@1185

```

java.lang.Thread.State: WAITING
    at sun.misc.Unsafe.park(Native Method)
    - parking to wait for <39f0959d> (a
java.util.concurrent.locks.AbstractQueuedSynchronizer$ConditionObject)

```

```

    at java.util.concurrent.locks.LockSupport.park(LockSupport.java:175)
    at
java.util.concurrent.locks.AbstractQueuedSynchronizer$ConditionObject.await(AbstractQueuedSynchronizer.java:2039)
    at
java.util.concurrent.ScheduledThreadPoolExecutor$DelayedWorkQueue.take(ScheduledThreadPoolExecutor.java:1081)
    at
java.util.concurrent.ScheduledThreadPoolExecutor$DelayedWorkQueue.take(ScheduledThreadPoolExecutor.java:809)
    at java.util.concurrent.ThreadPoolExecutor.getTask(ThreadPoolExecutor.java:1074)
    at java.util.concurrent.ThreadPoolExecutor.runWorker(ThreadPoolExecutor.java:1134)
    at java.util.concurrent.ThreadPoolExecutor$Worker.run(ThreadPoolExecutor.java:624)
    at java.lang.Thread.run(Thread.java:748)

```

Locked ownable synchronizers:
- None

```

"parallel-7" - Thread t@1184
  java.lang.Thread.State: WAITING
    at sun.misc.Unsafe.park(Native Method)
    - parking to wait for <424e56a4> (a
java.util.concurrent.locks.AbstractQueuedSynchronizer$ConditionObject)
    at java.util.concurrent.locks.LockSupport.park(LockSupport.java:175)
    at
java.util.concurrent.locks.AbstractQueuedSynchronizer$ConditionObject.await(AbstractQueuedSynchronizer.java:2039)
    at
java.util.concurrent.ScheduledThreadPoolExecutor$DelayedWorkQueue.take(ScheduledThreadPoolExecutor.java:1081)
    at
java.util.concurrent.ScheduledThreadPoolExecutor$DelayedWorkQueue.take(ScheduledThreadPoolExecutor.java:809)
    at java.util.concurrent.ThreadPoolExecutor.getTask(ThreadPoolExecutor.java:1074)
    at java.util.concurrent.ThreadPoolExecutor.runWorker(ThreadPoolExecutor.java:1134)
    at java.util.concurrent.ThreadPoolExecutor$Worker.run(ThreadPoolExecutor.java:624)
    at java.lang.Thread.run(Thread.java:748)

```

Locked ownable synchronizers:
- None

```

"parallel-6" - Thread t@1183
  java.lang.Thread.State: WAITING
    at sun.misc.Unsafe.park(Native Method)
    - parking to wait for <f67edac> (a
java.util.concurrent.locks.AbstractQueuedSynchronizer$ConditionObject)
    at java.util.concurrent.locks.LockSupport.park(LockSupport.java:175)
    at
java.util.concurrent.locks.AbstractQueuedSynchronizer$ConditionObject.await(AbstractQueuedSynchronizer.java:2039)
    at

```

```

java.util.concurrent.ScheduledThreadPoolExecutor$DelayedWorkQueue.take(ScheduledThread
PoolExecutor.java:1081)
    at
java.util.concurrent.ScheduledThreadPoolExecutor$DelayedWorkQueue.take(ScheduledThread
PoolExecutor.java:809)
    at java.util.concurrent.ThreadPoolExecutor.getTask(ThreadPoolExecutor.java:1074)
    at java.util.concurrent.ThreadPoolExecutor.runWorker(ThreadPoolExecutor.java:1134)
    at java.util.concurrent.ThreadPoolExecutor$Worker.run(ThreadPoolExecutor.java:624)
    at java.lang.Thread.run(Thread.java:748)

Locked ownable synchronizers:
- None

"parallel-5" - Thread t@1182
  java.lang.Thread.State: WAITING
    at sun.misc.Unsafe.park(Native Method)
    - parking to wait for <77b991ae> (a
java.util.concurrent.locks.AbstractQueuedSynchronizer$ConditionObject)
    at java.util.concurrent.locks.LockSupport.park(LockSupport.java:175)
    at
java.util.concurrent.locks.AbstractQueuedSynchronizer$ConditionObject.await(AbstractQu
euedSynchronizer.java:2039)
    at
java.util.concurrent.ScheduledThreadPoolExecutor$DelayedWorkQueue.take(ScheduledThread
PoolExecutor.java:1081)
    at
java.util.concurrent.ScheduledThreadPoolExecutor$DelayedWorkQueue.take(ScheduledThread
PoolExecutor.java:809)
    at java.util.concurrent.ThreadPoolExecutor.getTask(ThreadPoolExecutor.java:1074)
    at java.util.concurrent.ThreadPoolExecutor.runWorker(ThreadPoolExecutor.java:1134)
    at java.util.concurrent.ThreadPoolExecutor$Worker.run(ThreadPoolExecutor.java:624)
    at java.lang.Thread.run(Thread.java:748)

Locked ownable synchronizers:
- None

"parallel-4" - Thread t@1181
  java.lang.Thread.State: WAITING
    at sun.misc.Unsafe.park(Native Method)
    - parking to wait for <4a58beb9> (a
java.util.concurrent.locks.AbstractQueuedSynchronizer$ConditionObject)
    at java.util.concurrent.locks.LockSupport.park(LockSupport.java:175)
    at
java.util.concurrent.locks.AbstractQueuedSynchronizer$ConditionObject.await(AbstractQu
euedSynchronizer.java:2039)
    at
java.util.concurrent.ScheduledThreadPoolExecutor$DelayedWorkQueue.take(ScheduledThread
PoolExecutor.java:1081)
    at
java.util.concurrent.ScheduledThreadPoolExecutor$DelayedWorkQueue.take(ScheduledThread
PoolExecutor.java:809)

```

```
at java.util.concurrent.ThreadPoolExecutor.getTask(ThreadPoolExecutor.java:1074)
at java.util.concurrent.ThreadPoolExecutor.runWorker(ThreadPoolExecutor.java:1134)
at java.util.concurrent.ThreadPoolExecutor$Worker.run(ThreadPoolExecutor.java:624)
at java.lang.Thread.run(Thread.java:748)
```

Locked ownable synchronizers:

- None

"parallel-3" - Thread t@1180

java.lang.Thread.State: WAITING

at sun.misc.Unsafe.park(Native Method)

- parking to wait for <7a132a20> (a

java.util.concurrent.locks.AbstractQueuedSynchronizer\$ConditionObject)

at java.util.concurrent.locks.LockSupport.park(LockSupport.java:175)

at

java.util.concurrent.locks.AbstractQueuedSynchronizer\$ConditionObject.await(AbstractQueuedSynchronizer.java:2039)

at

java.util.concurrent.ScheduledThreadPoolExecutor\$DelayedWorkQueue.take(ScheduledThreadPoolExecutor.java:1081)

at

java.util.concurrent.ScheduledThreadPoolExecutor\$DelayedWorkQueue.take(ScheduledThreadPoolExecutor.java:809)

at java.util.concurrent.ThreadPoolExecutor.getTask(ThreadPoolExecutor.java:1074)

at java.util.concurrent.ThreadPoolExecutor.runWorker(ThreadPoolExecutor.java:1134)

at java.util.concurrent.ThreadPoolExecutor\$Worker.run(ThreadPoolExecutor.java:624)

at java.lang.Thread.run(Thread.java:748)

Locked ownable synchronizers:

- None

"parallel-2" - Thread t@1179

java.lang.Thread.State: WAITING

at sun.misc.Unsafe.park(Native Method)

- parking to wait for <4a29a243> (a

java.util.concurrent.locks.AbstractQueuedSynchronizer\$ConditionObject)

at java.util.concurrent.locks.LockSupport.park(LockSupport.java:175)

at

java.util.concurrent.locks.AbstractQueuedSynchronizer\$ConditionObject.await(AbstractQueuedSynchronizer.java:2039)

at

java.util.concurrent.ScheduledThreadPoolExecutor\$DelayedWorkQueue.take(ScheduledThreadPoolExecutor.java:1081)

at

java.util.concurrent.ScheduledThreadPoolExecutor\$DelayedWorkQueue.take(ScheduledThreadPoolExecutor.java:809)

at java.util.concurrent.ThreadPoolExecutor.getTask(ThreadPoolExecutor.java:1074)

at java.util.concurrent.ThreadPoolExecutor.runWorker(ThreadPoolExecutor.java:1134)

at java.util.concurrent.ThreadPoolExecutor\$Worker.run(ThreadPoolExecutor.java:624)

at java.lang.Thread.run(Thread.java:748)

Locked ownable synchronizers:

- None

"parallel-1" - Thread t@1178

java.lang.Thread.State: WAITING

at sun.misc.Unsafe.park(Native Method)

- parking to wait for <71a67e49> (a

java.util.concurrent.locks.AbstractQueuedSynchronizer\$ConditionObject)

at java.util.concurrent.locks.LockSupport.park(LockSupport.java:175)

at

java.util.concurrent.locks.AbstractQueuedSynchronizer\$ConditionObject.await(AbstractQueuedSynchronizer.java:2039)

at

java.util.concurrent.ScheduledThreadPoolExecutor\$DelayedWorkQueue.take(ScheduledThreadPoolExecutor.java:1081)

at

java.util.concurrent.ScheduledThreadPoolExecutor\$DelayedWorkQueue.take(ScheduledThreadPoolExecutor.java:809)

at java.util.concurrent.ThreadPoolExecutor.getTask(ThreadPoolExecutor.java:1074)

at java.util.concurrent.ThreadPoolExecutor.runWorker(ThreadPoolExecutor.java:1134)

at java.util.concurrent.ThreadPoolExecutor\$Worker.run(ThreadPoolExecutor.java:624)

at java.lang.Thread.run(Thread.java:748)

Locked ownable synchronizers:

- None

"PrometheusPushGatewayManager.PushGatewayTaskScheduler-1" - Thread t@1155

java.lang.Thread.State: WAITING

at sun.misc.Unsafe.park(Native Method)

- parking to wait for <7e04bbb2> (a

java.util.concurrent.locks.AbstractQueuedSynchronizer\$ConditionObject)

at java.util.concurrent.locks.LockSupport.park(LockSupport.java:175)

at

java.util.concurrent.locks.AbstractQueuedSynchronizer\$ConditionObject.await(AbstractQueuedSynchronizer.java:2039)

at

java.util.concurrent.ScheduledThreadPoolExecutor\$DelayedWorkQueue.take(ScheduledThreadPoolExecutor.java:1081)

at

java.util.concurrent.ScheduledThreadPoolExecutor\$DelayedWorkQueue.take(ScheduledThreadPoolExecutor.java:809)

at java.util.concurrent.ThreadPoolExecutor.getTask(ThreadPoolExecutor.java:1074)

at java.util.concurrent.ThreadPoolExecutor.runWorker(ThreadPoolExecutor.java:1134)

at java.util.concurrent.ThreadPoolExecutor\$Worker.run(ThreadPoolExecutor.java:624)

at java.lang.Thread.run(Thread.java:748)

Locked ownable synchronizers:

- None

"PrometheusPushGatewayManager.PushGatewayTaskScheduler-1" - Thread t@1154

java.lang.Thread.State: WAITING

```

    at sun.misc.Unsafe.park(Native Method)
    - parking to wait for <1da5cc78> (a
java.util.concurrent.locks.AbstractQueuedSynchronizer$ConditionObject)
    at java.util.concurrent.locks.LockSupport.park(LockSupport.java:175)
    at
java.util.concurrent.locks.AbstractQueuedSynchronizer$ConditionObject.await(AbstractQueuedSynchronizer.java:2039)
    at
java.util.concurrent.ScheduledThreadPoolExecutor$DelayedWorkQueue.take(ScheduledThreadPoolExecutor.java:1081)
    at
java.util.concurrent.ScheduledThreadPoolExecutor$DelayedWorkQueue.take(ScheduledThreadPoolExecutor.java:809)
    at java.util.concurrent.ThreadPoolExecutor.getTask(ThreadPoolExecutor.java:1074)
    at java.util.concurrent.ThreadPoolExecutor.runWorker(ThreadPoolExecutor.java:1134)
    at java.util.concurrent.ThreadPoolExecutor$Worker.run(ThreadPoolExecutor.java:624)
    at java.lang.Thread.run(Thread.java:748)

```

Locked ownable synchronizers:

- None

"PrometheusPushGatewayManager.PushGatewayTaskScheduler-1" - Thread t@1153

```

java.lang.Thread.State: TIMED_WAITING
    at sun.misc.Unsafe.park(Native Method)
    - parking to wait for <1a994e35> (a
java.util.concurrent.locks.AbstractQueuedSynchronizer$ConditionObject)
    at java.util.concurrent.locks.LockSupport.parkNanos(LockSupport.java:215)
    at
java.util.concurrent.locks.AbstractQueuedSynchronizer$ConditionObject.awaitNanos(AbstractQueuedSynchronizer.java:2078)
    at
java.util.concurrent.ScheduledThreadPoolExecutor$DelayedWorkQueue.take(ScheduledThreadPoolExecutor.java:1093)
    at
java.util.concurrent.ScheduledThreadPoolExecutor$DelayedWorkQueue.take(ScheduledThreadPoolExecutor.java:809)
    at java.util.concurrent.ThreadPoolExecutor.getTask(ThreadPoolExecutor.java:1074)
    at java.util.concurrent.ThreadPoolExecutor.runWorker(ThreadPoolExecutor.java:1134)
    at java.util.concurrent.ThreadPoolExecutor$Worker.run(ThreadPoolExecutor.java:624)
    at java.lang.Thread.run(Thread.java:748)

```

Locked ownable synchronizers:

- None

"sdk-metrics-registry-0" - Thread t@1135

```

java.lang.Thread.State: TIMED_WAITING
    at sun.misc.Unsafe.park(Native Method)
    - parking to wait for <580f2f19> (a
java.util.concurrent.locks.AbstractQueuedSynchronizer$ConditionObject)
    at java.util.concurrent.locks.LockSupport.parkNanos(LockSupport.java:215)
    at

```

```
java.util.concurrent.locks.AbstractQueuedSynchronizer$ConditionObject.awaitNanos(AbstractQueuedSynchronizer.java:2078)
    at
java.util.concurrent.ScheduledThreadPoolExecutor$DelayedWorkQueue.take(ScheduledThreadPoolExecutor.java:1093)
    at
java.util.concurrent.ScheduledThreadPoolExecutor$DelayedWorkQueue.take(ScheduledThreadPoolExecutor.java:809)
    at java.util.concurrent.ThreadPoolExecutor.getTask(ThreadPoolExecutor.java:1074)
    at java.util.concurrent.ThreadPoolExecutor.runWorker(ThreadPoolExecutor.java:1134)
    at java.util.concurrent.ThreadPoolExecutor$Worker.run(ThreadPoolExecutor.java:624)
    at java.lang.Thread.run(Thread.java:748)
```

Locked ownable synchronizers:

- None

"wavefrontClientSender-0" - Thread t@1134

java.lang.Thread.State: TIMED_WAITING

at sun.misc.Unsafe.park(Native Method)

- parking to wait for <30dc681> (a

java.util.concurrent.locks.AbstractQueuedSynchronizer\$ConditionObject)

at java.util.concurrent.locks.LockSupport.parkNanos(LockSupport.java:215)

at

java.util.concurrent.locks.AbstractQueuedSynchronizer\$ConditionObject.awaitNanos(AbstractQueuedSynchronizer.java:2078)

at

java.util.concurrent.ScheduledThreadPoolExecutor\$DelayedWorkQueue.take(ScheduledThreadPoolExecutor.java:1093)

at

java.util.concurrent.ScheduledThreadPoolExecutor\$DelayedWorkQueue.take(ScheduledThreadPoolExecutor.java:809)

at java.util.concurrent.ThreadPoolExecutor.getTask(ThreadPoolExecutor.java:1074)

at java.util.concurrent.ThreadPoolExecutor.runWorker(ThreadPoolExecutor.java:1134)

at java.util.concurrent.ThreadPoolExecutor\$Worker.run(ThreadPoolExecutor.java:624)

at java.lang.Thread.run(Thread.java:748)

Locked ownable synchronizers:

- None

"spectator-gauge-polling-0" - Thread t@1092

java.lang.Thread.State: TIMED_WAITING

at sun.misc.Unsafe.park(Native Method)

- parking to wait for <30f80c94> (a

java.util.concurrent.locks.AbstractQueuedSynchronizer\$ConditionObject)

at java.util.concurrent.locks.LockSupport.parkNanos(LockSupport.java:215)

at

java.util.concurrent.locks.AbstractQueuedSynchronizer\$ConditionObject.awaitNanos(AbstractQueuedSynchronizer.java:2078)

at

java.util.concurrent.ScheduledThreadPoolExecutor\$DelayedWorkQueue.take(ScheduledThreadPoolExecutor.java:1093)

```
at
java.util.concurrent.ScheduledThreadPoolExecutor$DelayedWorkQueue.take(ScheduledThread
PoolExecutor.java:809)
at java.util.concurrent.ThreadPoolExecutor.getTask(ThreadPoolExecutor.java:1074)
at java.util.concurrent.ThreadPoolExecutor.runWorker(ThreadPoolExecutor.java:1134)
at java.util.concurrent.ThreadPoolExecutor$Worker.run(ThreadPoolExecutor.java:624)
at java.lang.Thread.run(Thread.java:748)
```

Locked ownable synchronizers:

- None

"parallel-6" - Thread t@1091

```
java.lang.Thread.State: TIMED_WAITING
at sun.misc.Unsafe.park(Native Method)
- parking to wait for <60c00458> (a
java.util.concurrent.locks.AbstractQueuedSynchronizer$ConditionObject)
at java.util.concurrent.locks.LockSupport.parkNanos(LockSupport.java:215)
at
java.util.concurrent.locks.AbstractQueuedSynchronizer$ConditionObject.awaitNanos(Abstr
actQueuedSynchronizer.java:2078)
at
java.util.concurrent.ScheduledThreadPoolExecutor$DelayedWorkQueue.take(ScheduledThread
PoolExecutor.java:1093)
at
java.util.concurrent.ScheduledThreadPoolExecutor$DelayedWorkQueue.take(ScheduledThread
PoolExecutor.java:809)
at java.util.concurrent.ThreadPoolExecutor.getTask(ThreadPoolExecutor.java:1074)
at java.util.concurrent.ThreadPoolExecutor.runWorker(ThreadPoolExecutor.java:1134)
at java.util.concurrent.ThreadPoolExecutor$Worker.run(ThreadPoolExecutor.java:624)
at java.lang.Thread.run(Thread.java:748)
```

Locked ownable synchronizers:

- None

"parallel-5" - Thread t@1089

```
java.lang.Thread.State: TIMED_WAITING
at sun.misc.Unsafe.park(Native Method)
- parking to wait for <411688be> (a
java.util.concurrent.locks.AbstractQueuedSynchronizer$ConditionObject)
at java.util.concurrent.locks.LockSupport.parkNanos(LockSupport.java:215)
at
java.util.concurrent.locks.AbstractQueuedSynchronizer$ConditionObject.awaitNanos(Abstr
actQueuedSynchronizer.java:2078)
at
java.util.concurrent.ScheduledThreadPoolExecutor$DelayedWorkQueue.take(ScheduledThread
PoolExecutor.java:1093)
at
java.util.concurrent.ScheduledThreadPoolExecutor$DelayedWorkQueue.take(ScheduledThread
PoolExecutor.java:809)
at java.util.concurrent.ThreadPoolExecutor.getTask(ThreadPoolExecutor.java:1074)
at java.util.concurrent.ThreadPoolExecutor.runWorker(ThreadPoolExecutor.java:1134)
```

```
at java.util.concurrent.ThreadPoolExecutor$Worker.run(ThreadPoolExecutor.java:624)
at java.lang.Thread.run(Thread.java:748)
```

Locked ownable synchronizers:

- None

"parallel-7" - Thread t@1090

java.lang.Thread.State: TIMED_WAITING

at sun.misc.Unsafe.park(Native Method)

- parking to wait for <2c4277d3> (a

java.util.concurrent.locks.AbstractQueuedSynchronizer\$ConditionObject)

at java.util.concurrent.locks.LockSupport.parkNanos(LockSupport.java:215)

at

java.util.concurrent.locks.AbstractQueuedSynchronizer\$ConditionObject.awaitNanos(AbstractQueuedSynchronizer.java:2078)

at

java.util.concurrent.ScheduledThreadPoolExecutor\$DelayedWorkQueue.take(ScheduledThreadPoolExecutor.java:1093)

at

java.util.concurrent.ScheduledThreadPoolExecutor\$DelayedWorkQueue.take(ScheduledThreadPoolExecutor.java:809)

at java.util.concurrent.ThreadPoolExecutor.getTask(ThreadPoolExecutor.java:1074)

at java.util.concurrent.ThreadPoolExecutor.runWorker(ThreadPoolExecutor.java:1134)

at java.util.concurrent.ThreadPoolExecutor\$Worker.run(ThreadPoolExecutor.java:624)

at java.lang.Thread.run(Thread.java:748)

Locked ownable synchronizers:

- None

"parallel-4" - Thread t@1088

java.lang.Thread.State: TIMED_WAITING

at sun.misc.Unsafe.park(Native Method)

- parking to wait for <5c2e4263> (a

java.util.concurrent.locks.AbstractQueuedSynchronizer\$ConditionObject)

at java.util.concurrent.locks.LockSupport.parkNanos(LockSupport.java:215)

at

java.util.concurrent.locks.AbstractQueuedSynchronizer\$ConditionObject.awaitNanos(AbstractQueuedSynchronizer.java:2078)

at

java.util.concurrent.ScheduledThreadPoolExecutor\$DelayedWorkQueue.take(ScheduledThreadPoolExecutor.java:1093)

at

java.util.concurrent.ScheduledThreadPoolExecutor\$DelayedWorkQueue.take(ScheduledThreadPoolExecutor.java:809)

at java.util.concurrent.ThreadPoolExecutor.getTask(ThreadPoolExecutor.java:1074)

at java.util.concurrent.ThreadPoolExecutor.runWorker(ThreadPoolExecutor.java:1134)

at java.util.concurrent.ThreadPoolExecutor\$Worker.run(ThreadPoolExecutor.java:624)

at java.lang.Thread.run(Thread.java:748)

Locked ownable synchronizers:

- None

```

"parallel-3" - Thread t@1087
  java.lang.Thread.State: TIMED_WAITING
    at sun.misc.Unsafe.park(Native Method)
      - parking to wait for <3c2c7f7a> (a
java.util.concurrent.locks.AbstractQueuedSynchronizer$ConditionObject)
    at java.util.concurrent.locks.LockSupport.parkNanos(LockSupport.java:215)
    at
java.util.concurrent.locks.AbstractQueuedSynchronizer$ConditionObject.awaitNanos(Abstr
actQueuedSynchronizer.java:2078)
    at
java.util.concurrent.ScheduledThreadPoolExecutor$DelayedWorkQueue.take(ScheduledThread
PoolExecutor.java:1093)
    at
java.util.concurrent.ScheduledThreadPoolExecutor$DelayedWorkQueue.take(ScheduledThread
PoolExecutor.java:809)
      at java.util.concurrent.ThreadPoolExecutor.getTask(ThreadPoolExecutor.java:1074)
      at java.util.concurrent.ThreadPoolExecutor.runWorker(ThreadPoolExecutor.java:1134)
      at java.util.concurrent.ThreadPoolExecutor$Worker.run(ThreadPoolExecutor.java:624)
      at java.lang.Thread.run(Thread.java:748)

  Locked ownable synchronizers:
    - None

"parallel-2" - Thread t@1086
  java.lang.Thread.State: TIMED_WAITING
    at sun.misc.Unsafe.park(Native Method)
      - parking to wait for <498a5339> (a
java.util.concurrent.locks.AbstractQueuedSynchronizer$ConditionObject)
    at java.util.concurrent.locks.LockSupport.parkNanos(LockSupport.java:215)
    at
java.util.concurrent.locks.AbstractQueuedSynchronizer$ConditionObject.awaitNanos(Abstr
actQueuedSynchronizer.java:2078)
    at
java.util.concurrent.ScheduledThreadPoolExecutor$DelayedWorkQueue.take(ScheduledThread
PoolExecutor.java:1093)
    at
java.util.concurrent.ScheduledThreadPoolExecutor$DelayedWorkQueue.take(ScheduledThread
PoolExecutor.java:809)
      at java.util.concurrent.ThreadPoolExecutor.getTask(ThreadPoolExecutor.java:1074)
      at java.util.concurrent.ThreadPoolExecutor.runWorker(ThreadPoolExecutor.java:1134)
      at java.util.concurrent.ThreadPoolExecutor$Worker.run(ThreadPoolExecutor.java:624)
      at java.lang.Thread.run(Thread.java:748)

  Locked ownable synchronizers:
    - None

"parallel-1" - Thread t@1085
  java.lang.Thread.State: TIMED_WAITING
    at sun.misc.Unsafe.park(Native Method)
      - parking to wait for <76495934> (a

```

```

java.util.concurrent.locks.AbstractQueuedSynchronizer$ConditionObject)
    at java.util.concurrent.locks.LockSupport.parkNanos(LockSupport.java:215)
    at
java.util.concurrent.locks.AbstractQueuedSynchronizer$ConditionObject.awaitNanos(Abstr
actQueuedSynchronizer.java:2078)
    at
java.util.concurrent.ScheduledThreadPoolExecutor$DelayedWorkQueue.take(ScheduledThread
PoolExecutor.java:1093)
    at
java.util.concurrent.ScheduledThreadPoolExecutor$DelayedWorkQueue.take(ScheduledThread
PoolExecutor.java:809)
    at java.util.concurrent.ThreadPoolExecutor.getTask(ThreadPoolExecutor.java:1074)
    at java.util.concurrent.ThreadPoolExecutor.runWorker(ThreadPoolExecutor.java:1134)
    at java.util.concurrent.ThreadPoolExecutor$Worker.run(ThreadPoolExecutor.java:624)
    at java.lang.Thread.run(Thread.java:748)

```

Locked ownable synchronizers:

- None

"udp-nio-8" - Thread t@1084

```

java.lang.Thread.State: RUNNABLE
    at sun.nio.ch.EPollArrayWrapper.epollWait(Native Method)
    at sun.nio.ch.EPollArrayWrapper.poll(EPollArrayWrapper.java:269)
    at sun.nio.ch.EPollSelectorImpl.doSelect(EPollSelectorImpl.java:93)
    at sun.nio.ch.SelectorImpl.lockAndDoSelect(SelectorImpl.java:86)
    - locked <58da20c4> (a
io.micrometer.shaded.io.netty.channel.nio.SelectedSelectionKeySet)
    - locked <752530a> (a java.util.Collections$UnmodifiableSet)
    - locked <1cdadb42> (a sun.nio.ch.EPollSelectorImpl)
    at sun.nio.ch.SelectorImpl.select(SelectorImpl.java:97)
    at sun.nio.ch.SelectorImpl.select(SelectorImpl.java:101)
    at
io.micrometer.shaded.io.netty.channel.nio.SelectedSelectionKeySetSelector.select(Selec
tedSelectionKeySetSelector.java:68)
    at
io.micrometer.shaded.io.netty.channel.nio.NioEventLoop.select(NioEventLoop.java:805)
    at
io.micrometer.shaded.io.netty.channel.nio.NioEventLoop.run(NioEventLoop.java:457)
    at
io.micrometer.shaded.io.netty.util.concurrent.SingleThreadEventExecutor$4.run(SingleTh
readEventExecutor.java:989)
    at
io.micrometer.shaded.io.netty.util.internal.ThreadExecutorMap$2.run(ThreadExecutorMap.
java:74)
    at
io.micrometer.shaded.io.netty.util.concurrent.FastThreadLocalRunnable.run(FastThreadLo
calRunnable.java:30)
    at java.lang.Thread.run(Thread.java:748)

```

Locked ownable synchronizers:

- None

"udp-nio-7" - Thread t@1083

```
java.lang.Thread.State: RUNNABLE
  at sun.nio.ch.EPollArrayWrapper.epollWait(Native Method)
  at sun.nio.ch.EPollArrayWrapper.poll(EPollArrayWrapper.java:269)
  at sun.nio.ch.EPollSelectorImpl.doSelect(EPollSelectorImpl.java:93)
  at sun.nio.ch.SelectorImpl.lockAndDoSelect(SelectorImpl.java:86)
    - locked <20e6b114> (a
io.micrometer.shaded.io.netty.channel.nio.SelectedSelectionKeySet)
    - locked <29b369cc> (a java.util.Collections$UnmodifiableSet)
    - locked <3cecb5f3> (a sun.nio.ch.EPollSelectorImpl)
  at sun.nio.ch.SelectorImpl.select(SelectorImpl.java:97)
  at sun.nio.ch.SelectorImpl.select(SelectorImpl.java:101)
  at
io.micrometer.shaded.io.netty.channel.nio.SelectedSelectionKeySetSelector.select(SelectedSelectionKeySetSelector.java:68)
  at
io.micrometer.shaded.io.netty.channel.nio.NioEventLoop.select(NioEventLoop.java:805)
  at
io.micrometer.shaded.io.netty.channel.nio.NioEventLoop.run(NioEventLoop.java:457)
  at
io.micrometer.shaded.io.netty.util.concurrent.SingleThreadEventExecutor$4.run(SingleThreadEventExecutor.java:989)
  at
io.micrometer.shaded.io.netty.util.internal.ThreadExecutorMap$2.run(ThreadExecutorMap.java:74)
  at
io.micrometer.shaded.io.netty.util.concurrent.FastThreadLocalRunnable.run(FastThreadLocalRunnable.java:30)
    at java.lang.Thread.run(Thread.java:748)
```

Locked ownable synchronizers:

- None

"udp-nio-6" - Thread t@1082

```
java.lang.Thread.State: RUNNABLE
  at sun.nio.ch.EPollArrayWrapper.epollWait(Native Method)
  at sun.nio.ch.EPollArrayWrapper.poll(EPollArrayWrapper.java:269)
  at sun.nio.ch.EPollSelectorImpl.doSelect(EPollSelectorImpl.java:93)
  at sun.nio.ch.SelectorImpl.lockAndDoSelect(SelectorImpl.java:86)
    - locked <76a679e7> (a
io.micrometer.shaded.io.netty.channel.nio.SelectedSelectionKeySet)
    - locked <63dd0836> (a java.util.Collections$UnmodifiableSet)
    - locked <5112f088> (a sun.nio.ch.EPollSelectorImpl)
  at sun.nio.ch.SelectorImpl.select(SelectorImpl.java:97)
  at sun.nio.ch.SelectorImpl.select(SelectorImpl.java:101)
  at
io.micrometer.shaded.io.netty.channel.nio.SelectedSelectionKeySetSelector.select(SelectedSelectionKeySetSelector.java:68)
  at
io.micrometer.shaded.io.netty.channel.nio.NioEventLoop.select(NioEventLoop.java:805)
```



```
    at
io.micrometer.shaded.io.netty.channel.nio.NioEventLoop.run(NioEventLoop.java:457)
    at
io.micrometer.shaded.io.netty.util.concurrent.SingleThreadEventExecutor$4.run(SingleThreadEventExecutor.java:989)
    at
io.micrometer.shaded.io.netty.util.internal.ThreadExecutorMap$2.run(ThreadExecutorMap.java:74)
    at
io.micrometer.shaded.io.netty.util.concurrent.FastThreadLocalRunnable.run(FastThreadLocalRunnable.java:30)
    at java.lang.Thread.run(Thread.java:748)
```

Locked ownable synchronizers:

- None

"udp-nio-5" - Thread t@1081

java.lang.Thread.State: RUNNABLE

```
    at sun.nio.ch.EPollArrayWrapper.epollWait(Native Method)
    at sun.nio.ch.EPollArrayWrapper.poll(EPollArrayWrapper.java:269)
    at sun.nio.ch.EPollSelectorImpl.doSelect(EPollSelectorImpl.java:93)
    at sun.nio.ch.SelectorImpl.lockAndDoSelect(SelectorImpl.java:86)
    - locked <8089474> (a
```

io.micrometer.shaded.io.netty.channel.nio.SelectedSelectionKeySet)

- locked <4d24bdd3> (a java.util.Collections\$UnmodifiableSet)

- locked <463390f9> (a sun.nio.ch.EPollSelectorImpl)

```
    at sun.nio.ch.SelectorImpl.select(SelectorImpl.java:97)
    at sun.nio.ch.SelectorImpl.select(SelectorImpl.java:101)
    at
```

io.micrometer.shaded.io.netty.channel.nio.SelectedSelectionKeySetSelector.select(SelectedSelectionKeySetSelector.java:68)

at

io.micrometer.shaded.io.netty.channel.nio.NioEventLoop.select(NioEventLoop.java:805)

at

io.micrometer.shaded.io.netty.channel.nio.NioEventLoop.run(NioEventLoop.java:457)

at

io.micrometer.shaded.io.netty.util.concurrent.SingleThreadEventExecutor\$4.run(SingleThreadEventExecutor.java:989)

at

io.micrometer.shaded.io.netty.util.internal.ThreadExecutorMap\$2.run(ThreadExecutorMap.java:74)

at

io.micrometer.shaded.io.netty.util.concurrent.FastThreadLocalRunnable.run(FastThreadLocalRunnable.java:30)

at java.lang.Thread.run(Thread.java:748)

Locked ownable synchronizers:

- None

"udp-nio-4" - Thread t@1080

java.lang.Thread.State: RUNNABLE

```

    at sun.nio.ch.EPollArrayWrapper.epollWait(Native Method)
    at sun.nio.ch.EPollArrayWrapper.poll(EPollArrayWrapper.java:269)
    at sun.nio.ch.EPollSelectorImpl.doSelect(EPollSelectorImpl.java:93)
    at sun.nio.ch.SelectorImpl.lockAndDoSelect(SelectorImpl.java:86)
    - locked <63ae07> (a
io.micrometer.shaded.io.netty.channel.nio.SelectedSelectionKeySet)
    - locked <4c84314b> (a java.util.Collections$UnmodifiableSet)
    - locked <2426d72d> (a sun.nio.ch.EPollSelectorImpl)
    at sun.nio.ch.SelectorImpl.select(SelectorImpl.java:97)
    at sun.nio.ch.SelectorImpl.select(SelectorImpl.java:101)
    at
io.micrometer.shaded.io.netty.channel.nio.SelectedSelectionKeySetSelector.select(SelectedSelectionKeySetSelector.java:68)
    at
io.micrometer.shaded.io.netty.channel.nio.NioEventLoop.select(NioEventLoop.java:805)
    at
io.micrometer.shaded.io.netty.channel.nio.NioEventLoop.run(NioEventLoop.java:457)
    at
io.micrometer.shaded.io.netty.util.concurrent.SingleThreadEventExecutor$4.run(SingleThreadEventExecutor.java:989)
    at
io.micrometer.shaded.io.netty.util.internal.ThreadExecutorMap$2.run(ThreadExecutorMap.java:74)
    at
io.micrometer.shaded.io.netty.util.concurrent.FastThreadLocalRunnable.run(FastThreadLocalRunnable.java:30)
    at java.lang.Thread.run(Thread.java:748)

```

Locked ownable synchronizers:

- None

"udp-nio-3" - Thread t@1079

java.lang.Thread.State: RUNNABLE

```

    at sun.nio.ch.EPollArrayWrapper.epollWait(Native Method)
    at sun.nio.ch.EPollArrayWrapper.poll(EPollArrayWrapper.java:269)
    at sun.nio.ch.EPollSelectorImpl.doSelect(EPollSelectorImpl.java:93)
    at sun.nio.ch.SelectorImpl.lockAndDoSelect(SelectorImpl.java:86)
    - locked <7ec83f08> (a
io.micrometer.shaded.io.netty.channel.nio.SelectedSelectionKeySet)
    - locked <63c6b540> (a java.util.Collections$UnmodifiableSet)
    - locked <ea5de1a> (a sun.nio.ch.EPollSelectorImpl)
    at sun.nio.ch.SelectorImpl.select(SelectorImpl.java:97)
    at sun.nio.ch.SelectorImpl.select(SelectorImpl.java:101)
    at
io.micrometer.shaded.io.netty.channel.nio.SelectedSelectionKeySetSelector.select(SelectedSelectionKeySetSelector.java:68)
    at
io.micrometer.shaded.io.netty.channel.nio.NioEventLoop.select(NioEventLoop.java:805)
    at
io.micrometer.shaded.io.netty.channel.nio.NioEventLoop.run(NioEventLoop.java:457)
    at

```

```

io.micrometer.shaded.io.netty.util.concurrent.SingleThreadEventExecutor$4.run(SingleTh
readEventExecutor.java:989)
    at
io.micrometer.shaded.io.netty.util.internal.ThreadExecutorMap$2.run(ThreadExecutorMap.
java:74)
    at
io.micrometer.shaded.io.netty.util.concurrent.FastThreadLocalRunnable.run(FastThreadLo
calRunnable.java:30)
    at java.lang.Thread.run(Thread.java:748)

Locked ownable synchronizers:
- None

"udp-nio-2" - Thread t@1078
java.lang.Thread.State: RUNNABLE
    at sun.nio.ch.EPollArrayWrapper.epollWait(Native Method)
    at sun.nio.ch.EPollArrayWrapper.poll(EPollArrayWrapper.java:269)
    at sun.nio.ch.EPollSelectorImpl.doSelect(EPollSelectorImpl.java:93)
    at sun.nio.ch.SelectorImpl.lockAndDoSelect(SelectorImpl.java:86)
    - locked <1c28ff5c> (a
io.micrometer.shaded.io.netty.channel.nio.SelectedSelectionKeySet)
    - locked <2327b3ae> (a java.util.Collections$UnmodifiableSet)
    - locked <751d6e3f> (a sun.nio.ch.EPollSelectorImpl)
    at sun.nio.ch.SelectorImpl.select(SelectorImpl.java:97)
    at sun.nio.ch.SelectorImpl.select(SelectorImpl.java:101)
    at
io.micrometer.shaded.io.netty.channel.nio.SelectedSelectionKeySetSelector.select(Selec
tedSelectionKeySetSelector.java:68)
    at
io.micrometer.shaded.io.netty.channel.nio.NioEventLoop.select(NioEventLoop.java:805)
    at
io.micrometer.shaded.io.netty.channel.nio.NioEventLoop.run(NioEventLoop.java:457)
    at
io.micrometer.shaded.io.netty.util.concurrent.SingleThreadEventExecutor$4.run(SingleTh
readEventExecutor.java:989)
    at
io.micrometer.shaded.io.netty.util.internal.ThreadExecutorMap$2.run(ThreadExecutorMap.
java:74)
    at
io.micrometer.shaded.io.netty.util.concurrent.FastThreadLocalRunnable.run(FastThreadLo
calRunnable.java:30)
    at java.lang.Thread.run(Thread.java:748)

Locked ownable synchronizers:
- None

"udp-nio-1" - Thread t@1077
java.lang.Thread.State: RUNNABLE
    at sun.nio.ch.EPollArrayWrapper.epollWait(Native Method)
    at sun.nio.ch.EPollArrayWrapper.poll(EPollArrayWrapper.java:269)
    at sun.nio.ch.EPollSelectorImpl.doSelect(EPollSelectorImpl.java:93)

```

```

    at sun.nio.ch.SelectorImpl.lockAndDoSelect(SelectorImpl.java:86)
    - locked <55683b88> (a
io.micrometer.shaded.io.netty.channel.nio.SelectedSelectionKeySet)
    - locked <ee1fc66> (a java.util.Collections$UnmodifiableSet)
    - locked <104584d7> (a sun.nio.ch.EPollSelectorImpl)
    at sun.nio.ch.SelectorImpl.select(SelectorImpl.java:97)
    at sun.nio.ch.SelectorImpl.select(SelectorImpl.java:101)
    at
io.micrometer.shaded.io.netty.channel.nio.SelectedSelectionKeySetSelector.select(SelectedSelectionKeySetSelector.java:68)
    at
io.micrometer.shaded.io.netty.channel.nio.NioEventLoop.select(NioEventLoop.java:805)
    at
io.micrometer.shaded.io.netty.channel.nio.NioEventLoop.run(NioEventLoop.java:457)
    at
io.micrometer.shaded.io.netty.util.concurrent.SingleThreadEventExecutor$4.run(SingleThreadEventExecutor.java:989)
    at
io.micrometer.shaded.io.netty.util.internal.ThreadExecutorMap$2.run(ThreadExecutorMap.java:74)
    at
io.micrometer.shaded.io.netty.util.concurrent.FastThreadLocalRunnable.run(FastThreadLocalRunnable.java:30)
    at java.lang.Thread.run(Thread.java:748)

```

Locked ownable synchronizers:

- None

"nioEventLoopGroup-12-1" - Thread t@779

```

java.lang.Thread.State: RUNNABLE
    at sun.nio.ch.EPollArrayWrapper.epollWait(Native Method)
    at sun.nio.ch.EPollArrayWrapper.poll(EPollArrayWrapper.java:269)
    at sun.nio.ch.EPollSelectorImpl.doSelect(EPollSelectorImpl.java:93)
    at sun.nio.ch.SelectorImpl.lockAndDoSelect(SelectorImpl.java:86)
    - locked <eb77c76> (a io.netty.channel.nio.SelectedSelectionKeySet)
    - locked <1a17a253> (a java.util.Collections$UnmodifiableSet)
    - locked <1b147fbb> (a sun.nio.ch.EPollSelectorImpl)
    at sun.nio.ch.SelectorImpl.select(SelectorImpl.java:97)
    at sun.nio.ch.SelectorImpl.select(SelectorImpl.java:101)
    at
io.netty.channel.nio.SelectedSelectionKeySetSelector.select(SelectedSelectionKeySetSelector.java:68)
    at io.netty.channel.nio.NioEventLoop.select(NioEventLoop.java:810)
    at io.netty.channel.nio.NioEventLoop.run(NioEventLoop.java:457)
    at
io.netty.util.concurrent.SingleThreadEventExecutor$4.run(SingleThreadEventExecutor.java:989)
    at io.netty.util.internal.ThreadExecutorMap$2.run(ThreadExecutorMap.java:74)
    at
io.netty.util.concurrent.FastThreadLocalRunnable.run(FastThreadLocalRunnable.java:30)
    at java.lang.Thread.run(Thread.java:748)

```

Locked ownable synchronizers:

- None

"nioEventLoopGroup-10-1" - Thread t@758

java.lang.Thread.State: RUNNABLE

at sun.nio.ch.EPollArrayWrapper.epollWait(Native Method)
at sun.nio.ch.EPollArrayWrapper.poll(EPollArrayWrapper.java:269)
at sun.nio.ch.EPollSelectorImpl.doSelect(EPollSelectorImpl.java:93)
at sun.nio.ch.SelectorImpl.lockAndDoSelect(SelectorImpl.java:86)
- locked <274b3332> (a io.netty.channel.nio.SelectedSelectionKeySet)
- locked <122abf61> (a java.util.Collections\$UnmodifiableSet)
- locked <3508924d> (a sun.nio.ch.EPollSelectorImpl)
at sun.nio.ch.SelectorImpl.select(SelectorImpl.java:97)
at sun.nio.ch.SelectorImpl.select(SelectorImpl.java:101)
at

io.netty.channel.nio.SelectedSelectionKeySetSelector.select(SelectedSelectionKeySetSelector.java:68)

at io.netty.channel.nio.NioEventLoop.select(NioEventLoop.java:810)
at io.netty.channel.nio.NioEventLoop.run(NioEventLoop.java:457)
at

io.netty.util.concurrent.SingleThreadEventExecutor\$4.run(SingleThreadEventExecutor.java:989)

at io.netty.util.internal.ThreadExecutorMap\$2.run(ThreadExecutorMap.java:74)
at

io.netty.util.concurrent.FastThreadLocalRunnable.run(FastThreadLocalRunnable.java:30)
at java.lang.Thread.run(Thread.java:748)

Locked ownable synchronizers:

- None

"nioEventLoopGroup-8-1" - Thread t@738

java.lang.Thread.State: RUNNABLE

at sun.nio.ch.EPollArrayWrapper.epollWait(Native Method)
at sun.nio.ch.EPollArrayWrapper.poll(EPollArrayWrapper.java:269)
at sun.nio.ch.EPollSelectorImpl.doSelect(EPollSelectorImpl.java:93)
at sun.nio.ch.SelectorImpl.lockAndDoSelect(SelectorImpl.java:86)
- locked <dd9caf0> (a io.netty.channel.nio.SelectedSelectionKeySet)
- locked <73f5aada> (a java.util.Collections\$UnmodifiableSet)
- locked <34e3c272> (a sun.nio.ch.EPollSelectorImpl)
at sun.nio.ch.SelectorImpl.select(SelectorImpl.java:97)
at sun.nio.ch.SelectorImpl.select(SelectorImpl.java:101)
at

io.netty.channel.nio.SelectedSelectionKeySetSelector.select(SelectedSelectionKeySetSelector.java:68)

at io.netty.channel.nio.NioEventLoop.select(NioEventLoop.java:810)
at io.netty.channel.nio.NioEventLoop.run(NioEventLoop.java:457)
at

io.netty.util.concurrent.SingleThreadEventExecutor\$4.run(SingleThreadEventExecutor.java:989)

at io.netty.util.internal.ThreadExecutorMap\$2.run(ThreadExecutorMap.java:74)

```

    at
io.netty.util.concurrent.FastThreadLocalRunnable.run(FastThreadLocalRunnable.java:30)
    at java.lang.Thread.run(Thread.java:748)

Locked ownable synchronizers:
- None

"Keep-Alive-Timer" - Thread t@540
  java.lang.Thread.State: TIMED_WAITING
    at java.lang.Thread.sleep(Native Method)
    at sun.net.www.http.KeepAliveCache.run(KeepAliveCache.java:172)
    at java.lang.Thread.run(Thread.java:748)

Locked ownable synchronizers:
- None

"boundedElastic-2" - Thread t@399
  java.lang.Thread.State: WAITING
    at sun.misc.Unsafe.park(Native Method)
    - parking to wait for <4588b459> (a
java.util.concurrent.locks.AbstractQueuedSynchronizer$ConditionObject)
    at java.util.concurrent.locks.LockSupport.park(LockSupport.java:175)
    at
java.util.concurrent.locks.AbstractQueuedSynchronizer$ConditionObject.await(AbstractQueuedSynchronizer.java:2039)
    at
java.util.concurrent.ScheduledThreadPoolExecutor$DelayedWorkQueue.take(ScheduledThreadPoolExecutor.java:1081)
    at
java.util.concurrent.ScheduledThreadPoolExecutor$DelayedWorkQueue.take(ScheduledThreadPoolExecutor.java:809)
    at java.util.concurrent.ThreadPoolExecutor.getTask(ThreadPoolExecutor.java:1074)
    at java.util.concurrent.ThreadPoolExecutor.runWorker(ThreadPoolExecutor.java:1134)
    at java.util.concurrent.ThreadPoolExecutor$Worker.run(ThreadPoolExecutor.java:624)
    at java.lang.Thread.run(Thread.java:748)

Locked ownable synchronizers:
- None

"boundedElastic-1" - Thread t@15
  java.lang.Thread.State: WAITING
    at sun.misc.Unsafe.park(Native Method)
    - parking to wait for <6457852> (a
java.util.concurrent.locks.AbstractQueuedSynchronizer$ConditionObject)
    at java.util.concurrent.locks.LockSupport.park(LockSupport.java:175)
    at
java.util.concurrent.locks.AbstractQueuedSynchronizer$ConditionObject.await(AbstractQueuedSynchronizer.java:2039)
    at
java.util.concurrent.ScheduledThreadPoolExecutor$DelayedWorkQueue.take(ScheduledThreadPoolExecutor.java:1081)

```

```
at
java.util.concurrent.ScheduledThreadPoolExecutor$DelayedWorkQueue.take(ScheduledThread
PoolExecutor.java:809)
at java.util.concurrent.ThreadPoolExecutor.getTask(ThreadPoolExecutor.java:1074)
at java.util.concurrent.ThreadPoolExecutor.runWorker(ThreadPoolExecutor.java:1134)
at java.util.concurrent.ThreadPoolExecutor$Worker.run(ThreadPoolExecutor.java:624)
at java.lang.Thread.run(Thread.java:748)
```

Locked ownable synchronizers:

- None

```
"boundedElastic-evictor-1" - Thread t@14
java.lang.Thread.State: TIMED_WAITING
at sun.misc.Unsafe.park(Native Method)
- parking to wait for <5838a13a> (a
java.util.concurrent.locks.AbstractQueuedSynchronizer$ConditionObject)
at java.util.concurrent.locks.LockSupport.parkNanos(LockSupport.java:215)
at
java.util.concurrent.locks.AbstractQueuedSynchronizer$ConditionObject.awaitNanos(Abstr
actQueuedSynchronizer.java:2078)
at
java.util.concurrent.ScheduledThreadPoolExecutor$DelayedWorkQueue.take(ScheduledThread
PoolExecutor.java:1093)
at
java.util.concurrent.ScheduledThreadPoolExecutor$DelayedWorkQueue.take(ScheduledThread
PoolExecutor.java:809)
at java.util.concurrent.ThreadPoolExecutor.getTask(ThreadPoolExecutor.java:1074)
at java.util.concurrent.ThreadPoolExecutor.runWorker(ThreadPoolExecutor.java:1134)
at java.util.concurrent.ThreadPoolExecutor$Worker.run(ThreadPoolExecutor.java:624)
at java.lang.Thread.run(Thread.java:748)
```

Locked ownable synchronizers:

- None

```
"/127.0.0.1:36712 to /127.0.0.1:39623 workers Thread 3" - Thread t@13
java.lang.Thread.State: RUNNABLE
at sun.nio.ch.EPollArrayWrapper.epollWait(Native Method)
at sun.nio.ch.EPollArrayWrapper.poll(EPollArrayWrapper.java:269)
at sun.nio.ch.EPollSelectorImpl.doSelect(EPollSelectorImpl.java:93)
at sun.nio.ch.SelectorImpl.lockAndDoSelect(SelectorImpl.java:86)
- locked <7262181d> (a sun.nio.ch.Util$3)
- locked <72484074> (a java.util.Collections$UnmodifiableSet)
- locked <5fe22187> (a sun.nio.ch.EPollSelectorImpl)
at sun.nio.ch.SelectorImpl.select(SelectorImpl.java:97)
at sun.nio.ch.SelectorImpl.select(SelectorImpl.java:101)
at
org.gradle.internal.remote.internal.inet.SocketConnection$SocketInputStream.read(Socket
Connection.java:185)
at com.esotericsoftware.kryo.io.Input.fill(Input.java:146)
at com.esotericsoftware.kryo.io.Input.require(Input.java:178)
at com.esotericsoftware.kryo.io.Input.readByte(Input.java:295)
```

```

    at
org.gradle.internal.serialize.kryo.KryoBackedDecoder.readByte(KryoBackedDecoder.java:82)
    at
org.gradle.internal.remote.internal.hub.InterHubMessageSerializer$MessageReader.read(InterHubMessageSerializer.java:64)
    at
org.gradle.internal.remote.internal.hub.InterHubMessageSerializer$MessageReader.read(InterHubMessageSerializer.java:52)
    at
org.gradle.internal.remote.internal.inet.SocketConnection.receive(SocketConnection.java:81)
    at
org.gradle.internal.remote.internal.hub.MessageHub$ConnectionReceive.run(MessageHub.java:270)
    at
org.gradle.internal.concurrent.ExecutorPolicy$CatchAndRecordFailures.onExecute(ExecutorPolicy.java:64)
    at
org.gradle.internal.concurrent.ManagedExecutorImpl$1.run(ManagedExecutorImpl.java:48)
    at java.util.concurrent.ThreadPoolExecutor.runWorker(ThreadPoolExecutor.java:1149)
    at java.util.concurrent.ThreadPoolExecutor$Worker.run(ThreadPoolExecutor.java:624)
    at
org.gradle.internal.concurrent.ThreadFactoryImpl$ManagedThreadRunnable.run(ThreadFactoryImpl.java:56)
    at java.lang.Thread.run(Thread.java:748)

Locked ownable synchronizers:
- Locked <56de5251> (a java.util.concurrent.ThreadPoolExecutor$Worker)

"/127.0.0.1:36712 to /127.0.0.1:39623 workers Thread 2" - Thread t@12
java.lang.Thread.State: WAITING
    at sun.misc.Unsafe.park(Native Method)
    - parking to wait for <42ce6a30> (a
java.util.concurrent.locks.AbstractQueuedSynchronizer$ConditionObject)
    at java.util.concurrent.locks.LockSupport.park(LockSupport.java:175)
    at
java.util.concurrent.locks.AbstractQueuedSynchronizer$ConditionObject.await(AbstractQueuedSynchronizer.java:2039)
    at
org.gradle.internal.remote.internal.hub.queue.EndPointQueue.take(EndPointQueue.java:49)
    at
org.gradle.internal.remote.internal.hub.MessageHub$ConnectionDispatch.run(MessageHub.java:322)
    at
org.gradle.internal.concurrent.ExecutorPolicy$CatchAndRecordFailures.onExecute(ExecutorPolicy.java:64)
    at
org.gradle.internal.concurrent.ManagedExecutorImpl$1.run(ManagedExecutorImpl.java:48)
    at java.util.concurrent.ThreadPoolExecutor.runWorker(ThreadPoolExecutor.java:1149)

```



```

    at java.util.concurrent.ThreadPoolExecutor$Worker.run(ThreadPoolExecutor.java:624)
    at
org.gradle.internal.concurrent.ThreadFactoryImpl$ManagedThreadRunnable.run(ThreadFacto
ryImpl.java:56)
    at java.lang.Thread.run(Thread.java:748)

Locked ownable synchronizers:
- Locked <d4342c2> (a java.util.concurrent.ThreadPoolExecutor$Worker)

"Test worker" - Thread t@11
  java.lang.Thread.State: RUNNABLE
    at sun.management.ThreadImpl.dumpThreads0(Native Method)
    at sun.management.ThreadImpl.dumpAllThreads(ThreadImpl.java:454)
    at
org.springframework.boot.actuate.management.ThreadDumpEndpoint.getFormattedThreadDump(
ThreadDumpEndpoint.java:51)
    at
org.springframework.boot.actuate.management.ThreadDumpEndpoint.textThreadDump(ThreadDu
mpEndpoint.java:47)
    at sun.reflect.NativeMethodAccessorImpl.invoke0(Native Method)
    at sun.reflect.NativeMethodAccessorImpl.invoke(NativeMethodAccessorImpl.java:62)
    at
sun.reflect.DelegatingMethodAccessorImpl.invoke(DelegatingMethodAccessorImpl.java:43)
    at java.lang.reflect.Method.invoke(Method.java:498)
    at org.springframework.util.ReflectionUtils.invokeMethod(ReflectionUtils.java:282)
    at
org.springframework.boot.actuate.endpoint.invoke.reflect.ReflectiveOperationInvoker.in
voke(ReflectiveOperationInvoker.java:77)
    at
org.springframework.boot.actuate.endpoint.annotation.AbstractDiscoveredOperation.invo
ke(AbstractDiscoveredOperation.java:60)
    at
org.springframework.boot.actuate.endpoint.web.servlet.AbstractWebMvcEndpointHandlerMap
ping$ServletWebOperationAdapter.handle(AbstractWebMvcEndpointHandlerMapping.java:305)
    at
org.springframework.boot.actuate.endpoint.web.servlet.AbstractWebMvcEndpointHandlerMap
ping$OperationHandler.handle(AbstractWebMvcEndpointHandlerMapping.java:388)
    at sun.reflect.GeneratedMethodAccessor457.invoke(Unknown Source)
    at
sun.reflect.DelegatingMethodAccessorImpl.invoke(DelegatingMethodAccessorImpl.java:43)
    at java.lang.reflect.Method.invoke(Method.java:498)
    at
org.springframework.web.method.support.InvocableHandlerMethod.doInvoke(InvocableHandle
rMethod.java:190)
    at
org.springframework.web.method.support.InvocableHandlerMethod.invokeForRequest(Invocab
leHandlerMethod.java:138)
    at
org.springframework.web.servlet.mvc.method.annotation.ServletInvocableHandlerMethod.in
vokeAndHandle(ServletInvocableHandlerMethod.java:105)
    at

```

```

org.springframework.web.servlet.mvc.method.annotation.RequestMappingHandlerAdapter.invokeHandlerMethod(RequestMappingHandlerAdapter.java:878)
    at
org.springframework.web.servlet.mvc.method.annotation.RequestMappingHandlerAdapter.handleInternal(RequestMappingHandlerAdapter.java:792)
    at
org.springframework.web.servlet.mvc.method.AbstractHandlerMethodAdapter.handle(AbstractHandlerMethodAdapter.java:87)
    at
org.springframework.web.servlet.DispatcherServlet.doDispatch(DispatcherServlet.java:1040)
    at
org.springframework.web.servlet.DispatcherServlet.doService(DispatcherServlet.java:943)
    at
org.springframework.web.servlet.FrameworkServlet.processRequest(FrameworkServlet.java:1006)
    at
org.springframework.web.servlet.FrameworkServlet.doGet(FrameworkServlet.java:898)
    at javax.servlet.http.HttpServlet.service(HttpServlet.java:645)
    at
org.springframework.web.servlet.FrameworkServlet.service(FrameworkServlet.java:883)
    at
org.springframework.test.web.servlet.TestDispatcherServlet.service(TestDispatcherServlet.java:72)
    at javax.servlet.http.HttpServlet.service(HttpServlet.java:750)
    at
org.springframework.mock.web.MockFilterChain$ServletFilterProxy.doFilter(MockFilterChain.java:167)
    at org.springframework.mock.web.MockFilterChain.doFilter(MockFilterChain.java:134)
    at org.springframework.test.web.servlet.MockMvc.perform(MockMvc.java:183)
    at
org.springframework.boot.actuate.autoconfigure.endpoint.web.documentation.ThreadDumpEndpointDocumentationTests.textThreadDump(ThreadDumpEndpointDocumentationTests.java:186)
    at sun.reflect.NativeMethodAccessorImpl.invoke0(Native Method)
    at sun.reflect.NativeMethodAccessorImpl.invoke(NativeMethodAccessorImpl.java:62)
    at
sun.reflect.DelegatingMethodAccessorImpl.invoke(DelegatingMethodAccessorImpl.java:43)
    at java.lang.reflect.Method.invoke(Method.java:498)
    at
org.junit.platform.commons.util.ReflectionUtils.invokeMethod(ReflectionUtils.java:686)
    at
org.junit.jupiter.engine.execution.MethodInvocation.proceed(MethodInvocation.java:60)
    at
org.junit.jupiter.engine.execution.InvocationInterceptorChain$ValidatingInvocation.proceed(InvocationInterceptorChain.java:131)
    at
org.junit.jupiter.engine.extension.TimeoutExtension.intercept(TimeoutExtension.java:149)
    at
org.junit.jupiter.engine.extension.TimeoutExtension.interceptTestableMethod(TimeoutExt

```

```
ension.java:140)
    at
org.junit.jupiter.engine.extension.TimeoutExtension.interceptTestMethod(TimeoutExtensi
on.java:84)
    at
org.junit.jupiter.engine.descriptor.TestMethodTestDescriptor$$Lambda$120/1060925203.ap
ply(Unknown Source)
    at
org.junit.jupiter.engine.execution.ExecutableInvoker$ReflectiveInterceptorCall.lambda$
ofVoidMethod$0(ExecutableInvoker.java:115)
    at
org.junit.jupiter.engine.execution.ExecutableInvoker$ReflectiveInterceptorCall$$Lambda
$121/1643183871.apply(Unknown Source)
    at
org.junit.jupiter.engine.execution.ExecutableInvoker.lambda$invoke$0(ExecutableInvoker
.java:105)
    at
org.junit.jupiter.engine.execution.ExecutableInvoker$$Lambda$237/927275509.apply(Unkno
wn Source)
    at
org.junit.jupiter.engine.execution.InvocationInterceptorChain$InterceptedInvocation.pr
oceed(InvocationInterceptorChain.java:106)
    at
org.junit.jupiter.engine.execution.InvocationInterceptorChain.proceed(InvocationInterc
eptorChain.java:64)
    at
org.junit.jupiter.engine.execution.InvocationInterceptorChain.chainAndInvoke(Invocatio
nInterceptorChain.java:45)
    at
org.junit.jupiter.engine.execution.InvocationInterceptorChain.invoke(InvocationInterce
ptorChain.java:37)
    at
org.junit.jupiter.engine.execution.ExecutableInvoker.invoke(ExecutableInvoker.java:104
)
    at
org.junit.jupiter.engine.execution.ExecutableInvoker.invoke(ExecutableInvoker.java:98)
    at
org.junit.jupiter.engine.descriptor.TestMethodTestDescriptor.lambda$invokeTestMethod$6
(TestMethodTestDescriptor.java:212)
    at
org.junit.jupiter.engine.descriptor.TestMethodTestDescriptor$$Lambda$274/760487548.exe
cute(Unknown Source)
    at
org.junit.platform.engine.support.hierarchical.ThrowableCollector.execute(ThrowableCol
lector.java:73)
    at
org.junit.jupiter.engine.descriptor.TestMethodTestDescriptor.invokeTestMethod(TestMeth
odTestDescriptor.java:208)
    at
org.junit.jupiter.engine.descriptor.TestMethodTestDescriptor.execute(TestMethodTestDes
criptor.java:137)
```

```

    at
org.junit.jupiter.engine.descriptor.TestMethodTestDescriptor.execute(TestMethodTestDes
criptor.java:71)
    at
org.junit.platform.engine.support.hierarchical.NodeTestTask.lambda$executeRecursively$
5(NodeTestTask.java:135)
    at
org.junit.platform.engine.support.hierarchical.NodeTestTask$$Lambda$180/209753421.exec
ute(Unknown Source)
    at
org.junit.platform.engine.support.hierarchical.ThrowableCollector.execute(Throwab
leCollector.java:73)
    at
org.junit.platform.engine.support.hierarchical.NodeTestTask.lambda$executeRecursively$
7(NodeTestTask.java:125)
    at
org.junit.platform.engine.support.hierarchical.NodeTestTask$$Lambda$179/920619802.invo
ke(Unknown Source)
    at org.junit.platform.engine.support.hierarchical.Node.around(Node.java:135)
    at
org.junit.platform.engine.support.hierarchical.NodeTestTask.lambda$executeRecursively$
8(NodeTestTask.java:123)
    at
org.junit.platform.engine.support.hierarchical.NodeTestTask$$Lambda$178/1403385349.exe
cute(Unknown Source)
    at
org.junit.platform.engine.support.hierarchical.ThrowableCollector.execute(Throwab
leCollector.java:73)
    at
org.junit.platform.engine.support.hierarchical.NodeTestTask.executeRecursively(NodeTes
tTask.java:122)
    at
org.junit.platform.engine.support.hierarchical.NodeTestTask.execute(NodeTestTask.java:
80)
    at
org.junit.platform.engine.support.hierarchical.SameThreadHierarchicalTestExecutorServi
ce$$Lambda$184/1896273984.accept(Unknown Source)
    at java.util.ArrayList.forEach(ArrayList.java:1259)
    at
org.junit.platform.engine.support.hierarchical.SameThreadHierarchicalTestExecutorServi
ce.invokeAll(SameThreadHierarchicalTestExecutorService.java:38)
    at
org.junit.platform.engine.support.hierarchical.NodeTestTask.lambda$executeRecursively$
5(NodeTestTask.java:139)
    at
org.junit.platform.engine.support.hierarchical.NodeTestTask$$Lambda$180/209753421.exec
ute(Unknown Source)
    at
org.junit.platform.engine.support.hierarchical.ThrowableCollector.execute(Throwab
leCollector.java:73)
    at

```

```

org.junit.platform.engine.support.hierarchical.NodeTestTask.lambda$executeRecursively$
7(NodeTestTask.java:125)
    at
org.junit.platform.engine.support.hierarchical.NodeTestTask$$Lambda$179/920619802.invo
ke(Unknown Source)
    at org.junit.platform.engine.support.hierarchical.Node.around(Node.java:135)
    at
org.junit.platform.engine.support.hierarchical.NodeTestTask.lambda$executeRecursively$
8(NodeTestTask.java:123)
    at
org.junit.platform.engine.support.hierarchical.NodeTestTask$$Lambda$178/1403385349.exe
cute(Unknown Source)
    at
org.junit.platform.engine.support.hierarchical.ThrowableCollector.execute(ThrowableCol
lector.java:73)
    at
org.junit.platform.engine.support.hierarchical.NodeTestTask.executeRecursively(NodeTes
tTask.java:122)
    at
org.junit.platform.engine.support.hierarchical.NodeTestTask.execute(NodeTestTask.java:
80)
    at
org.junit.platform.engine.support.hierarchical.SameThreadHierarchicalTestExecutorServi
ce$$Lambda$184/1896273984.accept(Unknown Source)
    at java.util.ArrayList.forEach(ArrayList.java:1259)
    at
org.junit.platform.engine.support.hierarchical.SameThreadHierarchicalTestExecutorServi
ce.invokeAll(SameThreadHierarchicalTestExecutorService.java:38)
    at
org.junit.platform.engine.support.hierarchical.NodeTestTask.lambda$executeRecursively$
5(NodeTestTask.java:139)
    at
org.junit.platform.engine.support.hierarchical.NodeTestTask$$Lambda$180/209753421.exec
ute(Unknown Source)
    at
org.junit.platform.engine.support.hierarchical.ThrowableCollector.execute(ThrowableCol
lector.java:73)
    at
org.junit.platform.engine.support.hierarchical.NodeTestTask.lambda$executeRecursively$
7(NodeTestTask.java:125)
    at
org.junit.platform.engine.support.hierarchical.NodeTestTask$$Lambda$179/920619802.invo
ke(Unknown Source)
    at org.junit.platform.engine.support.hierarchical.Node.around(Node.java:135)
    at
org.junit.platform.engine.support.hierarchical.NodeTestTask.lambda$executeRecursively$
8(NodeTestTask.java:123)
    at
org.junit.platform.engine.support.hierarchical.NodeTestTask$$Lambda$178/1403385349.exe
cute(Unknown Source)
    at

```

```

org.junit.platform.engine.support.hierarchical.ThrowableCollector.execute(ThrowableCollector.java:73)
    at
org.junit.platform.engine.support.hierarchical.NodeTestTask.executeRecursively(NodeTestTask.java:122)
    at
org.junit.platform.engine.support.hierarchical.NodeTestTask.execute(NodeTestTask.java:80)
    at
org.junit.platform.engine.support.hierarchical.SameThreadHierarchicalTestExecutorService.submit(SameThreadHierarchicalTestExecutorService.java:32)
    at
org.junit.platform.engine.support.hierarchical.HierarchicalTestExecutor.execute(HierarchicalTestExecutor.java:57)
    at
org.junit.platform.engine.support.hierarchical.HierarchicalTestEngine.execute(HierarchicalTestEngine.java:51)
    at
org.junit.platform.launcher.core.DefaultLauncher.execute(DefaultLauncher.java:248)
    at
org.junit.platform.launcher.core.DefaultLauncher.lambda$execute$5(DefaultLauncher.java:211)
    at
org.junit.platform.launcher.core.DefaultLauncher$$Lambda$145/1643262044.accept(Unknown Source)
    at
org.junit.platform.launcher.core.DefaultLauncher.withInterceptedStreams(DefaultLauncher.java:226)
    at
org.junit.platform.launcher.core.DefaultLauncher.execute(DefaultLauncher.java:199)
    at
org.junit.platform.launcher.core.DefaultLauncher.execute(DefaultLauncher.java:132)
    at
org.gradle.api.internal.tasks.testing.junitplatform.JUnitPlatformTestClassProcessor$CollectAllTestClassesExecutor.processAllTestClasses(JUnitPlatformTestClassProcessor.java:99)
    at
org.gradle.api.internal.tasks.testing.junitplatform.JUnitPlatformTestClassProcessor$CollectAllTestClassesExecutor.access$000(JUnitPlatformTestClassProcessor.java:79)
    at
org.gradle.api.internal.tasks.testing.junitplatform.JUnitPlatformTestClassProcessor.stop(JUnitPlatformTestClassProcessor.java:75)
    at
org.gradle.api.internal.tasks.testing.SuiteTestClassProcessor.stop(SuiteTestClassProcessor.java:61)
    at sun.reflect.NativeMethodAccessorImpl.invoke0(Native Method)
    at sun.reflect.NativeMethodAccessorImpl.invoke(NativeMethodAccessorImpl.java:62)
    at
sun.reflect.DelegatingMethodAccessorImpl.invoke(DelegatingMethodAccessorImpl.java:43)
    at java.lang.reflect.Method.invoke(Method.java:498)
    at

```

```

org.gradle.internal.dispatch.ReflectionDispatch.dispatch(ReflectionDispatch.java:36)
    at
org.gradle.internal.dispatch.ReflectionDispatch.dispatch(ReflectionDispatch.java:24)
    at
org.gradle.internal.dispatch.ContextClassLoaderDispatch.dispatch(ContextClassLoaderDispatch.java:33)
    at
org.gradle.internal.dispatch.ProxyDispatchAdapter$DispatchingInvocationHandler.invoke(ProxyDispatchAdapter.java:94)
    at com.sun.proxy.$Proxy2.stop(Unknown Source)
    at
org.gradle.api.internal.tasks.testing.worker.TestWorker.stop(TestWorker.java:133)
    at sun.reflect.NativeMethodAccessorImpl.invoke0(Native Method)
    at sun.reflect.NativeMethodAccessorImpl.invoke(NativeMethodAccessorImpl.java:62)
    at
sun.reflect.DelegatingMethodAccessorImpl.invoke(DelegatingMethodAccessorImpl.java:43)
    at java.lang.reflect.Method.invoke(Method.java:498)
    at
org.gradle.internal.dispatch.ReflectionDispatch.dispatch(ReflectionDispatch.java:36)
    at
org.gradle.internal.dispatch.ReflectionDispatch.dispatch(ReflectionDispatch.java:24)
    at
org.gradle.internal.remote.internal.hub.MessageHubBackedObjectConnection$DispatchWrapper.dispatch(MessageHubBackedObjectConnection.java:182)
    at
org.gradle.internal.remote.internal.hub.MessageHubBackedObjectConnection$DispatchWrapper.dispatch(MessageHubBackedObjectConnection.java:164)
    at
org.gradle.internal.remote.internal.hub.MessageHub$Handler.run(MessageHub.java:414)
    at
org.gradle.internal.concurrent.ExecutorPolicy$CatchAndRecordFailures.onExecute(ExecutorPolicy.java:64)
    at
org.gradle.internal.concurrent.ManagedExecutorImpl$1.run(ManagedExecutorImpl.java:48)
    at java.util.concurrent.ThreadPoolExecutor.runWorker(ThreadPoolExecutor.java:1149)
    at java.util.concurrent.ThreadPoolExecutor$Worker.run(ThreadPoolExecutor.java:624)
    at
org.gradle.internal.concurrent.ThreadFactoryImpl$ManagedThreadRunnable.run(ThreadFactoryImpl.java:56)
    at java.lang.Thread.run(Thread.java:748)

```

Locked ownable synchronizers:

- Locked <2133814f> (a java.util.concurrent.ThreadPoolExecutor\$Worker)

"Signal Dispatcher" - Thread t@4
 java.lang.Thread.State: RUNNABLE

Locked ownable synchronizers:

- None

"Finalizer" - Thread t@3

```
java.lang.Thread.State: WAITING
  at java.lang.Object.wait(Native Method)
    - waiting on <10759f11> (a java.lang.ref.ReferenceQueue$Lock)
  at java.lang.ref.ReferenceQueue.remove(ReferenceQueue.java:144)
  at java.lang.ref.ReferenceQueue.remove(ReferenceQueue.java:165)
  at java.lang.ref.Finalizer$FinalizerThread.run(Finalizer.java:216)
```

Locked ownable synchronizers:
- None

"Reference Handler" - Thread t02

```
java.lang.Thread.State: WAITING
  at java.lang.Object.wait(Native Method)
    - waiting on <5ed56a81> (a java.lang.ref.Reference$Lock)
  at java.lang.Object.wait(Object.java:502)
  at java.lang.ref.Reference.tryHandlePending(Reference.java:191)
  at java.lang.ref.Reference$ReferenceHandler.run(Reference.java:153)
```

Locked ownable synchronizers:
- None