



Spring for Apache Hadoop Reference Manual

2.0.0.RC3-cdh5

Costin Leau Elasticsearch , Thomas Risberg Pivotal , Janne Valkealahti Pivotal

Copyright ©

Copies of this document may be made for your own use and for distribution to others, provided that you do not charge any fee for such copies and further provided that each copy contains this Copyright Notice, whether distributed in print or electronically.

Table of Contents

Preface	v
I. Introduction	1
1. Requirements	2
2. Additional Resources	4
II. Spring and Hadoop	5
3. Hadoop Configuration, MapReduce, and Distributed Cache	6
3.1. Using the Spring for Apache Hadoop Namespace	6
3.2. Configuring Hadoop	7
3.3. Creating a Hadoop Job	10
Creating a Hadoop Streaming Job	11
3.4. Running a Hadoop Job	12
Using the Hadoop Job tasklet	13
3.5. Running a Hadoop Tool	13
Replacing Hadoop shell invocations with <code>tool-runner</code>	14
Using the Hadoop Tool tasklet	15
3.6. Running a Hadoop Jar	15
Using the Hadoop Jar tasklet	16
3.7. Configuring the Hadoop <code>DistributedCache</code>	16
3.8. Map Reduce Generic Options	17
4. Working with the Hadoop File System	18
4.1. Configuring the file-system	18
4.2. Using HDFS Resource Loader	19
4.3. Scripting the Hadoop API	21
Using scripts	23
4.4. Scripting implicit variables	23
Running scripts	24
Using the Scripting tasklet	24
4.5. File System Shell (<code>FsShell</code>)	25
DistCp API	26
5. Working with HBase	27
5.1. Data Access Object (DAO) Support	27
6. Hive integration	29
6.1. Starting a Hive Server	29
6.2. Using the Hive Thrift Client	29
6.3. Using the Hive JDBC Client	30
6.4. Running a Hive script or query	30
Using the Hive tasklet	31
6.5. Interacting with the Hive API	31
7. Pig support	33
7.1. Running a Pig script	33
Using the Pig tasklet	34
7.2. Interacting with the Pig API	34
8. Using the <i>runner</i> classes	35
9. Security Support	37
9.1. HDFS permissions	37
9.2. User impersonation (Kerberos)	37
10. Yarn Support	38

10.1. Using the Spring for Apache Yarn Namespace	38
10.2. Using the Spring for Apache Yarn JavaConfig	40
10.3. Configuring Yarn	41
10.4. Local Resources	45
10.5. Container Environment	47
10.6. Application Client	48
10.7. Application Master	50
10.8. Application Container	53
10.9. Application Master Services	53
Basic Concepts	54
Using JSON	54
Converters	55
10.10. Application Master Service	55
10.11. Application Master Service Client	56
10.12. Using Spring Batch	58
Batch Jobs	58
Partitioning	60
Configuring Master	60
Configuring Container	61
10.13. Using Spring Boot Application Model	62
Auto Configuration	65
Application Files	65
Application Classpath	66
Simple Executable Jar	66
Simple Zip Archive	66
Container Runners	67
Custom Runner	67
Resource Localizing	67
Container as POJO	69
Configuration Properties	70
Controlling Applications	77
Generic Usage	77
Using Configuration Properties	77
Using YarnPushApplication	78
Using YarnSubmitApplication	78
Using YarnInfoApplication	78
Using YarnKillApplication	79
11. Testing Support	80
11.1. Testing MapReduce	80
Mini Clusters for MapReduce	80
Configuration	81
Simplified Testing	81
Wordcount Example	82
11.2. Testing Yarn	84
Mini Clusters for Yarn	84
Configuration	85
Simplified Testing	86
Multi Context Example	87
11.3. Testing Boot Based Applications	89
III. Developing Spring for Apache Hadoop Applications	92

12. Guidance and Examples	93
12.1. Scheduling	93
12.2. Batch Job Listeners	93
IV. Spring for Apache Hadoop sample applications	95
V. Other Resources	96
13. Useful Links	97
VI. Appendices	98
A. Using Spring for Apache Hadoop with Amazon EMR	99
A.1. Start up the cluster	99
A.2. Open an SSH Tunnel as a SOCKS proxy	100
A.3. Configuring Hadoop to use a SOCKS proxy	100
A.4. Accessing the file-system	101
A.5. Shutting down the cluster	101
A.6. Example configuration	102
B. Using Spring for Apache Hadoop with EC2/Apache Whirr	104
B.1. Setting up the Hadoop cluster on EC2 with Apache Whirr	104
C. Spring for Apache Hadoop Schema	106

Preface

Spring for Apache Hadoop provides extensions to Spring, Spring Batch, and Spring Integration to build manageable and robust pipeline solutions around Hadoop.

Spring for Apache Hadoop supports reading from and writing to HDFS, running various types of Hadoop jobs (Java MapReduce, Streaming), scripting and HBase, Hive and Pig interactions. An important goal is to provide excellent support for non-Java based developers to be productive using Spring for Apache Hadoop and not have to write any Java code to use the core feature set.

Spring for Apache Hadoop also applies the familiar Spring programming model to Java MapReduce jobs by providing support for dependency injection of simple jobs as well as a POJO based MapReduce programming model that decouples your MapReduce classes from Hadoop specific details such as base classes and data types.

This document assumes the reader already has a basic familiarity with the Spring Framework and Hadoop concepts and APIs.

While every effort has been made to ensure that this documentation is comprehensive and there are no errors, nevertheless some topics might require more explanation and some typos might have crept in. If you do spot any mistakes or even more serious errors and you can spare a few cycles during lunch, please do bring the error to the attention of the Spring for Apache Hadoop team by raising an issue. Thank you.

Part I. Introduction

Spring for Apache Hadoop provides integration with the Spring Framework to create and run Hadoop MapReduce, Hive, and Pig jobs as well as work with HDFS and HBase. If you have simple needs to work with Hadoop, including basic scheduling, you can add the Spring for Apache Hadoop namespace to your Spring based project and get going quickly using Hadoop. As the complexity of your Hadoop application increases, you may want to use Spring Batch and Spring Integration to regain on the complexity of developing a large Hadoop application.

This document is the reference guide for Spring for Apache Hadoop project (SHDP). It explains the relationship between the Spring framework and Hadoop as well as related projects such as Spring Batch and Spring Integration. The first part describes the integration with the Spring framework to define the base concepts and semantics of the integration and how they can be used effectively. The second part describes how you can build upon these base concepts and create workflow based solutions provided by the integration with Spring Batch.

1. Requirements

Spring for Apache Hadoop 2.0 requires JDK level 6.0 (just like Hadoop) and above, [Spring Framework](#) 4.0 and above and is by default built against [Apache Hadoop](#) 2.2.0.

Spring for Apache Hadoop 2.0 supports the following versions and distributions:

- [Apache Hadoop](#) 1.2.1
- [Apache Hadoop](#) 2.2.0 *
- [Apache Hadoop](#) 2.3.0 *
- [Pivotal](#) HD 1.1
- [Pivotal](#) HD 2.0 *
- [Cloudera](#) CDH4 (CDH4.6.0)
- [Cloudera](#) CDH5 (2.3.0-cdh5.0.0) *
- [Hortonworks](#) Data Platform 1.3
- [Hortonworks](#) Data Platform 2.0 *
- [Hortonworks](#) Data Platform 2.1 *

* The distributions noted with and asterisk will include spring-yarn support in the build.

Any distribution compatible with Apache Hadoop 1.x or 2.2.x should be supported.

Note

Spring for Apache Hadoop has been certified to work on Pivotal HD 1.0 and 1.1, Hortonworks HDP 1.3 and Cloudera CDH 4.4 distributions. Further certifications will be done once Spring for Apache 2.0 reaches GA.

Spring for Apache Hadoop 2.0 is tested daily against a number of Hadoop distributions. See the [test plan page](#) for current status.

Instructions for setting up project builds using various supported distributions are provided on the Spring for Apache Hadoop wiki - <https://github.com/spring-projects/spring-hadoop/wiki>

Regarding Hadoop-related projects, SDHP supports [HBase](#) 0.94.11, [Hive](#) 0.10.0 and [Pig](#) 0.10.1 and above. As a rule of thumb, when using Hadoop-related projects, such as Hive or Pig, use the required Hadoop version as a basis for discovering the supported versions.

To take full advantage of Spring for Apache Hadoop you need a running Hadoop cluster. If you don't already have one in your environment, a good first step is to create a single-node cluster. To install the most recent stable version of Hadoop, the "[Getting Started](#)" page from the official Apache documentation is a good general guide. There should be a link for "Single Node Setup".

It is also convenient to download a Virtual Machine where Hadoop is setup and ready to go. Cloudera, Hortonworks and Pivotal all provide virtual machines and provide VM downloads on their product pages.

Additionally, the [appendix](#) provides information on how to use Spring for Apache Hadoop and setup Hadoop with cloud providers, such as Amazon Web Services.

2. Additional Resources

While this documentation acts as a reference for Spring for Hadoop project, there are number of resources that, while optional, complement this document by providing additional background and code samples for the reader to try and experiment with:

- **Spring for Apache Hadoop [samples](#)**. Official repository full of SHDP samples demonstrating the various project features.
- **Spring Data [Book](#)**. Guide to Spring Data projects, written by the committers behind them. Covers Spring Data Hadoop stand-alone but in tandem with its *siblings* projects. All earnings from book sales are donated to [Creative Commons](#) organization.
- **Spring Data [Book examples](#)**. Complete running samples for the Spring Data book. Note that some of them are available inside Spring for Apache Hadoop samples as well.

Part II. Spring and Hadoop

Document structure

This part of the reference documentation explains the core functionality that Spring for Apache Hadoop (SHDP) provides to any Spring based application.

Chapter 3, *Hadoop Configuration, MapReduce, and Distributed Cache* describes the Spring support for bootstrapping, initializing and working with core Hadoop.

Chapter 4, *Working with the Hadoop File System* describes the Spring support for interacting with the Hadoop file system.

Chapter 5, *Working with HBase* describes the Spring support for HBase.

Chapter 6, *Hive integration* describes the Hive integration in SHDP.

Chapter 7, *Pig support* describes the Pig support in Spring for Apache Hadoop.

Chapter 9, *Security Support* describes how to configure and interact with Hadoop in a secure environment.

3. Hadoop Configuration, MapReduce, and Distributed Cache

One of the common tasks when using Hadoop is interacting with its *runtime* - whether it is a local setup or a remote cluster, one needs to properly configure and bootstrap Hadoop in order to submit the required jobs. This chapter will focus on how Spring for Apache Hadoop (SHDP) leverages Spring's lightweight IoC container to simplify the interaction with Hadoop and make deployment, testing and provisioning easier and more manageable.

3.1 Using the Spring for Apache Hadoop Namespace

To simplify configuration, SHDP provides a dedicated namespace for most of its components. However, one can opt to configure the beans directly through the usual `<bean>` definition. For more information about XML Schema-based configuration in Spring, see [this](#) appendix in the Spring Framework reference documentation.

To use the SHDP namespace, one just needs to import it inside the configuration:

```
<?xml version="1.0" encoding="UTF-8"?>
<beans xmlns="http://www.springframework.org/schema/beans"
  xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
  xmlns:hdp="Ⓚhttp://www.springframework.org/schema/hadoop"
  xsi:schemaLocation="
    http://www.springframework.org/schema/beans http://www.springframework.org/schema/
    beans/spring-beans.xsd
    http://www.springframework.org/schema/hadoop http://www.springframework.org/schema/
    hadoop/spring-hadoop.xsdⓁ" >

  <bean id ... >

  Ⓛ<hdp:configuration ...>
</beans>
```

- Ⓚ Spring for Apache Hadoop namespace prefix. Any name can do but throughout the reference documentation, `hdp` will be used.
- Ⓛ The namespace URI.
- Ⓛ The namespace URI location. Note that even though the location points to an external address (which exists and is valid), Spring will resolve the schema locally as it is included in the Spring for Apache Hadoop library.
- Ⓛ Declaration example for the Hadoop namespace. Notice the prefix usage.

Once imported, the namespace elements can be declared simply by using the aforementioned prefix. Note that it is possible to change the default namespace, for example from `<beans>` to `<hdp>`. This is useful for configuration composed mainly of Hadoop components as it avoids declaring the prefix. To achieve this, simply swap the namespace prefix declarations above:

```

<?xml version="1.0" encoding="UTF-8"?>
<beans:beans xmlns="http://www.springframework.org/schema/hadoop"❶
  xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
  ❷xmlns:beans="http://www.springframework.org/schema/beans"
  xsi:schemaLocation="
    http://www.springframework.org/schema/beans http://www.springframework.org/schema/
beans/spring-beans.xsd
    http://www.springframework.org/schema/hadoop http://www.springframework.org/schema/
hadoop/spring-hadoop.xsd">

  ❸<beans:bean id ... >

  ❹<configuration ...>

</beans:beans>

```

- ❶ The default namespace declaration for this XML file points to the Spring for Apache Hadoop namespace.
- ❷ The beans namespace prefix declaration.
- ❸ Bean declaration using the `<beans>` namespace. Notice the prefix.
- ❹ Bean declaration using the `<hdp>` namespace. Notice the *lack* of prefix (as `hdp` is the default namespace).

For the remainder of this doc, to improve readability, the XML examples may simply refer to the `<hdp>` namespace without the namespace declaration, where possible.

3.2 Configuring Hadoop

In order to use Hadoop, one needs to first configure it namely by creating a `Configuration` object. The configuration holds information about the job tracker, the input, output format and the various other parameters of the map reduce job.

In its simplest form, the configuration definition is a one liner:

```
<hdp:configuration />
```

The declaration above defines a `Configuration` bean (to be precise a factory bean of type `ConfigurationFactoryBean`) named, by default, `hadoopConfiguration`. The default name is used, by conventions, by the other elements that require a configuration - this leads to simple and very concise configurations as the main components can automatically wire themselves up without requiring any specific configuration.

For scenarios where the defaults need to be tweaked, one can pass in additional configuration files:

```
<hdp:configuration resources="classpath:/custom-site.xml, classpath:/hq-site.xml">
```

In this example, two additional Hadoop configuration resources are added to the configuration.

Note

Note that the configuration makes use of Spring's [Resource](#) abstraction to locate the file. This allows various search patterns to be used, depending on the running environment or the prefix specified (if any) by the value - in this example the classpath is used.

In addition to referencing configuration resources, one can tweak Hadoop settings directly through Java Properties. This can be quite handy when just a few options need to be changed:

```
<?xml version="1.0" encoding="UTF-8"?>
<beans xmlns="http://www.springframework.org/schema/beans"
  xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
  xmlns:hdp="http://www.springframework.org/schema/hadoop"
  xsi:schemaLocation="http://www.springframework.org/schema/beans http://
www.springframework.org/schema/beans/spring-beans.xsd
  http://www.springframework.org/schema/hadoop http://www.springframework.org/
schema/hadoop/spring-hadoop.xsd">

  <hdp:configuration>
    fs.default.name=hdfs://localhost:9000
    hadoop.tmp.dir=/tmp/hadoop
    electric=sea
  </hdp:configuration>
</beans>
```

One can further customize the settings by avoiding the so called *hard-coded* values by externalizing them so they can be replaced at runtime, based on the existing environment without touching the configuration:

Note

Usual configuration parameters for `fs.default.name`, `fs.defaultFS`, `mapred.job.tracker` and `yarn.resourcemanager.address` can be configured using tag attributes *file-system-uri*, *job-tracker-uri* and *rm-manager-uri* respectively.

```
<?xml version="1.0" encoding="UTF-8"?>
<beans xmlns="http://www.springframework.org/schema/beans"
  xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
  xmlns:hdp="http://www.springframework.org/schema/hadoop"
  xmlns:context="http://www.springframework.org/schema/context"
  xsi:schemaLocation="http://www.springframework.org/schema/beans http://
www.springframework.org/schema/beans/spring-beans.xsd
  http://www.springframework.org/schema/context http://www.springframework.org/
schema/context/spring-context.xsd
  http://www.springframework.org/schema/hadoop http://www.springframework.org/
schema/hadoop/spring-hadoop.xsd">

  <hdp:configuration>
    fs.default.name=${hd.fs}
    hadoop.tmp.dir=file://${java.io.tmpdir}
    hangar=${number:18}
  </hdp:configuration>

  <context:property-placeholder location="classpath:hadoop.properties" />
</beans>
```

Through Spring's property placeholder [support](#), [SpEL](#) and the [environment abstraction](#) (available in Spring 3.1). one can externalize environment specific properties from the main code base easing the deployment across multiple machines. In the example above, the default file system is replaced based on the properties available in `hadoop.properties` while the temp dir is determined dynamically through SpEL. Both approaches offer a lot of flexibility in adapting to the running environment - in fact we use this approach extensively in the Spring for Apache Hadoop test suite to cope with the differences between the different development boxes and the CI server.

Additionally, external `Properties` files can be loaded, `Properties` beans (typically declared through Spring's `util` namespace). Along with the nested properties declaration, this allows customized configurations to be easily declared:

```
<?xml version="1.0" encoding="UTF-8"?>
<beans xmlns="http://www.springframework.org/schema/beans"
  xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
  xmlns:hdp="http://www.springframework.org/schema/hadoop"
  xmlns:context="http://www.springframework.org/schema/context"
  xmlns:util="http://www.springframework.org/schema/util"
  xsi:schemaLocation="http://www.springframework.org/schema/beans http://
www.springframework.org/schema/beans/spring-beans.xsd
  http://www.springframework.org/schema/context http://www.springframework.org/
schema/context/spring-context.xsd
  http://www.springframework.org/schema/util http://www.springframework.org/schema/
util/spring-util.xsd
  http://www.springframework.org/schema/hadoop http://www.springframework.org/
schema/hadoop/spring-hadoop.xsd">

  <!-- merge the local properties, the props bean and the two properties files -->

  <hdp:configuration properties-ref="props" properties-location="cfg-1.properties,
cfg-2.properties">
    star=chasing
    captain=eo
  </hdp:configuration>

  <util:properties id="props" location="props.properties"/>
</beans>
```

When merging several properties, ones defined locally win. In the example above the configuration properties are the primary source, followed by the `props` bean followed by the external properties file based on their defined order. While it's not typical for a configuration to refer to so many properties, the example showcases the various options available.

Note

For more properties utilities, including using the System as a source or fallback, or control over the merging order, consider using Spring's [PropertiesFactoryBean](#) (which is what Spring for Apache Hadoop and `util:properties` use underneath).

It is possible to create configurations based on existing ones - this allows one to create dedicated configurations, slightly different from the main ones, usable for certain jobs (such as streaming - more on that [below](#)). Simply use the `configuration-ref` attribute to refer to the *parent* configuration - all its properties will be inherited and overridden as specified by the child:

```
<!-- default name is 'hadoopConfiguration' -->
<hdp:configuration>
  fs.default.name=${hd.fs}
  hadoop.tmp.dir=file://${java.io.tmpdir}
</hdp:configuration>

<hdp:configuration id="custom" configuration-ref="hadoopConfiguration">
  fs.default.name=${custom.hd.fs}
</hdp:configuration>

...
```

Make sure though that you specify a different name since otherwise, because both definitions will have the same name, the Spring container will interpret this as being the same definition (and will usually consider the last one found).

Another option worth mentioning is `register-url-handler` which, as the name implies, automatically registers an URL handler in the running VM. This allows urls referencing `hdfs` resource (by using the `hdfs` prefix) to be properly resolved - if the handler is not registered, such an URL will throw an exception since the VM does not know what `hdfs` means.

Note

Since only one URL handler can be registered per VM, at most once, this option is turned off by default. Due to the reasons mentioned before, once enabled if it fails, it will log the error but will not throw an exception. If your `hdfs` URLs stop working, make sure to investigate this aspect.

Last but not least a reminder that one can mix and match all these options to her preference. In general, consider externalizing Hadoop configuration since it allows easier updates without interfering with the application configuration. When dealing with multiple, similar configurations use configuration *composition* as it tends to keep the definitions concise, in sync and easy to update.

Table 3.1. `hdp:configuration` attributes

Name	Values	Description
<code>configuration-ref</code>	Bean Reference	Reference to existing <i>Configuration</i> bean
<code>properties-ref</code>	Bean Reference	Reference to existing <i>Properties</i> bean
<code>properties-location</code>	Comma delimited list	List or Spring <i>Resource</i> paths
<code>resources</code>	Comma delimited list	List or Spring <i>Resource</i> paths
<code>file-system-uri</code>	String	The HDFS filesystem address. Equivalent to <code>fs.default.name</code> and <code>fs.defaultFS</code> properties.
<code>job-tracker-uri</code>	String	Job tracker address for HadoopV1. Equivalent to <code>mapred.job.tracker</code> property.
<code>rm-manager-uri</code>	String	The Yarn Resource manager address for HadoopV2. Equivalent to <code>yarn.resourcemanager.address</code> property.

3.3 Creating a Hadoop Job

Once the Hadoop configuration is taken care of, one needs to actually submit some work to it. SHDP makes it easy to configure and run Hadoop jobs whether they are vanilla map-reduce type or streaming. Let us start with an example:

```
<hdp:job id="mr-job"
  input-path="/input/" output-path="/ouput/"
  mapper="org.apache.hadoop.examples.WordCount.TokenizerMapper"
  reducer="org.apache.hadoop.examples.WordCount.IntSumReducer"/>
```

The declaration above creates a typical Hadoop `Job`: specifies its input and output, the mapper and the reducer classes. Notice that there is no reference to the Hadoop configuration above - that's because, if not specified, the default naming convention (`hadoopConfiguration`) will be used instead. Neither is there to the key or value types - these two are automatically determined through a best-effort attempt by analyzing the class information of the mapper and the reducer. Of course, these settings can be overridden: the former through the `configuration-ref` element, the latter through `key` and `value` attributes. There are plenty of options available not shown in the example (for simplicity) such as the `jar` (specified directly or by class), `sort` or `group comparator`, the `combiner`, the `partitioner`, the `codecs` to use or the `input/output format` just to name a few - they are supported, just take a look at the SHDP schema (Appendix C, *Spring for Apache Hadoop Schema*) or simply trigger auto-completion (usually `CTRL+SPACE`) in your IDE; if it supports XML namespaces and is properly configured it will display the available elements. Additionally one can extend the default Hadoop configuration object and add any special properties not available in the namespace or its backing bean (`JobFactoryBean`).

It is worth pointing out that per-job specific configurations are supported by specifying the custom properties directly or referring to them (more information on the pattern is available [here](#)):

```
<hdp:job id="mr-job"
  input-path="/input/" output-path="/ouput/"
  mapper="mapper class" reducer="reducer class"
  jar-by-class="class used for jar detection"
  properties-location="classpath:special-job.properties">
  electric=sea
</hdp:job>
```

`<hdp:job>` provides additional properties, such as the [generic options](#), however one that is worth mentioning is `jar` which allows a job (and its dependencies) to be loaded entirely from a specified jar. This is useful for isolating jobs and avoiding classpath and versioning collisions. Note that provisioning of the jar into the cluster still depends on the target environment - see the aforementioned [section](#) for more info (such as `libs`).

Creating a Hadoop Streaming Job

Hadoop [Streaming](#) job (or in short streaming), is a popular feature of Hadoop as it allows the creation of Map/Reduce jobs with any executable or script (the equivalent of using the previous counting words example is to use `cat` and `wc` commands). While it is rather easy to start up streaming from the command line, doing so programatically, such as from a Java environment, can be challenging due to the various number of parameters (and their ordering) that need to be parsed. SHDP simplifies such a task - it's as easy and straightforward as declaring a `job` from the previous section; in fact most of the attributes will be the same:

```
<hdp:streaming id="streaming"
  input-path="/input/" output-path="/ouput/"
  mapper="${path.cat}" reducer="${path.wc}"/>
```

Existing users might be wondering how they can pass the command line arguments (such as `-D` or `-cmdenv`). While the former customize the Hadoop configuration (which has been covered in the previous [section](#)), the latter are supported through the `cmd-env` element:


```

<hdp:streaming id="streaming-env"
  input-path="/input/" output-path="/ouput/"
  mapper="${path.cat}" reducer="${path.wc}">
  <hdp:cmd-env>
    EXAMPLE_DIR=/home/example/dictionaries/
    ...
  </hdp:cmd-env>
</hdp:streaming>

```

Just like `job`, `streaming` supports the [generic options](#); follow the link for more information.

3.4 Running a Hadoop Job

The jobs, after being created and configured, need to be submitted for execution to a Hadoop cluster. For non-trivial cases, a coordinating, workflow solution such as Spring Batch is recommended. However for basic job submission SHDP provides the `job-runner` element (backed by `JobRunner` class) which submits several jobs sequentially (and waits by default for their completion):

```

<hdp:job-runner id="myjob-runner" pre-action="cleanup-script" post-action="export-
results" job-ref="myjob" run-at-startup="true"/>

<hdp:job id="myjob" input-path="/input/" output-path="/output/"
  mapper="org.apache.hadoop.examples.WordCount.TokenizerMapper"
  reducer="org.apache.hadoop.examples.WordCount.IntSumReducer" />

```

Multiple jobs can be specified and even nested if they are not used outside the runner:

```

<hdp:job-runner id="myjobs-runner" pre-action="cleanup-script" job-ref="myjob1,
myjob2" run-at-startup="true"/>

<hdp:job id="myjob1" ... />
<hdp:streaming id="myjob2" ... />

```

One or multiple Map-Reduce jobs can be specified through the `job` attribute in the order of the execution. The runner will trigger the execution during the application start-up (notice the `run-at-startup` flag which is by default `false`). Do note that the runner will not run unless triggered manually or if `run-at-startup` is set to `true`. Additionally the runner (as in fact do all [runners](#) in SHDP) allows one or multiple `pre` and `post` actions to be specified to be executed before and after each run. Typically other runners (such as other jobs or scripts) can be specified but any `JDK Callable` can be passed in. For more information on runners, see the [dedicated](#) chapter.

Note

As the Hadoop job submission and execution (when `wait-for-completion` is `true`) is blocking, `JobRunner` uses a `JDK Executor` to start (or stop) a job. The default implementation, `SyncTaskExecutor` uses the calling thread to execute the job, mimicking the hadoop command line behaviour. However, as the hadoop jobs are time-consuming, in some cases this can lead to “application freeze”, preventing normal operations or even application shutdown from occurring properly. Before going into production, it is recommended to double-check whether this strategy is suitable or whether a throttled or pooled implementation is better. One can customize the behaviour through the `executor-ref` parameter.

The job runner also allows running jobs to be cancelled (or killed) at shutdown. This applies only to jobs that the runner waits for (`wait-for-completion` is `true`) using a different executor than the default - that is, using a different thread than the calling one (since otherwise the calling thread has to wait for

the job to finish first before executing the next task). To customize this behaviour, one should set the `kill-job-at-shutdown` attribute to `false` and/or change the `executor-ref` implementation.

Using the Hadoop Job tasklet

For Spring Batch environments, SHDP provides a dedicated tasklet to execute Hadoop jobs as a step in a Spring Batch workflow. An example declaration is shown below:

```
<hdp:job-tasklet id="hadoop-tasklet" job-ref="mr-job" wait-for-completion="true" />
```

The tasklet above references a Hadoop job definition named "mr-job". By default, `wait-for-completion` is `true` so that the tasklet will wait for the job to complete when it executes. Setting `wait-for-completion` to `false` will submit the job to the Hadoop cluster but not wait for it to complete.

3.5 Running a Hadoop Tool

It is common for Hadoop utilities and libraries to be started from the command-line (ex: `hadoop jar some.jar`). SHDP offers generic support for such cases provided that the packages in question are built on top of Hadoop standard infrastructure, namely `Tool` and `ToolRunner` classes. As opposed to the command-line usage, `Tool` instances benefit from Spring's IoC features; they can be parameterized, created and destroyed on demand and have their properties (such as the Hadoop configuration) injected.

Consider the typical `jar` example - invoking a class with some (two in this case) arguments (notice that the Hadoop configuration properties are passed as well):

```
bin/hadoop jar -conf hadoop-site.xml -jt darwin:50020 -Dproperty=value
someJar.jar org.foo.SomeTool data/in.txt data/out.txt
```

Since SHDP has first-class support for [configuring](#) Hadoop, the so called `generic` options aren't needed any more, even more so since typically there is only one Hadoop configuration per application. Through `tool-runner` element (and its backing `ToolRunner` class) one typically just needs to specify the `Tool` implementation and its arguments:

```
<hdp:tool-runner id="someTool" tool-class="org.foo.SomeTool" run-at-startup="true">
  <hdp:arg value="data/in.txt"/>
  <hdp:arg value="data/out.txt"/>

  property=value
</hdp:tool-runner>
```

Additionally the runner (just like the job runner) allows one or multiple `pre` and `post` actions to be specified to be executed before and after each run. Typically other runners (such as other jobs or scripts) can be specified but any `JDK Callable` can be passed in. Do note that the runner will not run unless triggered manually or if `run-at-startup` is set to `true`. For more information on runners, see the [dedicated](#) chapter.

The previous example assumes the `Tool` dependencies (such as its class) are available in the classpath. If that is not the case, `tool-runner` allows a `jar` to be specified:

```
<hdp:tool-runner ... jar="myTool.jar">
  ...
</hdp:tool-runner>
```

The `jar` is used to instantiate and start the tool - in fact all its dependencies are loaded from the `jar` meaning they no longer need to be part of the classpath. This mechanism provides proper isolation

between tools as each of them might depend on certain libraries with different versions; rather than adding them all into the same app (which might be impossible due to versioning conflicts), one can simply point to the different jars and be on her way. Note that when using a jar, if the main class (as specified by the [Main-Class](#) entry) is the target `Tool`, one can skip specifying the tool as it will be picked up automatically.

Like the rest of the SHDP elements, `tool-runner` allows the passed Hadoop configuration (by default `hadoopConfiguration` but specified in the example for clarity) to be [customized](#) accordingly; the snippet only highlights the property initialization for simplicity but more options are available. Since usually the `Tool` implementation has a default argument, one can use the `tool-class` attribute. However it is possible to refer to another `Tool` instance or declare a nested one:

```
<hdp:tool-runner id="someTool" run-at-startup="true">
  <hdp:tool>
    <bean class="org.foo.AnotherTool" p:input="data/in.txt" p:output="data/out.txt"/>
  </hdp:tool>
</hdp:tool-runner>
```

This is quite convenient if the `Tool` class provides setters or richer constructors. Note that by default the `tool-runner` does not execute the `Tool` until its definition is actually called - this behavior can be changed through the `run-at-startup` attribute above.

Replacing Hadoop shell invocations with `tool-runner`

`tool-runner` is a nice way for migrating series of shell invocations or scripts into fully wired, managed Java objects. Consider the following shell script:

```
hadoop jar job1.jar -files fullpath:props.properties -Dconfig=config.properties ...
hadoop jar job2.jar arg1 arg2...
...
hadoop jar job10.jar ...
```

Each job is fully contained in the specified jar, including all the dependencies (which might conflict with the ones from other jobs). Additionally each invocation might provide some generic options or arguments but for the most part all will share the same configuration (as they will execute against the same cluster).

The script can be fully ported to SHDP, through the `tool-runner` element:

```
<hdp:tool-runner id="job1" tool-
class="job1.Tool" jar="job1.jar" files="fullpath:props.properties" properties-
location="config.properties"/>
<hdp:tool-runner id="job2" jar="job2.jar">
  <hdp:arg value="arg1"/>
  <hdp:arg value="arg2"/>
</hdp:tool-runner>
<hdp:tool-runner id="job3" jar="job3.jar"/>
...
```

All the features have been explained in the previous sections but let us review what happens here. As mentioned before, each tool gets autowired with the `hadoopConfiguration`; `job1` goes beyond this and uses its own properties instead. For the first jar, the `Tool` class is specified, however the rest assume the jar `Main-Classes` implement the `Tool` interface; the namespace will discover them automatically and use them accordingly. When needed (such as with `job1`), additional files or libs are provisioned in the cluster. Same thing with the job arguments.

However more things that go beyond scripting, can be applied to this configuration - each job can have multiple properties loaded or declared inlined - not just from the local file system, but also from the classpath or any url for that matter. In fact, the whole configuration can be externalized and parameterized (through Spring's [property placeholder](#) and/or [Environment abstraction](#)). Moreover, each job can be ran by itself (through the `JobRunner`) or as part of a workflow - either through Spring's `depends-on` or the much more powerful Spring Batch and `tool-tasklet`.

Using the Hadoop Tool tasklet

For Spring Batch environments, SHDP provides a dedicated tasklet to execute Hadoop tasks as a step in a Spring Batch workflow. The tasklet element supports the same configuration options as [tool-runner](#) except for `run-at-startup` (which does not apply for a workflow):

```
<hdp:tool-tasklet id="tool-tasklet" tool-ref="some-tool" />
```

3.6 Running a Hadoop Jar

SHDP also provides support for executing vanilla Hadoop jars. Thus the famous [WordCount](#) example:

```
bin/hadoop jar hadoop-examples.jar wordcount /wordcount/input /wordcount/output
```

becomes

```
<hdp:jar-runner id="wordcount" jar="hadoop-examples.jar" run-at-startup="true">
  <hdp:arg value="wordcount" />
  <hdp:arg value="/wordcount/input" />
  <hdp:arg value="/wordcount/output" />
</hdp:jar-runner>
```



Note

Just like the `hadoop jar` command, by default the jar support reads the jar's `Main-Class` if none is specified. This can be customized through the `main-class` attribute.

Additionally the runner (just like the job runner) allows one or multiple `pre` and `post` actions to be specified to be executed before and after each run. Typically other runners (such as other jobs or scripts) can be specified but any `JDK Callable` can be passed in. Do note that the runner will not run unless triggered manually or if `run-at-startup` is set to `true`. For more information on runners, see the [dedicated](#) chapter.

The `jar` support provides a nice and easy migration path from jar invocations from the command-line to SHDP (note that Hadoop [generic options](#) are also supported). Especially since SHDP enables Hadoop `Configuration` objects, created during the jar execution, to automatically inherit the context Hadoop configuration. In fact, just like other SHDP elements, the `jar` element allows [configurations properties](#) to be declared locally, just for the jar run. So for example, if one would use the following declaration:

```
<hdp:jar-runner id="wordcount" jar="hadoop-examples.jar" run-at-startup="true">
  <hdp:arg value="wordcount" />
  ...
  speed=fast
</hdp:jar-runner>
```

inside the jar code, one could do the following:

```
assert "fast".equals(new Configuration().get("speed"));
```

This enabled basic Hadoop jars to use, without changes, the enclosing application Hadoop configuration.

And while we think it is a useful feature (that is why we added it in the first place), we strongly recommend using the tool support instead or migrate to it; there are several reasons for this mainly because there are *no contracts* to use, leading to very poor embeddability caused by:

- No standard `Configuration` injection

While SHDP does a best effort to pass the Hadoop configuration to the jar, there is no guarantee the jar itself does not use a special initialization mechanism, ignoring the passed properties. After all, a vanilla `Configuration` is not very useful so applications tend to provide custom code to address this.

- `System.exit()` calls

Most jar examples out there (including `WordCount`) assume they are started from the command line and among other things, call `System.exit`, to shut down the JVM, whether the code is succesful or not. SHDP prevents this from happening (otherwise the entire application context would shutdown abruptly) but it is a clear sign of poor code collaboration.

SHDP tries to use sensible defaults to provide the best integration experience possible but at the end of the day, without any contract in place, there are no guarantees. Hence using the `Tool` interface is a much better alternative.

Using the Hadoop Jar tasklet

Like for the rest of its tasks, for Spring Batch environments, SHDP provides a dedicated tasklet to execute Hadoop jars as a step in a Spring Batch workflow. The tasklet element supports the same configuration options as [jar-runner](#) except for `run-at-startup` (which does not apply for a workflow):

```
<hdp:jar-tasklet id="jar-tasklet" jar="some-jar.jar" />
```

3.7 Configuring the Hadoop DistributedCache

[DistributedCache](#) is a Hadoop facility for distributing application-specific, large, read-only files (text, archives, jars and so on) efficiently. Applications specify the files to be cached via urls (`hdfs://`) using `DistributedCache` and the framework will copy the necessary files to the slave nodes before any tasks for the job are executed on that node. Its efficiency stems from the fact that the files are only copied once per job and the ability to cache archives which are un-archived on the slaves. Note that `DistributedCache` assumes that the files to be cached (and specified via `hdfs://` urls) are already present on the Hadoop `FileSystem`.

SHDP provides first-class configuration for the distributed cache through its `cache` element (backed by `DistributedCacheFactoryBean` class), allowing files and archives to be easily distributed across nodes:

```
<hdp:cache create-symlink="true">
  <hdp:classpath value="/cp/some-library.jar#library.jar" />
  <hdp:cache value="/cache/some-archive.tgz#main-archive" />
  <hdp:cache value="/cache/some-resource.res" />
  <hdp:local value="some-file.txt" />
</hdp:cache>
```

The definition above registers several resources with the cache (adding them to the job cache or classpath) and creates symlinks for them. As described in the `DistributedCache` [documentation](#), the declaration format is `(absolute-path#link-name)`. The link name is determined by the URI fragment (the text following the `#` such as `#library.jar` or `#main-archive` above) - if no name is specified, the cache bean will infer one based on the resource file name. Note that one does not have to specify the `hdfs://node:port` prefix as these are automatically determined based on the configuration wired into the bean; this prevents environment settings from being hard-coded into the configuration which becomes portable. Additionally based on the resource extension, the definition differentiates between archives (`.tgz`, `.tar.gz`, `.zip` and `.tar`) which will be uncompressed, and regular files that are copied as-is. As with the rest of the namespace declarations, the definition above relies on defaults - since it requires a `Hadoop Configuration` and `FileSystem` objects and none are specified (through `configuration-ref` and `file-system-ref`) it falls back to the default naming and is wired with the bean named `hadoopConfiguration`, creating the `FileSystem` automatically.



Warning

Clients setting up a `classpath` in the `DistributedCache`, running on Windows platforms should set the `System.path.separator` property to `:`. Otherwise the classpath will be set incorrectly and will be ignored; see [HADOOP-9123](#) bug report for more information.

There are multiple ways to change the `path.separator` `System` property - a quick one being a simple `script` in Javascript (that uses the Rhino package bundled with the JDK) that runs at start-up:

```
<hdp:script language="javascript" run-at-startup="true">
  // set System 'path.separator' to ':' - see HADOOP-9123
  java.lang.System.setProperty("path.separator", ":")
</hdp:script>
```

3.8 Map Reduce Generic Options

The `job`, `streaming` and `tool` all support a subset of [generic options](#), specifically `archives`, `files` and `libs`. `libs` is probably the most useful as it enriches a job classpath (typically with some jars) - however the other two allow resources or archives to be copied throughout the cluster for the job to consume. Whenever faced with provisioning issues, revisit these options as they can help up significantly. Note that the `fs`, `jt` or `conf` options are not supported - these are designed for command-line usage, for bootstrapping the application. This is no longer needed, as the SHDP offers first-class support for defining and customizing Hadoop [configurations](#).

4. Working with the Hadoop File System

A common task in Hadoop is interacting with its file system, whether for provisioning, adding new files to be processed, parsing results, or performing cleanup. Hadoop offers several ways to achieve that: one can use its Java API (namely `FileSystem`) or use the `hadoop` command line, in particular the file system `shell`. However there is no middle ground, one either has to use the (somewhat verbose, full of checked exceptions) API or fall back to the command line, outside the application. SHDP addresses this issue by bridging the two worlds, exposing both the `FileSystem` and the `fs` shell through an intuitive, easy-to-use Java API. Add your favorite [JVM scripting](#) language right inside your Spring for Apache Hadoop application and you have a powerful combination.

4.1 Configuring the file-system

The Hadoop file-system, HDFS, can be accessed in various ways - this section will cover the most popular protocols for interacting with HDFS and their pros and cons. SHDP does not enforce any specific protocol to be used - in fact, as described in this section any `FileSystem` implementation can be used, allowing even other implementations than HDFS to be used.

The table below describes the common HDFS APIs in use:

Table 4.1. HDFS APIs

File System	Comm. Method	Scheme / Prefix	Read / Write	Cross Version
HDFS	RPC	<code>hdfs://</code>	Read / Write	Same HDFS version only
HFTP	HTTP	<code>hftp://</code>	Read only	Version independent
WebHDFS	HTTP (REST)	<code>webhdfs://</code>	Read / Write	Version independent

What about FTP, Kosmos, S3 and the other file systems?

This chapter focuses on the core file-system protocols supported by Hadoop. S3 (see the [Appendix](#)), FTP and the rest of the other `FileSystem` implementations are supported as well - Spring for Apache Hadoop has no dependency on the underlying system rather just on the public Hadoop API.

`hdfs://` protocol should be familiar to most readers - most docs (and in fact the previous chapter as well) mention it. It works out of the box and it's fairly efficient. However because it is RPC based, it requires both the client and the Hadoop cluster to share the same version. Upgrading one without the other causes serialization errors meaning the client cannot interact with the cluster. As an alternative one can use `hftp://` which is HTTP-based or its more secure brother `hsftp://` (based on SSL) which gives you a version independent protocol meaning you can use it to interact with clusters with an unknown or different version than that of the client. `hftp` is read only (write operations will fail right away) and it is typically used with `disctp` for reading data. `webhdfs://` is one of the additions in Hadoop 1.0 and is a mixture between `hdfs` and `hftp` protocol - it provides a version-independent, read-write, REST-based protocol which means that you can read and write to/from Hadoop clusters

no matter their version. Furthermore, since `webhdfs://` is backed by a REST API, clients in other languages can use it with minimal effort.

Note

Not all file systems work out of the box. For example WebHDFS needs to be enabled first in the cluster (through `dfs.webhdfs.enabled` property, see this [document](#) for more information) while the secure `hftp`, `hsftp` requires the SSL configuration (such as certificates) to be specified. More about this (and how to use `hftp/hsftp` for proxying) in this [page](#).

Once the scheme has been decided upon, one can specify it through the standard Hadoop [configuration](#), either through the Hadoop configuration files or its properties:

```
<hdp:configuration>
  fs.default.name=webhdfs://localhost
  ...
</hdp:configuration>
```

This instructs Hadoop (and automatically SHDP) what the default, implied file-system is. In SHDP, one can create additional file-systems (potentially to connect to other clusters) and specify a different scheme:

```
<!-- manually creates the default SHDP file-system named 'hadoopFs' -->
<hdp:file-system uri="webhdfs://localhost"/>

<!-- creates a different FileSystem instance -->
<hdp:file-system id="old-cluster" uri="hftp://old-cluster"/>
```

As with the rest of the components, the file systems can be injected where needed - such as file shell or inside scripts (see the next section).

4.2 Using HDFS Resource Loader

In Spring the `ResourceLoader` interface is meant to be implemented by objects that can return (i.e. load) Resource instances.

```
public interface ResourceLoader {
    Resource getResource(String location);
}
```

All application contexts implement the `ResourceLoader` interface, and therefore all application contexts may be used to obtain Resource instances.

When you call `getResource()` on a specific application context, and the location path specified doesn't have a specific prefix, you will get back a `Resource` type that is appropriate to that particular application context. For example, assume the following snippet of code was executed against a `ClassPathXmlApplicationContext` instance:

```
Resource template = ctx.getResource("some/resource/path/myTemplate.txt");
```

What would be returned would be a `ClassPathResource`; if the same method was executed against a `FileSystemXmlApplicationContext` instance, you'd get back a `FileSystemResource`. For a `WebApplicationContext`, you'd get back a `ServletContextResource`, and so on.

As such, you can load resources in a fashion appropriate to the particular application context.

On the other hand, you may also force `ClassPathResource` to be used, regardless of the application context type, by specifying the special `classpath:` prefix:

```
Resource template = ctx.getResource("classpath:some/resource/path/myTemplate.txt");
```

Note

More information about the generic usage of resource loading, check the *Spring Framework Documentation*.

Spring Hadoop is adding its own functionality into generic concept of resource loading. Resource abstraction in Spring has always been a way to ease resource access in terms of not having a need to know where there resource is and how it's accessed. This abstraction also goes beyond a single resource by allowing to use patterns to access multiple resources.

Lets first see how `HdfsResourceLoader` is used manually.

```
<hdp:file-system />
<hdp:resource-loader id="loader" file-system-ref="hadoopFs" />
<hdp:resource-loader id="loaderWithUser" user="myuser" uri="hdfs://localhost:8020" />
```

In above configuration we created two beans, one with reference to existing Hadoop `FileSystem` bean and one with impersonated user.

```
// get path '/tmp/file.txt'
Resource resource = loader.getResource("/tmp/file.txt");
// get path '/tmp/file.txt' with user impersonation
Resource resource = loaderWithUser.getResource("/tmp/file.txt");

// get path '/user/<current user>/file.txt'
Resource resource = loader.getResource("file.txt");
// get path '/user/myuser/file.txt'
Resource resource = loaderWithUser.getResource("file.txt");

// get all paths under '/tmp/'
Resource[] resources = loader.getResources("/tmp/**");
// get all paths under '/tmp/' recursively
Resource[] resources = loader.getResources("/tmp/**/*");
// get all paths under '/tmp/' using more complex ant path matching
Resource[] resources = loader.getResources("/tmp/?file?.txt");
```

What would be returned in above examples would be instances of `HdfsResources`.

If there is a need for *Spring Application Context* to be aware of `HdfsResourceLoader` it needs to be registered using `hdp:resource-loader-registrar` namespace tag.

```
<hdp:file-system />
<hdp:resource-loader file-system-ref="hadoopFs" handle-noprefix="false" />
<hdp:resource-loader-registrar />
```

Note

On default the `HdfsResourceLoader` will handle all resource paths without prefix. Attribute `handle-noprefix` can be used to control this behaviour. If this attribute is set to `false`, non-prefixed resource uris will be handled by *Spring Application Context*.

```
// get 'default.txt' from current user's home directory
Resource[] resources = context.getResources("hdfs:default.txt");
// get all files from hdfs root
Resource[] resources = context.getResources("hdfs/*");
// let context handle classpath prefix
Resource[] resources = context.getResources("classpath:cfg*properties");
```

What would be returned in above examples would be instances of `HdfsResources` and `ClassPathResource` for the last one. If requesting resource paths without existing prefix, this example would fall back into *Spring Application Context*. It may be advisable to let `HdfsResourceLoader` to handle paths without prefix if your application doesn't rely on loading resources from underlying context without prefixes.

Table 4.2. `hdp:resource-loader` attributes

Name	Values	Description
<code>file-system-ref</code>	Bean Reference	Reference to existing <i>Hadoop FileSystem</i> bean
<code>use-codecs</code>	Boolean(defaults to true)	Indicates whether to use (or not) the codecs found inside the Hadoop configuration when accessing the resource input stream.
<code>user</code>	String	The security user (ugi) to use for impersonation at runtime.
<code>uri</code>	String	The underlying HDFS system URI.
<code>handle-noprefix</code>	Boolean(defaults to true)	Indicates if loader should handle resource paths without prefix.

Table 4.3. `hdp:resource-loader-registrar` attributes

Name	Values	Description
<code>loader-ref</code>	Bean Reference	Reference to existing <i>Hdfs resource loader</i> bean. Default value is 'hadoopResourceLoader'.

4.3 Scripting the Hadoop API

Supported scripting languages

SHDP scripting supports any [JSR-223](#) (also known as `javax.scripting`) compliant scripting engine. Simply add the engine jar to the classpath and the application should be able to find it. Most languages (such as Groovy or JRuby) provide JSR-223 support out of the box; for those that do not see the [scripting](#) project that provides various adapters.

Since Hadoop is written in Java, accessing its APIs in a *native* way provides maximum control and flexibility over the interaction with Hadoop. This holds true for working with its file systems; in fact all the other tools that one might use are built upon these. The main entry point is the `org.apache.hadoop.fs.FileSystem` abstract class which provides the foundation of most (if not all) of the actual file system implementations out there. Whether one is using a local, remote or distributed store through the `FileSystem` API she can query and manipulate the available resources or create new ones. To do so however, one needs to write Java code, compile the classes and configure them which is somewhat cumbersome especially when performing simple, straightforward operations (like copy a file or delete a directory).

JVM scripting languages (such as [Groovy](#), [JRuby](#), [Jython](#) or [Rhino](#) to name just a few) provide a nice solution to the Java language; they run on the JVM, can interact with the Java code with no or few changes or restrictions and have a nicer, simpler, less *ceremonial* syntax; that is, there is no need to define a class or a method - simply write the code that you want to execute and you are done. SHDP combines the two, taking care of the configuration and the infrastructure so one can interact with the Hadoop environment from her language of choice.

Let us take a look at a JavaScript example using Rhino (which is part of JDK 6 or higher, meaning one does not need any extra libraries):

```
<beans xmlns="http://www.springframework.org/schema/beans" ...>
  <hdp:configuration .../>

  <hdp:script id="inlined-js" language="javascript" run-at-startup="true">
    try {load("nashorn:mozilla_compat.js");} catch (e) {} // for Java 8
    importPackage(java.util);

    name = UUID.randomUUID().toString()
    scriptName = "src/test/resources/test.properties"
    // fs - FileSystem instance based on 'hadoopConfiguration' bean
    // call FileSystem#copyFromLocal(Path, Path)
    fs.copyFromLocalFile(scriptName, name)
    // return the file length
    fs.getLength(name)
  </hdp:script>
</beans>
```

The `script` element, part of the SHDP namespace, builds on top of the scripting support in Spring permitting script declarations to be evaluated and declared as normal bean definitions. Furthermore it automatically exposes Hadoop-specific objects, based on the existing configuration, to the script such as the `FileSystem` (more on that in the next section). As one can see, the script is fairly obvious: it generates a random name (using the `UUID` class from `java.util` package) and then copies a local file into HDFS under the random name. The last line returns the length of the copied file which becomes the value of the declaring bean (in this case `inlined-js`) - note that this might vary based on the scripting engine used.



Note

The attentive reader might have noticed that the arguments passed to the `FileSystem` object are not of type `Path` but rather `String`. To avoid the creation of `Path` object, SHDP uses a wrapper class (`SimplerFileSystem`) which automatically does the conversion so you don't have to. For more information see the [implicit variables](#) section.

Note that for inlined scripts, one can use Spring's property placeholder configurer to automatically expand variables at runtime. Using one of the examples seen before:

```
<beans ... >
  <context:property-placeholder location="classpath:hadoop.properties" />

  <hdp:script language="javascript" run-at-startup="true">
    ...
    tracker=${hd.fs}
    ...
  </hdp:script>
</beans>
```

Notice how the script above relies on the property placeholder to expand `${hd.fs}` with the values from `hadoop.properties` file available in the classpath.

As you might have noticed, the `script` element defines a runner for JVM scripts. And just like the rest of the SHDP runners, it allows one or multiple `pre` and `post` actions to be specified to be executed before and after each run. Typically other runners (such as other jobs or scripts) can be specified but any JDK `Callable` can be passed in. Do note that the runner will not run unless triggered manually or if `run-at-startup` is set to `true`. For more information on runners, see the [dedicated](#) chapter.

Using scripts

Inlined scripting is quite handy for doing simple operations and coupled with the property expansion is quite a powerful tool that can handle a variety of use cases. However when more logic is required or the script is affected by XML formatting, encoding or syntax restrictions (such as Jython/Python for which white-spaces are important) one should consider externalization. That is, rather than declaring the script directly inside the XML, one can declare it in its own file. And speaking of Python, consider the variation of the previous example:

```
<hdp:script location="org/company/basic-script.py" run-at-startup="true"/>
```

The definition does not bring any surprises but do notice there is no need to specify the language (as in the case of a inlined declaration) since script extension (`py`) already provides that information. Just for completeness, the `basic-script.py` looks as follows:

```
from java.util import UUID
from org.apache.hadoop.fs import Path

print "Home dir is " + str(fs.homeDirectory)
print "Work dir is " + str(fs.workingDirectory)
print "/user exists " + str(fs.exists("/user"))

name = UUID.randomUUID().toString()
scriptName = "src/test/resources/test.properties"
fs.copyFromLocalFile(scriptName, name)
print Path(name).makeQualified(fs)
```

4.4 Scripting implicit variables

To ease the interaction of the script with its enclosing context, SHDP binds by default the so-called *implicit* variables. These are:

Table 4.4. Implicit variables

Name	Type	Description
<code>org.apache.hadoop.conf.Configuration</code>		Hadoop Configuration (relies on <code>hadoopConfiguration</code> bean or singleton type match)
<code>cl</code>	<code>java.lang.ClassLoader</code>	ClassLoader used for executing the script
<code>ctx</code>	<code>org.springframework.context.ApplicationContext</code>	Enclosing application context
<code>ctxRL</code>	<code>org.springframework.io.support.ResourcePathResolver</code>	Enclosing application context ResourceLoader

	Name	Type	Description
org.springframework	distcp	org.apache.hadoop.fs.DistributedCopy	Programmatic access to DistCp
org.springframework	fs	org.apache.hadoop.fs.FileSystem	Hadoop File System (relies on 'hadoop-fs' bean or singleton type match, falls back to creating one based on 'cfg')
org.springframework	fsh	org.apache.hadoop.fs.FileSystemShell	File System shell, exposing hadoop 'fs' commands as an API
org.springframework	hdfsRL	org.apache.hadoop.io.HdfsResourceLoader	Hdfs resource loader (relies on 'hadoop-resource-loader' or singleton type match, falls back to creating one automatically based on 'cfg')



Note

If no Hadoop Configuration can be detected (either by name `hadoopConfiguration` or by type), several log warnings will be made and none of the Hadoop-based variables (namely `cfg`, `distcp`, `fs`, `fsh`, `distcp` or `hdfsRL`) will be bound.

As mentioned in the *Description* column, the variables are first looked (either by name or by type) in the application context and, in case they are missing, created on the spot based on the existing configuration. Note that it is possible to override or add new variables to the scripts through the `property` sub-element that can set values or references to other beans:

```
<hdp:script location="org/company/basic-script.js" run-at-startup="true">
  <hdp:property name="foo" value="bar"/>
  <hdp:property name="ref" ref="some-bean"/>
</hdp:script>
```

Running scripts

The `script` namespace provides various options to adjust its behaviour depending on the script content. By default the script is simply declared - that is, no execution occurs. One however can change that so that the script gets evaluated at startup (as all the examples in this section do) through the `run-at-startup` flag (which is by default `false`) or when invoked manually (through the `Callable`). Similarly, by default the script gets evaluated on each run. However for scripts that are expensive and return the same value every time one has various *caching* options, so the evaluation occurs only when needed through the `evaluate` attribute:

Table 4.5. *script* attributes

Name	Values	Description
<code>run-at-startup</code>	<code>false</code> (default), <code>true</code>	Whether the script is executed at startup or not
<code>evaluate</code>	<code>ALWAYS</code> (default), <code>IF_MODIFIED</code> , <code>ONCE</code>	Whether to actually evaluate the script when invoked or used a previous value. <code>ALWAYS</code> means evaluate every time, <code>IF_MODIFIED</code> evaluate if the backing resource (such as a file) has been modified in the meantime and <code>ONCE</code> only once.

Using the Scripting tasklet

For Spring Batch environments, SHDP provides a dedicated tasklet to execute scripts.

```

<script-tasklet id="script-tasklet">
  <script language="groovy">
    inputPath = "/user/gutenberg/input/word/"
    outputPath = "/user/gutenberg/output/word/"
    if (fsh.test(inputPath)) {
      fsh.rmr(inputPath)
    }
    if (fsh.test(outputPath)) {
      fsh.rmr(outputPath)
    }
    inputFile = "src/main/resources/data/nietzsche-chapter-1.txt"
    fsh.put(inputFile, inputPath)
  </script>
</script-tasklet>

```

The tasklet above embeds the script as a nested element. You can also declare a reference to another script definition, using the `script-ref` attribute which allows you to externalize the scripting code to an external resource.

```

<script-tasklet id="script-tasklet" script-ref="clean-up"/>
<hdp:script id="clean-up" location="org/company/myapp/clean-up-wordcount.groovy"/>

```

4.5 File System Shell (FsShell)

A handy utility provided by the Hadoop distribution is the file system [shell](#) which allows UNIX-like commands to be executed against HDFS. One can check for the existence of files, delete, move, copy directories or files or set up permissions. However the utility is only available from the command-line which makes it hard to use from/inside a Java application. To address this problem, SHDP provides a lightweight, fully embeddable shell, called `FsShell` which mimics most of the commands available from the command line: rather than dealing with `System.in` or `System.out`, one deals with objects.

Let us take a look at using `FsShell` by building on the previous scripting examples:

```

<hdp:script location="org/company/basic-script.groovy" run-at-startup="true"/>

```

```

name = UUID.randomUUID().toString()
scriptName = "src/test/resources/test.properties"
fs.copyFromLocalFile(scriptName, name)

// use the shell made available under variable fsh
dir = "script-dir"
if (!fsh.test(dir)) {
  fsh.mkdir(dir); fsh.cp(name, dir); fsh.chmodr(700, dir)
  println "File content is " + fsh.cat(dir + name).toString()
}
println fsh.ls(dir).toString()
fsh.rmr(dir)

```

As mentioned in the previous section, a `FsShell` instance is automatically created and configured for scripts, under the name `fsh`. Notice how the entire block relies on the usual commands: `test`, `mkdir`, `cp` and so on. Their semantics are exactly the same as in the command-line version however one has access to a native Java API that returns actual objects (rather than `Strings`) making it easy to use them programmatically whether in Java or another language. Furthermore, the class offers enhanced methods (such as `chmodr` which stands for *recursive chmod*) and multiple overloaded methods taking advantage of [varargs](#) so that multiple parameters can be specified. Consult the [API](#) for more information.

To be as close as possible to the command-line shell, `FsShell` mimics even the messages being displayed. Take a look at line 9 which prints the result of `fsh.cat()`. The method returns a `Collection` of Hadoop `Path` objects (which one can use programatically). However when invoking `toString` on the collection, the same printout as from the command-line shell is being displayed:

```
File content is some text
```

The same goes for the rest of the methods, such as `ls`. The same script in JRuby would look something like this:

```
require 'java'
name = java.util.UUID.randomUUID().to_s
scriptName = "src/test/resources/test.properties"
$fs.copyFromLocalFile(scriptName, name)

# use the shell
dir = "script-dir/"
...
print $fsh.ls(dir).to_s
```

which prints out something like this:

```
drwx-----  - user      supergroup      0 2012-01-26 14:08 /user/user/script-dir
-rw-r--r--   3 user      supergroup     344 2012-01-26 14:08 /user/user/script-
dir/520cf2f6-a0b6-427e-a232-2d5426c2bc4e
```

As you can see, not only can you reuse the existing tools and commands with Hadoop inside SHDP, but you can also code against them in various scripting languages. And as you might have noticed, there is no special configuration required - this is automatically inferred from the enclosing application context.

Note

The careful reader might have noticed that besides the syntax, there are some minor differences in how the various languages interact with the java objects. For example the automatic `toString` call called in Java for doing automatic `String` conversion is not necessarily supported (hence the `to_s` in Ruby or `str` in Python). This is to be expected as each language has its own semantics - for the most part these are easy to pick up but do pay attention to details.

DistCp API

Similar to the `FsShell`, SHDP provides a lightweight, fully embeddable `DistCp` version that builds on top of the `distcp` from the Hadoop distro. The semantics and configuration options are the same however, one can use it from within a Java application without having to use the command-line. See the [API](#) for more information:

```
<hdp:script language="groovy">distcp.copy("${distcp.src}", "${distcp.dst}")</hdp:script>
```

The bean above triggers a distributed copy relying again on Spring's property placeholder variable expansion for its source and destination.

5. Working with HBase

SHDP provides basic configuration for [HBase](#) through the `hbase-configuration` namespace element (or its backing `HbaseConfigurationFactoryBean`).

```
<!-- default bean id is 'hbaseConfiguration' that uses the existing 'hadoopConfiguration'
object -->
<hdp:hbase-configuration configuration-ref="hadoopConfiguration" />
```

The above declaration does more than easily create an HBase configuration object; it will also manage the backing HBase connections: when the application context shuts down, so will any HBase connections opened - this behavior can be adjusted through the `stop-proxy` and `delete-connection` attributes:

```
<!-- delete associated connections but do not stop the proxies -->
<hdp:hbase-configuration stop-proxy="false" delete-connection="true">
  foo=bar
  property=value
</hdp:hbase-configuration>
```

Additionally, one can specify the ZooKeeper port used by the HBase server - this is especially useful when connecting to a remote instance (note one can fully configure HBase including the ZooKeeper host and port through properties; the attributes here act as shortcuts for easier declaration):

```
<!-- specify ZooKeeper host/port -->
<hdp:hbase-configuration zk-quorum="{hbase.host}" zk-port="{hbase.port}">
```

Notice that like with the other elements, one can specify additional properties specific to this configuration. In fact `hbase-configuration` provides the same properties configuration knobs as [hadoop configuration](#):

```
<hdp:hbase-configuration properties-ref="some-props-bean" properties-location="classpath:/
conf/testing/hbase.properties"/>
```

5.1 Data Access Object (DAO) Support

One of the most popular and powerful feature in Spring Framework is the Data Access Object (or DAO) [support](#). It makes dealing with data access technologies easy and consistent allowing easy switch or interconnection of the aforementioned persistent stores with minimal friction (no worrying about catching exceptions, writing boiler-plate code or handling resource acquisition and disposal). Rather than reiterating here the value proposal of the DAO support, we recommend the DAO [section](#) in the Spring Framework reference documentation

SHDP provides the same functionality for Apache HBase through its `org.springframework.data.hadoop.hbase` package: an `HbaseTemplate` along with several callbacks such as `TableCallback`, `RowMapper` and `ResultsExtractor` that remove the low-level, tedious details for finding the HBase table, run the query, prepare the scanner, analyze the results then clean everything up, letting the developer focus on her actual job (users familiar with Spring should find the class/method names quite familiar).

At the core of the DAO support lies `HbaseTemplate` - a high-level abstraction for interacting with HBase. The template requires an HBase [configuration](#), once it's set, the template is thread-safe and can be reused across multiple instances at the same time:


```
// default HBase configuration
<hdp:hbase-configuration/>

// wire hbase configuration (using default name 'hbaseConfiguration') into the template
<bean id="htemplate" class="org.springframework.data.hadoop.hbase.HbaseTemplate" p:configuration-
ref="hbaseConfiguration"/>
```

The template provides generic callbacks, for executing logic against the tables or doing result or row extraction, but also utility methods (the so-called *one-liners*) for common operations. Below are some examples of how the template usage looks like:

```
// writing to 'MyTable'
template.execute("MyTable", new TableCallback<Object>() {
    @Override
    public Object doInTable(HTable table) throws Throwable {
        Put p = new Put(Bytes.toBytes("SomeRow"));
        p.add(Bytes.toBytes("SomeColumn"), Bytes.toBytes("SomeQualifier"),
Bytes.toBytes("AValue"));
        table.put(p);
        return null;
    }
});
```

```
// read each row from 'MyTable'
List<String> rows = template.find("MyTable", "SomeColumn", new RowMapper<String>() {
    @Override
    public String mapRow(Result result, int rowNum) throws Exception {
        return result.toString();
    }
}));
```

The first snippet showcases the generic `TableCallback` - the most generic of the callbacks, it does the table lookup and resource cleanup so that the user code does not have to. Notice the callback signature - any exception thrown by the HBase API is automatically caught, converted to Spring's [DAO exceptions](#) and resource clean-up applied transparently. The second example, displays the dedicated lookup methods - in this case `find` which, as the name implies, finds all the rows matching the given criteria and allows user code to be executed against each of them (typically for doing some sort of type conversion or mapping). If the entire result is required, then one can use `ResultsExtractor` instead of `RowMapper`.

Besides the template, the package offers support for automatically binding HBase table to the current thread through `HbaseInterceptor` and `HbaseSynchronizationManager`. That is, each class that performs DAO operations on HBase can be *wrapped* by `HbaseInterceptor` so that each table in use, once found, is bound to the thread so any subsequent call to it avoids the lookup. Once the call ends, the table is automatically closed so there is no leakage between requests. Please refer to the Javadocs for more information.

6. Hive integration

When working with <http://hive.apache.org> from a Java environment, one can choose between the [Thrift](#) client or using the Hive JDBC-like [driver](#). Both have their pros and cons but no matter the choice, Spring and SHDP support both of them.

6.1 Starting a Hive Server

SHDP provides a dedicated namespace element for starting a Hive server as a Thrift service (only when using Hive 0.8 or higher). Simply specify the host, the port (the defaults are localhost and 10000 respectively) and you're good to go:

```
<!-- by default, the definition name is 'hive-server' -->
<hdp:hive-server host="some-other-host" port="10001" />
```

If needed the Hadoop configuration can be passed in or additional properties specified. In fact `hive-server` provides the same properties configuration knobs as [hadoop configuration](#):

```
<hdp:hive-server host="some-other-host" port="10001" properties-location="classpath:hive-
dev.properties" configuration-ref="hadoopConfiguration">
  someproperty=somevalue
  hive.exec.scratchdir=/tmp/mydir
</hdp:hive-server>
```

The Hive server is bound to the enclosing application context life-cycle, that is it will automatically startup and shutdown along-side the application context.

6.2 Using the Hive Thrift Client

Similar to the server, SHDP provides a dedicated namespace element for configuring a Hive client (that is Hive accessing a server node through the Thrift). Likewise, simply specify the host, the port (the defaults are localhost and 10000 respectively) and you're done:

```
<!-- by default, the definition name is 'hiveClientFactory' -->
<hdp:hive-client-factory host="some-other-host" port="10001" />
```

Note that since Thrift clients are not thread-safe, `hive-client-factory` returns a factory (named `org.springframework.data.hadoop.hive.HiveClientFactory`) for creating `HiveClient` new instances for each invocation. Furthermore, the client definition also allows Hive scripts (either declared inlined or externally) to be executed during initialization, once the client connects; this is quite useful for doing Hive specific initialization:

```
<hive-client-factory host="some-host" port="some-port" xmlns="http://
www.springframework.org/schema/hadoop">
  <hdp:script>
    DROP TABLE IF EXISTS testHiveBatchTable;
    CREATE TABLE testHiveBatchTable (key int, value string);
  </hdp:script>
  <hdp:script location="classpath:org/company/hive/script.q">
    <arguments>ignore-case=true</arguments>
  </hdp:script>
</hive-client-factory>
```

In the example above, two scripts are executed each time a new Hive client is created (if the scripts need to be executed only once consider using a tasklet) by the factory. The first script is defined inline while the second is read from the classpath and passed one parameter. For more information on using parameters (or variables) in Hive scripts, see [this](#) section in the Hive manual.

6.3 Using the Hive JDBC Client

Another attractive option for accessing Hive is through its JDBC driver. This exposes Hive through the [JDBC API](#) meaning one can use the standard API or its derived utilities to interact with Hive, such as the rich [JDBC support](#) in Spring Framework.

Warning

Note that the JDBC driver is a work-in-progress and not all the JDBC features are available (and probably never will since Hive cannot support all of them as it is not the typical relational database). Do read the official documentation and examples.

SHDP does not offer any dedicated support for the JDBC integration - Spring Framework itself provides the needed tools; simply configure Hive as you would with any other JDBC Driver:

```
<beans xmlns="http://www.springframework.org/schema/beans"
  xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
  xmlns:c="http://www.springframework.org/schema/c"
  xmlns:context="http://www.springframework.org/schema/context"
  xsi:schemaLocation="http://www.springframework.org/schema/beans http://
www.springframework.org/schema/beans/spring-beans.xsd
    http://www.springframework.org/schema/context http://www.springframework.org/
schema/context/spring-context.xsd">

  <!-- basic Hive driver bean -->
  <bean id="hive-driver" class="org.apache.hadoop.hive.jdbc.HiveDriver"/>

  <!-- wrapping a basic datasource around the driver -->
  <!-- notice the 'c:' namespace (available in Spring 3.1+) for inlining constructor
arguments,
    in this case the url (default is 'jdbc:hive://localhost:10000/default') -->
  <bean id="hive-ds" class="org.springframework.jdbc.datasource.SimpleDriverDataSource"
    c:driver-ref="hive-driver" c:url="${hive.url}"/>

  <!-- standard JdbcTemplate declaration -->
  <bean id="template" class="org.springframework.jdbc.core.JdbcTemplate" c:data-source-
ref="hive-ds"/>

  <context:property-placeholder location="hive.properties"/>
</beans>
```

And that is it! Following the example above, one can use the `hive-ds` `DataSource` bean to manually get a hold of `Connections` or better yet, use Spring's [JdbcTemplate](#) as in the example above.

6.4 Running a Hive script or query

Like the rest of the Spring Hadoop components, a runner is provided out of the box for executing Hive scripts, either inlined or from various locations through `hive-runner` element:

```

<hdp:hive-runner id="hiveRunner" run-at-startup="true">
  <hdp:script>
    DROP TABLE IF EXISTS testHiveBatchTable;
    CREATE TABLE testHiveBatchTable (key int, value string);
  </hdp:script>
  <hdp:script location="hive-scripts/script.q" />
</hdp:hive-runner>

```

The runner will trigger the execution during the application start-up (notice the `run-at-startup` flag which is by default `false`). Do note that the runner will not run unless triggered manually or if `run-at-startup` is set to `true`. Additionally the runner (as in fact do all [runners](#) in SHDP) allows one or multiple `pre` and `post` actions to be specified to be executed before and after each run. Typically other runners (such as other jobs or scripts) can be specified but any JDK `Callable` can be passed in. For more information on runners, see the [dedicated](#) chapter.

Using the Hive tasklet

For Spring Batch environments, SHDP provides a dedicated tasklet to execute Hive queries, on demand, as part of a batch or workflow. The declaration is pretty straightforward:

```

<hdp:hive-tasklet id="hive-script">
  <hdp:script>
    DROP TABLE IF EXISTS testHiveBatchTable;
    CREATE TABLE testHiveBatchTable (key int, value string);
  </hdp:script>
  <hdp:script location="classpath:org/company/hive/script.q" />
</hdp:hive-tasklet>

```

The tasklet above executes two scripts - one declared as part of the bean definition followed by another located on the classpath.

6.5 Interacting with the Hive API

For those that need to programmatically interact with the Hive API, Spring for Apache Hadoop provides a dedicated [template](#), similar to the aforementioned `JdbcTemplate`. The template handles the redundant, boiler-plate code, required for interacting with Hive such as creating a new `HiveClient`, executing the queries, catching any exceptions and performing clean-up. One can programmatically execute queries (and get the raw results or convert them to longs or ints) or scripts but also interact with the Hive API through the `HiveClientCallback`. For example:

```

<hdp:hive-client-factory ... />
<!-- Hive template wires automatically to 'hiveClientFactory'-->
<hdp:hive-template />

<!-- wire hive template into a bean -->
<bean id="someBean" class="org.SomeClass" p:hive-template-ref="hiveTemplate"/>

```

```
public class SomeClass {  
  
    private HiveTemplate template;  
  
    public void setHiveTemplate(HiveTemplate template) { this.template = template; }  
  
    public List<String> getDbs() {  
        return hiveTemplate.execute(new HiveClientCallback<List<String>>() {  
            @Override  
            public List<String> doInHive(HiveClient hiveClient) throws Exception {  
                return hiveClient.get_all_databases();  
            }  
        }));  
    }  
}
```

The example above shows a basic container configuration wiring a `HiveTemplate` into a user class which uses it to interact with the `HiveClient` Thrift API. Notice that the user does not have to handle the lifecycle of the `HiveClient` instance or catch any exception (out of the many thrown by Hive itself and the Thrift fabric) - these are handled automatically by the template which converts them, like the rest of the Spring templates, into `DataAccessExceptions`. Thus the application only has to track only one exception hierarchy across all data technologies instead of one per technology.

7. Pig support

For [Pig](#) users, SHDP provides easy creation and configuration of `PigServer` instances for registering and executing scripts either locally or remotely. In its simplest form, the declaration looks as follows:

```
<hdp:pig />
```

This will create a `org.springframework.data.hadoop.pig.PigServerFactory` instance, named `pigFactory`, a factory that creates `PigServer` instances on demand configured with a default `PigContext`, executing scripts in `MapReduce` mode. The factory is needed since `PigServer` is not thread-safe and thus cannot be used by multiple objects at the same time. In typical scenarios however, one might want to connect to a remote Hadoop tracker and register some scripts automatically so let us take a look of how the configuration might look like:

```
<pig-factory exec-type="LOCAL" job-name="pig-script" configuration-
ref="hadoopConfiguration" properties-location="pig-dev.properties"
xmlns="http://www.springframework.org/schema/hadoop">
  source=${pig.script.src}
  <script location="org/company/pig/script.pig">
    <arguments>electric=sea</arguments>
  </script>
  <script>
    A = LOAD 'src/test/resources/logs/apache_access.log' USING PigStorage() AS
(name:chararray, age:int);
    B = FOREACH A GENERATE name;
    DUMP B;
  </script>
</pig-factory />
```

The example exposes quite a few options so let us review them one by one. First the top-level `pig` definition configures the `pig` instance: the execution type, the Hadoop configuration used and the job name. Notice that additional properties can be specified (either by declaring them inlined or/and loading them from an external file) - in fact, `<hdp:pig-factory/>` just like the rest of the libraries configuration elements, supports common properties attributes as described in the [hadoop configuration](#) section.

The definition contains also two scripts: `script.pig` (read from the classpath) to which one pair of arguments, relevant to the script, is passed (notice the use of property placeholder) but also an inlined script, declared as part of the definition, without any arguments.

As you can tell, the `pig-factory` namespace offers several options pertaining to Pig configuration.

7.1 Running a Pig script

Like the rest of the Spring Hadoop components, a runner is provided out of the box for executing Pig scripts, either inlined or from various locations through `pig-runner` element:

```
<hdp:pig-runner id="pigRunner" run-at-startup="true">
  <hdp:script>
    A = LOAD 'src/test/resources/logs/apache_access.log' USING PigStorage() AS
(name:chararray, age:int);
    ...
  </hdp:script>
  <hdp:script location="pig-scripts/script.pig"/>
</hdp:pig-runner>
```

The runner will trigger the execution during the application start-up (notice the `run-at-startup` flag which is by default `false`). Do note that the runner will not run unless triggered manually or if `run-at-startup` is set to `true`. Additionally the runner (as in fact do all [runners](#) in SHDP) allows one or multiple `pre` and `post` actions to be specified to be executed before and after each run. Typically other runners (such as other jobs or scripts) can be specified but any JDK `Callable` can be passed in. For more information on runners, see the [dedicated](#) chapter.

Using the Pig tasklet

For Spring Batch environments, SHDP provides a dedicated tasklet to execute Pig queries, on demand, as part of a batch or workflow. The declaration is pretty straightforward:

```
<hdp:pig-tasklet id="pig-script">
  <hdp:script location="org/company/pig/handsome.pig" />
</hdp:pig-tasklet>
```

The syntax of the scripts declaration is similar to that of the `pig` namespace.

7.2 Interacting with the Pig API

For those that need to programmatically interact directly with Pig, Spring for Apache Hadoop provides a dedicated [template](#), similar to the aforementioned `HiveTemplate`. The template handles the redundant, boiler-plate code, required for interacting with Pig such as creating a new `PigServer`, executing the scripts, catching any exceptions and performing clean-up. One can programmatically execute scripts but also interact with the Hive API through the `PigServerCallback`. For example:

```
<hdp:pig-factory ... />
<!-- Pig template wires automatically to 'pigFactory'-->
<hdp:pig-template />

<!-- use component scanning-->
<context:component-scan base-package="some.pkg" />
```

```
public class SomeClass {
    @Inject
    private PigTemplate template;

    public Set<String> getDbs() {
        return template.execute(new PigCallback<Set<String>>() {
            @Override
            public Set<String> doInPig(PigServer pig) throws ExecException, IOException {
                return pig.getAliasKeySet();
            }
        });
    }
}
```

The example above shows a basic container configuration wiring a `PigTemplate` into a user class which uses it to interact with the `PigServer` API. Notice that the user does not have to handle the lifecycle of the `PigServer` instance or catch any exception - these are handled automatically by the template which converts them, like the rest of the Spring templates, into `DataAccessExceptions`. Thus the application only has to track only one exception hierarchy across all data technologies instead of one per technology.

8. Using the *runner* classes

Spring for Apache Hadoop provides for each Hadoop interaction type, whether it is vanilla Map/Reduce, Hive or Pig, a *runner*, a dedicated class used for declarative (or programmatic) interaction. The list below illustrates the existing *runner* classes for each type, their name and namespace element.

Table 8.1. Available Runners

Type	Name	Namespace element	Description
Map/Reduce Job	JobRunner	job-runner	Runner for Map/Reduce jobs, whether vanilla M/R or streaming
Hadoop Tool	ToolRunner	tool-runner	Runner for Hadoop <code>Tools</code> (whether stand-alone or as jars).
Hadoop jars	JarRunner	jar-runner	Runner for Hadoop jars.
Hive queries and scripts	HiveRunner	hive-runner	Runner for executing Hive queries or scripts.
Pig queries and scripts	PigRunner	pig-runner	Runner for executing Pig scripts.
JSR-223/JVM scripts	HdfsScriptRunner	script	Runner for executing JVM 'scripting' languages (implementing the JSR-223 API).

While most of the configuration depends on the underlying type, the runners share common attributes and behaviour so one can use them in a predictive, consistent way. Below is a list of common features:

- declaration does **not** imply execution

The runner allows a script, a job to run but the execution can be triggered either programmatically or by the container at start-up.

- `run-at-startup`

Each runner can execute its action at start-up. By default, this flag is set to `false`. For multiple or on demand execution (such as scheduling) use the `Callable` contract (see below).

- JDK `Callable` interface

Each runner implements the JDK `Callable` interface. Thus one can inject the runner into other beans or its own classes to trigger the execution (as many or as little times as she wants).

- `pre` and `post` actions

Each runner allows one or multiple, pre or/and post actions to be specified (to chain them together such as executing a job after another or performing clean up). Typically other runners can be used but *any* `Callable` can be specified. The actions will be executed before and after the main action, in the declaration order. The runner uses a *fail-safe* behaviour meaning, any exception will interrupt the run and will propagated immediately to the caller.

- consider Spring Batch

The runners are meant as a way to execute basic tasks. When multiple executions need to be coordinated and the flow becomes non-trivial, we strongly recommend using Spring Batch which provides all the features of the runners and more (a complete, mature framework for batch execution).

9. Security Support

Spring for Apache Hadoop is aware of the security constraints of the running Hadoop environment and allows its components to be configured as such. For clarity, this document breaks down *security* into HDFS permissions and user impersonation (also known as *secure* Hadoop). The rest of this document discusses each component and the impact (and usage) it has on the various SHDP features.

9.1 HDFS permissions

HDFS layer provides file permissions designed to be similar to those present in *nix OS. The official [guide](#) explains the major components but in short, the access for each file (whether it's for reading, writing or in case of directories accessing) can be restricted to certain users or groups. Depending on the user identity (which is typically based on the host operating system), code executing against the Hadoop cluster can see or/and interact with the file-system based on these permissions. Do note that each HDFS or `FileSystem` implementation can have slightly different semantics or implementation.

SHDP obeys the HDFS permissions, using the identity of the current user (by default) for interacting with the file system. In particular, the `HdfsResourceLoader` considers when doing pattern matching, only the files that it's supposed to see and does not perform any privileged action. It is possible however to specify a different user, meaning the `ResourceLoader` interacts with HDFS using that user's rights - however this obeys the [user impersonation](#) rules. When using different users, it is recommended to create separate `ResourceLoader` instances (one per user) instead of assigning additional permissions or groups to one user - this makes it easier to manage and wire the different HDFS *views* without having to modify the ACLs. Note however that when using impersonation, the `ResourceLoader` might (and will typically) return *restricted* files that might not be consumed or seen by the callee.

9.2 User impersonation (Kerberos)

Securing a Hadoop cluster can be a difficult task - each machine can have a different set of users and groups, each with different passwords. Hadoop relies on [Kerberos](#), a ticket-based protocol for allowing nodes to communicate over a non-secure network to prove their identity to one another in a secure manner. Unfortunately there is not a lot of documentation on this topic out there. However there are [some resources](#) to get you started.

SHDP does not require any extra configuration - it simply obeys the security system in place. By default, when running inside a *secure* Hadoop, SHDP uses the current user (as expected). It also supports *user impersonation*, that is, interacting with the Hadoop cluster with a different identity (this allows a superuser to submit job or access hdfs on behalf of another user in a secure way, without *leaking* permissions). The major MapReduce components, such as `job`, `streaming` and `tool` as well as `pig` support user impersonation through the `user` attribute. By default, this property is empty, meaning the current user is used - however one can specify the different identity (also known as *ugi*) to be used by the target component:

```
<hdp:job id="jobFromJoe" user="joe" .../>
```

Note that the user running the application (or the current user) must have the proper kerberos credentials to be able to impersonate the target user (in this case *joe*).

10. Yarn Support

You've probably seen a lot of topics around Yarn and next version of Hadoop's Map Reduce called *MapReduce Version 2*. Originally Yarn was a component of MapReduce itself created to overcome some performance issues in Hadoop's original design. The fundamental idea of MapReduce v2 is to split up the two major functionalities of the JobTracker, resource management and job scheduling/monitoring, into separate daemons. The idea is to have a global *Resource Manager* (RM) and per-application *Application Master* (AM). An application is either a single job in the classical sense of Map-Reduce jobs or a group of jobs.

Let's take a step back and see how original *MapReduce Version 1* works. *Job Tracker* is a global singleton entity responsible for managing resources like per node *Task Trackers* and job life-cycle. *Task Tracker* is responsible for executing tasks from a *Job Tracker* and periodically reporting back the status of the tasks. Naturally there is a much more going on behind the scenes but the main point of this is that the *Job Tracker* has always been a bottleneck in terms of scalability. This is where Yarn steps in by splitting the load away from a global resource management and job tracking into per application masters. Global resource manager can then concentrate in its main task of handling the management of resources.

Note

Yarn is usually referred as a synonym for *MapReduce Version 2*. This is not exactly true and it's easier to understand the relationship between those two by saying that *MapReduce Version 2* is an application running on top of *Yarn*.

As we just mentioned *MapReduce Version 2* is an application running on top of *Yarn*. It is possible to make similar custom *Yarn* based application which have nothing to do with *MapReduce*. *Yarn* itself doesn't know that it is running *MapReduce Version 2*. While there's nothing wrong to do everything from scratch one will soon realise that steps to learn how to work with *Yarn* are rather deep. This is where Spring Hadoop support for Yarn steps in by trying to make things easier so that user could concentrate on his own code and not having to worry about framework internals.

10.1 Using the Spring for Apache Yarn Namespace

To simplify configuration, SHDP provides a dedicated namespace for *Yarn* components. However, one can opt to configure the beans directly through the usual `<bean>` definition. For more information about XML Schema-based configuration in Spring, see [this](#) appendix in the Spring Framework reference documentation.

To use the SHDP namespace, one just needs to import it inside the configuration:

```

<?xml version="1.0" encoding="UTF-8"?>
<beans xmlns="http://www.springframework.org/schema/beans"
  xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
  xmlns:①yarn="②http://www.springframework.org/schema/yarn"
  xmlns:③yarn-int="④http://www.springframework.org/schema/yarn/integration"
  xmlns:⑤yarn-batch="⑥http://www.springframework.org/schema/yarn/batch"
  xsi:schemaLocation="
    http://www.springframework.org/schema/beans
    http://www.springframework.org/schema/beans/spring-beans.xsd
    http://www.springframework.org/schema/yarn
    http://www.springframework.org/schema/yarn/spring-yarn.xsd⑦
    http://www.springframework.org/schema/yarn/integration
    http://www.springframework.org/schema/yarn/integration/spring-yarn-integration.xsd⑧
    http://www.springframework.org/schema/yarn/batch
    http://www.springframework.org/schema/yarn/batch/spring-yarn-batch.xsd⑨">

  <bean id ... >

    ⑩<yarn:configuration ...>
</beans>

```

- ❶ Spring for Apache Hadoop Yarn namespace prefix for core package. Any name can do but through out the reference documentation, the `yarn` will be used.
- ❷ The namespace URI.
- ❸ Spring for Apache Hadoop Yarn namespace prefix for integration package. Any name can do but through out the reference documentation, the `yarn-int` will be used.
- ❹ The namespace URI.
- ❺ Spring for Apache Hadoop Yarn namespace prefix for batch package. Any name can do but through out the reference documentation, the `yarn-batch` will be used.
- ❻ The namespace URI.
- ❼ The namespace URI location. Note that even though the location points to an external address (which exists and is valid), Spring will resolve the schema locally as it is included in the Spring for Apache Hadoop Yarn library.
- ❽ The namespace URI location.
- ❾ The namespace URI location.
- ❿ Declaration example for the Yarn namespace. Notice the prefix usage.

Once declared, the namespace elements can be declared simply by appending the aforementioned prefix. Note that is possible to change the default namespace, for example from `<beans>` to `<yarn>`. This is useful for configuration composed mainly of Hadoop components as it avoids declaring the prefix. To achieve this, simply swap the namespace prefix declaration above:

```

<?xml version="1.0" encoding="UTF-8"?>
<beans:beans xmlns="http://www.springframework.org/schema/yarn"❶
  xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
  ❷xmlns:beans="http://www.springframework.org/schema/beans"
  xsi:schemaLocation="
    http://www.springframework.org/schema/beans
    http://www.springframework.org/schema/beans/spring-beans.xsd
    http://www.springframework.org/schema/yarn
    http://www.springframework.org/schema/yarn/spring-yarn.xsd">

  ❸<beans:bean id ... >

  ❹<configuration ...>

</beans:beans>

```

- ❶ The default namespace declaration for this XML file points to the Spring for Apache Yarn namespace.
- ❷ The beans namespace prefix declaration.
- ❸ Bean declaration using the <beans> namespace. Notice the prefix.
- ❹ Bean declaration using the <yarn> namespace. Notice the *lack* of prefix (as *yarn* is the default namespace).

10.2 Using the Spring for Apache Yarn JavaConfig

It is also possible to work without XML configuration and rely on Annotation based configuration model. XML and JavaConfig for *Spring YARN* are not full replacement for each others but we try to mimic the behaviour as much as we can.

We basically rely on two concepts when working with JavaConfig. Firstly an annotation `@EnableYarn` is used to activate different parts of a Spring Configuration depending on *enable* attribute. We can enable configuration for *CONTAINER*, *APPMASTER* or *CLIENT*. Secondly when configuration is enabled one can use `SpringYarnConfigurerAdapter` whose callback methods can be used to do further configuration for components familiar from XML.

```

@Configuration
@EnableYarn(enable=Enable.CONTAINER)
public class ContainerConfiguration extends SpringYarnConfigurerAdapter {

  @Override
  public void configure(YarnContainerConfigurer container) throws Exception {
    container
      .containerClass(MultiContextContainer.class);
  }
}

```

In above example we enabled configuration for *CONTAINER* and used `SpringYarnConfigurerAdapter` and its `configure` callback method for `YarnContainerConfigurer`. In this method we instructed container class to be a `MultiContextContainer`.

```

@Configuration
@EnableYarn(enable=Enable.APPMASTER)
public class AppmasterConfiguration extends SpringYarnConfigurerAdapter {

    @Override
    public void configure(YarnAppmasterConfigurer master) throws Exception {
        master
            .withContainerRunner();
    }
}

```

In above example we enabled configuration for *APPMASTER* and because of this a callback method for *YarnAppmasterConfigurer* is called automatically.

```

@Configuration
@EnableYarn(enable=Enable.CLIENT)
@PropertySource("classpath:hadoop.properties")
public class ClientConfiguration extends SpringYarnConfigurerAdapter {

    @Autowired
    private Environment env;

    @Override
    public void configure(YarnConfigConfigurer config) throws Exception {
        config
            .fileSystemUri(env.getProperty("hd.fs"))
            .resourceManagerAddress(env.getProperty("hd.rm"));
    }

    @Override
    public void configure(YarnClientConfigurer client) throws Exception {
        Properties arguments = new Properties();
        arguments.put("container-count", "4");
        client
            .appName("multi-context-jc")
            .withMasterRunner()
            .contextClass(AppmasterConfiguration.class)
            .arguments(arguments);
    }
}

```

In above example we enabled configuration for *CLIENT*. Here one will get yet another callback for *YarnClientConfigurer*. Additionally this shows how a Hadoop configuration can be customized using a callback for *YarnConfigConfigurer*.

10.3 Configuring Yarn

In order to use Hadoop and Yarn, one needs to first configure it namely by creating a *YarnConfiguration* object. The configuration holds information about the various parameters of the Yarn system.



Note

Configuration for `<yarn:configuration>` looks very similar than `<hdp:configuration>`. Reason for this is a simple separation for Hadoop's *YarnConfiguration* and *JobConf* classes.

In its simplest form, the configuration definition is a one liner:

```
<yarn:configuration />
```

The declaration above defines a `YarnConfiguration` bean (to be precise a factory bean of type `ConfigurationFactoryBean`) named, by default, `yarnConfiguration`. The default name is used, by conventions, by the other elements that require a configuration - this leads to simple and very concise configurations as the main components can automatically wire themselves up without requiring any specific configuration.

For scenarios where the defaults need to be tweaked, one can pass in additional configuration files:

```
<yarn:configuration resources="classpath:/custom-site.xml, classpath:/hq-site.xml">
```

In this example, two additional Hadoop configuration resources are added to the configuration.



Note

Note that the configuration makes use of Spring's [Resource](#) abstraction to locate the file. This allows various search patterns to be used, depending on the running environment or the prefix specified (if any) by the value - in this example the classpath is used.

In addition to referencing configuration resources, one can tweak Hadoop settings directly through Java `Properties`. This can be quite handy when just a few options need to be changed:

```
<?xml version="1.0" encoding="UTF-8"?>
<beans xmlns="http://www.springframework.org/schema/beans"
  xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
  xmlns:yarn="http://www.springframework.org/schema/yarn"
  xsi:schemaLocation="http://www.springframework.org/schema/beans http://
www.springframework.org/schema/beans/spring-beans.xsd
  http://www.springframework.org/schema/yarn http://www.springframework.org/schema/yarn/
spring-yarn.xsd">

  <yarn:configuration>
    fs.defaultFS=hdfs://localhost:9000
    hadoop.tmp.dir=/tmp/hadoop
    electric=sea
  </yarn:configuration>
</beans>
```

One can further customize the settings by avoiding the so called *hard-coded* values by externalizing them so they can be replaced at runtime, based on the existing environment without touching the configuration:

```

<?xml version="1.0" encoding="UTF-8"?>
<beans xmlns="http://www.springframework.org/schema/beans"
  xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
  xmlns:yarn="http://www.springframework.org/schema/yarn"
  xmlns:context="http://www.springframework.org/schema/context"
  xsi:schemaLocation="http://www.springframework.org/schema/beans http://
www.springframework.org/schema/beans/spring-beans.xsd
  http://www.springframework.org/schema/context http://www.springframework.org/schema/
context/spring-context.xsd
  http://www.springframework.org/schema/yarn http://www.springframework.org/schema/yarn/
spring-yarn.xsd">

  <yarn:configuration>
    fs.defaultFS=${hd.fs}
    hadoop.tmp.dir=file://${java.io.tmpdir}
    hangar=${number:18}
  </yarn:configuration>

  <context:property-placeholder location="classpath:hadoop.properties" />
</beans>

```

Through Spring's property placeholder [support](#), [SpEL](#) and the [environment abstraction](#) (available in Spring 3.1). one can externalize environment specific properties from the main code base easing the deployment across multiple machines. In the example above, the default file system is replaced based on the properties available in `hadoop.properties` while the temp dir is determined dynamically through [SpEL](#). Both approaches offer a lot of flexibility in adapting to the running environment - in fact we use this approach extensively in the Spring for Apache Hadoop test suite to cope with the differences between the different development boxes and the CI server.

Additionally, external `Properties` files can be loaded, `Properties` beans (typically declared through Spring's [util](#) namespace). Along with the nested properties declaration, this allows customized configurations to be easily declared:

```

<?xml version="1.0" encoding="UTF-8"?>
<beans xmlns="http://www.springframework.org/schema/beans"
  xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
  xmlns:yarn="http://www.springframework.org/schema/yarn"
  xmlns:context="http://www.springframework.org/schema/context"
  xmlns:util="http://www.springframework.org/schema/util"
  xsi:schemaLocation="http://www.springframework.org/schema/beans http://
www.springframework.org/schema/beans/spring-beans.xsd
  http://www.springframework.org/schema/context http://www.springframework.org/schema/
context/spring-context.xsd
  http://www.springframework.org/schema/util http://www.springframework.org/schema/util/
spring-util.xsd
  http://www.springframework.org/schema/yarn http://www.springframework.org/schema/yarn/
spring-yarn.xsd">

  <!-- merge the local properties, the props bean and the two properties files -->
  <yarn:configuration properties-ref="props" properties-location="cfg-1.properties,
cfg-2.properties">
    star=chasing
    captain=eo
  </yarn:configuration>

  <util:properties id="props" location="props.properties"/>
</beans>

```


When merging several properties, ones defined locally win. In the example above the configuration properties are the primary source, followed by the `props` bean followed by the external properties file based on their defined order. While it's not typical for a configuration to refer to use so many properties, the example showcases the various options available.

Note

For more properties utilities, including using the System as a source or fallback, or control over the merging order, consider using Spring's [PropertiesFactoryBean](#) (which is what Spring for Apache Hadoop Yarn and `util:properties` use underneath).

It is possible to create configuration based on existing ones - this allows one to create dedicated configurations, slightly different from the main ones, usable for certain jobs (such as streaming - more on that [below](#)). Simply use the `configuration-ref` attribute to refer to the *parent* configuration - all its properties will be inherited and overridden as specified by the child:

```
<!-- default name is 'yarnConfiguration' -->
<yarn:configuration>
  fs.defaultFS=${hd.fs}
  hadoop.tmp.dir=file://${java.io.tmpdir}
</yarn:configuration>

<yarn:configuration id="custom" configuration-ref="yarnConfiguration">
  fs.defaultFS=${custom.hd.fs}
</yarn:configuration>

...

```

Make sure though you specify a different name since otherwise, since both definitions will have the same name, the Spring container will interpret this as being the same definition (and will usually consider the last one found).

Last but not least a reminder that one can mix and match all these options to her preference. In general, consider externalizing configuration since it allows easier updates without interfering with the application configuration. When dealing with multiple, similar configuration use configuration *composition* as it tends to keep the definitions concise, in sync and easy to update.

Table 10.1. *yarn:configuration* attributes

Name	Values	Description
<code>configuration-ref</code>	Bean Reference	Reference to existing <i>Configuration</i> bean
<code>properties-ref</code>	Bean Reference	Reference to existing <i>Properties</i> bean
<code>properties-location</code>	Comma delimited list	List or Spring <i>Resource</i> paths
<code>resources</code>	Comma delimited list	List or Spring <i>Resource</i> paths
<code>fs-uri</code>	String	The HDFS filesystem address. Equivalent to <code>fs.defaultFS</code> property.

Name	Values	Description
rm-address	String	The Yarn Resource manager address. Equivalent to <code>yarn.resourcemanager.address</code> property.
scheduler-address	String	The Yarn Resource manager scheduler address. Equivalent to <code>yarn.resourcemanager.scheduler.address</code> property.

10.4 Local Resources

When *Application Master* or any other *Container* is run in a hadoop cluster, there are usually dependencies to various application and configuration files. These files needs to be localized into a running *Container* by making a physical copy. Localization is a process where dependent files are copied into node's directory structure and thus can be used within the *Container* itself. Yarn itself tries to provide isolation in a way that multiple containers and applications would not clash.

In order to use local resources, one needs to create an implementation of `ResourceLocalizer` interface. In its simplest form, resource localizer can be defined as:

```
<yarn:localresources>
  <yarn:hdfs path="/path/in/hdfs/my.jar"/>
</yarn:localresources>
```

The declaration above defines a `ResourceLocalizer` bean (to be precise a factory bean of type `LocalResourcesFactoryBean`) named, by default, `yarnLocalresources`. The default name is used, by conventions, by the other elements that require a reference to a resource localizer. It's explained later how this reference is used when container launch context is defined.

It is also possible to define path as pattern. This makes it easier to pick up all or subset of files from a directory.

```
<yarn:localresources>
  <yarn:hdfs path="/path/in/hdfs/*.jar"/>
</yarn:localresources>
```

Behind the scenes it's not enough to simple have a reference to file in a hdfs file system. Yarn itself when localizing resources into container needs to do a consistency check for copied files. This is done by checking file size and timestamp. This information needs to be passed to yarn together with a file path. Order to do this the one who defines these beans needs to ask this information from hdfs prior to sending out resource localizer request. This kind of behaviour exists to make sure that once localization is defined, *Container* will fail fast if dependant files were replaced during the process.

On default the hdfs base address is coming from a Yarn configuration and `ResourceLocalizer` bean will use configuration named `yarnLocalresources`. If there is a need to use something else than the default bean, `configuration` parameter can be used to make a reference to other defined configurations.

```
<yarn:localresources configuration="yarnConfiguration">
  <yarn:hdfs path="/path/in/hdfs/my.jar"/>
</yarn:localresources>
```

For example, client defining a launch context for *Application Master* needs to access dependent hdfs entries. Effectively hdfs entry given to resource localizer needs to be accessed from a *Node Manager*.

Yarn resource localizer is using additional parameters to define entry type and visibility. Usage is described below:

```
<yarn:localresources>
  <yarn:hdfs path="/path/in/hdfs/my.jar" type="FILE" visibility="APPLICATION"/>
</yarn:localresources>
```

For convenience it is possible to copy files into hdfs during the localization process using a `yarn:copy` tag. Currently base staging directory is `/syarn/staging/xx` where `xx` is a unique identifier per application instance.

```
<yarn:localresources>
  <yarn:copy src="file:/local/path/to/files/*jar" staging="true"/>
  <yarn:hdfs path="/*" staging="true"/>
</yarn:localresources>
```

Table 10.2. `yarn:localresources` attributes

Name	Values	Description
configuration	Bean Reference	A reference to configuration bean name, default is <code>yarnConfiguration</code>
type	ARCHIVE, FILE, PATTERN	Global default if not defined in entry level
visibility	PUBLIC, PRIVATE, APPLICATION	Global default if not defined in entry level

Table 10.3. `yarn:hdfs` attributes

Name	Values	Description
path	HDFS Path	Path in hdfs
type	ARCHIVE, FILE(default), PATTERN	ARCHIVE - automatically unarchived by the Node Manager, FILE - regular file, PATTERN - hybrid between archive and file.
visibility	PUBLIC, PRIVATE, APPLICATION(default)	PUBLIC - Shared by all users on the node, PRIVATE - Shared among all applications of the <i>same user</i> on the node, APPLICATION - Shared only among containers of the <i>same application</i> on the node
staging	true, false(default)	Internal temporary staging directory.

Table 10.4. `yarn:copy` attributes

Name	Values	Description
src	Copy sources	Comma delimited list of resource patterns
staging	true, false(default)	Internal temporary staging directory.

10.5 Container Environment

One central concept in Yarn is to use environment variables which then can be read from a container. While it's possible to read those variable at any time it is considered bad design if one choose to do so. Spring Yarn will pass variable into application before any business methods are executed, which makes things more clearly and testing becomes much more easier.

```
<yarn:environment/>
```

The declaration above defines a `Map` bean (to be precise a factory bean of type `EnvironmentFactoryBean`) named, by default, `yarnEnvironment`. The default name is used, by conventions, by the other elements that require a reference to a environment variables.

For convenience it is possible to define a classpath entry directly into an environment. Most likely one is about to run some java code with libraries so classpath needs to be defined anyway.

```
<yarn:environment include-local-system-env="false">
  <yarn:classpath use-default-yarn-classpath="true" delimiter=":">
    ./*
  </yarn:classpath>
</yarn:environment>
```

If `use-default-yarn-classpath` parameter is set to `true`(default value) a default yarn entries will be added to classpath automatically. These entries are on default resolved from a normal Hadoop Yarn Configuration using its `yarn.application.classpath` property or if `default-yarn-app-classpath` has a any content entries are resolved from there.

Note

Be carefull if passing environment variables between different systems. For example if running a client on Windows and passing variables to Application Master running on Linux, execution wrapper in Yarn may silently fail.

Table 10.5. `yarn:environment` attributes

Name	Values	Description
include-local-system-env	true, false(default)	Defines whether system environment variables are actually added to this bean.

Table 10.6. `classpath` attributes

Name	Values	Description
use-default-yarn-classpath	true(default), false	Defines whether default yarn entries are added to classpath.
default-yarn-app-classpath	Classpath entries	Defines a comma delimited list of default yarn application classpath entries.

Name	Values	Description
delimiter	Delimiter string, default is ":"	Defines delimiter used in a classpath string

10.6 Application Client

Client is always your entry point when interacting with a Yarn system whether one is about to submit a new application instance or just querying *Resource Manager* for running application(s) status. Currently support for client is very limited and a simple command to start *Application Master* can be defined. If there is just a need to query *Resource Manager*, command definition is not needed.

```
<yarn:client app-name="customAppName">
  <yarn:master-command>
    <![CDATA[
      /usr/local/java/bin/java
      org.springframework.yarn.am.CommandLineAppmasterRunner
      appmaster-context.xml
      yarnAppmaster
      container-count=2
      1><LOG_DIR>/AppMaster.stdout
      2><LOG_DIR>/AppMaster.stderr
    ]]>
  </yarn:master-command>
</yarn:client>
```

The declaration above defines a `YarnClient` bean (to be precise a factory bean of type `YarnClientFactoryBean`) named, by default, `yarnClient`. It also defines a command launching an *Application Master* using `<master-command>` entry which is also a way to define the raw commands. If this `yarnClient` instance is used to submit an application, its name would come from a `app-name` attribute.

```
<yarn:client app-name="customAppName">
  <yarn:master-runner/>
</yarn:client>
```

For a convenience entry `<master-runner>` can be used to define same command entries.

```
<yarn:client app-name="customAppName">
  <util:properties id="customArguments">
    container-count=2
  </util:properties>
  <yarn:master-runner
    command="java"
    context-file="appmaster-context.xml"
    bean-name="yarnAppmaster"
    arguments="customArguments"
    stdout="<LOG_DIR>/AppMaster.stdout"
    stderr="<LOG_DIR>/AppMaster.stderr" />
</yarn:client>
```

All previous three examples are effectively identical from Spring Yarn point of view.

 **Note**

The <LOG_DIR> refers to Hadoop's dedicated log directory for the running container.

```
<yarn:client app-name="customAppName"
  configuration="customConfiguration"
  resource-localizer="customResources"
  environment="customEnv"
  priority="1"
  virtualcores="2"
  memory="11"
  queue="customqueue">
  <yarn:master-runner/>
</yarn:client>
```

If there is a need to change some of the parameters for the *Application Master* submission, `memory` and `virtualcores` defines the container settings. For submission, `queue` and `priority` defines how submission is actually done.

Table 10.7. *yarn:client* attributes

Name	Values	Description
app-name	Name as string, default is empty	Yarn submitted application name
configuration	Bean Reference	A reference to configuration bean name, default is <i>yarnConfiguration</i>
resource-localizer	Bean Reference	A reference to resource localizer bean name, default is <i>yarnLocalresources</i>
environment	Bean Reference	A reference to environment bean name, default is <i>yarnEnvironment</i>
template	Bean Reference	A reference to a bean implementing <i>ClientRmOperations</i>
memory	Memory as integer, default is "64"	Amount of memory for appmaster resource
virtualcores	Cores as integer, default is "1"	Number of appmaster resource virtual cores
priority	Priority as integer, default is "0"	Submission priority
queue	Queue string, default is "default"	Submission queue

Table 10.8. *yarn:master-command*

Name	Values	Description
Entry content	List of commands	Commands defined in this entry are aggregated into a single command line

Table 10.9. *yarn:master-runner attributes*

Name	Values	Description
command	Main command as string, default is "java"	Command line first entry
context-file	Name of the Spring context file, default is "appmaster-context.xml"	Command line second entry
bean-name	Name of the Spring bean, default is "yarnAppmaster"	Command line third entry
arguments	Reference to Java's Properties	Added to command line parameters as key/value pairs separated by '='
stdout	Stdout, default is "<LOG_DIR>/AppMaster.stdout"	Appended with 1>
stderr	Stderr, default is "<LOG_DIR>/AppMaster.stderr"	Appended with 2>

10.7 Application Master

Application master is responsible for container allocation, launching and monitoring.

```

<yarn:master>
  <yarn:container-allocator virtualcores="1" memory="64" priority="0"/>
  <yarn:container-launcher username="whoami"/>
  <yarn:container-command>
    <![CDATA[
      /usr/local/java/bin/java
      org.springframework.hadoop.yarn.container.CommandLineContainerRunner
      container-context.xml
      1><LOG_DIR>/Container.stdout
      2><LOG_DIR>/Container.stderr
    ]]>
  </yarn:container-command>
</yarn:master>

```

The declaration above defines a `YarnAppmaster` bean (to be precise a bean of type `StaticAppmaster`) named, by default, `yarnAppmaster`. It also defines a command launching a `Container(s)` using `<container-command>` entry, parameters for allocation using `<container-allocator>` entry and finally a launcher parameter using `<container-launcher>` entry.

Currently there is a simple implementation of `StaticAppmaster` which is able to allocate and launch a number of containers. These containers are monitored by querying resource manager for container execution completion.

```

<yarn:master>
  <yarn:container-runner/>
</yarn:master>

```

For a convenience entry `<container-runner>` can be used to define same command entries.

```

<yarn:master>
  <util:properties id="customArguments">
    some-argument=myvalue
  </util:properties>
  <yarn:container-runner
    command="java"
    context-file="container-context.xml"
    bean-name="yarnContainer"
    arguments="customArguments"
    stdout="<LOG_DIR>/Container.stdout"
    stderr="<LOG_DIR>/Container.stderr" />
</yarn:master>

```

Table 10.10. `yarn:master` attributes

Name	Values	Description
configuration	Bean Reference	A reference to configuration bean name, default is <code>yarnConfiguration</code>
resource-localizer	Bean Reference	A reference to resource localizer bean name, default is <code>yarnLocalresources</code>
environment	Bean Reference	A reference to environment bean name, default is <code>yarnEnvironment</code>

Table 10.11. *yarn:container-allocator* attributes

Name	Values	Description
virtualcores	Integer	<i>number of virtual cpu cores</i> of the resource.
memory	Integer, as of MBs.	<i>memory</i> of the resource.
priority	Integer	Assigned priority of a request.
locality	Boolean	If set to true indicates that resources are not relaxed. Default is <i>FALSE</i> .

Table 10.12. *yarn:container-launcher* attributes

Name	Values	Description
username	String	Set the <i>user</i> to whom the container has been allocated.

Table 10.13. *yarn:container-runner* attributes

Name	Values	Description
command	Main command as string, default is "java"	Command line first entry
context-file	Name of the Spring context file, default is "container-context.xml"	Command line second entry
bean-name	Name of the Spring bean, default is "yarnContainer"	Command line third entry
arguments	Reference to Java's Properties	Added to command line parameters as key/value pairs separated by '='
stdout	Stdout, default is "<LOG_DIR>/Container.stdout"	Appended with 1>
stderr	Stderr, default is "<LOG_DIR>/Container.stderr"	Appended with 2>

10.8 Application Container

There is very little what Spring Yarn needs to know about the Container in terms of its configuration. There is a simple contract between `org.springframework.yarn.container.CommandLineContainerRunner` and a bean it's trying to run on default. Default bean name is `yarnContainer`.

There is a simple interface `org.springframework.yarn.container.YarnContainer` which container needs to implement.

```
public interface YarnContainer {
    void run();
    void setEnvironment(Map<String, String> environment);
    void setParameters(Properties parameters);
}
```

There are few different ways how Container can be defined in Spring xml configuration. Natively without using namespaces bean can be defined with a correct name:

```
<bean id="yarnContainer" class="org.springframework.yarn.container.TestContainer">
```

Spring Yarn namespace will make it even more simpler. Below example just defines class which implements needed interface.

```
<yarn:container container-class="org.springframework.yarn.container.TestContainer"/>
```

It's possible to make a reference to existing bean. This is useful if bean cannot be instantiated with default constructor.

```
<bean id="testContainer" class="org.springframework.yarn.container.TestContainer"/>
<yarn:container container-ref="testContainer"/>
```

It's also possible to inline the bean definition.

```
<yarn:container>
  <bean class="org.springframework.yarn.container.TestContainer"/>
</yarn:container>
```

10.9 Application Master Services

It is fairly easy to create an application which launches a few containers and then leave those to do their tasks. This is pretty much what *Distributed Shell* example application in Yarn is doing. In that example a container is configured to run a simple shell command and *Application Master* only tracks when containers have finished. If only need from a framework is to be able to fire and forget then that's all you need, but most likely a real-world Yarn application will need some sort of collaboration with *Application Master*. This communication is initiated either from *Application Client* or *Application Container*.

Yarn framework itself doesn't define any kind of general communication API for *Application Master*. There are APIs for communicating with *Container Manager* and *Resource Manager* which are used on

within a layer not necessarily exposed to a user. Spring Yarn defines a general framework to talk to *Application Master* through an abstraction and currently a JSON based rpc system exists.

This chapter concentrates on developer concepts to create a custom services for *Application Master*, configuration options for built-in services can be found from sections below - [Appmaster Service](#) and [Appmaster Service Client](#).

Basic Concepts

Having a communication framework between *Application Master* and *Container/Client* involves few moving parts. Firstly there has to be some sort of service running on an *Application Master*. Secondly user of this service needs to know where it is and how to connect to it. Thirdly, if not creating these services from scratch, it'd be nice if some sort of abstraction already exist.

Contract for appmaster service is very simple, *Application Master Service* needs to implement `AppmasterService` interface be registered with Spring application context. Actual appmaster instance will then pick it up from a bean factory.

```
public interface AppmasterService {
    int getPort();
    boolean hasPort();
    String getHost();
}
```

Application Master Service framework currently provides integration for services acting as service for a *Client* or a *Container*. Only difference between these two roles is how the *Service Client* gets notified about the address of the service. For the *Client* this information is stored within the Hadoop Yarn resource manager. For the *Container* this information is passed via environment within the launch context.

```
<bean id="yarnAmservice" class="AppmasterServiceImpl" />
<bean id="yarnClientAmservice" class="AppmasterClientServiceImpl" />
```

Example above shows a default bean names, `yarnAmservice` and `yarnClientAmservice` respectively recognised by Spring Yarn.

Interface `AppmasterServiceClient` is currently an empty interface just marking class to be a appmaster service client.

```
public interface AppmasterServiceClient {
}
```

Using JSON

Default implementations can be used to exchange messages using a simple domain classes and actual messages are converted into json and send over the transport.

```
<yarn-int:amservice
  service-impl="org.springframework.yarn.integration.ip.mind.TestService"
  default-port="1234"/>
<yarn-int:amservice-client
  service-
  impl="org.springframework.yarn.integration.ip.mind.DefaultMindAppmasterServiceClient"
  host="localhost"
  port="1234"/>
```

```

@Autowired
AppmasterServiceClient appmasterServiceClient;

@Test
public void testServiceInterfaces() throws Exception {
    SimpleTestRequest request = new SimpleTestRequest();
    SimpleTestResponse response =
        (SimpleTestResponse) ((MindAppmasterServiceClient) appmasterServiceClient).
            doMindRequest(request);
    assertThat(response.stringField, is("echo:stringFieldValue"));
}

```

Converters

When default implementations for Application master services are exchanging messages, converters are not registered automatically. There is a namespace tag `converters` to ease this configuration.

```

<bean id="mapper"
    class="org.springframework.yarn.integration.support.Jackson2ObjectMapperFactoryBean" />

<yarn-int:converter>
    <bean class="org.springframework.yarn.integration.convert.MindObjectToHolderConverter">
        <constructor-arg ref="mapper"/>
    </bean>
</yarn-int:converter>

<yarn-int:converter>
    <bean class="org.springframework.yarn.integration.convert.MindHolderToObjectConverter">
        <constructor-arg ref="mapper"/>
        <constructor-arg value="org.springframework.yarn.batch.repository.bindings"/>
    </bean>
</yarn-int:converter>

```

10.10 Application Master Service

This section of this document is about configuration, more about general concepts for see a Section 10.9, “Application Master Services”.

Currently Spring Yarn have support for services using Spring Integration tcp channels as a transport.

```

<bean id="mapper"
    class="org.springframework.yarn.integration.support.Jackson2ObjectMapperFactoryBean" />

<yarn-int:converter>
    <bean class="org.springframework.yarn.integration.convert.MindObjectToHolderConverter">
        <constructor-arg ref="mapper"/>
    </bean>
</yarn-int:converter>

<yarn-int:converter>
    <bean class="org.springframework.yarn.integration.convert.MindHolderToObjectConverter">
        <constructor-arg ref="mapper"/>
        <constructor-arg value="org.springframework.yarn.integration.ip.mind"/>
    </bean>
</yarn-int:converter>

<yarn-int:amservice
    service-impl="org.springframework.yarn.integration.ip.mind.TestService"/>

```

If there is a need to manually configure the server side dispatch channel, a little bit more configuration is needed.

```

<bean id="serializer"
  class="org.springframework.yarn.integration.ip.mind.MindRpcSerializer" />
<bean id="deserializer"
  class="org.springframework.yarn.integration.ip.mind.MindRpcSerializer" />
<bean id="socketSupport"
  class="org.springframework.yarn.integration.support.DefaultPortExposingTcpSocketSupport"
  />

<ip:tcp-connection-factory id="serverConnectionFactory"
  type="server"
  port="0"
  socket-support="socketSupport"
  serializer="serializer"
  deserializer="deserializer"/>

<ip:tcp-inbound-gateway id="inboundGateway"
  connection-factory="serverConnectionFactory"
  request-channel="serverChannel" />

<int:channel id="serverChannel" />

<yarn-int:amservice
  service-impl="org.springframework.yarn.integration.ip.mind.TestService"
  channel="serverChannel"
  socket-support="socketSupport"/>

```

Table 10.14. `yarn-int:amservice` attributes

Name	Values	Description
service-impl	Class Name	Full name of the class implementing a service
service-ref	Bean Reference	Reference to a bean name implementing a service
channel	Spring Int channel	Custom message dispatching channel
socket-support	Socket support reference	Custom socket support class

10.11 Application Master Service Client

This section of this document is about configuration, more about general concepts for see a Section 10.9, “Application Master Services”.

Currently Spring Yarn have support for services using Spring Integration tcp channels as a transport.

```

<bean id="mapper"
  class="org.springframework.yarn.integration.support.Jackson2ObjectMapperFactoryBean" />

<yarn-int:converter>
  <bean class="org.springframework.yarn.integration.convert.MindObjectToHolderConverter">
    <constructor-arg ref="mapper"/>
  </bean>
</yarn-int:converter>

<yarn-int:converter>
  <bean class="org.springframework.yarn.integration.convert.MindHolderToObjectConverter">
    <constructor-arg ref="mapper"/>
    <constructor-arg value="org.springframework.yarn.integration.ip.mind"/>
  </bean>
</yarn-int:converter>

<yarn-int:amservice-client
  service-
  impl="org.springframework.yarn.integration.ip.mind.DefaultMindAppmasterServiceClient"
  host="${SHDP_AMSERVICE_HOST}"
  port="${SHDP_AMSERVICE_PORT}"/>

```

If there is a need to manually configure the server side dispatch channel, a little bit more configuration is needed.

```

<bean id="serializer"
  class="org.springframework.yarn.integration.ip.mind.MindRpcSerializer" />
<bean id="deserializer"
  class="org.springframework.yarn.integration.ip.mind.MindRpcSerializer" />

<ip:tcp-connection-factory id="clientConnectionFactory"
  type="client"
  host="localhost"
  port="${SHDP_AMSERVICE_PORT}"
  serializer="serializer"
  deserializer="deserializer"/>

<ip:tcp-outbound-gateway id="outboundGateway"
  connection-factory="clientConnectionFactory"
  request-channel="clientRequestChannel"
  reply-channel="clientResponseChannel" />

<int:channel id="clientRequestChannel" />
<int:channel id="clientResponseChannel" >
  <int:queue />
</int:channel>

<yarn-int:amservice-client
  service-
  impl="org.springframework.yarn.integration.ip.mind.DefaultMindAppmasterServiceClient"
  request-channel="clientRequestChannel"
  response-channel="clientResponseChannel"/>

```

Table 10.15. `yarn-int:amservice-client` attributes

Name	Values	Description
service-impl	Class Name	Full name of the class implementing a service client

Name	Values	Description
host	Hostname	Host of the running appmaster service
port	Port	Port of the running appmaster service
request-channel	Reference to Spring Int request channel	Custom channel
response-channel	Reference to Spring Int response channel	Custom channel

10.12 Using Spring Batch

In this chapter we assume you are fairly familiar with concepts using *Spring Batch*. Many batch processing problems can be solved with single threaded, single process jobs, so it is always a good idea to properly check if that meets your needs before thinking about more complex implementations. When you are ready to start implementing a job with some parallel processing, Spring Batch offers a range of options. At a high level there are two modes of parallel processing: single process, multi-threaded; and multi-process.

Spring Hadoop contains a support for running Spring Batch jobs on a Hadoop cluster. For better parallel processing Spring Batch partitioned steps can be executed on a Hadoop cluster as remote steps.

Batch Jobs

Starting point running a *Spring Batch Job* is always the *Application Master* whether a job is just simple job with or without partitioning. In case partitioning is not used the whole job would be run within the *Application Master* and no *Containers* would be launched. This may seem a bit odd to run something on Hadoop without using *Containers* but one should remember that *Application Master* is also just a resource allocated from a Hadoop cluster.

Order to run Spring Batch jobs on a Hadoop cluster, few constraints exists:

- *Job Context* - Application Master is the main entry point of running the job.
- *Job Repository* - Application Master needs to have access to a repository which is located either in-memory or in a database. These are the two type natively supported by Spring Batch.
- *Remote Steps* - Due to nature how Spring Batch partitioning works, remote step needs an access to a job repository.

Configuration for Spring Batch Jobs is very similar what is needed for normal batch configuration because effectively that's what we are doing. Only difference is a way a job is launched which in this case is automatically handled by *Application Master*. Implementation of a job launching logic is very similar compared to `CommandLineJobRunner` found from a Spring Batch.

```

<bean id="transactionManager" class="org.springframework.batch.support.transaction.ResourcelessTransactionM
>

<bean id="jobRepository" class="org.springframework.batch.core.repository.support.MapJobRepositoryFactoryBe
  <property name="transactionManager" ref="transactionManager"/>
</bean>

<bean id="jobLauncher" class="org.springframework.batch.core.launch.support.SimpleJobLauncher">
  <property name="jobRepository" ref="jobRepository"/>
</bean>

```

The declaration above define beans for `JobRepository` and `JobLauncher`. For simplicity we used in-memory repository while it would be possible to switch into repository working with a database if persistence is needed. A bean named `jobLauncher` is later used within the *Application Master* to launch jobs.

```

<bean id="yarnEventPublisher" class="org.springframework.yarn.event.DefaultYarnEventPublisher"/
>

<yarn-batch:master/>

```

The declaration above defines `BatchAppmaster` bean named, by default, `yarnAppmaster` and `YarnEventPublisher` bean named `yarnEventPublisher` which is not created automatically.

Final step to finalize our very simple batch configuration is to define the actual batch job.

```

<bean id="hello" class="org.springframework.yarn.examples.PrintTasklet">
  <property name="message" value="Hello"/>
</bean>

<batch:job id="job">
  <batch:step id="master">
    <batch:tasklet transaction-manager="transactionManager" ref="hello"/>
  </batch:step>
</batch:job>

```

The declaration above defines a simple job and tasklet. Job is named as `job` which is the default job name searched by *Application Master*. It is possible to use different name by changing the launch configuration.

Table 10.16. `yarn-batch:master` attributes

Name	Values	Description
configuration	Bean Reference	A reference to configuration bean name, default is <i>yarnConfiguration</i>
resource-localizer	Bean Reference	A reference to resource localizer bean name, default is <i>yarnLocalresources</i>
environment	Bean Reference	A reference to environment bean name, default is <i>yarnEnvironment</i>
job-name	Bean Name Reference	A name reference to Spring Batch job, default is <i>job</i>

Name	Values	Description
job-launcher	Bean Reference	A reference to job launcher bean name, default is <i>jobLauncher</i> . Target is a normal Spring Batch bean implementing <i>JobLauncher</i> .

Partitioning

Let's take a quick look how Spring Batch partitioning is handled. Concept of running a partitioned job involves three things, *Remote steps*, *Partition Handler* and a *Partitioner*. If we do a little bit of oversimplification a remote step is like any other step from a user point of view. Spring Batch itself does not contain implementations for any proprietary grid or remoting fabrics. Spring Batch does however provide a useful implementation of *PartitionHandler* that executes Steps locally in separate threads of execution, using the *TaskExecutor* strategy from Spring. Spring Hadoop provides implementation to execute Steps remotely on a Hadoop cluster.

Note

For more background information about the Spring Batch Partitioning, read the Spring Batch reference documentation.

Configuring Master

As we previously mentioned a step executed on a remote host also need to access a job repository. If job repository would be based on a database instance, configuration could be similar on a container compared to application master. In our configuration example the job repository is in-memory based and remote steps needs access for it. Spring Yarn Batch contains implementation of a job repository which is able to proxy request via json requests. Order to use that we need to enable application client service which is exposing this service.

```
<bean id="jobRepositoryRemoteService" class="org.springframework.yarn.batch.repository.JobRepositoryRemoteService"
>
  <property name="mapJobRepositoryFactoryBean" ref="&jobRepository"/>
</bean>

<bean id="batchService" class="org.springframework.yarn.batch.repository.BatchAppmasterService"
>
  <property name="jobRepositoryRemoteService" ref="jobRepositoryRemoteService"/>
</bean>

<yarn-int:amservice service-ref="batchService"/>
```

The declaration above defines *JobRepositoryRemoteService* bean named *jobRepositoryRemoteService* which is then connected into *Application Master Service* exposing job repository via Spring Integration Tcp channels.

As job repository communication messages are exchanged via custom json messages, converters needs to be defined.

```

<bean id="mapper" class="org.springframework.yarn.integration.support.Jackson2ObjectMapperFactoryBean"
/>

<yarn-int:converter>
  <bean class="org.springframework.yarn.integration.convert.MindObjectToHolderConverter">
    <constructor-arg ref="mapper"/>
  </bean>
</yarn-int:converter>

<yarn-int:converter>
  <bean class="org.springframework.yarn.integration.convert.MindHolderToObjectConverter">
    <constructor-arg ref="mapper"/>
    <constructor-arg value="org.springframework.yarn.batch.repository.bindings"/>
  </bean>
</yarn-int:converter>

```

Configuring Container

Previously we made a choice to use in-memory job repository running inside the application master. Now we need to talk to this repository via client service. We start by adding some converters as in application master.

```

<bean id="mapper" class="org.springframework.yarn.integration.support.Jackson2ObjectMapperFactoryBean"
/>

<yarn-int:converter>
  <bean class="org.springframework.yarn.integration.convert.MindObjectToHolderConverter">
    <constructor-arg ref="mapper"/>
  </bean>
</yarn-int:converter>

<yarn-int:converter>
  <bean class="org.springframework.yarn.integration.convert.MindHolderToObjectConverter">
    <constructor-arg ref="mapper"/>
    <constructor-arg value="org.springframework.yarn.batch.repository.bindings"/>
  </bean>
</yarn-int:converter>

```

We use general client implementation able to communicate with a service running on *Application Master*.

```

<yarn-int:amservice-client
  service-
  impl="org.springframework.yarn.integration.ip.mind.DefaultMindAppmasterServiceClient"
  host="${SHDP_AMSERVICE_HOST}"
  port="${SHDP_AMSERVICE_PORT}" />

```

Remote step is just like any other step.

```

<bean id="hello" class="org.springframework.yarn.examples.PrintTasklet">
  <property name="message" value="Hello"/>
</bean>

<batch:step id="remoteStep">
  <batch:tasklet transaction-manager="transactionManager" start-limit="100" ref="hello"/>
</batch:step>

```

We need to have a way to locate the step from an application context. For this we can define a step locator which is later configured into running container.

```
<bean id="stepLocator" class="org.springframework.yarn.batch.partition.BeanFactoryStepLocator"/>
```

Spring Hadoop contains a custom job repository implementation which is able to talk back to a remote instance via custom json protocol.

```
<bean id="transactionManager" class="org.springframework.batch.support.transaction.ResourcelessTransactionManager"/>

<bean id="jobRepository" class="org.springframework.yarn.batch.repository.RemoteJobRepositoryFactoryBean">
  <property name="transactionManager" ref="transactionManager"/>
  <property name="appmasterScOperations" ref="yarnAmServiceClient"/>
</bean>

<bean id="jobExplorer" class="org.springframework.yarn.batch.repository.RemoteJobExplorerFactoryBean">
  <property name="repositoryFactory" ref="&jobRepository" />
</bean>
```

Finally we define a *Container* understanding how to work with a remote steps.

```
<bean id="yarnContainer" class="org.springframework.yarn.batch.container.DefaultBatchYarnContainer">
  <property name="stepLocator" ref="stepLocator"/>
  <property name="jobExplorer" ref="jobExplorer"/>
  <property name="integrationServiceClient" ref="yarnAmServiceClient"/>
</bean>
```

10.13 Using Spring Boot Application Model

We have additional support for leveraging *Spring Boot* when creating applications using *Spring YARN*. All dependencies for this exists in a sub-module named `spring-yarn-boot` which itself depends on *Spring Boot*.

Spring Boot extensions in *Spring YARN* are used to ease following issues:

- Create a clear model how application is built, packaged and run on *Hadoop YARN*.
- Automatically configure components depending whether we are on *Client*, *Appmaster* or *Container*.
- Create an easy to use externalized configuration model based on *Boot's ConfigurationProperties*.

Before we get into details let's go through how simple it is to create and deploy a custom application to a Hadoop cluster. Notice that there are no need to use XML.

```

@Configuration
@EnableAutoConfiguration
public class ContainerApplication {

    public static void main(String[] args) {
        SpringApplication.run(ContainerApplication.class, args);
    }

    @Bean
    public HelloPojo helloPojo() {
        return new HelloPojo();
    }
}

```

In above `ContainerApplication`, notice how we added `@Configuration` in a class level itself and `@Bean` for a `helloPojo()` method.

```

@YarnContainer
public class HelloPojo {

    private static final Log log = LoggerFactory.getLog(HelloPojo.class);

    @Autowired
    private Configuration configuration;

    @OnYarnContainerStart
    public void publicVoidNoArgsMethod() {
        log.info("Hello from HelloPojo");
        log.info("About to list from hdfs root content");
        FsShell shell = new FsShell(configuration);
        for (FileStatus s : shell.ls(false, "/")) {
            log.info(s);
        }
    }
}

```

`HelloPojo` class is a simple POJO in a sense that it doesn't extend any *Spring YARN* base classes. What we did in this class:

- We've added a class level `@YarnContainer` annotation.
- We've added a method level `@OnYarnContainerStart` annotation.
- We've `@Autowired` a Hadoop's Configuration class.

To demonstrate that we actually have some real functionality in this class, we simply use Spring Hadoop's `FsShell` to list entries from a root of a HDFS file system. For this we need to have access to Hadoop's Configuration which is prepared for you so that you can just autowire it.

```
@EnableAutoConfiguration
public class ClientApplication {

    public static void main(String[] args) {
        SpringApplication.run(ClientApplication.class, args)
            .getBean(YarnClient.class)
            .submitApplication();
    }
}
```

- `@EnableAutoConfiguration` tells Spring Boot to start adding beans based on classpath setting, other beans, and various property settings.
- Specific auto-configuration for Spring YARN components takes place since Spring YARN is on the classpath.

The `main()` method uses Spring Boot's `SpringApplication.run()` method to launch an application. From there we simply request a bean of type `YarnClient` and execute its `submitApplication()` method. What happens next depends on application configuration, which we go through later in this document.

```
@EnableAutoConfiguration
public class AppmasterApplication {

    public static void main(String[] args) {
        SpringApplication.run(AppmasterApplication.class, args);
    }
}
```

Application class for `YarnAppmaster` looks even simpler than what we just did for `ClientApplication`. Again the `main()` method uses Spring Boot's `SpringApplication.run()` method to launch an application.

In real life, you most likely need to start adding more custom functionality to your application component and you'd do that by start adding more beans. To do that you need to define a `Spring @Configuration` or `@ComponentScan`. `AppmasterApplication` would then act as your main starting point to define more custom functionality.

```
spring:
  hadoop:
    fsUri: hdfs://localhost:8020
    resourceManagerHost: localhost
  yarn:
    appName: yarn-boot-simple
    applicationDir: /app/yarn-boot-simple/
    client:
      files:
        - "file:build/libs/yarn-boot-simple-container-0.1.0.jar"
        - "file:build/libs/yarn-boot-simple-appmaster-0.1.0.jar"
      launchcontext:
        archiveFile: yarn-boot-simple-appmaster-0.1.0.jar
    appmaster:
      containerCount: 1
      launchcontext:
        archiveFile: yarn-boot-simple-container-0.1.0.jar
```

Final part for your application is its runtime configuration which glues all the components together which then can be called as a Spring YARN application. This configuration act as source for Spring Boot's `@ConfigurationProperties` and contains relevant configuration properties which cannot be auto-discovered or otherwise needs to have an option to be overwritten by an end user.

You can then write your own defaults for your own environment. Because these `@ConfigurationProperties` are resolved at runtime by Spring Boot, you even have an easy option to overwrite these properties either by using command-line options or provide additional configuration property files.

Auto Configuration

Spring Boot is heavily influenced by auto-configuration trying to predict what user wants to do. These decisions are based on configuration properties, what's currently available from a classpath and generally everything what auto-configurers are able to see.

Auto-configuration is able to see if it's currently running on a YARN cluster and can also differentiate between *YarnContainer* and *YarnAppmaster*. Parts of the auto-configuration which cannot be automatically detected are guarded by a flags in configuration properties which then allows end-user to either enable or disable these functionalities.

Application Files

As we already mentioned *Spring Boot* creates a clear model how you would work with your application files. Most likely what you need in your application is jar or zip file(s) having needed application code and optional configuration properties to customize the application logic. Customization via an external properties files makes it easier to change application functionality and reduce a need to hard-code application logic.

Running an application on YARN needs an instance of *YarnAppmaster* and instances of *YarnContainers*. Both of these containers will need a set of files and instructions how to execute a container. Based on auto-configuration and configuration properties we will make few assumptions how a container is executed.

We are fundamentally supporting three different type of combinations:

- If a container main archive file is a jar file we expect it to be packaged with Boot and be self container executable jar archive.
- If a container main archive is a zip file we expect it to be packages with Boot. In this case we use a special runner which knows how to run this exploded archive.
- User defines a main class to be run and everything this class will need is already setup.

More detailed functionality can be found from a below sections; the section called “Application Classpath”, the section called “Container Runners” and the section called “Configuration Properties”.

Application Classpath

Let's go through as an examples how a classpath is configured on different use cases.

Simple Executable Jar

Running a container using an executable jar archive is the most simple scenario due to classpath limitation imposed by a JVM. Everything needed for the classpath needs to be inside the archive itself. Boot plugins for maven and gradle will greatly help to package all library dependencies into this archive.

```
spring:
  yarn:
    client:
      launchcontext:
        archiveFile: yarn-boot-appmaster-0.1.0.jar
    appmaster:
      launchcontext:
        archiveFile: yarn-boot-container-0.1.0.jar
```

Simple Zip Archive

Using a zip archive is basically needed in two use cases. In first case you want to re-use existing libraries in YARN cluster for your classpath. In second case you want to add custom classpath entries from an exploded zip archive.

```
spring:
  yarn:
    defaultYarnAppClasspath: "/path/to/hadoop/libs/*"
    appmaster:
      launchcontext:
        useDefaultYarnClasspath: true
        archiveFile: yarn-boot-container-0.1.0.zip
```

In above example you can have a zip archive which doesn't bundle all dependant Hadoop YARN libraries. Default classpath entries are then resolved from `defaultYarnAppClasspath` property.

```
spring:
  yarn:
    appmaster:
      launchcontext:
        archiveFile: yarn-boot-container-0.1.0.zip
        classpath:
          - "./yarn-boot-container-0.1.0.zip/config"
          - "./yarn-boot-container-0.1.0.zip/lib"
```

In above example you needed to use custom classpath entries from an exploded zip archive.

Container Runners

Using a property `spring.yarn.client.launchcontext.archiveFile` and `spring.yarn.appmaster.launchcontext.archiveFile` respectively, will indicate that container is run based on an archive file and Boot runners are used. These runner classes are either used manually when constructing an actual raw command for container or internally within an executable jar archive.

However there are times when you may need to work on much lower level. Maybe you are having trouble using an executable jar archive or Boot runner is not enough what you want to do. For this use case you would use property `spring.yarn.client.launchcontext.runnerClass` and `spring.yarn.appmaster.launchcontext.runnerClass`.

Custom Runner

```
spring:
  yarn:
    appmaster:
      launchcontext:
        runnerClass: com.example.MyMainClazz
```

Resource Localizing

Order for containers to use application files, a YARN resource localization process needs to do its tasks. We have a few configuration properties which are used to determine which files are actually localized into container's working directory.

```
spring:
  yarn:
    client:
      localizer:
        patterns:
          - "*appmaster*jar"
          - "*appmaster*zip"
        zipPattern: "*zip"
        propertiesNames: [application]
        propertiesSuffixes: [properties, yml]
    appmaster:
      localizer:
        patterns:
          - "*container*jar"
          - "*container*zip"
        zipPattern: "*zip"
        propertiesNames: [application]
        propertiesSuffixes: [properties, yml]
```

Above is an example which equals a default functionality when localized resources are chosen. For example for a container we automatically choose all files matching a simple patterns `*container*jar` and `*container*zip`. Additionally we choose configuration properties files matching names `application.properties` and `application.yml`. Property `zipPattern` is used as an pattern to instruct YARN resource localizer to treat file as an archive to be automatically exploded.

If for some reason the default functionality and how it can be configured via configuration properties is not suitable, one can define a custom bean to change how things work. Interface `LocalResourcesSelector` is used to find localized resources.

```
public interface LocalResourcesSelector {
    List<Entry> select(String dir);
}
```

Below you see a logic how a default `BootLocalResourcesSelector` is created during the auto-configuration. You would then create a custom implementation and create it as a bean in your Configuration class. You would not need to use any Conditionals but not how in auto-configuration we use `@ConditionalOnMissingBean` to check if user have already created his own implementation.

```
@Configuration
@EnableConfigurationProperties({ SpringYarnAppmasterLocalizerProperties.class })
public static class LocalResourcesSelectorConfig {

    @Autowired
    private SpringYarnAppmasterLocalizerProperties syalp;

    @Bean
    @ConditionalOnMissingBean(LocalResourcesSelector.class)
    public LocalResourcesSelector localResourcesSelector() {
        BootLocalResourcesSelector selector = new BootLocalResourcesSelector(Mode.CONTAINER);
        if (StringUtils.hasText(syalp.getZipPattern())) {
            selector.setZipArchivePattern(syalp.getZipPattern());
        }
        if (syalp.getPropertiesNames() != null) {
            selector.setPropertiesNames(syalp.getPropertiesNames());
        }
        if (syalp.getPropertiesSuffixes() != null) {
            selector.setPropertiesSuffixes(syalp.getPropertiesSuffixes());
        }
        selector.addPatterns(syalp.getPatterns());
        return selector;
    }
}
```

Your configuration could then look like:

```
@EnableAutoConfiguration
public class AppmasterApplication {

    @Bean
    public LocalResourcesSelector localResourcesSelector() {
        return MyLocalResourcesSelector();
    }

    public static void main(String[] args) {
        SpringApplication.run(AppmasterApplication.class, args);
    }
}
```

Container as POJO

In Boot application model if *YarnContainer* is not explicitly defined it defaults to *DefaultYarnContainer* which expects to find a POJO created as a bean having a specific annotations instructing the actual functionality.

`@YarnContainer` is a stereotype annotation itself having a Spring's `@Component` defined in it. This is automatically marking a class to be a candidate having a `@YarnContainer` functionality.

Within a POJO class we can use `@OnYarnContainerStart` annotation to mark a public method to act as an activator for a method endpoint.

```
@OnYarnContainerStart
public void publicVoidNoArgsMethod() {
}
```

Returning type of `int` participates in a *YarnContainer* exit value.

```
@OnYarnContainerStart
public int publicIntNoArgsMethod() {
    return 0;
}
```

Returning type of `boolean` participates in a *YarnContainer* exit value where *true* would mean complete and *false* failed container.

```
@OnYarnContainerStart
public boolean publicBooleanNoArgsMethod() {
    return true;
}
```

Returning type of `String` participates in a *YarnContainer* exit value by matching `ExitStatus` and getting exit value from `ExitCodeMapper`.

```
@OnYarnContainerStart
public String publicVoidNoArgsMethod() {
    return "COMPLETE";
}
```

If method throws any `Exception` *YarnContainer* is marked as failed.

```
@OnYarnContainerStart
public void publicThrowsException() {
    throw new RuntimeException("My Error");
}
```

Method parameter can be bound with `@YarnEnvironments` to get access to current *YarnContainer* environment variables.

```
@OnYarnContainerStart
public void publicVoidNoArgsMethod(@YarnEnvironments Map<String,String> env) {
}
```

Method parameter can be bound with `@YarnEnvironment` to get access to specific *YarnContainer* environment variable.

```
@OnYarnContainerStart
public void publicVoidNoArgsMethod(@YarnEnvironment("key") String value) {
}
```

Method parameter can be bound with `@YarnParameters` to get access to current *YarnContainer* arguments.

```
@OnYarnContainerStart
public void publicVoidNoArgsMethod(@YarnParameters Properties properties) {
}
```

Method parameter can be bound with `@YarnParameter` to get access to a specific *YarnContainer* arguments.

```
@OnYarnContainerStart
public void publicVoidNoArgsMethod(@YarnParameter("key") String value) {
}
```

Configuration Properties

Configuration properties can be defined using various methods. See a Spring Boot documentation for details.

Table 10.17. *spring.hadoop* configuration properties

Property Name	Required	Type	Default Value
<code>spring.hadoop.fsUri</code>	Yes	String	null
<code>spring.hadoop.resourceManagerAddress</code>	No	String	null
<code>spring.hadoop.resourceManagerSchedulerAddress</code>	No	String	null
<code>spring.hadoop.resourceManagerHost</code>	No	String	null
<code>spring.hadoop.resourceManagerPort</code>	No	Integer	8032
<code>spring.hadoop.resourceManagerSchedulerPort</code>	No	Integer	8030

`spring.hadoop.fsUri`
A hdfs file system uri for a namenode.

`spring.hadoop.resourceManagerAddress`
Address of a YARN resource manager.

`spring.hadoop.resourceManagerSchedulerAddress`
Address of a YARN resource manager scheduler.

`spring.hadoop.resourceManagerHost`
 Hostname of a YARN resource manager.

`spring.hadoop.resourceManagerPort`
 Port of a YARN resource manager.

`spring.hadoop.resourceManagerSchedulerPort`
 Port of a YARN resource manager scheduler. This property is only needed for an application master.

Table 10.18. spring.yarn configuration properties

Property Name	Required	Type	Default Value
<code>spring.yarn.applicationDir</code>	No	String	null
<code>spring.yarn.applicationBaseDir</code>	No	String	null
<code>spring.yarn.applicationVersion</code>	No	String	null
<code>spring.yarn.stagingDir</code>	No	String	/spring/staging
<code>spring.yarn.appName</code>	No	String	null
<code>spring.yarn.appType</code>	No	String	YARN
<code>spring.yarn.defaultYarnAppClasspath</code>	No	String	null

`spring.yarn.applicationDir`

An application home directory in hdfs. If client copies files into a hdfs during an application submission, files will end up in this directory. If this property is omitted, a staging directory will be used instead.

`spring.yarn.applicationBaseDir`

An applications base directory where build-in application deployment functionality would create a new application instance. For a normal application submit operation, this is not needed.

`spring.yarn.applicationVersion`

An application version identifier used together with `applicationBaseDir` in deployment scenarios where `applicationDir` cannot be hard coded.

`spring.yarn.stagingDir`

A global staging base directory in hdfs.

`spring.yarn.appName`

Defines a registered application name visible from a YARN resource manager.

`spring.yarn.appType`

Defines a registered application type used in YARN resource manager.

`spring.yarn.defaultYarnAppClasspath`

Defines a default base YARN application classpath entries.

Table 10.19. spring.yarn.appmaster configuration properties

Property Name	Required	Type	Default Value
<code>spring.yarn.appmaster.appmasterClassNo</code>		Class	null

Property Name	Required	Type	Default Value
<code>spring.yarn.appmaster.containerCountNo</code>	No	Integer	1
<code>spring.yarn.appmaster.keepContextAlive</code>	No	Boolean	true

`spring.yarn.appmaster.appmasterClass`

Fully qualified classname which auto-configuration can automatically instantiate as a custom application master.

`spring.yarn.appmaster.containerCount`

Property which is automatically kept in configuration as a hint which an application master can choose to use when determining how many containers should be launched.

`spring.yarn.appmaster.keepContextAlive`

Setting for an application master runner to stop main thread to wait a latch before continuing. This is needed in cases where main thread needs to wait event from other threads to be able to exit.

Table 10.20. `spring.yarn.appmaster.launchcontext` configuration properties

Property Name	Required	Type	Default Value
<code>spring.yarn.appmaster.launchcontext.archiveFile</code>	No	String	null
<code>spring.yarn.appmaster.launchcontext.runnerClass</code>	No	Class	null
<code>spring.yarn.appmaster.launchcontext.options</code>	No	List	null
<code>spring.yarn.appmaster.launchcontext.arguments</code>	No	Map	null
<code>spring.yarn.appmaster.launchcontext.classpath</code>	No	List	null
<code>spring.yarn.appmaster.launchcontext.pathSeparator</code>	No	String	:
<code>spring.yarn.appmaster.launchcontext.includeBaseDirectory</code>	No	Boolean	true
<code>spring.yarn.appmaster.launchcontext.useDefaultYarnClasspath</code>	No	Boolean	true
<code>spring.yarn.appmaster.launchcontext.includeSystemClasspath</code>	No	Boolean	true
<code>spring.yarn.appmaster.launchcontext.locality</code>	No	Boolean	false

`spring.yarn.appmaster.launchcontext.archiveFile`

Indicates that a container main file is treated as executable jar or exploded zip.

`spring.yarn.appmaster.launchcontext.runnerClass`

Indicates a fully qualified class name for a container runner.

`spring.yarn.appmaster.launchcontext.options`

JVM system options.

`spring.yarn.appmaster.launchcontext.arguments`

Application arguments.

`spring.yarn.appmaster.launchcontext.classpath`

Additional classpath entries.

`spring.yarn.appmaster.launchcontext.pathSeparator`
Separator in a classpath.

`spring.yarn.appmaster.launchcontext.includeBaseDirectory`
If base directory should be added in a classpath.

`spring.yarn.appmaster.launchcontext.useDefaultYarnClasspath`
If default yarn application classpath should be added.

`spring.yarn.appmaster.launchcontext.includeSystemEnv`
If system environment variables are added to a container environment.

`spring.yarn.appmaster.launchcontext.locality`
If set to true indicates that resources are not relaxed.

Table 10.21. spring.yarn.appmaster.localizer configuration properties

Property Name	Required	Type	Default Value
<code>spring.yarn.appmaster.localizer.patterns</code>	No	List	null
<code>spring.yarn.appmaster.localizer.zipPattern</code>	No	String	null
<code>spring.yarn.appmaster.localizer.propertiesNames</code>	No	List	null
<code>spring.yarn.appmaster.localizer.propertiesSuffixes</code>	No	List	null

`spring.yarn.appmaster.localizer.patterns`
A simple patterns to choose localized files.

`spring.yarn.appmaster.localizer.zipPattern`
A simple pattern to mark a file as archive to be exploded.

`spring.yarn.appmaster.localizer.propertiesNames`
Base name of a configuration files.

`spring.yarn.appmaster.localizer.propertiesSuffixes`
Suffixes for a configuration files.

Table 10.22. spring.yarn.appmaster.resource configuration properties

Property Name	Required	Type	Default Value
<code>spring.yarn.appmaster.resource.priority</code>	No	String	null
<code>spring.yarn.appmaster.resource.memory</code>	No	String	null
<code>spring.yarn.appmaster.resource.virtualCores</code>	No	String	null

`spring.yarn.appmaster.resource.priority`
Container priority.

`spring.yarn.appmaster.resource.memory`
Container memory allocation.

`spring.yarn.appmaster.resource.virtualCores`
Container cpu allocation.

Table 10.23. *spring.yarn.client* configuration properties

Property Name	Required	Type	Default Value
<code>spring.yarn.client.files</code>	No	List	null
<code>spring.yarn.client.priority</code>	No	Integer	null
<code>spring.yarn.client.queue</code>	No	String	null
<code>spring.yarn.client.clientClass</code>	No	Class	null

`spring.yarn.client.files`

Files to copy into hdfs during application submission.

`spring.yarn.client.priority`

Application priority.

`spring.yarn.client.queue`

Application submission queue.

`spring.yarn.client.clientClass`

Fully qualified classname which auto-configuration can automatically instantiate as a custom client.

Table 10.24. *spring.yarn.client.launchcontext* configuration properties

Property Name	Required	Type	Default Value
<code>spring.yarn.client.launchcontext.archiveFile</code>	No	String	null
<code>spring.yarn.client.launchcontext.runnerClass</code>	No	Class	null
<code>spring.yarn.client.launchcontext.options</code>	No	List	null
<code>spring.yarn.client.launchcontext.arguments</code>	No	Map	null
<code>spring.yarn.client.launchcontext.classpath</code>	No	List	null
<code>spring.yarn.client.launchcontext.pathSeparator</code>	No	String	:
<code>spring.yarn.client.launchcontext.includeNodeBaseDir</code>	No	Boolean	true
<code>spring.yarn.client.launchcontext.useDefaultYarnClient</code>	No	Boolean	true
<code>spring.yarn.client.launchcontext.includeNodeSystemEnv</code>	No	Boolean	true

`spring.yarn.client.launchcontext.archiveFile`

Indicates that a container main file is treated as executable jar or exploded zip.

`spring.yarn.client.launchcontext.runnerClass`

Indicates a fully qualified class name for a container runner.

`spring.yarn.client.launchcontext.options`

JVM system options.

`spring.yarn.client.launchcontext.arguments`

Application arguments.

`spring.yarn.client.launchcontext.classpath`
Additional classpath entries.

`spring.yarn.client.launchcontext.pathSeparator`
Separator in a classpath.

`spring.yarn.client.launchcontext.includeBaseDirectory`
If base directory should be added in a classpath.

`spring.yarn.client.launchcontext.useDefaultYarnClasspath`
If default yarn application classpath should be added.

`spring.yarn.client.launchcontext.includeSystemEnv`
If system environment variables are added to a container environment.

Table 10.25. spring.yarn.client.localizer configuration properties

Property Name	Required	Type	Default Value
<code>spring.yarn.client.localizer.patterns</code>	No	List	null
<code>spring.yarn.client.localizer.zipPattern</code>	No	String	null
<code>spring.yarn.client.localizer.propertiesNames</code>	No	List	null
<code>spring.yarn.client.localizer.propertiesSuffixes</code>	No	List	null

`spring.yarn.client.localizer.patterns`
A simple patterns to choose localized files.

`spring.yarn.client.localizer.zipPattern`
A simple pattern to mark a file as archive to be exploded.

`spring.yarn.client.localizer.propertiesNames`
Base name of a configuration files.

`spring.yarn.client.localizer.propertiesSuffixes`
Suffixes for a configuration files.

Table 10.26. spring.yarn.client.resource configuration properties

Property Name	Required	Type	Default Value
<code>spring.yarn.client.resource.memory</code>	No	String	null
<code>spring.yarn.client.resource.virtualCores</code>	No	String	null

`spring.yarn.client.resource.memory`
Application master memory allocation.

`spring.yarn.client.resource.virtualCores`
Application master cpu allocation.

Table 10.27. spring.yarn.container configuration properties

Property Name	Required	Type	Default Value
<code>spring.yarn.container.keepContextAlive</code>	Yes	Boolean	true

Property Name	Required	Type	Default Value
<code>spring.yarn.container.containerClassNo</code>		Class	null

`spring.yarn.container.keepContextAlive`

Setting for an application container runner to stop main thread to wait a latch before continuing. This is needed in cases where main thread needs to wait event from other threads to be able to exit.

`spring.yarn.container.containerClass`

Fully qualified classname which auto-configuration can automatically instantiate as a custom container.

Table 10.28. spring.yarn.batch configuration properties

Property Name	Required	Type	Default Value
<code>spring.yarn.batch.name</code>	No	String	null
<code>spring.yarn.batch.enabled</code>	No	Boolean	false
<code>spring.yarn.batch.jobs</code>	No	List	null

`spring.yarn.batch.name`

Comma-delimited list of search patterns to find jobs to run defined either locally in application context or in job registry.

`spring.yarn.batch.enabled`

Indicates if batch processing on yarn is enabled.

`spring.yarn.batch.jobs`

Indicates a list of individual configuration properties for jobs.

Table 10.29. spring.yarn configuration properties

Property Name	Required	Type	Default Value
<code>spring.yarn.batch.jobs.name</code>	No	String	null
<code>spring.yarn.batch.jobs.enabled</code>	No	Boolean	false
<code>spring.yarn.batch.jobs.next</code>	No	Boolean	false
<code>spring.yarn.batch.jobs.failNext</code>	No	Boolean	false
<code>spring.yarn.batch.jobs.restart</code>	No	Boolean	false
<code>spring.yarn.batch.jobs.failRestart</code>	No	Boolean	false
<code>spring.yarn.batch.jobs.parameters</code>	No	String	null

Descriptions

`spring.yarn.batch.jobs.name`

Name of a job to configure.

`spring.yarn.batch.jobs.enabled`

Indicates if job is enabled.

`spring.yarn.batch.jobs.next`

Indicates if job parameters incrementer is used to prepare a job for next run.

`spring.yarn.batch.jobs.failNext`

Indicates if job execution should fail if job cannot be prepared for next execution.

`spring.yarn.batch.jobs.restart`

Indicates of job should be restarted.

`spring.yarn.batch.jobs.failRestart`

Indicates if job execution should fail if job cannot be restarted.

`spring.yarn.batch.jobs.parameters`

Defines a Map of additional job parameters. Keys and values are in normal format supported by Batch.

Controlling Applications

We've already talked about how resources are localized into a running container. These resources are always localized from a HDFS file system which effectively means that the whole process of getting application files into a newly launched YARN application is a two phase process; firstly files are copied into HDFS and secondly files are localized from a HDFS.

When application instance is submitted into YARN, there are two ways how these application files can be handled. First which is the most obvious is to just copy all the necessary files into a known location in HDFS and then instruct YARN to localize files from there. Second method is to split this into two different stages, first install application files into HDFS and then submit application from there. At first there seem to be no difference with these two ways to handle application deployment. However if files are always copied into HDFS when application is submitted, you need a physical access to those files. This may not always be possible so it's easier if you have a change to prepare these files by first installing application into HDFS and then just send a submit command to a YARN resource manager.

To ease a process of handling a full application life cycle, few utility classes exist which are meant to be used with Spring Boot. These classes are considered to be a foundational Boot application classes, not a ready packaged Boot executable jars. Instead you would use these from your own application whether that application is a Boot or other Spring based application.

Generic Usage

Internally these applications are executed using a `SpringApplicationBuilder` and a dedicated *Spring Application Context*. This allows to isolate Boot application instance from your current context if you have one. One fundamental idea in these applications is to make it possible to work with Spring profiles and Boot configuration properties. If your existing application is already using profiles and configuration properties, simply launching a new Boot would most likely derive those settings automatically which is something what you may not want.

`AbstractClientApplication` which all these built-in applications are based on contains methods to work with *Spring profiles* and additional configuration properties.

Let's go through all this using an example:

Using Configuration Properties

Below sample is pretty much a similar from all other examples except of two settings, `applicationBaseDir` and `clientClass`. Property `applicationBaseDir` defines where in HDFS

a new app will be installed. `DefaultApplicationYarnClient` defined using `clientClass` adds better functionality to guard against starting app which doesn't exist or not overwriting existing apps in HDFS.

```
spring:
  hadoop:
    fsUri: hdfs://localhost:8020
    resourceManagerHost: localhost
  yarn:
    appType: GS
    appName: gs-yarn-appmodel
    applicationBaseDir: /app/
    applicationDir: /app/gs-yarn-appmodel/
    client:
      clientClass: org.springframework.yarn.client.DefaultApplicationYarnClient
    files:
      - "file:build/libs/gs-yarn-appmodel-container-0.1.0.jar"
      - "file:build/libs/gs-yarn-appmodel-appmaster-0.1.0.jar"
    launchcontext:
      archiveFile: gs-yarn-appmodel-appmaster-0.1.0.jar
    appmaster:
      containerCount: 1
      launchcontext:
        archiveFile: gs-yarn-appmodel-container-0.1.0.jar
```

Using YarnPushApplication

`YarnPushApplication` is used to push your application into HDFS.

```
public void doInstall() {
    YarnPushApplication app = new YarnPushApplication();
    app.applicationVersion("version1");
    Properties instanceProperties = new Properties();
    instanceProperties.setProperty("spring.yarn.applicationVersion", "version1");
    app.configFile("application.properties", instanceProperties);
    app.run();
}
```

In above example we simply created a `YarnPushApplication`, set its `applicationVersion` and executed a `run` method. We also instructed `YarnPushApplication` to write used `applicationVersion` into a configuration file named `application.properties` so that it'd be available to an application itself.

Using YarnSubmitApplication

`YarnSubmitApplication` is used to submit your application from HDFS into YARN.

```
public void doSubmit() {
    YarnSubmitApplication app = new YarnSubmitApplication();
    app.applicationVersion("version1");
    ApplicationId applicationId = app.run();
}
```

In above example we simply created a `YarnSubmitApplication`, set its `applicationVersion` and executed a `run` method.

Using YarnInfoApplication

`YarnInfoApplication` is used to query application info from a YARN Resource Manager and HDFS.

```
public void doListPushed() {
    YarnInfoApplication app = new YarnInfoApplication();
    Properties appProperties = new Properties();

    appProperties.setProperty("spring.yarn.internal.YarnInfoApplication.operation", "PUSHED");
    app.appProperties(appProperties);
    String info = app.run();
    System.out.println(info);
}

public void doListSubmitted() {
    YarnInfoApplication app = new YarnInfoApplication();
    Properties appProperties = new Properties();

    appProperties.setProperty("spring.yarn.internal.YarnInfoApplication.operation", "SUBMITTED");
    appProperties.setProperty("spring.yarn.internal.YarnInfoApplication.verbose", "true");
    appProperties.setProperty("spring.yarn.internal.YarnInfoApplication.type", "GS");
    app.appProperties(appProperties);
    String info = app.run();
    System.out.println(info);
}
```

In above example we simply created a `YarnInfoApplication`, and used it to list installed and running applications. By adding `appProperties` will make Boot to pick these properties after every other source of configuration properties but still allows to pass command-line options to override everything which is a normal way in Boot.

Using YarnKillApplication

`YarnKillApplication` is used to kill running application instances.

```
public void doKill() {
    YarnKillApplication app = new YarnKillApplication();
    Properties appProperties = new Properties();

    appProperties.setProperty("spring.yarn.internal.YarnKillApplication.applicationId", "application_139505803");
    app.appProperties(appProperties);
    String info = app.run();
    System.out.println(info);
}
```

In above example we simply created a `YarnKillApplication`, and used it to send a application kill request into a YARN resource manager.

11. Testing Support

Hadoop testing has always been a cumbersome process especially if you try to do testing phase during the normal project build process. Traditionally developers have had few options like running Hadoop cluster either as a local or pseudo-distributed mode and then utilise that to run MapReduce jobs. Hadoop project itself is using a lot of mini clusters during the tests which provides better tools to run your code in an isolated environment.

Spring Hadoop and especially its Yarn module faced similar testing problems. Spring Hadoop provides testing facilities order to make testing on Hadoop much easier especially if code relies on Spring Hadoop itself. These testing facilities are also used internally to test Spring Hadoop, although some test cases still rely on a running Hadoop instance on a host where project build is executed.

Two central concepts of testing using Spring Hadoop is, firstly fire up the mini cluster and secondly use the configuration prepared by the mini cluster to talk to the Hadoop components. Now let's go through the general testing facilities offered by Spring Hadoop.

Testing for MapReduce and Yarn in Spring Hadoop is separated into different packages mostly because these two components doesn't have hard dependencies with each others. You will see a lot of similarities when creating tests for MapReduce and Yarn.

11.1 Testing MapReduce

Mini Clusters for MapReduce

Mini clusters usually contain testing components from a Hadoop project itself. These are clusters for *MapReduce Job* handling and *HDFS* which are all run within a same process. In Spring Hadoop mini clusters are implementing interface `HadoopCluster` which provides methods for lifecycle and configuration. *Spring Hadoop* provides transitive maven dependencies against different *Hadoop* distributions and thus mini clusters are started using different implementations. This is mostly because we want to support *HadoopV1* and *HadoopV2* at a same time. All this is handled automatically at runtime so everything should be transparent to the end user.

```
public interface HadoopCluster {
    Configuration getConfiguration();
    void start() throws Exception;
    void stop();
    FileSystem getFileSystem() throws IOException;
}
```

Currently one implementation named *StandaloneHadoopCluster* exists which supports simple cluster type where a number of nodes can be defined and then all the nodes will contain utilities for *MapReduce Job* handling and *HDFS*.

There are few ways how this cluster can be started depending on a use case. It is possible to use `StandaloneHadoopCluster` directly or configure and start it through `HadoopClusterFactoryBean`. Existing `HadoopClusterManager` is used in unit tests to cache running clusters.

Note

It's advisable not to use `HadoopClusterManager` outside of tests because literally it is using static fields to cache cluster references. This is a same concept used in *Spring Test* order to cache application contexts between the unit tests within a jvm.

```
<bean id="hadoopCluster" class="org.springframework.data.hadoop.test.support.HadoopClusterFactoryBean">
  <property name="clusterId" value="HadoopClusterTests"/>
  <property name="autoStart" value="true"/>
  <property name="nodes" value="1"/>
</bean>
```

Example above defines a bean named `hadoopCluster` using a factory bean `HadoopClusterFactoryBean`. It defines a simple one node cluster which is started automatically.

Configuration

Spring Hadoop components usually depend on *Hadoop* configuration which is then wired into these components during the application context startup phase. This was explained in previous chapters so we don't go through it again. However this is now a catch-22 because we need the configuration for the context but it is not known until mini cluster has done its startup magic and prepared the configuration with correct values reflecting current runtime status of the cluster itself. Solution for this is to use other bean named `ConfigurationDelegatingFactoryBean` which will simply delegate the configuration request into the running cluster.

```
<bean id="hadoopConfiguredConfiguration" class="org.springframework.data.hadoop.test.support.ConfigurationDelegatingFactoryBean">
  <property name="cluster" ref="hadoopCluster"/>
</bean>

<hdp:configuration id="hadoopConfiguration" configuration-
ref="hadoopConfiguredConfiguration"/>
```

In the above example we created a bean named `hadoopConfiguredConfiguration` using `ConfigurationDelegatingFactoryBean` which simple delegates to `hadoopCluster` bean. Returned bean `hadoopConfiguredConfiguration` is type of *Hadoop's* `Configuration` object so it could be used as it is.

Latter part of the example show how *Spring Hadoop* namespace is used to create another `Configuration` object which is using `hadoopConfiguredConfiguration` as a reference. This scenario would make sense if there is a need to add additional configuration options into running configuration used by other components. Usually it is suiteable to use cluster prepared configuration as it is.

Simplified Testing

It is perfectly all right to create your tests from scratch and for example create the cluster manually and then get the runtime configuration from there. This just needs some boilerplate code in your context configuration and unit test lifecycle.

Spring Hadoop adds additional facilities for the testing to make all this even easier.

```

@RunWith(SpringJUnit4ClassRunner.class)
public abstract class AbstractHadoopClusterTests implements ApplicationContextAware {
    ...
}

@ContextConfiguration(loader=HadoopDelegatingSmartContextLoader.class)
@MiniHadoopCluster
public class ClusterBaseTestClassTests extends AbstractHadoopClusterTests {
    ...
}

```

Above example shows the `AbstractHadoopClusterTests` and how `ClusterBaseTestClassTests` is prepared to be aware of a mini cluster. `HadoopDelegatingSmartContextLoader` offers same base functionality as the default `DelegatingSmartContextLoader` in a `spring-test` package. One additional thing what `HadoopDelegatingSmartContextLoader` does is to automatically handle running clusters and inject `Configuration` into the application context.

```

@MiniHadoopCluster(configName="hadoopConfiguration", clusterName="hadoopCluster", nodes=1,
id="default")

```

Generally `@MiniHadoopCluster` annotation allows you to define injected bean name for mini cluster, its `Configurations` and a number of nodes you like to have in a cluster.

Spring Hadoop testing is dependant of general facilities of *Spring Test framework* meaning that everything what is cached during the test are reusable withing other tests. One need to understand that if *Hadoop* mini cluster and its `Configuration` is injected into an `Application Context`, caching happens on a mercy of a `Spring Testing` meaning if a test `Application Context` is cached also mini cluster instance is cached. While caching is always preferred, one needs to understand that if tests are expecting vanilla environment to be present, test context should be dirtied using `@DirtiesContext` annotation.

Wordcount Example

Let's study a proper example of existing *MapReduce Job* which is executed and tested using *Spring Hadoop*. This example is the *Hadoop's* classic wordcount. We don't go through all the details of this example because we want to concentrate on testing specific code and configuration.

```
<context:property-placeholder location="hadoop.properties" />

<hdp:job id="wordcountJob"
  input-path="${wordcount.input.path}"
  output-path="${wordcount.output.path}"
  libs="file:build/libs/mapreduce-examples-wordcount-*.jar"
  mapper="org.springframework.data.hadoop.examples.TokenizerMapper"
  reducer="org.springframework.data.hadoop.examples.IntSumReducer" />

<hdp:script id="setupScript" location="copy-files.groovy">
  <hdp:property name="localSourceFile" value="data/nietzsche-chapter-1.txt" />
  <hdp:property name="inputDir" value="${wordcount.input.path}" />
  <hdp:property name="outputDir" value="${wordcount.output.path}" />
</hdp:script>

<hdp:job-runner id="runner"
  run-at-startup="false"
  kill-job-at-shutdown="false"
  wait-for-completion="false"
  pre-action="setupScript"
  job-ref="wordcountJob" />
```

In above configuration example we can see few differences with the actual runtime configuration. Firstly you can see that we didn't specify any kind of configuration for hadoop. This is because it's injected automatically by testing framework. Secondly because we want to explicitly wait the job to be run and finished, *kill-job-at-shutdown* and *wait-for-completion* are set to *false*.


```

@ContextConfiguration(loader=HadoopDelegatingSmartContextLoader.class)
@MiniHadoopCluster
public class WordcountTests extends AbstractMapReduceTests {
    @Test
    public void testWordcountJob() throws Exception {
        // run blocks and throws exception if job failed
        JobRunner runner = getApplicationContext().getBean("runner", JobRunner.class);
        Job wordcountJob = getApplicationContext().getBean("wordcountJob", Job.class);

        runner.call();

        JobStatus finishedStatus = waitFinishedStatus(wordcountJob, 60, TimeUnit.SECONDS);
        assertNotNull(finishedStatus);

        // get output files from a job
        Path[] outputFiles = getOutputFilePaths("/user/gutenberg/output/word/");
        assertEquals(1, outputFiles.length);
        assertTrue(getFileSystem().getFileStatus(outputFiles[0]).getLen(), greaterThan(0L));

        // read through the file and check that line with
        // "themselves 6" was found
        boolean found = false;
        InputStream in = getFileSystem().open(outputFiles[0]);
        BufferedReader reader = new BufferedReader(new InputStreamReader(in));
        String line = null;
        while ((line = reader.readLine()) != null) {
            if (line.startsWith("themselves")) {
                assertTrue(line, is("themselves\t6"));
                found = true;
            }
        }
        reader.close();
        assertTrue("Keyword 'themselves' not found", found);
    }
}

```

In above unit test class we simply run the job defined in xml, explicitly wait it to finish and then check the output content from *HDFS* by searching expected strings.

11.2 Testing Yarn

Mini Clusters for Yarn

Mini cluster usually contain testing components from a *Hadoop* project itself. These are *MiniYARNCluster* for Resource Manager and *MiniDFSCluster* for Datanode and Namenode which are all run within a same process. In *Spring Hadoop* mini clusters are implementing interface *YarnCluster* which provides methods for lifecycle and configuration.

```

public interface YarnCluster {
    Configuration getConfiguration();
    void start() throws Exception;
    void stop();
    File getYarnWorkDir();
}

```

Currently one implementation named *StandaloneYarnCluster* exists which supports simple cluster type where a number of nodes can be defined and then all the nodes will have *Yarn Node Manager* and *Hdfs Datanode*, additionally a *Yarn Resource Manager* and *Hdfs Namenode* components are started.

There are few ways how this cluster can be started depending on a use case. It is possible to use `StandaloneYarnCluster` directly or configure and start it through `YarnClusterFactoryBean`. Existing `YarnClusterManager` is used in unit tests to cache running clusters.

Note

It's advisable not to use `YarnClusterManager` outside of tests because literally it is using static fields to cache cluster references. This is a same concept used in *Spring Test* order to cache application contexts between the unit tests within a jvm.

```
<bean id="yarnCluster" class="org.springframework.yarn.test.support.YarnClusterFactoryBean">
  <property name="clusterId" value="YarnClusterTests"/>
  <property name="autoStart" value="true"/>
  <property name="nodes" value="1"/>
</bean>
```

Example above defines a bean named `yarnCluster` using a factory bean `YarnClusterFactoryBean`. It defines a simple one node cluster which is started automatically. Cluster working directories would then exist under below paths:

```
target/YarnClusterTests/
target/YarnClusterTests-dfs/
```

Note

We rely on base classes from a *Hadoop* distribution and target base directory is hardcoded in Hadoop and is not configurable.

Configuration

Spring Yarn components usually depend on *Hadoop* configuration which is then wired into these components during the application context startup phase. This was explained in previous chapters so we don't go through it again. However this is now a catch-22 because we need the configuration for the context but it is not known until mini cluster has done its startup magic and prepared the configuration with correct values reflecting current runtime status of the cluster itself. Solution for this is to use other factory bean class named `ConfigurationDelegatingFactoryBean` which will simple delegate the configuration request into the running cluster.

```
<bean id="yarnConfiguredConfiguration" class="org.springframework.yarn.test.support.ConfigurationDelegatingFactoryBean">
  <property name="cluster" ref="yarnCluster"/>
</bean>

<yarn:configuration id="yarnConfiguration" configuration-
ref="yarnConfiguredConfiguration"/>
```

In the above example we created a bean named `yarnConfiguredConfiguration` using `ConfigurationDelegatingFactoryBean` which simple delegates to `yarnCluster` bean. Returned bean `yarnConfiguredConfiguration` is type of *Hadoop's* `Configuration` object so it could be used as it is.

Latter part of the example show how *Spring Yarn* namespace is used to create another `Configuration` object which is using `yarnConfiguredConfiguration` as a reference. This scenario would make sense if there is a need to add additional configuration options into running configuration used by other components. Usually it is suiteable to use cluster prepared configuration as it is.

Simplified Testing

It is perfectly all right to create your tests from scratch and for example create the cluster manually and then get the runtime configuration from there. This just needs some boilerplate code in your context configuration and unit test lifecycle.

Spring Hadoop adds additional facilities for the testing to make all this even easier.

```
@RunWith(SpringJUnit4ClassRunner.class)
public abstract class AbstractYarnClusterTests implements ApplicationContextAware {
    ...
}

@ContextConfiguration(loader=YarnDelegatingSmartContextLoader.class)
@MiniYarnCluster
public class ClusterBaseTestClassTests extends AbstractYarnClusterTests {
    ...
}
```

Above example shows the `AbstractYarnClusterTests` and how `ClusterBaseTestClassTests` is prepared to be aware of a mini cluster. `YarnDelegatingSmartContextLoader` offers same base functionality as the default `DelegatingSmartContextLoader` in a `spring-test` package. One additional thing what `YarnDelegatingSmartContextLoader` does is to automatically handle running clusters and inject `Configuration` into the application context.

```
@MiniYarnCluster(configName="yarnConfiguration", clusterName="yarnCluster", nodes=1,
id="default")
```

Generally `@MiniYarnCluster` annotation allows you to define injected bean names for mini cluster, its `Configurations` and a number of nodes you like to have in a cluster.

Spring Hadoop Yarn testing is dependant of general facilities of *Spring Test* framework meaning that everything what is cached during the test are reusable withing other tests. One need to understand that if *Hadoop* mini cluster and its `Configuration` is injected into an `Application Context`, caching happens on a mercy of a `Spring Testing` meaning if a test `Application Context` is cached also mini cluster instance is cached. While caching is always preferred, one needs to understand that if tests are expecting vanilla environment to be present, test context should be dirtied using `@DirtiesContext` annotation.

Spring Test Context configuration works exactly like you'd work with any other *Spring Test* based tests. It defaults on finding xml based config and fall back to Annotation based config. For example if one is working with *JavaConfig* a simple static configuration class can be used within the test class.

For test cases where additional context configuration is not needed a simple helper annotation `@MiniYarnClusterTest` can be used.

```
@MiniYarnClusterTest
public class ActivatorTests extends AbstractBootYarnClusterTests {
    @Test
    public void testSomething(){
        ...
    }
}
```

In above example a simple test case was created using annotation `@MiniYarnClusterTest`. Behind a scenes it's using junit and prepares a YARN minicluster for you and injects needed configuration for you.

Drawback of using a composed annotation like this is that the `@Configuration` is then applied from an annotation class itself and user can't no longer add a static `@Configuration` class in a test class itself and expect Spring to pick it up from there which is a normal behaviour in Spring testing support. If user wants to use a simple composed annotation and use a custom `@Configuration`, one can simply duplicate functionality of this `@MiniYarnClusterTest` annotation.

```

@Retention(RetentionPolicy.RUNTIME)
@Target(ElementType.TYPE)
@ContextConfiguration(loader=YarnDelegatingSmartContextLoader.class)
@MiniYarnCluster
public @interface CustomMiniYarnClusterTest {

    @Configuration
    public static class Config {
        @Bean
        public String myCustomBean() {
            return "myCustomBean";
        }
    }
}

@RunWith(SpringJUnit4ClassRunner.class)
@CustomMiniYarnClusterTest
public class ComposedAnnotationTests {

    @Autowired
    private ApplicationContext ctx;

    @Test
    public void testBean() {
        assertTrue(ctx.containsBean("myCustomBean"));
    }
}

```

In above example a custom composed annotation `@CustomMiniYarnClusterTest` was created and then used within a test class. This a great way to put your configuration in one place and still keep your test class relatively non-verbose.

Multi Context Example

Let's study a proper example of existing Spring Yarn application and how this is tested during the build process. Multi Context Example is a simple Spring Yarn based application which simply launches Application Master and four Containers and within those containers a custom code is executed. In this case simply a log message is written.

In real life there are different ways to test whether Hadoop Yarn application execution has been successful or not. The obvious method would be to check the application instance execution status reported by Hadoop Yarn. Status of the execution doesn't always tell the whole truth so i.e. if application is about to write something into HDFS as an output that could be used to check the proper outcome of an execution.

This example doesn't write anything into HDFS and anyway it would be out of scope of this document for obvious reason. It is fairly straightforward to check file content from HDFS. One other interesting method is simply to check application log files that being the Application Master and Container logs. Test methods can check exceptions or expected log entries from a log files to determine whether test is successful or not.

In this chapter we don't go through how Multi Context Example is configured and what it actually does, for that read the documentation about the examples. However we go through what needs to be done order to test this example application using testing support offered by Spring Hadoop.

In this example we gave instructions to copy library dependencies into Hdfs and then those entries were used within resource localizer to tell Yarn to copy those files into Container working directory. During the unit testing when mini cluster is launched there are no files present in Hdfs because cluster is initialized from scratch. Fortunately Spring Hadoop allows you to copy files into Hdfs during the localization process from a local file system where Application Context is executed. Only thing we need is the actual library files which can be assembled during the build process. Spring Hadoop Examples build system rely on Gradle so collecting dependencies is an easy task.

```
<yarn:localresources>
  <yarn:hdfs path="/app/multi-context/*.jar"/>
  <yarn:hdfs path="/lib/*.jar"/>
</yarn:localresources>
```

Above configuration exists in application-context.xml and appmaster-context.xml files. This is a normal application configuration expecting static files already be present in Hdfs. This is usually done to minimize latency during the application submission and execution.

```
<yarn:localresources>
  <yarn:copy src="file:build/dependency-libs/*" dest="/lib"/>
  <yarn:copy src="file:build/libs/*" dest="/app/multi-context"/>
  <yarn:hdfs path="/app/multi-context/*.jar"/>
  <yarn:hdfs path="/lib/*.jar"/>
</yarn:localresources>
```

Above example is from MultiContextTest-context.xml which provides the runtime context configuration talking with mini cluster during the test phase.

When we do context configuration for YarnClient during the testing phase all we need to do is to add copy elements which will transfer needed libraries into Hdfs before the actual localization process will fire up. When those files are copied into Hdfs running in a mini cluster we're basically in a same point if using a real Hadoop cluster with existing files.

Note

Running tests which depends on copying files into Hdfs it is mandatory to use build system which is able to prepare these files for you. You can't do this within IDE's which have its own ways to execute unit tests.

The complete example of running the test, checking the application execution status and finally checking the expected state of log files:

```

@ContextConfiguration(loader=YarnDelegatingSmartContextLoader.class)
@MiniYarnCluster
public class MultiContextTests extends AbstractYarnClusterTests {
    @Test
    @Timed(millis=70000)
    public void testAppSubmission() throws Exception {
        YarnApplicationState state = submitApplicationAndWait();
        assertNotNull(state);
        assertTrue(state.equals(YarnApplicationState.FINISHED));

        File workDir = getYarnCluster().getYarnWorkDir();

        PathMatchingResourcePatternResolver resolver = new
PathMatchingResourcePatternResolver();
        String locationPattern = "file:" + workDir.getAbsolutePath() + "**/*.std*";
        Resource[] resources = resolver.getResources(locationPattern);

        // appmaster and 4 containers should
        // make it 10 log files
        assertThat(resources, notNullValue());
        assertThat(resources.length, is(10));

        for (Resource res : resources) {
            File file = res.getFile();
            if (file.getName().endsWith("stdout")) {
                // there has to be some content in stdout file
                assertThat(file.length(), greaterThan(0L));
                if (file.getName().equals("Container.stdout")) {
                    Scanner scanner = new Scanner(file);
                    String content = scanner.useDelimiter("\\A").next();
                    scanner.close();
                    // this is what container will log in stdout
                    assertThat(content, containsString("Hello from MultiContextBeanExample"));
                }
            } else if (file.getName().endsWith("stderr")) {
                // can't have anything in stderr files
                assertThat(file.length(), is(0L));
            }
        }
    }
}

```

11.3 Testing Boot Based Applications

In previous sections we showed a generic concepts of unit testing in *Spring Hadoop* and *Spring YARN*. We also have a first class support for testing *Spring Boot* based applications made for YARN.

```

@MiniYarnClusterTest
public class AppTests extends AbstractBootYarnClusterTests {

    @Test
    public void testApp() throws Exception {
        ApplicationInfo info = submitApplicationAndWait(ClientApplication.class, new
String[0]);
        assertThat(info.getYarnApplicationState(), is(YarnApplicationState.FINISHED));

        List<Resource> resources = ContainerLogUtils.queryContainerLogs(
            getYarnCluster(), info.getApplicationId());
        assertThat(resources, notNullValue());
        assertThat(resources.size(), is(4));

        for (Resource res : resources) {
            File file = res.getFile();
            String content = ContainerLogUtils.getFileContent(file);
            if (file.getName().endsWith("stdout")) {
                assertThat(file.length(), greaterThan(0L));
                if (file.getName().equals("Container.stdout")) {
                    assertThat(content, containsString("Hello from HelloPojo"));
                }
            } else if (file.getName().endsWith("stderr")) {
                assertThat("stderr with content: " + content, file.length(), is(0L));
            }
        }
    }
}

```

Let's go through step by step what's happening in this JUnit class. As already mentioned earlier we don't need any existing or running Hadoop instances, instead testing framework from Spring YARN provides an easy way to fire up a mini cluster where your tests can be run in an isolated environment.

- `@ContextConfiguration` together with `YarnDelegatingSmartContextLoader` tells Spring to prepare a testing context for a mini cluster. `EmptyConfig` is a simple helper class to use if there are no additional configuration for tests.
- `@MiniYarnCluster` tells Spring to start a Hadoop's mini cluster having components for *HDFS* and *YARN*. Hadoop's configuration from this minicluster is automatically injected into your testing context.
- `@MiniYarnClusterTest` is basically a replacement of `@MiniYarnCluster` and `@ContextConfiguration` having an empty context configuration.
- `AbstractBootYarnClusterTests` is a class containing a lot of base functionality what you need in your tests.

Then it's time to deploy the application into a running minicluster

- `submitApplicationAndWait()` method simply runs your `ClientApplication` and expects it to an application deployment. On default it will wait 60 seconds an application to finish and returns an current state.
- We make sure that we have a correct application state

We use `ContainerLogUtils` to find our container logs files from a minicluster.

- We assert count of a log files

- We expect some specified content from log file
- We expect stderr files to be empty

Part III. Developing Spring for Apache Hadoop Applications

This section provides some guidance on how one can use the Spring for Apache Hadoop project in conjunction with other Spring projects, starting with the Spring Framework itself, then Spring Batch, and then Spring Integration.

12. Guidance and Examples

Spring for Apache Hadoop provides integration with the Spring Framework to create and run Hadoop MapReduce, Hive, and Pig jobs as well as work with HDFS and HBase. If you have simple needs to work with Hadoop, including basic scheduling, you can add the Spring for Apache Hadoop namespace to your Spring based project and get going quickly using Hadoop.

As the complexity of your Hadoop application increases, you may want to use Spring Batch to regain on the complexity of developing a large Hadoop application. Spring Batch provides an extension to the Spring programming model to support common batch job scenarios characterized by the processing of large amounts of data from flat files, databases and messaging systems. It also provides a workflow style processing model, persistent tracking of steps within the workflow, event notification, as well as administrative functionality to start/stop/restart a workflow. As Spring Batch was designed to be extended, Spring for Apache Hadoop plugs into those extensibility points, allowing for Hadoop related processing to be a first class citizen in the Spring Batch processing model.

Another project of interest to Hadoop developers is Spring Integration. Spring Integration provides an extension of the Spring programming model to support the well-known [Enterprise Integration Patterns](#). It enables lightweight messaging *within* Spring-based applications and supports integration with external systems via declarative adapters. These adapters are of particular interest to Hadoop developers, as they directly support common Hadoop use-cases such as polling a directory or FTP folder for the presence of a file or group of files. Then once the files are present, a message is sent internally to the application to do additional processing. This additional processing can be calling a Hadoop MapReduce job directly or starting a more complex Spring Batch based workflow. Similarly, a step in a Spring Batch workflow can invoke functionality in Spring Integration, for example to send a message through an email adapter.

No matter if you use the Spring Batch project with the Spring Framework by itself or with additional extensions such as Spring Batch and Spring Integration that focus on a particular domain, you will benefit from the core values that Spring projects bring to the table, namely enabling modularity, reuse and extensive support for unit and integration testing.

12.1 Scheduling

Spring Batch integrates with a variety of job schedulers and is not a scheduling framework. There are many good enterprise schedulers available in both the commercial and open source spaces such as Quartz, Tivoli, Control-M, etc. It is intended to work in conjunction with a scheduler, not replace a scheduler. As a lightweight solution, you can use Spring's built in scheduling support that will give you cron-like and other basic scheduling trigger functionality. See the [Task Execution and Scheduling](#) documentation for more info. A middle ground it to use Spring's Quartz integration, see [Using the OpenSymphony Quartz Scheduler](#) for more information. The Spring Batch distribution contains an example, but this documentation will be updated to provide some more directed examples with Hadoop, check for updates on the [main web site of Spring for Apache Hadoop](#).

12.2 Batch Job Listeners

Spring Batch lets you attach listeners at the job and step levels to perform additional processing. For example, at the end of a job you can perform some notification or perhaps even start another Spring Batch job. As a brief example, implement the interface [JobExecutionListener](#) and configure it into the Spring Batch job as shown below.

```
<batch:job id="job1">
  <batch:step id="import" next="wordcount">
    <batch:tasklet ref="script-tasklet"/>
  </batch:step>

  <batch:step id="wordcount">
    <batch:tasklet ref="wordcount-tasklet" />
  </batch:step>

  <batch:listeners>
    <batch:listener ref="simpleNotificatonListener"/>
  </batch:listeners>
</batch:job>

<bean id="simpleNotificatonListener" class="com.mycompany.myapp.SimpleNotificationListener"/>
</bean>
```

Part IV. Spring for Apache Hadoop sample applications

Document structure

The sample applications have been moved into their own repository so they can be developed independently of the Spring for Apache Hadoop release cycle. They can be found on GitHub <https://github.com/spring-projects/spring-hadoop-samples/>.

The [wiki page](#) for the Spring for Apache Hadoop project has more documentation for building and running the examples and there is also some instructions in the *README* file of each example.

Part V. Other Resources

In addition to this reference documentation, there are a number of other resources that may help you learn how to use Hadoop and Spring framework. These additional, third-party resources are enumerated in this section.

13. Useful Links

- *Spring for Apache Hadoop* - [Home Page](#)
- *Spring Data* - [Home Page](#)
- *Spring Data Book* - [Home Page](#)
- *Spring* - [Blog](#)
- *Apache Hadoop* - [Home Page](#)
- *Pivotal HD* - [Home Page](#)

Part VI. Appendices

Appendix A. Using Spring for Apache Hadoop with Amazon EMR

A popular option for creating on-demand Hadoop cluster is Amazon Elastic Map Reduce or [Amazon EMR service](#). The user can through the command-line, API or a web UI configure, start, stop and manage a Hadoop cluster in the *cloud* without having to worry about the actual set-up or hardware resources used by the cluster. However, as the setup is different then a *locally* available cluster, so does the interaction between the application that want to use it and the target cluster. This section provides information on how to setup Amazon EMR with Spring for Apache Hadoop so the changes between a using a local, pseudo-distributed or owned cluster and EMR are minimal.



Important

This chapter assumes the user is familiar with Amazon EMR and the [cost](#) associated with it and its related services - we strongly recommend getting familiar with the official EMR [documentation](#).

One of the big differences when using Amazon EMR versus a local cluster is the lack of access of the file system server and the job tracker. This means submitting jobs or reading and writing to the file-system isn't available out of the box - which is understandable for security reasons. If the cluster would be open, it could be easily abused while charging its rightful owner. However, it is fairly straight-forward to get access to both the file system and the job tracker so the deployment flow does not have to change.

Amazon EMR allows clusters to be created through the management console, through the API or the command-line. This documentation will focus on the [command-line](#) but the setup is not limited to it - feel free to adjust it according to your needs or preference. Make sure to properly setup the [credentials](#) so that the S3 file-system can be properly accessed.

A.1 Start up the cluster



Important

Make sure you read the whole chapter before starting up the EMR cluster

A nice feature of Amazon EMR is starting a cluster for an indefinite period. That is rather than submitting a job and creating the cluster until it finished, one can create a cluster (along side a job) but request to be kept *alive* even if there is no work for it. This is [easily done](#) through the `--create --alive` parameters:

```
./elastic-mapreduce --create --alive
```

The output will be similar to this:

```
Created job flowJobFlowID
```

One can verify the results in the console through the `list` command or through the web management console. Depending on the cluster setup and the user account, the Hadoop cluster initialization should be complete anywhere between 1 to 5 minutes. The cluster is ready once its state changes from `STARTING/PROVISIONING` to `WAITING`.



Note

By default, each newly created cluster has a new public IP that is not typically reused. To simplify the setup, one can use [Amazon Elastic IP](#), that is a static, predefined IP, so that she knows

before-hand the cluster address. Refer to [this](#) section inside the EMR documentation for more information. As an alternative, one can use the [EC2 API](#) in combination with the [EMR API](#) to retrieve the private IP of address of the master node of her cluster or even programatically configure and start the EMR cluster on demand without having to hard-code the private IPs.

However, to remotely access the cluster from outside (as oppose to just running a jar within the cluster), one needs to tweak the cluster settings just a tiny bit - as mentioned below.

A.2 Open an SSH Tunnel as a SOCKS proxy

Due to security reasons, the EMR cluster is not exposed to the outside world and is bound only to the machine internal IP. While you can open up the firewall to allow access (note that you also have to do some port forwarding since again, Hadoop is bound to the cluster internal IP rather than all available network cards), it is recommended to use a SSH tunnel instead. The SSH tunnel provides a secure connection between your machine on the cluster preventing any snooping or man-in-the-middle attacks. Further more it is quite easy to automate and be executed along side the cluster creation, programmatically or through some script. The Amazon EMR docs have dedicated sections on [SSH Setup and Configuration](#) and on opening a [SSH Tunnel to the master node](#) so please refer to them. Make sure to setup the SSH tunnel as a SOCKS proxy, that is to redirect all calls to remote ports - this is crucial when working with Hadoop (or other applications) that use a range of ports for communication.

A.3 Configuring Hadoop to use a SOCKS proxy

Once the tunnel or the SOCKS proxy is in place, one needs to configure Hadoop to use it. By default, Hadoop makes connections directly to its target which is fine for regular use, but in this case, we need to use the SOCKS proxy to pass through the firewall. One can do so through the `hadoop.rpc.socket.factory.class.default` and `hadoop.socks.server` properties:

```
hadoop.rpc.socket.factory.class.default=org.apache.hadoop.net.SocksSocketFactory
# this configure assumes the SOCKS proxy is opened on local port 6666
hadoop.socks.server=localhost:6666
```

At this point, all Hadoop communication will go through the SOCKS proxy at localhost on port 6666. The main advantage is that all the IPs, domain names, ports are resolved on the 'remote' side of the proxy so one can just start using the remote cluster IPs. However, only the Hadoop client needs to use the proxy - to avoid having the client configuration be read by the cluster nodes (which would mean the nodes would try to use a SOCKS proxy on the remote side as well), make sure the master node (and thus all its nodes) `hadoop-site.xml` marks the default network setting as final (see this [blog post](#) for a detailed explanation):

```
<property>
  <name>hadoop.rpc.socket.factory.class.default</name>
  <value>org.apache.hadoop.net.StandardSocketFactory</value>
  <final>true</final>
</property>
```

Simply pass this configuration (and other options that you might have) to the master node using a [bootstrap](#) action. One can find this file ready for usage, already deployed to Amazon S3 at [s3://dist.springframework.org/release/SHDP/emr-settings.xml](#). Simply pass the file to command-line used for firing up the EMR cluster:

```
./elastic-mapreduce --create --alive --bootstrap-action s3://elasticmapreduce/bootstrap-
actions/configure-hadoop --args "--site-config-file,s3://dist.springframework.org/release/
SHDP/emr-settings.xml"
```



Note

For security reasons, we recommend copying the 'emr-settings.xml' file to one of your S3 buckets and use that location instead.

A.4 Accessing the file-system

Amazon EMR offers Simple Storage Service, also known as [S3](#) service, as means for durable read-write storage for EMR. While the cluster is active, one can write additional data to HDFS but unless S3 is used, the data will be lost once the cluster shuts down. Note that when using an S3 location for the first time, the proper [access permissions](#) needs to be setup. Accessing S3 is easier then the job tracker - in fact the Hadoop distribution provides not one but two file-system [implementations for S3](#):

Table A.1. Hadoop S3 File Systems

Name	URI Prefix	Access Method	Description
S3 Native FS	s3n://	S3 Native	Native access to S3. The recommended file-system as the data is read/written in its native format and can be used not just by Hadoop but also other systems without any translation. The downside is that it does not support large files (5GB) out of the box (though there is a work-around through the multipart upload feature).
S3 Block FS	s3://	Block Based	The files are stored as blocks (similar to the underlying structure in HDFS). This is somewhat more efficient in terms of renames and file sizes but requires a dedicated bucket and is not inter-operable with other S3 tools.

To access the data in S3 one can either use an HDFS file-system on top of it, which requires no extra setup, or copy the data from S3 to the HDFS cluster using manual tools, [distcp with S3](#), its dedicated version [s3distcp](#), Hadoop [DistributedCache](#) (which SHDP [supports](#) as well) or third-party tools such as [s3cmd](#).

For newbies and development we recommend accessing the S3 directly through the File-System abstraction as in most cases, its performance is close to that of the data inside the native HDFS. When dealing with data that is read multiple times, copying the data from S3 locally inside the cluster might improve performance but we advice running some performance tests first.

A.5 Shutting down the cluster

Once the cluster is no longer needed for a longer period of time, one can shut it down fairly [straight forward](#):

```
./elastic-mapreduce --terminate JobFlowID
```

Note that the EMR cluster is billed by the hour and since the time is rounded upwards, starting and shutting down the cluster repeatedly might end up being more expensive than just keeping it alive. Consult the [documentation](#) for more information.

A.6 Example configuration

To put it all together, to use Amazon EMR one can use the following work-flow with SHDP:

- Start an *alive* cluster using the bootstrap action to guarantee the cluster does NOT use a socks proxy. Open a SSH tunnel, in SOCKS mode, to the EMR cluster. Start the cluster for an indefinite period. Once the server is up, create an SSH tunnel, in SOCKS mode, to the remote cluster. This allows the client to communicate directly with the remote nodes as if they are part of the same network. This step does not have to be repeated unless the cluster is terminated - one can (and should) submit multiple jobs to it.
- Configure SHDP
- Once the cluster is up and the SSH tunnel/SOCKS proxy is in place, point SHDP to the new configuration. The example below shows how the configuration can look like:

hadoop-context.xml

```
<beans xmlns="http://www.springframework.org/schema/beans"
  xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
  xmlns:context="http://www.springframework.org/schema/context"
  xmlns:hdp="http://www.springframework.org/schema/hadoop"
  xsi:schemaLocation="http://www.springframework.org/schema/beans http://
www.springframework.org/schema/beans/spring-beans.xsd
  http://www.springframework.org/schema/context http://www.springframework.org/schema/
context/spring-context.xsd
  http://www.springframework.org/schema/hadoop http://www.springframework.org/schema/
hadoop/spring-hadoop.xsd">

  <!-- property placeholder backed by hadoop.properties -->
  <context:property-placeholder location="hadoop.properties"/>

  <!-- Hadoop FileSystem using a placeholder and emr.properties -->
  <hdp:configuration properties-location="emr.properties" file-system-uri="${hd.fs}" job-
tracker-uri="${hd.jt}/>
```

hadoop.properties

```
# Amazon EMR
# S3 bucket backing the HDFS S3 fs
hd.fs=s3n://my-working-bucket/
# job tracker pointing to the EMR internal IP
hd.jt=10.123.123.123:9000
```

emr.properties

```
# Amazon EMR
# Use a SOCKS proxy
hadoop.rpc.socket.factory.class.default=org.apache.hadoop.net.SocksSocketFactory
hadoop.socks.server=localhost:6666

# S3 credentials
# for s3:// uri
fs.s3.awsAccessKeyId=XXXXXXXXXXXXXXXXXXXX
fs.s3.awsSecretAccessKey=XXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX

# for s3n:// uri
fs.s3n.awsAccessKeyId=XXXXXXXXXXXXXXXXXXXX
fs.s3n.awsSecretAccessKey=XXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX
```

Spring Hadoop is now ready to talk to your Amazon EMR cluster. Try it out!



Note

The inquisitive reader might wonder why the example above uses two properties file, `hadoop.properties` and `emr.properties` instead of just one. While one file is enough, the example tries to isolate the EMR configuration into a separate configuration (especially as it contains security credentials).

- Shutdown the tunnel and the cluster

Once the jobs submitted are completed, unless new jobs are shortly scheduled, one can shutdown the cluster. Just like the first step, this is optional. Again, make sure you understand the billing process first.

Appendix B. Using Spring for Apache Hadoop with EC2/Apache Whirr

As mentioned above, those interested in using on-demand Hadoop clusters can use Amazon Elastic Map Reduce (or Amazon EMR) service. An alternative to that, for those that want maximum control over the cluster, is to use Amazon Elastic Compute Cloud or [EC2](#). EC2 is in fact the service on top of which Amazon EMR runs and that is, a resizable, configurable compute capacity in the cloud.



Important

This chapter assumes the user is familiar with Amazon EC2 and the [cost](#) associated with it and its related services - we strongly recommend getting familiar with the official EC2 [documentation](#).

Just like Amazon EMR, using EC2 means the Hadoop cluster (or whatever service you run on it) runs in the cloud and thus 'development' access to it, is different then when running the service in local network. There are various tips and tools out there that can handle the initial provisioning and configure the access to the cluster. Such a solution is [Apache Whirr](#) which is a set of libraries for running cloud services. Though it provides a Java API as well, one can easily configure, start and stop services from the command-line.

B.1 Setting up the Hadoop cluster on EC2 with Apache Whirr

The Whirr [documentation](#) provides more detail on how to interact with the various cloud providers out-there through Whirr. In case of EC2, one needs Java 6 (which is required by Apache Hadoop), an account on EC2 and an SSH client (available out of the box on *nix platforms and freely downloadable (such as PuTTY) on Windows). Since Whirr does most of the heavy lifting, one needs to tell Whirr what Cloud provider and account is used, either by setting some environment properties or through the `~/.whirr/credentials` file:

```
whirr.provider=aws-ec2
whirr.identity=your-aws-key
whirr.credential=your-aws-secret
```

Now instruct Whirr to configure a Hadoop cluster on EC2 - just add the following properties to a configuration file (say `hadoop.properties`):

```
whirr.cluster-name=myhadoopcluster
whirr.instance-templates=1 hadoop-jobtracker+hadoop-namenode,1 hadoop-datanode+hadoop-
tasktracker
whirr.provider=aws-ec2
whirr.private-key-file=${sys:user.home}/.ssh/id_rsa
whirr.public-key-file=${sys:user.home}/.ssh/id_rsa.pub
```

The configuration above assumes the SSH keys for your user have been already generated. Now start your Hadoop cluster:

```
bin/whirr launch-cluster --config hadoop.properties
```

As with Amazon EMR, one cannot correct to the Hadoop cluster from outside - however Whirr provides out of the box the feature to create an SSH tunnel to create a SOCKS proxy (on port 6666). When

a cluster is created, Whirr creates a script to launch the cluster which may be found in `~/whirr/cluster-name`. Run it as follows (in a new terminal window):

```
~/whirr/myhadoopcluster/hadoop-proxy.sh
```

At this point, one can just the [SOCKS proxy](#) configuration from the Amazon EMR section to configure the Hadoop client.

To destroy the cluster, one can use the Amazon EMR console or Whirr itself:

```
bin/whirr destroy-cluster --config hadoop.properties
```

Appendix C. Spring for Apache Hadoop Schema

Spring for Apache Hadoop Schema

```
FIXME: SHDP SCHEMA LOCATION/NAME CHANGED
```